

TECHNISCHE UNIVERSITÄT DRESDEN

FAKULTÄT INFORMATIK

INSTITUT FÜR SOFTWARE- UND MULTIMEDIATECHNIK

PROFESSUR FÜR COMPUTERGRAPHIK UND VISUALISIERUNG

PROF. DR. STEFAN GUMHOLD

Diplomarbeit

zur Erlangung des akademischen Grades
Diplom-Informatiker

Validierung einer Gathering-Strategie zur Szenendiskretisierung für Partikeldaten im Kontext der Berechnung von ambienter Verdeckung

Maximilian Richter

(Geboren am 8. April 1993 in Schleiz, Mat.-Nr.: 3802290)

Betreuer: Dipl.-Medieninf. Joachim Staib

Dresden, 27. Februar 2018

Aufgabenstellung

Selbstständigkeitserklärung

Hiermit erkläre ich, dass ich die von mir am heutigen Tag dem Prüfungsausschuss der Fakultät Informatik eingereichte Arbeit zum Thema:

*Validierung einer Gathering-Strategie zur Szenendiskretisierung für Partikeldaten im Kontext der
Berechnung von ambienter Verdeckung*

vollkommen selbstständig verfasst und keine anderen als die angegebenen Quellen und Hilfsmittel benutzt sowie Zitate kenntlich gemacht habe.

Dresden, den 27. Februar 2018

Maximilian Richter

Kurzfassung

Abstract

Inhaltsverzeichnis

1	Introduction	3
1.1	Task	3
1.2	Outline	4
2	Related Work	5
2.1	Spatial Particle Search	5
2.2	Ambient Occlusion	7
3	Ambient Occlusion	9
3.1	Ray Casting	9
3.2	Voxel Cone Tracing	9
4	Particle Voxelization	10
4.1	Scattering Method	10
4.2	Gathering Method	10
4.3	Hashed Uniform Grid	10
4.3.1	Spatial Hashing	10
4.3.2	Address Calculation	10
4.3.3	Particle Sorting	10
4.3.4	Particle Gathering	11
5	Algorithm	12
5.1	Software Architecture	12
5.1.1	Design Considerations	12
5.2	Hashed Uniform Grid Construction	12
5.2.1	Spatial Hashing	12
5.2.2	Address Calculation	12
5.2.3	Particle Sorting	12

5.3	Particle Voxelization	12
5.3.1	Scattering	12
5.3.2	Gathering	12
5.3.3	X	13
5.4	Particle Rendering	13
5.4.1	Conservative Rasterization	13
5.4.2	Perspective Projection	13
5.5	Ambient Occlusion	13
5.5.1	Voxel Cone Tracing	13
5.5.2	Ray Casting	13
6	Results	14
6.1	Evaluation	14
6.1.1	Voxelization Quality	14
6.1.2	Runtime Performance	14
6.1.3	Memory Consumption	14
6.2	Discussion	14
7	Conclusion	15
	Literaturverzeichnis	16

1 Introduction

Modern particle-based simulations contain several millions of particles. With increasing density and depth complexity they require refined rendering techniques for visualization. Local lighting lacks visual cues for depth and occlusion and therefore introduces perception issues. Global illumination allows to visualize complex structures in particle data, that otherwise would remain unseen. While ray tracing based techniques converge to exact results, their computation is costly. For real-time rendering less expensive approximations like ambient occlusion are used. Ambient occlusion is especially useful for visualization, as it assumes no parameters for illumination and by that introduces no new information. Instead it mimics indirect diffuse light by calculating the level of occlusion for visible surfaces. The more occluded a surface point is, the less light reaches it and the darker it has to appear. The calculation of the ambient terms is still costly, but several methods exist to approximate it. One of them, Voxel Cone Tracing, uses an discretized voxel representation of the geometry. This requires a method to transfer particles into a voxel grid. Scattering iterates all particles and adds their partial contributions to the intersected voxels. Parallel scattering processes the particles simultaneously. Synchronization has to assure correct summation of the contributions whenever multiple spheres intersect the same voxel causing race conditions. As synchronization increases, parallelism decreases. Therefore scattering performs the worse, the more dense the particle data is.

1.1 Task

To find a particle voxelization technique that better fits the parallel nature of graphics processing units a gathering approach is validated. Gathering determines for each voxel which particles it intersects with. Contrary to scattering each voxel is processed by an individual thread. This ensures that all write operations on one voxel happen sequentially and require no synchronization. For efficient particle search around voxels an acceleration data structure is required, as exhaustive search on all particles has $O(n^2)$ complexity. By sorting particles into spatial bins the search can be limited to near particles. The data structure has to be GPU based, as transferring particles to CPU and back would waste bandwidth and synchronization would reduce performance. Starting from an unordered list of particles an algorithm is

designed to first build a hashed uniform grid and then use it to calculate the voxel densities. To compare the gathering approach against scattering both construction time and memory usage are measured for particle clouds of variable size and density. The created voxel data structure is used to calculate ambient occlusion using voxel cone tracing. To evaluate the quality of the proposed solution a ground truth renderer using ray-casting is implemented. The influence of both voxelization and voxel cone tracing on the determined error is examined.

1.2 Outline

The work is organized as follows. In chapter 2 related works are discussed. First concerning acceleration data structures on particles, followed by voxelization techniques and finally ambient occlusion for particle data. Chapter 3 presents the proposed gathering based voxelization technique. Chapter 4 details the techniques used to calculate ambient occlusion. In chapter 5 implementation details are given. Chapter 6 finally presents the results of the work.

2 Related Work

2.1 Spatial Particle Search

Gathering requires an efficient method to retrieve particles in a given region of space. Spatial particle search is related to physical simulation of particles, where properties are determined according to neighboring particles. To detect ...

[HKK07b] was first to present entirely GPU based particle simulations. As no general purpose compute API was available it was implemented using OpenGL shaders. To create a three-dimensional grid, particle indices were stored in the RGBA channels of a two-dimensional texture. Because only four particles can be stored per grid cell, a small cell size has to be chosen to avoid artifacts. This leads to significant amount of memory occupied by empty cells, as SPH simulations fill the simulation volume in a non uniform way. To avoid reduced performance due to high memory transfer [HKK07a] proposed an adaptive uniform grid for variable sized volumes. Here the computational region is sliced into planes of voxels that are stored as texels. To avoid the wasted memory associated with a high amount of empty cells, only regions that actually contain particles are represented as voxel planes.

Another method using textures to sort data into spatial bins is presented by [OBS09]. The bins are specified as 2D texture coordinates into a texture array. Each bin is composed of all texels that share it's 2D coordinate, one from each slice. A distinct texture counts the elements in each bin and determines which slice provides the next texel to store the input value in. To represent 3D data this implementation requires a mapping function from spatial coordinates to 2D texture coordinates. As the texture array's depth limits the number of items it does not suit this thesis' task.

The CUDA SDK [Gre10] evaluates the assignment of particles to uniform grid cells with atomic operations against sorting. Atomic operations are used to update the number of particles per cell and in a second array the indices of these particles. With sorting every particle's cell is calculated as a hash. Using radix sort with the hash value as key the particles are then sorted based on their hashes. Finally for each cell it's start in the sorted list is calculated. Due to memory coherence and reduced warp divergence they found that sorting achieves highest performance. Additionally it has shown to be less sensitive to dense and randomly distributed data.

[Hoe14] improves the sorting based algorithm presented in [Gre10]. Radix sort works best for... For efficient particle access it is not necessary to sort the particles finer than per bin. Therefore the radix sort used in [Gre10] is replaced with a prefix sum and subsequent counting sort. Once prefix sum calculated bins final address the sorting is achieved by copying each particle to the address of its bin. Additionally they replaced the computation of each bin's particle count with an atomic addition during particle assignment.

Spatial hashing is also used for collision detection of polygonal meshes in [THM⁺03]. The domain is implicitly subdivided into uniform grid cells by mapping them to a hash table, avoiding complex data structures. This way the number of elements is only limited by memory capacity and arbitrary non-uniform distributions of objects can be stored. CPU only...

[How16] implements several algorithms to determine neighbor lists for particle simulation. They state that stenciled cell lists and linear bounding volume hierarchies work better for data sets with variable cutoff radius, while uniform grids are better suited for fixed cutoff radius. In molecular dynamics the cutoff radius is the maximum distance in which particles effect others. As particle search for fixed sized voxels is conceptually equivalent to searching particles within a fixed cutoff radius, the uniform grid approach is most relevant for this work.

Similarly to this thesis [GLX⁺15] maps particle positions to mesh contributions. They compare a gathering approach to a scattering method. Unlike the method presented in [Gre10, Hoe14] their gathering algorithm uses a fixed amount of storage to assign particles to mesh points. Particles exceeding this storage are stored in a separate list and are scattered in an subsequent step. To perform better than scattering this approach requires the overflow list to be small. This sensitivity to the distribution of particles it is not desired for this thesis.

[ZD15] proposes a memory efficient method to voxelize particles to surfaces. They start with a view adaptive voxel grid and voxelize the particles using splatting. To compress the grid only surface entries and exits are stored, without any representation of the distribution inbetween. The depth values are then connected to create a watertight mesh. While this approach allows efficiently extract the surface of volumetric data this thesis requires a full volumetric representation.

Another class of spatial search algorithms does not try to find neighbors for a given point but This is most relevant for tracing rays through scenes until they hit any geometry. As the ... , hierarchical methods subdivide the scene into regions of increasing resolution as the amount of geometry inside grows. These methods' effectiveness relies on their ability to skip large empty areas. While this allows for efficient traversal of rays with unknown length, for particle gathering only a neighbourhood of limited and constant size is considered.

2.2 Ambient Occlusion

[ZIK98] introduced ambient occlusion as an ambient light illumination model to reproduce effects of indirect light. The assumption is that the more open the scene around a point is, the more indirect light reaches this point. To determine a point's level of occlusion, its hemisphere has to be sampled in every direction. The more rays intersect close geometry, the more occluded the point is. Due to its computational cost naive sampling is unsuitable for interactive visualization.

[PG04] pre-computes ambient occlusion offline using ray tracing on the CPU or using shadow maps on the GPU. For rendering the ambient occlusion terms are then provided as color values to the vertices. The pre-computation takes minutes, therefore this implementation only works for static scenes.

To allow scenes with moving objects [Bun05] converts all vertices to disc-shaped occluder elements. Then for each vertex the occlusion value is calculated by adding the form factors of the other occluders. Form factor represents how much occlusion a surface creates depending on disk area and distance to it. As the ambient occlusion term is calculated per vertex, detailed meshes are required to avoid artifacts. The pre-computation prevents this from being suitable for deformable objects.

For scenes with arbitrary geometry it is necessary to recompute ambient occlusion per frame without pre-processing. [Mit07] introduced screen space ambient occlusion, a method to approximate the occlusion terms as a postprocessing pass with screen space information only. Instead of sampling polygonal meshes itself, the scene is rendered into a normal and a depth buffer first. Then each pixel's surrounding pixels are sampled from the buffers to determine an approximated occlusion factor. This is done by sampling a sphere around each pixel's world position. Then each sample is reprojected into depth buffer to determine if it is occluded. For realtime performance undersampling is required, which introduces noise. To counteract, a blur step finalizes the ambient occlusion postprocessing. The method by [SA07] is conceptually similar but combines the screen space occlusion with occlusion from spherical proxy geometry for far-field occlusion. (!)

A different measure of occlusion is used in [BSD08]. From each sampling point rays in random directions are marched in screen space to find the maximum angle from which light falls in. These horizon angles are averaged resulting in an estimate of occlusion with the occlusion factor growing proportionally to the angle.

While these methods provide fast results, they also introduce errors by only considering screen space regions. Artifacts are typically introduced due to the combination of low resolution occlusion calculation and high depth complexity. The issue here is that only a single depth value per pixel is considered, ignoring any geometry behind. [BA12] reduces flickering using temporal filtering. Ambient occlusion

depends only on geometry and is independent of the view. Therefore the last frame's occlusion values can be reprojected to the current view to reduce temporal variance. To avoid trailing effects the pixels are classified into a stable and unstable set and temporal filtering is only applied to the unstable, flickering pixels.

Another screen space artifact are halos around objects, when their background is distant. The depth discontinuity between the object's and the background's pixels the horizon sampling. While this applies for every geometry, it is most visible when moving objects pass static ones. [TP16] approaches this by separating static and moving objects to distinct depth buffers. While this reduces the error, it does not solve the underlying problem. Due to screen space limitations increasing depth complexity causes increased artifacts. World space methods avoid this by directly sampling the geometry. [TP16] describes voxel cone tracing as one method to calculate world space ambient occlusion.

Voxel cone tracing has been introduced by [CNS⁺11]. The fundamental idea is to transfer the geometry into a multiresolution volumetric representation. The voxel hierarchy is then used to sample cones, approximating the amount of geometry in that region. For each cone a series of increasingly bigger voxels is sampled along the cones direction, each from a coarser resolution than before. The voxels' density values are blended along

[SGG15] applies voxel cone tracing to molecular dynamics data. A 3D texture is used as voxel data structure into which the particles are voxelized. To create the coarser resolutions the texture is mipmapped. The particles are then rendered using raycasting. For each pixel three cones are traced around the normal.

In [GKSE12] a grid stores the occupancy information derived from the neighboring atoms.

3 Ambient Occlusion

3.1 Ray Casting

idea + hemisphere sampling

Ray Sphere Intersection Math - not even once

3.2 Voxel Cone Tracing

cone tracing idea + cone approximation with voxels construction of hierarchy

4 Particle Voxelization

4.1 Scattering Method

unregelmäßig -> regelmäßig

Disadvantages

4.2 Gathering Method

regelmäßig -> unregelmäßig

Data Structures Review of possible data structures considering requirements of gathering approach.

4.3 Hashed Uniform Grid

Presentation of a fast particle access data structure including underlying structure (grid..) and acceleration methods (sorting..).

hash grid = uniform grid = cell lists = buckets = bins

4.3.1 Spatial Hashing

4.3.2 Address Calculation

Prefix sum

4.3.3 Particle Sorting

Counting Sort

4.3.4 Particle Gathering

Voxel -> Hash Cells -> Particles

+ how to transfer particles to voxel contributions -> sampling

5 Algorithm

Graphics API WHY OPENGL -> https://developer.nvidia.com/gpugems/GPUGems3/gpugems3_ch39.html chapter 39.2.6 -> all disadvantages of old opengl implementations are removed with compute shaders

5.1 Software Architecture

5.1.1 Design Considerations

5.2 Hashed Uniform Grid Construction

5.2.1 Spatial Hashing

Different Hashing Strategies? Linear, Morton, 2x2x2Block

5.2.2 Address Calculation

5.2.3 Particle Sorting

5.3 Particle Voxelization

5.3.1 Scattering

5.3.2 Gathering

? multiple variants

5.3.3 X

5.4 Particle Rendering

5.4.1 Conservative Rasterization

5.4.2 Perspective Projection

Raycasting

5.5 Ambient Occlusion

5.5.1 Voxel Cone Tracing

-> Voxel Cone Tracing

-> hemisphere of n cones per frame

-> variable cone size + variable voxel grid size for comparison

5.5.2 Ray Casting

-> GPU Raycast on spheres

-> progressive pipeline

-> also on voxels for comparison

6 Results

6.1 Evaluation

6.1.1 Voxelization Quality

einfluss von verschiedenen parametern auf fehler -> voxel auflösung, anzahl cones

Vergleich: VCT mit ray casting auf partik data -> Fehlerquellen:

VCT on high resolution grid -> voxelization error

Ray casting/Fine cones on voxel grid -> cone tracing error

6.1.2 Runtime Performance

Scattering vs Gathering Performance

Einzelne Schritte des Gatherings

Teuerste Schritte in shadern

6.1.3 Memory Consumption

...

6.2 Discussion

7 Conclusion

[GLX⁺15] [Gre10] [HKK07a] [THM⁺03] [ZD15] [GKSE12] [SGG15] [HKK07b] [How16] [Hoe14]
[OBS09] [ZIK98] [PG04] [Bun05] [CNS⁺11] [Mit07] [BSD08] [BA12] [TP16] [SA07]

Literaturverzeichnis

- [BA12] BAVOIL, Louis ; ANDERSSON, Johan: Stable SSAO In Battlefield 3 With Selective Temporal Filtering. In: *Game Developer Conference Course, San Francisco, CA*, 2012
- [BSD08] BAVOIL, Louis ; SAINZ, Miguel ; DIMITROV, Rouslan: Image-space horizon-based ambient occlusion. In: *ACM SIGGRAPH 2008 talks*, ACM, 2008, S. 22
- [Bun05] BUNNELL, Michael: Dynamic ambient occlusion and indirect lighting. In: *GPU Gems 2*. Addison-Wesley Professional, 2005, Kapitel 14, S. 223–233
- [CNS⁺11] CRASSIN, Cyril ; NEYRET, Fabrice ; SAINZ, Miguel ; GREEN, Simon ; EISEMANN, Elmar: Interactive indirect illumination using voxel cone tracing. In: *Computer Graphics Forum* Bd. 30 Wiley Online Library, 2011, S. 1921–1930
- [GKSE12] GROTTTEL, Sebastian ; KRONE, Michael ; SCHARNOWSKI, Katrin ; ERTL, Thomas: Object-Space Ambient Occlusion for Molecular Dynamics. In: *Proceedings of IEEE Pacific Visualization Symposium*, IEEE Computer Society, 2012, S. 209 – 216
- [GLX⁺15] GUO, Xiangyu ; LIU, Xing ; XU, Peng ; DU, Zhihui ; CHOW, Edmond: Efficient Particle-mesh Spreading on GPUs. In: *Procedia Computer Science 51 ICCS*, Elsevier, 2015, S. 120–129
- [Gre10] GREEN, Simon: *Particle Simulation using CUDA*, NVIDIA Corporation, 2010. <http://hoomd-blue.readthedocs.io/en/stable/nlist.html>
- [HKK07a] HARADA, Takahiro ; KOSHIZUKA, Seiichi ; KAWAGUCHI, Yoichiro: Sliced data structure for particle-based simulations on GPUs. In: *Proceedings of the 5th international conference on Computer graphics and interactive techniques in Australia and Southeast Asia*, ACM, 2007, S. 55–62
- [HKK07b] HARADA, Takahiro ; KOSHIZUKA, Seiichi ; KAWAGUCHI, Yoichiro: Smoothed Particle Hydrodynamics on GPUs. In: *Proceedings of Computer Graphics International*, IEEE Computer Society, 2007, S. 63–70
- [Hoe14] HOETZLEIN, Rama: *Fast Fixed Radius Nearest Neighbors: Interacti-*

- ve *Million-Particle Fluids*, GPU Technology Conference, 2014. <http://on-demand.gputechconf.com/gtc/2014/presentations/S4117-fast-fixed-radius-nearest-neighbor-gpu.pdf>
- [How16] HOWARD, Michael: *HOOMD-blue Neighbor lists*, Univerity of Michigan, 2016. <http://hoomd-blue.readthedocs.io/en/stable/nlist.html>
- [Mit07] MITTRING, Martin: Finding next gen: Cryengine 2. In: *ACM SIGGRAPH 2007 courses*, ACM, 2007, S. 97–121
- [OBS09] OAT, Christopher ; BARCZAK, Joshua ; SHOPF, Jeremy: *Efficient Spatial Binning on the GPU*. AMD Technical Report, 2009
- [PG04] PHARR, Matt ; GREEN, Simon: Ambient Occlusion. In: *GPU Gems*. Addison-Wesley Professional, 2004, Kapitel 17, S. 279–292
- [SA07] SHANMUGAM, Perumaal ; ARIKAN, Okan: Hardware Accelerated Ambient Occlusion Techniques on GPUs. In: *Proceedings of the 2007 Symposium on Interactive 3D Graphics and Games*. New York, NY, USA : ACM, 2007 (I3D '07), S. 73–80
- [SGG15] STAIB, Joachim ; GROTTTEL, Sebastian ; GUMHOLD, Stefan: Visualization of Particle-based Data with Transparency and Ambient Occlusion. In: *Proceedings of the 2015 Eurographics Conference on Visualization*, Eurographics Association, 2015, S. 151–160
- [THM⁺03] TESCHNER, Matthias ; HEIDELBERGER, Bruno ; MÜLLER, Matthias ; POMERANTES, Darnat ; GROSS, Markus: Optimized Spatial Hashing for Collision Detection of Deformable Objects. In: *Proceedings of Vision, Modeling, Visualization*, Aka GmbH, 2003, S. 47–54
- [TP16] TATARINOV, Andrei ; PANTELEEV, Alexey: *Advanced Ambient Occlusion Methods for Modern Games*. http://developer.download.nvidia.com/gameworks/events/GDC2016/atatarinov_alpanteleev_advanced_ao.pdf.
Version: 2016. – Game Developers Conference 2016
- [ZD15] ZIRR, Tobias ; DACHSBACHER, Carsten: Memory-efficient On-the-fly Voxelization of Particle Data. In: *Proceedings of the 15th Eurographics Symposium on Parallel Graphics and Visualization*, Eurographics Association, 2015, S. 11–18
- [ZIK98] ZHUKOV, Sergey ; IONES, Andrei ; KRONIN, Grigorij: An Ambient Light Illumination Model. In: *Proceedings of the Eurographics Workshop: Rendering Techniques '98*, Springer, 1998, S. 45–56