

API Test Scenarios

Complete Testing Reference — 138 Scenarios

Banking Domain API Playground · Generated 2026-07-08

Getting Started

1. Start the platform: `make up-full`
2. Import Postman environment: `docs/postman/playground-environment.json`
3. Import Postman collection: `docs/postman/playground-api-collection.json`
4. Run login scenarios first (008–010) to obtain JWT tokens
5. Execute scenarios in order or jump to critical scenarios below

Service Base URLs

Service	Base URL	Auth Type
Platform API	<code>http://localhost:8080</code>	Basic (learner / learner)
Banking API	<code>http://localhost:8081</code>	JWT Bearer token
Enterprise API	<code>http://localhost:8082</code>	JWT Bearer token
Test Lab API	<code>http://localhost:8083</code>	Basic (learner / learner)

Postman Variables

Variable	Purpose
<code>jwt_token</code>	Customer JWT — set automatically after Scenario 008
<code>admin_jwt</code>	Ops/Admin JWT — set after Scenario 009 or 010
<code>idempotency_key</code>	Unique key for payment/transfer/card calls (auto-generated)

Token-Based API Calls (JWT Bearer)

Most Banking and Enterprise endpoints require a JWT obtained via login. This is the standard tokenised authentication flow for protected API calls.

Step	Action	Details
------	--------	---------

1	Run Scenario 008	POST /v1/auth/login as customer → save accessToken to jwt_token
2	Run Scenario 009 or 010	Login as ops/admin → save accessToken to admin_jwt
3	Use Bearer header	Authorization: Bearer {{jwt_token}} on Banking & Enterprise calls
4	Set tenant header	X-Tenant-Id: tenant-demo (must match token tenant)
5	Mutating payments/transfers	Add Idempotency-Key: {{idempotency_key}} (auto-generated in Postman)

Every protected request must include both Authorization: Bearer <token> and X-Tenant-Id: tenant-demo. Mismatch between token tenant and header returns 403 (Scenario 135).

Critical & Complex Scenarios

These scenarios cover security boundaries, financial integrity, idempotency, fraud detection, concurrency, and resilience. Prioritise them for regression and learning paths.

Scenarios	Topic	Why It Matters
008–010	JWT login (customer, ops, admin)	Obtain Bearer tokens before any protected Banking/Enterprise call
011	Get current user	Verify JWT is valid and party context is correct
022	BOLA — access other party	Security: customer must get 403 on another party's data
033–035	Payment happy path	Create, get, and list payments with JWT + Idempotency-Key
036	Payment without auth	Security: unauthenticated payment must return 401
037–039	Transfer flow	Internal transfer with idempotency protection
043	Card authorization	Tokenised card spend simulation with idempotency
075–078	Fraud screening & alerts	High-value transaction triggers velocity alert

086	Admin endpoint as customer	Role-based access: customer cannot read admin settings
129	Idempotency replay (lab)	Same key + body replays without double debit
130	Fraud velocity alert (lab)	End-to-end fraud scenario walkthrough
131	Webhook retry & DLQ (lab)	Async delivery failures and dead-letter queue
132	Concurrent transfer race (lab)	Optimistic locking under parallel transfers
133	BOLA party access (lab)	Authorization boundary for cross-party reads
134	Invalid login password	Authentication failure returns 401
135	Wrong tenant header	JWT tenant must match X-Tenant-Id header
136	Idempotency conflict	Same key with different body returns 409
137	Insufficient funds	Business rule: payment over balance returns 400
138	Lab without auth	Protected lab endpoints require Basic auth

Scenario Categories

- **001–007** Platform API — health, version, error demos, validation
- **008–052** Banking API — auth, parties, KYC, accounts, payments, transfers, cards, FX, ledger
- **053–098** Enterprise API — loans, deposits, fraud, AML, admin, webhooks, resilience
- **099–133** Test Lab — reset, scenarios, mocks, faults, performance, security profiles
- **134–138** Negative & edge cases — auth failures, tenant mismatch, idempotency conflict, insufficient funds

Scenario Index

Platform API

001	Platform — Get health
002	Platform — Get version
003	Platform — Demo bad request error
004	Platform — Demo not found error
005	Platform — Demo internal error
006	Platform — Validate body (valid)
007	Platform — Validate body (invalid)

Banking API

008	Banking — Login as customer
009	Banking — Login as ops
010	Banking — Login as admin
011	Banking — Get current user
012	Banking — Get health
013	Banking — Get version
014	Banking — List roles
015	Banking — List users
016	Banking — Get user by id
017	Banking — Create user
018	Banking — Get party
019	Banking — List parties
020	Banking — Create party
021	Banking — Update party
022	Banking — BOLA get other party (negative)

023	Banking — List KYC cases
024	Banking — Get KYC case
025	Banking — Submit KYC case
026	Banking — Review KYC case
027	Banking — List accounts
028	Banking — Get account
029	Banking — Open account
030	Banking — List beneficiaries
031	Banking — Add beneficiary
032	Banking — Delete beneficiary
033	Banking — Create payment
034	Banking — Get payment
035	Banking — List payments
036	Banking — Payment without auth (negative)
037	Banking — Create transfer
038	Banking — Get transfer
039	Banking — List transfers
040	Banking — Issue card
041	Banking — List cards
042	Banking — Get card
043	Banking — Authorize card
044	Banking — Create FX quote
045	Banking — Execute FX conversion
046	Banking — Get FX conversion
047	Banking — List transactions

048	Banking — Get transaction
049	Banking — List ledger entries
050	Banking — Generate statement
051	Banking — List statements
052	Banking — Get statement
134	Banking — Login invalid password
135	Banking — Wrong tenant header
136	Banking — Idempotency conflict
137	Banking — Insufficient funds

Enterprise API

053	Enterprise — Get health
054	Enterprise — Get version
055	Enterprise — Create loan
056	Enterprise — Get loan
057	Enterprise — List loans
058	Enterprise — Create loan repayment
059	Enterprise — Create fixed deposit
060	Enterprise — Get fixed deposit
061	Enterprise — List fixed deposits
062	Enterprise — Create recurring deposit
063	Enterprise — Get recurring deposit
064	Enterprise — List recurring deposits
065	Enterprise — Post RD installment
066	Enterprise — Create notification
067	Enterprise — List notifications

068	Enterprise — Mark notification read
069	Enterprise — Register document
070	Enterprise — Get document
071	Enterprise — List documents
072	Enterprise — Generate report
073	Enterprise — Get report
074	Enterprise — List reports
075	Enterprise — Fraud screen (alert)
076	Enterprise — Fraud screen (no alert)
077	Enterprise — List fraud alerts
078	Enterprise — Review fraud alert
079	Enterprise — Create AML case
080	Enterprise — Get AML case
081	Enterprise — List AML cases
082	Enterprise — Submit AML screening
083	Enterprise — List admin settings
084	Enterprise — Get admin setting
085	Enterprise — Update admin setting
086	Enterprise — Admin as customer (negative)
087	Enterprise — List audit events
088	Enterprise — List domain events
089	Enterprise — Submit job
090	Enterprise — Get job
091	Enterprise — List jobs
092	Enterprise — List scheduler tasks

093	Enterprise — Register scheduler task
094	Enterprise — Register webhook
095	Enterprise — List webhooks
096	Enterprise — List webhook deliveries
097	Enterprise — List circuit breakers
098	Enterprise — Get circuit breaker

Lab API

099	Lab — Get health
100	Lab — Get version
101	Lab — Reset all data
102	Lab — List scenarios
103	Lab — Get scenario payment-happy-path
104	Lab — Start scenario run
105	Lab — Complete scenario run
106	Lab — List contracts
107	Lab — Get contract file
108	Lab — List config
109	Lab — Get config key
110	Lab — Update config
111	Lab — List fault rules
112	Lab — Create fault rule
113	Lab — Disable fault rule
114	Lab — List mocks
115	Lab — Create mock
116	Lab — Call AML clear mock (public)

117	Lab — Call AML review mock (public)
118	Lab — Generate test data
119	Lab — List test data handles
120	Lab — Delete test data namespace
121	Lab — Generate seed
122	Lab — Get dashboard
123	Lab — List performance profiles
124	Lab — List security test cases
125	Lab — List concurrency scenarios
126	Lab — Get race profile
127	Lab — List failure simulations
128	Lab — Get failure simulation
129	Lab — Get scenario idempotency-replay
130	Lab — Get scenario fraud-velocity-alert
131	Lab — Get scenario webhook-retry-dlq
132	Lab — Get scenario concurrent-transfer-race
133	Lab — Get scenario bola-party-access
138	Lab — Scenarios without auth

Detailed Scenarios



Scenario 001

Platform — Get health

URL	http://localhost:8080/health
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "status": "UP", "service": "platform-api", "components": { "database": "UP" } }
```

Scenario 002

Platform — Get version

URL	http://localhost:8080/version
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "name": "platform-api", "version": "0.1.0-SNAPSHOT" }
```

Scenario 003

Platform — Demo bad request error

URL	http://localhost:8080/v1/demo/errors/bad-request
Method	GET
Authentication	Basic (learner/learner)
Expected Status	400 Bad Request

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "type": "https://playground.example/problems/bad-request", "title": "Bad Request", "status": 400, "detail": "Demonstration bad request", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 004

Platform — Demo not found error

URL	http://localhost:8080/v1/demo/errors/not-found
Method	GET
Authentication	Basic (learner/learner)
Expected Status	404 Not Found

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "type": "https://playground.example/problems/not-found", "title": "Not Found", "status": 404, "detail": "Demonstration not found", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 005

Platform — Demo internal error

URL	http://localhost:8080/v1/demo/errors/internal
-----	---

Method	GET
Authentication	Basic (learner/learner)
Expected Status	500 Internal Server Error

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "type": "https://playground.example/problems/internal-server-error", "title": "Internal Server Error", "status": 500, "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 006

Platform — Validate body (valid)

URL	http://localhost:8080/v1/demo/validate
Method	POST
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Content-Type	application/json
--------------	------------------

Request Body

```
{ "name": "Jane" }
```

Expected Response

```
{ "message": "Validation passed", "name": "Jane" }
```

Scenario 007

Platform — Validate body (invalid)

URL	http://localhost:8080/v1/demo/validate
Method	POST
Authentication	Basic (learner/learner)
Expected Status	422 Unprocessable Entity

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY
Content-Type	application/json

Request Body

```
{ "name": "" }
```

Expected Response

```
{ "title": "Validation Failed", "status": 422, "errors": [{ "field": "name", "message": "name must not be blank" }], "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 008

Banking — Login as customer

URL	http://localhost:8081/v1/auth/login
Method	POST
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{ "tenantId": "tenant-demo", "username": "customer", "password": "password" }
```

Expected Response

```
{ "accessToken":  
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiJ1c2VyaW50SwQ0iJ0ZW5hbnQtZGVtbyJ9.SIGNATURE"  
"tokenType": "Bearer", "expiresIn": 3600 }
```

Note: Save accessToken as jwt_token in Postman.

Scenario 009

Banking — Login as ops

URL	http://localhost:8081/v1/auth/login
-----	-------------------------------------

Method	POST
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{ "tenantId": "tenant-demo", "username": "ops", "password": "password" }
```

Expected Response

```
{ "accessToken":  
  "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiJ1c2VyLWN1c3RvbWVyIiwidGVuYW50SWQiOiJ0ZW5hbnQtZGVtbyJ9.SIGNATURE"  
  "tokenType": "Bearer", "expiresIn": 3600 }
```

Scenario 010

Banking — Login as admin

URL	http://localhost:8081/v1/auth/login
Method	POST
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{ "tenantId": "tenant-demo", "username": "admin", "password": "password" }
```

Expected Response

```
{ "accessToken":  
  "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiJ1c2VyLWN1c3RvbWVyaWwidGVuYW50SWQiOiJ0ZW5hbnQtZGVtb3R5J9.SIGNATURE",  
  "tokenType": "Bearer", "expiresIn": 3600 }
```

Scenario 011

Banking — Get current user

URL	http://localhost:8081/v1/auth/me
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "user-customer", "tenantId": "tenant-demo", "username": "customer", "partyId":  
"party-customer-1", "enabled": true, "roles": ["RETAIL_CUSTOMER"] }
```

Scenario 012

Banking — Get health

URL	http://localhost:8081/health
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "status": "UP", "service": "banking-api", "components": { "database": "UP" } }
```

Scenario 013

Banking — Get version

URL	http://localhost:8081/version
Method	GET

Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "name": "banking-api", "version": "0.1.0-SNAPSHOT" }
```

Scenario 014

Banking — List roles

URL	http://localhost:8081/v1/roles
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo

Content-Type	application/json
--------------	------------------

Request Body

None

Expected Response

```
[ { "id": "role-customer", "tenantId": "tenant-demo", "name": "RETAIL_CUSTOMER" }, { "id": "role-ops", "tenantId": "tenant-demo", "name": "OPS_AGENT" }, { "id": "role-admin", "tenantId": "tenant-demo", "name": "ADMIN" } ]
```

Scenario 015

Banking — List users

URL	http://localhost:8081/v1/users?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "user-customer", "username": "customer", "partyId": "party-customer-1",  
"enabled": true, "roles": ["RETAIL_CUSTOMER"] }], "page": 0, "size": 20, "totalElements": 3,  
"totalPages": 1, "nextCursor": null }
```

Scenario 016

Banking — Get user by id

URL	http://localhost:8081/v1/users/user-customer
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "user-customer", "tenantId": "tenant-demo", "username": "customer", "partyId":  
"party-customer-1", "enabled": true, "roles": ["RETAIL_CUSTOMER"] }
```

Scenario 017

Banking — Create user

URL	http://localhost:8081/v1/users
Method	POST
Authentication	Bearer JWT (admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "username": "newuser", "password": "password123", "partyId": "party-customer-1", "roleNames": ["RETAIL_CUSTOMER"] }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "tenantId": "tenant-demo", "username": "newuser", "partyId": "party-customer-1", "enabled": true, "roles": ["RETAIL_CUSTOMER"] }
```

Scenario 018

Banking — Get party

URL	http://localhost:8081/v1/parties/party-customer-1
Method	GET
Authentication	Bearer JWT

Expected Status	200 OK
-----------------	--------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "party-customer-1", "tenantId": "tenant-demo", "partyType": "INDIVIDUAL", "status": "ACTIVE",  
  "firstName": "Jane", "lastName": "Doe", "email": "jane.doe@example.com", "version": 0 }
```

Scenario 019

Banking — List parties

URL	http://localhost:8081/v1/parties?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "party-customer-1", "firstName": "Jane", "lastName": "Doe", "status": "ACTIVE" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 020

Banking — Create party

URL	http://localhost:8081/v1/parties
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyType": "INDIVIDUAL", "firstName": "John", "lastName": "Smith", "email": "john.smith@example.com" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "tenantId": "tenant-demo", "partyType": "INDIVIDUAL", "status": "PROSPECT", "firstName": "John", "lastName": "Smith", "email": "john.smith@example.com" }
```

Scenario 021

Banking — Update party

URL	http://localhost:8081/v1/parties/party-customer-1
Method	PATCH
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "firstName": "Jane", "email": "jane.updated@example.com" }
```

Expected Response

```
{ "id": "party-customer-1", "firstName": "Jane", "email": "jane.updated@example.com", "status": "ACTIVE" }
```

Scenario 022

Banking — BOLA get other party (negative)

URL	http://localhost:8081/v1/parties/party-other
Method	GET
Authentication	Bearer JWT (customer)
Expected Status	403 Forbidden

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "title": "Forbidden", "status": 403, "detail": "Access to this party is not permitted",  
  "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 023

Banking — List KYC cases

URL	http://localhost:8081/v1/kyc-cases?partyId=party-customer-1
Method	GET
Authentication	Bearer JWT

Expected Status	200 OK
-----------------	--------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
[{ "id": "kyc-1", "partyId": "party-customer-1", "status": "APPROVED", "level": "STANDARD" }]
```

Scenario 024

Banking — Get KYC case

URL	http://localhost:8081/v1/kyc-cases/kyc-1
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "kyc-1", "partyId": "party-customer-1", "status": "APPROVED", "level": "STANDARD" }
```

Scenario 025

Banking — Submit KYC case

URL	http://localhost:8081/v1/kyc-cases
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "status": "OPEN",  
  "level": "STANDARD" }
```

Note: Fails 409 if open case already exists for party.

Scenario 026

Banking — Review KYC case

URL	http://localhost:8081/v1/kyc-cases/kyc-1/review
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "status": "APPROVED", "decisionReason": "Documents verified" }
```

Expected Response

```
{ "id": "kyc-1", "status": "APPROVED", "decisionReason": "Documents verified" }
```

Scenario 027

Banking — List accounts

URL	http://localhost:8081/v1/accounts?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [ { "id": "acct-customer-1", "accountNumber": "GB1234567890", "currency": "GBP",  
"productCode": "CURRENT", "status": "ACTIVE", "availableBalance": 5000.00, "ledgerBalance": 5000.00  
}, { "id": "acct-customer-2", "accountNumber": "GB9876543210", "currency": "GBP", "productCode":  
"SAVINGS", "status": "ACTIVE", "availableBalance": 1000.00, "ledgerBalance": 1000.00 } ], "page": 0,  
"size": 20, "totalElements": 3, "totalPages": 1, "nextCursor": null }
```

Scenario 028

Banking — Get account

URL	http://localhost:8081/v1/accounts/acct-customer-1
Method	GET

Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "acct-customer-1", "tenantId": "tenant-demo", "partyId": "party-customer-1", "accountNumber": "GB1234567890", "currency": "GBP", "productCode": "CURRENT", "status": "ACTIVE", "availableBalance": 5000.00, "ledgerBalance": 5000.00, "version": 0 }
```

Scenario 029

Banking — Open account

URL	http://localhost:8081/v1/accounts
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "currency": "GBP", "productCode": "CURRENT" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "currency": "GBP",  
"productCode": "CURRENT", "status": "ACTIVE", "availableBalance": 0.00, "ledgerBalance": 0.00 }
```

Scenario 030

Banking — List beneficiaries

URL	http://localhost:8081/v1/beneficiaries?partyId=party-customer-1
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
[{ "id": "ben-1", "partyId": "party-customer-1", "nickname": "Savings Pot", "status": "ACTIVE",  
  "sortCode": "12-34-56", "accountNumber": "87654321" }]
```

Scenario 031

Banking — Add beneficiary

URL	http://localhost:8081/v1/beneficiaries
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "nickname": "Landlord", "sortCode": "11-22-33", "accountNumber":  
  "12345678" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "nickname":  
  "Landlord", "status": "PENDING_VERIFICATION" }
```

Scenario 032

Banking — Delete beneficiary

URL	http://localhost:8081/v1/beneficiaries/ben-1
Method	DELETE
Authentication	Bearer JWT
Expected Status	204 No Content

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

None (empty body)

Scenario 033

Banking — Create payment

URL	http://localhost:8081/v1/payments
Method	POST

Authentication	Bearer JWT + Idempotency-Key
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount": 25.50, "currency": "GBP", "reference": "rent" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount": 25.50, "currency": "GBP", "reference": "rent", "status": "COMPLETED", "createdAt": "2026-07-08T12:00:00Z" }
```

Scenario 034

Banking — Get payment

URL	http://localhost:8081/v1/payments/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId":  
"b2c3d4e5-f6a7-8901-bcde-f12345678901", "partyId": "party-customer-1", "accountId":  
"acct-customer-1", "beneficiaryId": "ben-1", "amount": 25.50, "currency": "GBP", "reference": "rent",  
"status": "COMPLETED", "createdAt": "2026-07-08T12:00:00Z" }
```

Scenario 035

Banking — List payments

URL	http://localhost:8081/v1/payments?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo

Content-Type	application/json
--------------	------------------

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount": 25.50, "currency": "GBP", "reference": "rent", "status": "COMPLETED", "createdAt": "2026-07-08T12:00:00Z" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 036

Banking — Payment without auth (negative)

URL	http://localhost:8081/v1/payments
Method	POST
Authentication	None
Expected Status	401 Unauthorized

Request Headers

Header	Value
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount": 25.50, "currency": "GBP", "reference": "rent" }
```

Expected Response

```
{ "title": "Unauthorized", "status": 401, "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 037

Banking — Create transfer

URL	http://localhost:8081/v1/transfers
Method	POST
Authentication	Bearer JWT + Idempotency-Key
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "fromAccountId": "acct-customer-1", "toAccountId": "acct-customer-2", "amount": 50.00, "currency": "GBP", "reference": "savings" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "fromAccountId": "acct-customer-1", "toAccountId": "acct-customer-2", "amount": 50.00, "currency": "GBP", "reference": "savings", "status": "COMPLETED" }
```

Scenario 038

Banking — Get transfer

URL	http://localhost:8081/v1/transfers/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId":  
  "b2c3d4e5-f6a7-8901-bcde-f12345678901", "fromAccountId": "acct-customer-1", "toAccountId":  
  "acct-customer-2", "amount": 50.00, "currency": "GBP", "reference": "savings", "status": "COMPLETED"  
}
```

Scenario 039

Banking — List transfers

URL	http://localhost:8081/v1/transfers?accountId=acct-customer-1&page=0&size=20
-----	---

Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "transactionId": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "fromAccountId": "acct-customer-1", "toAccountId": "acct-customer-2", "amount": 50.00, "currency": "GBP", "reference": "savings", "status": "COMPLETED" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 040

Banking — Issue card

URL	http://localhost:8081/v1/cards
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "productCode": "DEBIT" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "accountId": "acct-customer-1", "panLast4": "1234", "productCode": "DEBIT", "status": "ACTIVE" }
```

Scenario 041

Banking — List cards

URL	http://localhost:8081/v1/cards?partyId=party-customer-1
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
[{ "id": "card-1", "partyId": "party-customer-1", "accountId": "acct-customer-1", "panLast4": "4242", "productCode": "DEBIT", "status": "ACTIVE" }]
```

Scenario 042

Banking — Get card

URL	http://localhost:8081/v1/cards/card-1
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "card-1", "panLast4": "4242", "status": "ACTIVE" }
```

Scenario 043

Banking — Authorize card

URL	http://localhost:8081/v1/cards/card-1/authorizations
Method	POST
Authentication	Bearer JWT + Idempotency-Key
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "merchantName": "Coffee Shop", "amount": 4.50, "currency": "GBP" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "cardId": "card-1", "merchantName": "Coffee Shop",  
  "amount": 4.50, "currency": "GBP", "status": "APPROVED" }
```

Scenario 044

Banking — Create FX quote

URL	http://localhost:8081/v1/fx/quotes
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "fromCurrency": "GBP", "toCurrency": "EUR", "fromAmount": 100.00 }
```

Expected Response

```
{ "id": "c3d4e5f6-a7b8-9012-cdef-345678901234", "fromCurrency": "GBP", "toCurrency": "EUR", "rate": 1.17, "fromAmount": 100.00, "toAmount": 117.00, "expiresAt": "2026-07-08T12:05:00Z" }
```

Scenario 045

Banking — Execute FX conversion

URL	http://localhost:8081/v1/fx/conversions
Method	POST
Authentication	Bearer JWT + Idempotency-Key
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "quoteId": "c3d4e5f6-a7b8-9012-cdef-345678901234", "fromAccountId": "acct-customer-1",  
  "toAccountId": "acct-customer-eur", "partyId": "party-customer-1" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "quoteId": "c3d4e5f6-a7b8-9012-cdef-345678901234",  
  "fromAmount": 100.00, "toAmount": 117.00, "fromCurrency": "GBP", "toCurrency": "EUR", "rate": 1.17,  
  "status": "COMPLETED" }
```

Scenario 046

Banking — Get FX conversion

URL	http://localhost:8081/v1/fx/conversions/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "fromCurrency": "GBP", "toCurrency": "EUR", "rate": 1.17, "fromAmount": 100.00, "toAmount": 117.00, "status": "COMPLETED" }
```

Scenario 047

Banking — List transactions

URL	http://localhost:8081/v1/transactions?accountId=acct-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "txnType": "PAYMENT", "status": "COMPLETED", "amount": 25.50, "currency": "GBP" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 048

Banking — Get transaction

URL	http://localhost:8081/v1/transactions/b2c3d4e5-f6a7-8901-bcde-f12345678901
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "txnType": "PAYMENT", "status": "COMPLETED", "amount": 25.50, "currency": "GBP", "accountId": "acct-customer-1" }
```

Scenario 049

Banking — List ledger entries

URL	http://localhost:8081/v1/ledger-entries?accountId=acct-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [ { "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "entryType": "DEBIT", "amount": 25.50, "currency": "GBP", "balanceAfter": 4974.50 }, ], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 050

Banking — Generate statement

URL	http://localhost:8081/v1/accounts/acct-customer-1/statements
Method	POST
Authentication	Bearer JWT

Expected Status	201 Created
-----------------	-------------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "periodStart": "2026-01-01", "periodEnd": "2026-01-31" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "accountId": "acct-customer-1", "periodStart": "2026-01-01", "periodEnd": "2026-01-31", "openingBalance": 5000.00, "closingBalance": 4974.50, "currency": "GBP", "status": "PUBLISHED" }
```

Scenario 051

Banking — List statements

URL	http://localhost:8081/v1/accounts/acct-customer-1/statements?page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "periodStart": "2026-01-01", "periodEnd": "2026-01-31", "status": "PUBLISHED" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 052

Banking — Get statement

URL	http://localhost:8081/v1/statements/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "accountId": "acct-customer-1", "periodStart": "2026-01-01", "periodEnd": "2026-01-31", "openingBalance": 5000.00, "closingBalance": 4974.50, "currency": "GBP", "lines": [{ "description": "Payment rent", "amount": -25.50, "postedAt": "2026-07-08T12:00:00Z" }] }
```

Scenario 053

Enterprise — Get health

URL	http://localhost:8082/health
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "status": "UP", "service": "enterprise-api", "components": { "database": "UP" } }
```

Scenario 054

Enterprise — Get version

URL	http://localhost:8082/version
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "name": "enterprise-api", "version": "0.1.0-SNAPSHOT" }
```

Scenario 055

Enterprise — Create loan

URL	http://localhost:8082/v1/loans
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "productCode": "PERSONAL",  
  "principal": 10000.00, "currency": "GBP", "interestRate": 5.5, "termMonths": 24 }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "accountId":  
  "acct-customer-1", "productCode": "PERSONAL", "principal": 10000.00, "currency": "GBP",  
  "interestRate": 5.5, "termMonths": 24, "status": "ACTIVE", "outstandingBalance": 10000.00 }
```

Scenario 056

Enterprise — Get loan

URL	http://localhost:8082/v1/loans/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "accountId": "acct-customer-1", "productCode": "PERSONAL", "principal": 10000.00, "currency": "GBP", "interestRate": 5.5, "termMonths": 24, "status": "ACTIVE", "outstandingBalance": 10000.00 }
```

Scenario 057

Enterprise — List loans

URL	http://localhost:8082/v1/loans?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"accountId": "acct-customer-1", "productCode": "PERSONAL", "principal": 10000.00, "currency": "GBP",  
"interestRate": 5.5, "termMonths": 24, "status": "ACTIVE", "outstandingBalance": 10000.00 }], "page":  
0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 058

Enterprise — Create loan repayment

URL	http://localhost:8082/v1/loans/a1b2c3d4-e5f6-7890-abcd-ef1234567890/repayments
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "amount": 500.00 }
```

Expected Response

```
{ "id": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "loanId": "a1b2c3d4-e5f6-7890-abcd-ef1234567890",  
"amount": 500.00, "currency": "GBP", "status": "COMPLETED" }
```

Scenario 059

Enterprise — Create fixed deposit

URL	http://localhost:8082/v1/fixed-deposits
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "principal": 5000.00, "currency": "GBP", "interestRate": 4.25, "termDays": 365 }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "principal": 5000.00, "currency": "GBP", "termDays": 365, "status": "ACTIVE", "maturityDate": "2027-07-08" }
```

Scenario 060

Enterprise — Get fixed deposit

URL	http://localhost:8082/v1/fixed-deposits/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "principal": 5000.00, "currency": "GBP", "termDays": 365, "status": "ACTIVE", "maturityDate": "2027-07-08" }
```

Scenario 061

Enterprise — List fixed deposits

URL	http://localhost:8082/v1/fixed-deposits?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo

Content-Type	application/json
--------------	------------------

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"principal": 5000.00, "currency": "GBP", "termDays": 365, "status": "ACTIVE", "maturityDate":  
"2027-07-08" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 062

Enterprise — Create recurring deposit

URL	http://localhost:8082/v1/recurring-deposits
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "installmentAmount": 200.00,  
"currency": "GBP", "frequency": "MONTHLY" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "installmentAmount": 200.00, "currency": "GBP",  
"frequency": "MONTHLY", "status": "ACTIVE" }
```

Scenario 063

Enterprise — Get recurring deposit

URL	http://localhost:8082/v1/recurring-deposits/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "installmentAmount":  
200.00, "currency": "GBP", "frequency": "MONTHLY", "status": "ACTIVE" }
```

Scenario 064

Enterprise — List recurring deposits

URL	http://localhost:8082/v1/recurring-deposits?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [ { "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"installmentAmount": 200.00, "currency": "GBP", "frequency": "MONTHLY", "status": "ACTIVE" } ],  
"page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 065

Enterprise — Post RD installment

URL	http://localhost:8082/v1/recurring-deposits/a1b2c3d4-e5f6-7890-abcd-ef1234567890/i
Method	POST
Authentication	Bearer JWT

Expected Status	201 Created
-----------------	-------------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "recurringDepositId":  
"a1b2c3d4-e5f6-7890-abcd-ef1234567890", "amount": 200.00, "currency": "GBP", "status": "PAID" }
```

Scenario 066

Enterprise — Create notification

URL	http://localhost:8082/v1/notifications
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "channel": "EMAIL", "subject": "Loan approved", "body": "Your loan has been approved." }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "channel": "EMAIL", "subject": "Loan approved", "status": "UNREAD" }
```

Scenario 067

Enterprise — List notifications

URL	http://localhost:8082/v1/notifications?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "channel": "EMAIL", "subject": "Loan approved", "status": "UNREAD" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 068

Enterprise — Mark notification read

URL	http://localhost:8082/v1/notifications/a1b2c3d4-e5f6-7890-abcd-ef1234567890/read
Method	PATCH
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "channel": "EMAIL", "subject": "Loan approved", "status": "READ", "readAt": "2026-07-08T12:00:00Z" }
```

Scenario 069

Enterprise — Register document

URL	http://localhost:8082/v1/documents
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "documentType": "PASSPORT", "fileName": "passport.pdf",  
  "contentType": "application/pdf" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "documentType":  
  "PASSPORT", "fileName": "passport.pdf", "status": "UPLOADED" }
```

Scenario 070

Enterprise — Get document

URL	http://localhost:8082/v1/documents/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT

Expected Status	200 OK
-----------------	--------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "documentType": "PASSPORT", "fileName": "passport.pdf", "contentType": "application/pdf", "status": "UPLOADED" }
```

Scenario 071

Enterprise — List documents

URL	http://localhost:8082/v1/documents?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}

X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"documentType": "PASSPORT", "fileName": "passport.pdf", "status": "UPLOADED" }], "page": 0, "size":  
20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 072

Enterprise — Generate report

URL	http://localhost:8082/v1/reports
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "reportType": "LOAN_PORTFOLIO", "parameters": "partyId=party-customer-1" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "reportType": "LOAN_PORTFOLIO", "status": "PENDING" }
```

Scenario 073

Enterprise — Get report

URL	http://localhost:8082/v1/reports/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "reportType": "LOAN_PORTFOLIO", "status":  
"COMPLETED", "resultLocation": "/reports/a1b2c3d4-e5f6-7890-abcd-ef1234567890.csv", "generatedAt":  
"2026-07-08T12:00:00Z" }
```

Scenario 074

Enterprise — List reports

URL	http://localhost:8082/v1/reports?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [ { "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "reportType": "LOAN_PORTFOLIO", "status": "COMPLETED", "resultLocation": "/reports/a1b2c3d4-e5f6-7890-abcd-ef1234567890.csv" } ], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 075

Enterprise — Fraud screen (alert)

URL	http://localhost:8082/v1/fraud/screen
Method	POST
Authentication	Bearer JWT

Expected Status	201 Created
-----------------	-------------

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "entityType": "PAYMENT", "entityId": "pay-lab-1", "amount": 6000.00 }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "entityType": "PAYMENT", "entityId": "pay-lab-1", "ruleCode": "VELOCITY", "riskScore": 85, "status": "OPEN", "details": "Amount exceeds velocity threshold" }
```

Scenario 076

Enterprise — Fraud screen (no alert)

URL	http://localhost:8082/v1/fraud/screen
Method	POST
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
--------	-------

Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "entityType": "PAYMENT", "entityId": "pay-lab-2", "amount": 100.00 }
```

Expected Response

None (empty body)

Note: Amount 100.00 is below fraud.velocity.threshold (5000). Response has no JSON body.

Scenario 077

Enterprise — List fraud alerts

URL	http://localhost:8082/v1/fraud/alerts?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"entityType": "PAYMENT", "entityId": "pay-lab-1", "ruleCode": "VELOCITY", "riskScore": 85, "status":  
"OPEN", "details": "Amount exceeds velocity threshold" }], "page": 0, "size": 20, "totalElements": 1,  
"totalPages": 1, "nextCursor": null }
```

Scenario 078

Enterprise — Review fraud alert

URL	http://localhost:8082/v1/fraud/alerts/a1b2c3d4-e5f6-7890-abcd-ef1234567890/review
Method	PATCH
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "status": "REVIEWED" }
```

Expected Response


```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "status": "REVIEWED", "reviewedAt": "2026-07-08T12:00:00Z" }
```

Scenario 079

Enterprise — Create AML case

URL	http://localhost:8082/v1/aml/cases
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "partyId": "party-customer-1", "caseType": "SANCTIONS", "priority": "HIGH" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "caseType": "SANCTIONS", "status": "OPEN", "priority": "HIGH" }
```

Scenario 080

Enterprise — Get AML case

URL	http://localhost:8082/v1/aml/cases/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "caseType": "SANCTIONS", "status": "OPEN", "priority": "HIGH" }
```

Scenario 081

Enterprise — List AML cases

URL	http://localhost:8082/v1/aml/cases?partyId=party-customer-1&page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1",  
"caseType": "SANCTIONS", "status": "OPEN", "priority": "HIGH" }], "page": 0, "size": 20,  
"totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 082

Enterprise — Submit AML screening

URL	http://localhost:8082/v1/aml/screenings
Method	POST
Authentication	Bearer JWT
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo

Content-Type	application/json
--------------	------------------

Request Body

```
{ "partyId": "party-customer-1", "screeningType": "SANCTIONS" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "partyId": "party-customer-1", "screeningType": "SANCTIONS", "result": "CLEAR", "matchScore": 0 }
```

Scenario 083

Enterprise — List admin settings

URL	http://localhost:8082/v1/admin/settings
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
[{ "settingKey": "fraud.velocity.threshold", "settingValue": "5000", "updatedBy": "user-admin" }, { "settingKey": "aml.auto_escalate_score", "settingValue": "80", "updatedBy": "user-admin" }]
```

Scenario 084

Enterprise — Get admin setting

URL	http://localhost:8082/v1/admin/settings/fraud.velocity.threshold
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "settingKey": "fraud.velocity.threshold", "settingValue": "5000", "updatedBy": "user-admin" }
```

Scenario 085

Enterprise — Update admin setting

URL	http://localhost:8082/v1/admin/settings/fraud.velocity.threshold
-----	--

Method	PUT
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "settingValue": "6000" }
```

Expected Response

```
{ "settingKey": "fraud.velocity.threshold", "settingValue": "6000" }
```

Scenario 086

Enterprise — Admin as customer (negative)

URL	http://localhost:8082/v1/admin/settings
Method	GET
Authentication	Bearer JWT (customer)
Expected Status	403 Forbidden

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "title": "Forbidden", "status": 403, "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 087

Enterprise — List audit events

URL	http://localhost:8082/v1/audit/events?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "entityType": "PAYMENT", "action": "CREATE", "actorId": "user-customer", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 088

Enterprise — List domain events

URL	http://localhost:8082/v1/events?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "eventType": "FRAUD_ALERT_CREATED", "status": "PUBLISHED" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```


Scenario 089

Enterprise — Submit job

URL	http://localhost:8082/v1/jobs
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "jobType": "REPORT_GENERATION", "payload": "reportId=abc-123" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "jobType": "REPORT_GENERATION", "status": "PENDING", "progress": 0 }
```

Scenario 090

Enterprise — Get job

URL	http://localhost:8082/v1/jobs/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	GET

Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "jobType": "REPORT_GENERATION", "status": "COMPLETED", "progress": 100, "completedAt": "2026-07-08T12:01:00Z" }
```

Scenario 091

Enterprise — List jobs

URL	http://localhost:8082/v1/jobs?page=0&size=20
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
--------	-------

Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "jobType": "REPORT_GENERATION", "status": "COMPLETED", "progress": 100 }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 092

Enterprise — List scheduler tasks

URL	http://localhost:8082/v1/scheduler/tasks?page=0&size=20
Method	GET
Authentication	Bearer JWT
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "sched-rd-reminder", "taskType": "RD_INSTALLMENT_REMINDER", "cronExpression": "0 0 9 * * *", "enabled": true }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 093

Enterprise — Register scheduler task

URL	http://localhost:8082/v1/scheduler/tasks
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "taskType": "RD_INSTALLMENT_REMINDER", "cronExpression": "0 0 9 * * *", "payload": {"partyId": "party-customer-1"} }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "taskType": "RD_INSTALLMENT_REMINDER", "enabled": true }
```

Scenario 094

Enterprise — Register webhook

URL	http://localhost:8082/v1/webhooks
Method	POST
Authentication	Bearer JWT (ops/admin)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

```
{ "eventType": "FRAUD_ALERT_CREATED", "targetUrl": "http://localhost:8083/v1/mocks/webhooks/fail",  
  "secret": "my-hmac-secret" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "eventType": "FRAUD_ALERT_CREATED", "targetUrl":  
  "http://localhost:8083/v1/mocks/webhooks/fail", "status": "ACTIVE" }
```

Scenario 095

Enterprise — List webhooks

URL	http://localhost:8082/v1/webhooks?page=0&size=20
Method	GET

Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "eventType": "FRAUD_ALERT_CREATED", "targetUrl": "http://localhost:8083/v1/mocks/webhooks/fail", "status": "ACTIVE" }], "page": 0, "size": 20, "totalElements": 1, "totalPages": 1, "nextCursor": null }
```

Scenario 096

Enterprise — List webhook deliveries

URL	http://localhost:8082/v1/webhooks/a1b2c3d4-e5f6-7890-abcd-ef1234567890/deliveries?
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "items": [{ "id": "b2c3d4e5-f6a7-8901-bcde-f12345678901", "webhookId":  
"a1b2c3d4-e5f6-7890-abcd-ef1234567890", "status": "DLQ", "attemptCount": 3, "httpStatus": 500,  
"lastAttemptAt": "2026-07-08T12:00:00Z" }], "page": 0, "size": 20, "totalElements": 1, "totalPages":  
1, "nextCursor": null }
```

Scenario 097

Enterprise — List circuit breakers

URL	http://localhost:8082/v1/resilience/circuit-breakers
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
[{ "name": "webhook-delivery", "state": "CLOSED", "failureCount": 0, "successCount": 10 }]
```

Scenario 098

Enterprise — Get circuit breaker

URL	http://localhost:8082/v1/resilience/circuit-breakers/webhook-delivery
Method	GET
Authentication	Bearer JWT (ops/admin)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Bearer {{admin_jwt}}
X-Tenant-Id	tenant-demo
Content-Type	application/json

Request Body

None

Expected Response

```
{ "name": "webhook-delivery", "state": "CLOSED", "failureCount": 0, "successCount": 10 }
```


Scenario 099

Lab — Get health

URL	http://localhost:8083/health
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "status": "UP", "service": "playground-api", "components": { "database": "UP" } }
```

Scenario 100

Lab — Get version

URL	http://localhost:8083/version
Method	GET
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "name": "playground-api", "version": "0.1.0-SNAPSHOT" }
```

Scenario 101

Lab — Reset all data

URL	http://localhost:8083/v1/playground/reset
Method	POST
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy
Content-Type	application/json

Request Body

```
{ "scope": "ALL" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "scope": "ALL", "status": "COMPLETED", "details": "Playground lab tables cleared; Banking transactional data cleared; Enterprise transactional data cleared" }
```

Scenario 102

Lab — List scenarios

URL	http://localhost:8083/v1/scenarios
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
[{ "slug": "payment-happy-path", "title": "Payment Happy Path", "difficulty": "L1" }, { "slug": "idempotency-replay", "title": "Idempotency Replay", "difficulty": "L2" }]
```

Scenario 103

Lab — Get scenario payment-happy-path

URL	http://localhost:8083/v1/scenarios/payment-happy-path
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "slug": "payment-happy-path", "title": "Payment Happy Path", "difficulty": "L1",
"learningObjectives": ["LO-REST-01", "LO-REST-08"], "tags": ["payments", "idempotency"],
"description": "Authenticate as customer, create a payment to a seeded beneficiary, and verify ledger
balance decreases. Replay with the same Idempotency-Key to observe safe retry.", "steps": [ {
"action": "login", "service": "banking-api", "path": "POST /v1/auth/login" }, { "action":
"create_payment", "service": "banking-api", "path": "POST /v1/payments", "headers": {
"Idempotency-Key": "{{uuid}}" } }, { "action": "verify_transaction", "service": "banking-api",
"path": "GET /v1/transactions" } ], "rubric": [ { "signal": "payment.status", "expected": "COMPLETED"
}, { "signal": "idempotency.replayed", "expected": false } ], "expectedSignals": [ "correlationId
present in response", "application/problem+json on validation errors" ] }
```

Scenario 104

Lab — Start scenario run

URL	http://localhost:8083/v1/scenarios/payment-happy-path/runs
Method	POST
Authentication	Basic (learner/learner)

Expected Status	201 Created
-----------------	-------------

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "scenarioSlug": "payment-happy-path", "status": "RUNNING", "startedAt": "2026-07-08T12:00:00Z", "completedAt": null }
```

Scenario 105

Lab — Complete scenario run

URL	http://localhost:8083/v1/scenarios/runs/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	PATCH
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy
Content-Type	application/json

Request Body

```
{ "status": "COMPLETED" }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "scenarioSlug": "payment-happy-path", "status": "COMPLETED", "startedAt": "2026-07-08T12:00:00Z", "completedAt": "2026-07-08T12:05:00Z" }
```

Scenario 106

Lab — List contracts

URL	http://localhost:8083/v1/contracts
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
[{ "service": "banking-api", "filename": "openapi.yaml" }, { "service": "enterprise-api", "filename": "openapi.yaml" }]
```

Scenario 107

Lab — Get contract file

URL	http://localhost:8083/v1/contracts/banking-api/openapi.yaml
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "service": "banking-api", "filename": "openapi.yaml", "content": "openapi: 3.1.0\ninfo:\n  title: Banking API\n  version: 0.1.0-SNAPSHOT\nservers:\n  - url: http://localhost:8081\npaths:\n  /v1/auth/login:\n    post:\n      summary: Login\n"} }
```

Scenario 108

Lab — List config

URL	http://localhost:8083/v1/playground/config
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
[{ "key": "default_tenant", "value": "tenant-demo" }, { "key": "reset_enabled", "value": "true" }]
```

Scenario 109

Lab — Get config key

URL	http://localhost:8083/v1/playground/config/default_tenant
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "key": "default_tenant", "value": "tenant-demo" }
```

Scenario 110

Lab — Update config

URL	http://localhost:8083/v1/playground/config/default_tenant
Method	PUT
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy
Content-Type	application/json

Request Body

```
{ "value": "tenant-demo" }
```

Expected Response

```
{ "key": "default_tenant", "value": "tenant-demo" }
```

Scenario 111

Lab — List fault rules

URL	http://localhost:8083/v1/playground/faults
-----	--

Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

[]

Scenario 112

Lab — Create fault rule

URL	http://localhost:8083/v1/playground/faults
Method	POST
Authentication	Basic (learner/learner)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Content-Type	application/json
--------------	------------------

Request Body

```
{ "targetService": "BANKING", "pathPattern": "/v1/payments", "faultType": "LATENCY", "config": {  
  "delayMs": 500 } }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "targetService": "BANKING", "pathPattern":  
"/v1/payments", "faultType": "LATENCY", "enabled": true }
```

Scenario 113

Lab — Disable fault rule

URL	http://localhost:8083/v1/playground/faults/a1b2c3d4-e5f6-7890-abcd-ef1234567890
Method	DELETE
Authentication	Basic (learner/learner)
Expected Status	204 No Content

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

None (empty body)

Scenario 114

Lab — List mocks

URL	http://localhost:8083/v1/playground/mocks
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
[{ "path": "/v1/mocks/aMl/screen/clear", "httpMethod": "POST", "statusCode": 200 }]
```

Scenario 115

Lab — Create mock

URL	http://localhost:8083/v1/playground/mocks
Method	POST
Authentication	Basic (learner/learner)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY
Content-Type	application/json

Request Body

```
{ "path": "/v1/mocks/webhooks/fail", "httpMethod": "POST", "statusCode": 500, "responseBody":  
  "{ \"error\": \"fail\" }", "delayMs": 0, "enabled": true }
```

Expected Response

```
{ "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "path": "/v1/mocks/webhooks/fail", "statusCode": 500  
}
```

Scenario 116

Lab — Call AML clear mock (public)

URL	http://localhost:8083/v1/mocks/aml/screen/clear
Method	POST
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{}
```

Expected Response

```
{ "result": "CLEAR", "matchScore": 0 }
```

Scenario 117

Lab — Call AML review mock (public)

URL	http://localhost:8083/v1/mocks/aml/screen/review
Method	POST
Authentication	None
Expected Status	200 OK

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{}
```

Expected Response

```
{ "result": "REVIEW", "matchScore": 75 }
```

Scenario 118

Lab — Generate test data

URL	http://localhost:8083/v1/playground/test-data
Method	POST
Authentication	Basic (learner/learner)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy
Content-Type	application/json

Request Body

```
{ "namespace": "lab-session-1", "profile": "retail-customer" }
```

Expected Response

```
[{ "namespace": "lab-session-1", "entityType": "PARTY", "entityId": "party-customer-1" }, {
"namespace": "lab-session-1", "entityType": "ACCOUNT", "entityId": "acct-customer-1" }]
```

Scenario 119

Lab — List test data handles

URL	http://localhost:8083/v1/playground/test-data?namespace=lab-session-1
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
[{ "namespace": "lab-session-1", "entityType": "PARTY", "entityId": "party-customer-1" }]
```

Scenario 120

Lab — Delete test data namespace

URL	http://localhost:8083/v1/playground/test-data/lab-session-1
Method	DELETE
Authentication	Basic (learner/learner)
Expected Status	204 No Content

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

None (empty body)

Scenario 121

Lab — Generate seed

URL	http://localhost:8083/v1/playground/seed
Method	POST
Authentication	Basic (learner/learner)
Expected Status	201 Created

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy
Content-Type	application/json

Request Body

```
{ "profile": "retail-customer" }
```

Expected Response

```
{ "profile": "retail-customer", "entities": { "party": "party-customer-1", "account":  
"acct-customer-1" } }
```

Scenario 122

Lab — Get dashboard

URL	http://localhost:8083/v1/playground/dashboard
-----	---

Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "serviceHealth": { "playground-api": "UP", "platform-api": "UP", "banking-api": "UP",
"enterprise-api": "UP" }, "scenarioCount": 6, "activeFaultCount": 0, "recentRuns": [],
"configSummary": [{ "key": "default_tenant", "value": "tenant-demo" }] }
```

Scenario 123

Lab — List performance profiles

URL	http://localhost:8083/v1/playground/performance/profiles
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
--------	-------

Authorization	Basic bGVhcm5lcjpsZWYbmVY
---------------	---------------------------

Request Body

None

Expected Response

```
{ "profiles": [{ "name": "payment-throughput", "targetPath": "/v1/payments", "method": "POST", "suggestedVUs": 20, "durationSec": 120 }] }
```

Scenario 124

Lab — List security test cases

URL	http://localhost:8083/v1/playground/security/test-cases
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
[{ "id": "bola-party-read", "category": "BOLA", "expectedStatus": 403, "method": "GET", "path": "/v1/parties/party-other" }]
```

Scenario 125

Lab — List concurrency scenarios

URL	http://localhost:8083/v1/playground/concurrency/scenarios
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWZybWVy

Request Body

None

Expected Response

```
[{ "slug": "concurrent-transfer-race", "title": "Concurrent Transfer Race" }]
```

Scenario 126

Lab — Get race profile

URL	http://localhost:8083/v1/playground/concurrency/scenarios/concurrent-transfer-race
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYybmVy

Request Body

None

Expected Response

```
{ "slug": "concurrent-transfer-race", "service": "banking-api", "method": "POST", "path":  
"/v1/transfers", "concurrency": 5 }
```

Scenario 127

Lab — List failure simulations

URL	http://localhost:8083/v1/playground/failures
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYybmVy

Request Body

None

Expected Response

```
[{ "slug": "banking-latency-spike", "title": "Banking API Latency Spike" }]
```

Scenario 128

Lab — Get failure simulation

URL	http://localhost:8083/v1/playground/failures/banking-latency-spike
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "slug": "banking-latency-spike", "faultType": "LATENCY", "pathPattern": "/v1/payments/**",  
  "config": { "delayMs": 2000 } }
```

Scenario 129

Lab — Get scenario idempotency-replay

URL	http://localhost:8083/v1/scenarios/idempotency-replay
-----	---

Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "slug": "idempotency-replay", "title": "Idempotency Replay", "difficulty": "L2",
  "learningObjectives": ["LO-REST-08"], "tags": ["payments", "idempotency"], "description": "Submit the
  same payment twice with an identical Idempotency-Key and body. The second response must replay the
  first without double-posting.", "steps": [ { "action": "login", "service": "banking-api" }, {
  "action": "create_payment", "service": "banking-api", "note": "Use fixed Idempotency-Key idem-lab-1"
  }, { "action": "replay_payment", "service": "banking-api", "note": "Same key and body – expect
  replay" } ], "rubric": [ { "signal": "second_response.replayed", "expected": true }, { "signal":
  "account.balance_delta", "expected": "single_debit_only" } ] }
```

Scenario 130

Lab — Get scenario fraud-velocity-alert

URL	http://localhost:8083/v1/scenarios/fraud-velocity-alert
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "slug": "fraud-velocity-alert", "title": "Fraud Velocity Alert", "difficulty": "L2",  
  "learningObjectives": ["LO-ASYNC-02"], "tags": ["fraud", "enterprise-api"], "description": "Screen a  
high-value transaction via enterprise-api fraud endpoint and verify an OPEN alert is created when  
amount exceeds velocity threshold.", "steps": [ { "action": "login", "service": "banking-api" }, {  
  "action": "fraud_screen", "service": "enterprise-api", "path": "POST /v1/fraud/screen", "body": {  
    "amount": 6000.00 } } ], "rubric": [ { "signal": "alert.status", "expected": "OPEN" }, { "signal":  
  "alert.riskScore", "expected": 85 } ] }
```

Scenario 131

Lab — Get scenario webhook-retry-dlq

URL	http://localhost:8083/v1/scenarios/webhook-retry-dlq
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVY

Request Body

None

Expected Response

```
{ "slug": "webhook-retry-dlq", "title": "Webhook Retry and DLQ", "difficulty": "L3",  
  "learningObjectives": ["LO-ASYNC-02", "LO-RES-01"], "tags": ["webhooks", "resilience"],  
  "description": "Register a webhook pointing to a failing mock URL, trigger an event, and observe  
  retry attempts before DLQ status.", "steps": [ { "action": "login_as_ops", "service": "banking-api"  
}, { "action": "register_webhook", "service": "enterprise-api", "target_url":  
"http://localhost:8083/v1/mocks/webhooks/fail" }, { "action": "trigger_event", "service":  
"enterprise-api" } ], "rubric": [ { "signal": "delivery.attempt_count", "expected": ">1" }, {  
"signal": "delivery.final_status", "expected": "DLQ" } ] }
```

Scenario 132

Lab — Get scenario concurrent-transfer-race

URL	http://localhost:8083/v1/scenarios/concurrent-transfer-race
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYybmVy

Request Body

None

Expected Response

```
{ "slug": "concurrent-transfer-race", "title": "Concurrent Transfer Race", "difficulty": "L3",  
  "learningObjectives": ["LO-REST-11"], "tags": ["concurrency", "transfers"], "description": "Fire  
  parallel transfers from the same account and observe optimistic locking (409 Conflict) when balances  
  race.", "steps": [ { "action": "login", "service": "banking-api" }, { "action": "parallel_transfers",  
  "service": "banking-api", "concurrency": 5 } ], "rubric": [ { "signal": "at_least_one.conflict",  
  "expected": true }, { "signal": "final_balance.consistent", "expected": true } ] }
```

Scenario 133

Lab — Get scenario bola-party-access

URL	http://localhost:8083/v1/scenarios/bola-party-access
Method	GET
Authentication	Basic (learner/learner)
Expected Status	200 OK

Request Headers

Header	Value
Authorization	Basic bGVhcm5lcjpsZWYbmVy

Request Body

None

Expected Response

```
{ "slug": "bola-party-access", "title": "BOLA Party Access", "difficulty": "L2",  
  "learningObjectives": ["LO-SEC-12"], "tags": ["security", "authorization"], "description": "Verify a  
  retail customer cannot read another party's account. Use JWT party_id mismatch and expect 403  
  Forbidden with RFC 7807 problem+json.", "steps": [ { "action": "login_as_customer", "service":  
  "banking-api" }, { "action": "access_other_party", "service": "banking-api", "path": "GET  
  /v1/parties/party-other", "expect_status": 403 } ], "rubric": [ { "signal": "response.content_type",  
  "expected": "application/problem+json" }, { "signal": "response.status", "expected": 403 } ] }
```

Scenario 134

Banking — Login invalid password

URL	http://localhost:8081/v1/auth/login
Method	POST

Authentication	None
Expected Status	401 Unauthorized

Request Headers

Header	Value
Content-Type	application/json

Request Body

```
{ "tenantId": "tenant-demo", "username": "customer", "password": "wrong" }
```

Expected Response

```
{ "title": "Unauthorized", "status": 401, "detail": "Invalid credentials", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 135

Banking — Wrong tenant header

URL	http://localhost:8081/v1/accounts?partyId=party-customer-1
Method	GET
Authentication	Bearer JWT
Expected Status	403 Forbidden

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	wrong-tenant

Content-Type	application/json
--------------	------------------

Request Body

None

Expected Response

```
{ "title": "Forbidden", "status": 403, "detail": "X-Tenant-Id does not match token tenant",  
  "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 136

Banking — Idempotency conflict

URL	http://localhost:8081/v1/payments
Method	POST
Authentication	Bearer JWT + Idempotency-Key
Expected Status	409 Conflict

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	fixed-key-123

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount":  
99.00, "currency": "GBP", "reference": "conflict" }
```

Expected Response

```
{ "title": "Conflict", "status": 409, "detail": "Idempotency-Key was already used with a different request body", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Note: Send after successful payment with same key but different amount.

Scenario 137

Banking — Insufficient funds

URL	http://localhost:8081/v1/payments
Method	POST
Authentication	Bearer JWT + Idempotency-Key
Expected Status	400 Bad Request

Request Headers

Header	Value
Authorization	Bearer {{jwt_token}}
X-Tenant-Id	tenant-demo
Content-Type	application/json
Idempotency-Key	{{idempotency_key}}

Request Body

```
{ "partyId": "party-customer-1", "accountId": "acct-customer-1", "beneficiaryId": "ben-1", "amount": 999999.00, "currency": "GBP", "reference": "too-much" }
```

Expected Response

```
{ "title": "Bad Request", "status": 400, "detail": "Insufficient funds", "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```

Scenario 138

Lab — Scenarios without auth

URL	http://localhost:8083/v1/scenarios
Method	GET
Authentication	None
Expected Status	401 Unauthorized

Request Headers

Header	Value
Accept	application/json

Request Body

None

Expected Response

```
{ "title": "Unauthorized", "status": 401, "correlationId": "c1d2e3f4-a5b6-7890-cdef-123456789abc" }
```