



Undimensioned edges

-0.2
-0.5

+0.2

General roughness: Ra 1.6

Minimal Dimensioned TPD

Geometry of .STEP file is leading

For all surfaces $\sqrt{0.2}$ A B C

For all cylindrical holes $\phi 0.3$ A B C

Tolerances on cylindrical hole diameter +/-0.1

Tolerances on hole/thread depth 0/+1

NOBLEO
TECHNOLOGY

DIMENSIONS ARE IN **MM**
INCL SURFACE/AFTER TREATMENT
UNLESS OTHERWISE SPECIFIED
DIM WITHOUT TOLERANCE ISO 2768mk
GEOMETRIC TOLERANCES ISO 1101
BREAK SHARP EDGES ISO 13715
ROUGHNESS ISO 1302
PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
NOBLEO TECHNOLOGY B.V.
ANY REPRODUCTION WITHOUT THE
WRITTEN PERMISSION OF NOBLEO
TECHNOLOGY B.V. IS PROHIBITED.

DOCUMENT STATUS		CREATED BY VS	
--		CREATION DATE 22-07-2025	
		APPROVED BY --	
		APPROVAL DATE --/--/----	
MATERIAL		DRW NR	
1.4305 (X8CrNiS18-9)		PB-P-0306 - ELBOW.0	
SURFACE/HEAT/AFTER TREATMENT		REVISION	
Untreated/Uncoated		CABLE PULLEY	
ESTIMATED MASS: 0.02 KG		SHEET	
		1 OF 1	
		SCALE	
		2:1	
		A3	