

THIEN NGHIA CO., LTDFloor 7th, Perfect Building, 150 Bis Le Thi Hong Gam St, Cau Ong Lanh Ward , Dist 01, HCMC

Phone : 08. 2990540 Fax: 08. 2990528



CHEMSTATIONASIA

Material Safety Data Sheet

R&D DEPARTMENT

Revision: 05th January 2024

Chemical product and company identification

Product Details:

Product Name : **Thinner**
Trade Name : **Thinner**
Product Code : **Thinner –CT1**
Chemical Name :
Application : **Thinner Reducer**

Company Identification:

Seller Name : Thien Nghia Co., Ltd
Address : 150 bis Le Thi Hong Gam Street, Ward Cau Ong
Lanh, District 1, Hochiminh, Vietnam
Telephone Number : +84 28 6299 0540
Fax Number : +84 28 6299 0534

Composition / information on ingredients

<u>Ingredients</u>	<u>CAS number</u>	<u>Approx % weigh</u>	<u>Expose limits</u>
Toluene	108-88-3	10 – 15	100 ppm
Acetone	67-64-1	85 - 90	250 ppm

Physical and chemical properties

Appearance : **Clear,colorless Liquid**
Odour : **Solvent smell**
Boiling Point : **Toluene 111 °C (232 °F; 384 K)**
Melting Point : **Toluene Melting point, -95 °C (-139 °F; 178 K)**
Boiling point, : **Acetone, 56.05 °C (132.89 °F; 329.20 K)**
Melting Point : **Acetone -95.4 °C**
Specific Gravity : **0.791 ± 0.05 g/cm³**
Flash Point : **40°F (based on Toluene)**
Flash Point : **-18°C (based on Acetone)**

Hazard identification

Health Hazards:

- Harmful by inhalation and in contact with skin.
- Irritating to skin.

Environmental Hazards:

- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Physical and Chemical Hazards / Fire and Explosion Hazards:
 - High hazard. Liquids can release vapors that can readily form flammable mixtures at room temperatures.
 - Static Discharge. Product can accumulate static charges which can cause an incendiary electrical discharge.

First aid measures

Inhalation:

- Bring the patient to fresh air, if unconscious, keep breathing passages open.
If patient does not recover, seek medical attention.

Skin Contact:

- Contact with skin is relatively low irritant. If exposure is prolonged however, wash skin with soap and warm water or detergent.

Eye Contact:

- Flush eye with water or any approved eye wash solution, and seek medical attention if required.

Ingestion:

THIEN NGHIA CO., LTD

Floor 7th, Perfect Building, 150 Bis Le Thi Hong Gam St, Cau Ong Lanh Ward , Dist 01, HCMC

Phone : 08. 2990540 Fax: 08. 2990528



CHEMSTATION ASIA

- Give water or milk. Vomiting may cause aspiration of solvents and must therefore not be induced. Get medical attention.

Fire fighting measures

General:

- Material is relatively flammable. Keep away from open flame and sparks. After spillage, leakage, keep away from drains and other water systems.

Extinguishing Media:

- Use dry powder, foam, carbon dioxide or Halon extinguishers. Never use water stream due to the possibility to float burning material and thus spread the fire.

Accidental release measure

Once spilled, immediately absorb in vermiculite or dry sand and dispose in licensed special waste agents. Confirm disposal procedures with environmental engineer and local regulations.

Handling and storage

Handling:

- Ensure adequate ventilation or exhaust ventilation in the working area. Exhaust ventilation necessary if product is sprayed. Avoid contact with skin and eyes.

Storage:

- Store in closed containers. Avoid heat sources, sparks, open flames, and high temperature. Provide good housekeeping and cleanliness at all times. Ensure efficient and effective ventilation.

Exposure control and personal protection

Engineering Control Measures / Ventilation:

- The use of local exhaust ventilation is recommended to control process emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

Respiratory Protection:

- Where concentrations in air may exceed the limits given in this section, it is recommended to use a half face filter mask to protect from over exposure by inhalation.

Hand Protection:

- When handling this product, it is recommended to wear chemical resistant gauntlets. The choice of suitable protective gloves depends on work conditions and what chemicals are handled, but we have positive experience with gloves made of Nitrile. Gloves should be replaced immediately if sign of degradation is observed.

Eye protection:

- When handling this product, it is recommended to wear safety glasses and a face shield.

Skin / Body Protection:

- When handling this product, it is recommended to wear a chemical resistant apron, jacket and rubber boots.

Stability and reactivity

Materials/Conditions to Avoid:

- Heat, strong oxidizing agent, sparks

Thermal Decomposition Products:

- May release toxic fumes

Hazardous Polymerization:

- Will not occur.

Toxicological information

Acute Toxicity:

Dermal :

Toluene 108-88-3

LD50 (Rabbit): 12.124 mg/kg

LD50 (Rat): 5000 mg/kg

Toxicological Data:

Acetone 67-64-1

Oral Rat LD50: 5800 mg/kg

Skin Rabbit LD50: 20000 mg/kg

Inhalation Rat LC50: 76 mg/L 4H

THIEN NGHIA CO., LTD

Floor 7th, Perfect Building, 150 Bis Le Thi Hong Gam St, Cau Ong Lanh Ward , Dist 01, HCMC

Phone : 08. 2990540 Fax: 08. 2990528

**CHEMSTATIONASIA****General:**

- Toxicity of the product depends on the overexposure of the content of organic solvents which are mixed in this product.

Inhalation:

- Irritation of the eyes and mucous membranes and absorption of solvents. Signs of overexposure may be one of the following like headache, dizziness, vomiting that may lead to unconsciousness. Chronic exposure may cause impairment of brain functions, liver and kidney damages.

Ingestion:

- There is a high risk of aspiration of solvents to the lungs.

Skin Contact:

- May cause sensitization of the skin for prolonged contact.

Eye Contact:

- Splashes or vapor from the product give irritation and / or burning sensation due to the organic contents.

Ecological information**Mobility & Bioaccumulation:**

- Some substances of this product will rapidly evaporate to the air if released on water. Not expected to bioaccumulate in aquatic organisms.

Biodegradability:

- Readily Biodegradable

Disposal information

Product treatment and disposal must be technically evaluated. For further information consult supplier. Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or license contractor. Case should in any case be taken to ensure compliance with national and local regulations. This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers.

Transport information**Road Transport:**

UN No. Road 1263
Class 3

Packaging information:

Protect oil

Regulatory information**Classification and Labelling:**

- Classification / symbol: **Flammable / F-**
- Governing Directive:
Occupational Safety and Health (Classification, Packaging and Labeling of Hazardous Chemicals) Regulations 1997
- Nature of Special Risk
R10 Flammable
R20/21 Harmful by inhalation and in contact with skin
R38 Irritating to skin
- Safety Advice
(May contain information in excess of requirements under applicable laws)
S25 Avoid contact with eyes
S33 Take precautionary measures against static discharges
S36 Wear suitable protective clothing
S43A In case of fire use sand, earth, chemical powder or foam

Other information

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of **Deh Fu Company's** knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty

THIEN NGHIA CO., LTD

Floor 7th, Perfect Building, 150 Bis Le Thi Hong Gam St, Cau Ong Lanh Ward , Dist 01, HCMC

Phone : 08. 2990540 Fax: 08. 2990528



CHEMSTATION ASIA

or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.