Efficient Vocabulary Discovery in Late Antique Texts-Code Examples

Andrew J. Hayes May 22, 2025

The following are the code examples interactively demonstrated in the presentation. Each example follows the number that designates it.

```
(1)
lualatex -output-dir=build repaginate.tex
(2)
pdfgrep -e '[Ss]ch[aä]tz' HdE\ German.pdf -H --page-number=label
(3)
pdfgrep -e '[Ss]ch[aä]tz' HdE\ German.pdf -H -c
(4)
pdfgrep -e '[Ss]ch[aä]tz' HdE\ German.pdf HdV\ German.pdf -c
(5)
pdfgrep *.pdf -e 'G[aei]hen(n)?a' --page-number=label -H
(6)
pdfgrep -i -e '([Kk]ingdom)|(Königtum)|(\(Himmel\)[Rr]eich)' --page-number=label -H *.pdf
(7)
pdfgrep -P '(?<![Zz]u )Ende(?! des [a-z])'</pre>
--page-number=label -H -C 3
--color=always *.pdf | grep -v -e '[Zz]u'
(8)
pdfgrep -P '(?<![Zz]u )Ende(?! des [a-z])'</pre>
--page-number=label -H
--color=always *.pdf | grep -v -e '[Zz]u'
(9)
pdfgrep -e '[Ss]ch[aä]tz' HdE\ German.pdf
-H --page-number=label > results.txt
```

```
(10)
pdfgrep *.pdf -e 'G[aei]hen(n)?a'
 --page-number=label | awk -f grep_to_csv.awk > gehenna.csv
(11)
BEGIN { FS = ":"; print "text", ",", "citation" }
    cutoff = index($1, " ");
   # print "cutoff index is " cutoff # for debugging purposes
    print substr($1, 1, cutoff) ",", $2
}
```

^{© 2025} Andrew Hayes. This work (apart from any source code it contains) is licensed under CC BY 4.0. To view a copy of this license, visit https://creativecommons.org/licenses/by/4.0/.