## Monkey knows SE! ()

☆ Home (/)  $\blacksquare$  Posts (/posts)  $\blacktriangle$  Friends (/friends)  $\boxdot$  Contact (/contact)

QSearch (/search) GitHub (https://github.com/lumiere000/blog)

## teampass server with docker-compose

[ docker (/tag/docker) password (/tag/password) tools (/tag/tools) management (/tag/management) webbased (/tag/webbased) ]

docker-compose.yaml :

```
version: "3"
services:
  nginx:
    image: jwilder/nginx-proxy:alpine
    restart: always
    networks:
      - frontend
    ports:
      - "443:443"
      - "80:80"
    volumes:
      - ./volumes/ssl:/etc/nginx/certs
      - /var/run/docker.sock:/tmp/docker.sock:ro
  teampass:
    image: teampass/teampass
    restart: always
    environment:
      VIRTUAL_HOST: teampass.yourdomain.local
    networks:
      - frontend
      - backend
    volumes:
      - ./volumes/teampass:/var/www/html
  db:
    restart: always
    image: mysql/mysql-server:5.7
    environment:
      MYSQL_ROOT_PASSWORD: mypass
      MYSQL_DATABASE: teampass
      MYSQL_PASSWORD: teampass
      MYSQL_USER: teampass
    volumes:
      - ./volumes/db:/var/lib/mysql
    networks:
      - backend
networks:
  frontend:
  backend:
```

go to http://teampass.yourdomain.local/ complete the installation

Host: teampass\_db\_1
DataBase name : teampass
Login : teampass
Password : teampass
Port : 3306

login : admin password : yourpassword

##ldap problem, after teampass version 2.1.27, cannot use
password expiry fuction (TeamPass 2.1.27.30 don't need to do
this)

vi /home/teampass/volumes/teampass/www/sources/identify.php

commented the following block of code: (TeamPass 2.1.27.30 don't need to do this)

```
// if (is_array($adldap->user()->passwordExpiry($auth_username)) === fa
// echo '[{"value" : "user_not_exists '.$auth_username.'", "text":""}]'
// exit();
// }
```

## ##SSL:

vi docker-compose.yaml

```
version: "3"
services:
  nginx:
    image: jwilder/nginx-proxy:alpine
    restart: always
    networks:
      - frontend
    ports:
      - "443:443"
    volumes:
      - ./volumes/ssl:/etc/nginx/certs
      - /var/run/docker.sock:/tmp/docker.sock:ro
      - ./volumes/teampass.conf:/etc/nginx/conf.d/teampass.conf
  teampass:
    image: teampass/teampass
    restart: always
    environment:
      VIRTUAL_HOST: teampass.yourdomain.local
    networks:
      - frontend
      - backend
    volumes:
      - ./volumes/teampass:/var/www/html
  db:
    restart: always
    image: mysql/mysql-server:5.7
    environment:
      MYSQL_ROOT_PASSWORD: mypass
      MYSQL_DATABASE: teampass
      MYSQL_PASSWORD: teampass
      MYSQL_USER: teampass
    volumes:
      - ./volumes/db:/var/lib/mysql
    networks:
      - backend
networks:
  frontend:
  backend:
```

## vi teampass.conf

```
upstream teampass {
    server 192.168.0.5:80;
}
server {
    listen
                         443 ssl;
    server_name
                          teampass.yourdomain.local;
                        /etc/nginx/certs/fullchain.pem;
    ssl_certificate
    ssl_certificate_key /etc/nginx/certs/privkey.pem;
    location / {
                                    http://teampass.yourdomain.local;
                proxy_pass
    }
}
```

A geek does not have to be smart. We interested in things that others are not interested in.

We know a lot about our interests.

semonkey.com © 2019. All rights reserved.