

Lag Penalized Weighted Correlation (LPWC)

Thevaa Chandereng, Anthony Gitter

Biological Time Series




Figure 1: Simple time series plot with 8 time points and 3 replicates

Toy Example: Intuitive Clustering





Figure 2: Hypothetical example with 4 genes

Toy Example: Algorithmic Clustering



(a) Hypothetical example with 4 genes

Clustering Algorithm	Cluster 1	Cluster 2
hLPPWC/ILPPWC	• •	• •
DTW	•	• • •
STS	•	• • •
heuc	•	• • •

(b) Cluster assignment of the 4 genes

Figure 3: Existing methods do not group early and late genes

Motivation

Irregular time sampling




Figure 4: Irregularly sampled time series data

Motivation

Delayed response (lags)




Figure 5: Gene 1 spikes after gene 2

What is a Lag?




Figure 6: An example of the effects of applying different lags to genes 1 and 2. Gene 1 and 2 are not lagged in top row. Gene 1 with lag 1 i

Method Overview

LPWC is composed of two steps:

- computing optimal lags for each gene
- computing final correlation matrix for all gene

General Formula

$$\text{corr}_{LPWC}(i, j, X_i, X_j) = \underbrace{\exp\left(\frac{-E(w)}{C}\right)}_{\text{penalty}} * \underbrace{\text{corr}_w(L^{X_i} Y_i, L^{X_j} Y_j, \exp\left(\frac{-w}{C}\right))}_{\text{weighed correlation}}$$

$$w = (L^{X_i} T_i - L^{X_j} T_j)^2$$

Algorithm

Computing optimal lag

$$score_j = \max_{X_i \in \{-m, \dots, m\}} corr_{LPWC}(i, j, X_i, 0) \quad \forall j \neq i$$

$$lag_j = \arg \max_{X_i \in \{-m, \dots, m\}} corr_{LPWC}(i, j, X_i, 0) \quad \forall j \neq i$$

Then, a best lag \hat{X}_i for gene i assigned by

$$\hat{X}_i = \arg \max_{k \in \{-m, \dots, m\}} \sum_{j \neq i} I(lag_j = k) * score_j$$

This is repeated to select a best lag for all genes.

Computing final correlation matrix

$$corr_{LPWC}(i, j, \hat{X}_i, \hat{X}_j) = \exp\left(\frac{-E(w)}{C}\right) * corr_w(L^{\hat{X}_i} Y_i, L^{\hat{X}_j} Y_j, \exp\left(\frac{-w}{C}\right))$$

- Adjusted Rand Index (ARI): similarity between two data clusterings and adjusted for chance
- ARI score close to 1 indicates similar clusterings, score close to 0 otherwise

Simulated Data




Figure 7: Four models simulated using ImpulseDE. Random noise was added to the model parameters to induce variation around a common trend.

ARI Score for Simulated Data




Figure 8: ARI score for different clustering methods for the simulated data where the real clusters are known.

Yeast Osmotic Stress Response Data




Figure 9: Clustering 344 phosphopeptides in yeast osmotic stress into 3 different clusters.

Conclusion & Future Work

- Algorithm tackles the issue of irregular time samples and delayed responses
- R package available on CRAN (LPWC) and preprint on bioRxiv
- Allow missing data (imputation) and support mixed dataset with different time points
- Improve the optimal lag assignments

Acknowledgements

- Ron Stewart, Karl Broman, James Dowell, Wenzhi Cao, Jen Birstler, and members of Gitter lab
- Funding from the NSF and UW Carbone Cancer Center