

Lag Penalized Weighted Correlation (LPWC)

Thevaa Chandereng, Anthony Gitter

Biological Time Series




Figure 1: Simple time series plot with 8 time points and 3 replicates

Existing Time Series Clustering Methods


Partition-based

- Short Time-series Expression Miner (STEM)
- Graphical Query Language (GQL)
- Cluster Analysis of Gene Expression Dynamics (CAGED)

Hierarchical-based

- Dynamic Time Warping (DTW)
- Short Time Series Distance (STS)

Toy Example: Algorithmic Clustering



(a) Hypothetical example with 4 genes

Clustering Algorithm	Cluster 1	Cluster 2
hLPPWC/ILPPWC	● ●	● ●
DTW	●	● ● ●
STS	●	● ● ●
heuc	●	● ● ●

(b) Cluster assignment of the 4 genes

Figure 2: Existing methods do not group early and late genes

Motivation

Irregular time sampling




Figure 3: Irregularly sampled time series data

Motivation

Delayed response (lags)




Figure 4: Gene 1 spikes after gene 2

What is a Lag?




Figure 5: This plot shows two genes that are lagged. The upper plot shows the actual intensity of the genes. The middle plot shows a -1 lag for gene 1 and the lower plot shows a lag of 1 for gene 2.

LPWC is composed of two steps:

- computing optimal lags for each gene
- computing final correlation matrix for all gene

General Formula

$$\text{corr}_{LPWC}(i, j, X_i, X_j) = \exp\left(\frac{-E(w)}{C}\right) * \text{corr}_w(L^{X_i} Y_i, L^{X_j} Y_j, \exp\left(\frac{-w}{C}\right))$$

Algorithm

Computing optimal lag

$$score_j = \max_{X_i \in \{-m, \dots, m\}} corr_{LPWC}(i, j, X_i, 0) \quad \forall j \neq i$$

$$lag_j = \arg \max_{X_i \in \{-m, \dots, m\}} corr_{LPWC}(i, j, X_i, 0) \quad \forall j \neq i$$

Then, a best lag \hat{X}_i for gene i assigned by

$$\hat{X}_i = \arg \max_{k \in \{-m, \dots, m\}} \sum_{j \neq i} I(lag_j = k) * score_j$$

This is repeated to select a best lag for all genes.

Computing final correlation matrix

$$corr_{LPWC}(i, j, \hat{X}_i, \hat{X}_j) = \exp\left(\frac{-E(w)}{C}\right) * corr_w(L^{\hat{X}_i} Y_i, L^{\hat{X}_j} Y_j, \exp\left(\frac{-w}{C}\right))$$

Simulated Data




Figure 6: Four models simulated using ImpulseDE. Random noise was added to the model parameters to induce variation around a common trend.

- Adjusted Rand Index (ARI): similarity between two data clusterings and adjusted for chance
- ARI score close to 1 indicates similar clusterings, score close to 0 otherwise

ARI Score for Simulated Data




Figure 7: ARI score for different clustering methods for the simulated data where the real clusters are known.

Conclusion & Future Work

- Algorithm tackles the issue of irregular time samples and delayed responses
- Preference for distance-based or correlation-based clustering is subjective
- R package available on CRAN (LPWC) and preprint on Bioarxiv
- Allow missing data (imputation)
- Support clustering a mixed dataset with different time points
- Improve the optimal lag assignments

Acknowledgements

- Ron Stewart, Karl Broman, James Dowell, Wenzhi Cao, Jen Birstler, and members of Gitter lab
- Funding from the NSF and UW Carbone Cancer Center