

CS4830 : Big Data Lab-7 Assignment

Vasudev Gupta (ME18B182)

1) File producer.py reads every line from iris.csv file line by line and converts it into json. Then it encodes every row and publishes it to topic- **me18b182-lab7**. This is decoded back when subscriber.py is run and converted into data frame following the same schema used to train the model.

```
[g7vasudev@kafka-centos-1-vm kafka]$ sudo bin/kafka-topics.sh --create --topic me18b182-lab7 --bootstrap-se
rver localhost:9092
[2022-04-04 16:15:13,449] INFO Creating topic me18b182-lab7 with configuration {} and initial partition assignme
nt HashMap(0 -> ArrayBuffer(0)) (kafka.zk.AdminZkClient)
[2022-04-04 16:15:13,585] INFO [ReplicaFetcherManager on broker 0] Removed fetcher for partitions Set(me18b182-l
ab7-0) (kafka.server.ReplicaFetcherManager)
[2022-04-04 16:15:13,664] INFO [LogLoader partition=me18b182-lab7-0, dir=/tmp/kafka-logs] Loading producer state
till offset 0 with message format version 2 (kafka.log.UnifiedLog)
[2022-04-04 16:15:13,683] INFO Created log for partition me18b182-lab7-0 in /tmp/kafka-logs/me18b182-lab7-0 with
properties {} (kafka.log.LogManager)
[2022-04-04 16:15:13,685] INFO [Partition me18b182-lab7-0 broker=0] No checkpointed highwatermark is found for p
artition me18b182-lab7-0 (kafka.cluster.Partition)
[2022-04-04 16:15:13,686] INFO [Partition me18b182-lab7-0 broker=0] Log loaded for partition me18b182-lab7-0 wit
h initial high watermark 0 (kafka.cluster.Partition)
Created topic me18b182-lab7
```

producer.py > ...

```
1  #!/usr/bin/env python
2  # coding: utf-8
3
4  # https://cloudinfrastructureservices.co.uk/how-to-setup-apache-kafka-server-on-azure-aws-gcp/
5  # !pip3 install kafka-python
6
7  import time
8
9  from kafka import KafkaProducer
10 from pyspark.sql import SparkSession
11 from pyspark.sql.types import FloatType, StringType, StructType
12
13 BROKER = "10.164.0.17:9092"
14 TOPIC = "me18b182-lab7"
15 DATA_PATH = "gs://big-data-cs4830/lab-7/iris.csv"
16
17 producer = KafkaProducer(
18     bootstrap_servers=[BROKER], value_serializer=lambda row: row.encode("utf-8")
19 )
20
21 spark = SparkSession.builder.appName("data_producer").getOrCreate()
22 schema = (
23     StructType()
24     .add("sepal_length", FloatType())
25     .add("sepal_width", FloatType())
26     .add("petal_length", FloatType())
27     .add("petal_width", FloatType())
28     .add("class", StringType())
29 )
30
31 data = spark.read.csv(DATA_PATH, header=True, schema=schema)
32
33 for row in data.toJSON().collect():
34     print(row)
35     producer.send(TOPIC, value=row)
36     time.sleep(1)
37
```

The below picture shows the console output in real-time as the producer.py is run.

The image displays a terminal window with a dark background and light-colored text. At the top, a status bar shows the SSH session details: 'ssh.cloud.google.com/v2/ssh/projects/gsoc-wav2vec2/zones/europe-west4-a/instances/me18b182-lab7-vm?authuser=0&hl=en_US&projectNumber=290596474871&useAdminProxy=true&troubleshoot4005E...'. Below this, the terminal shows the last login time and IP address, followed by the execution of several commands. The first command is 'g/vasudevvgupta@me18b182-lab7-vm ~\$ cd /opt/kafka/'. The second command is 'g/vasudevvgupta@me18b182-lab7-vm ~\$ kafka\$ sudo bin/kafka-topics.sh --create --topic me18b182-lab7 --bootstrap-server localhost:9092'. The third command is 'g/vasudevvgupta@me18b182-lab7-vm kafka\$ sudo bin/kafka-console-consumer.sh --topic quickstart-events --from-beginning --bootstrap-server localhost:9092'. The output of the third command shows a warning message and a list of messages. The terminal also shows the execution of 'g/vasudevvgupta@me18b182-lab7-vm kafka\$ sudo bin/kafka-console-consumer.sh --topic me18b182-lab7 --from-beginning --bootstrap-server localhost:9092', which outputs a large number of messages, each containing a 'sepal_length' and 'petal_length' value. The terminal window is titled 'SSH-IN-BROWSER' and 'Terminal'. The status bar at the bottom shows the same SSH session details as the top bar.

2) In order to make real-time predictions, we saved the pipeline in GCS bucket. The pipeline was saved using `.save()` method and loaded for real-time predictions using `.load()` method.

Following is the code for subscriber.py

```
producer.py 3 subscriber.py 5 ×
subscriber.py > ...
1  #!/usr/bin/env python
2  # coding: utf-8
3
4  import os
5  from itertools import chain
6
7  import pyspark.sql.functions as f
8  from pyspark import SparkContext
9  from pyspark.ml import PipelineModel
10 from pyspark.sql import SparkSession
11 from pyspark.sql.types import FloatType, StringType, StructType
12
13 os.environ[
14     "PYSPARK_SUBMIT_ARGS"
15 ] = "--packages org.apache.spark:spark-sql-kafka-0-10_2.12:3.1.2 pyspark-shell"
16
17 sc = SparkContext()
18 spark = SparkSession(sc)
19
20 BROKERS = "10.164.0.17:9092"
21 TOPIC = "me18b182-lab7"
22
23 df = (
24     spark.readStream.format("kafka")
25     .option("kafka.bootstrap.servers", BROKERS)
26     .option("subscribe", TOPIC)
27     .load()
28 )
29
30 schema = (
31     StructType()
32     .add("sepal_length", FloatType())
33     .add("sepal_width", FloatType())
34     .add("petal_length", FloatType())
35     .add("petal_width", FloatType())
36     .add("class", StringType())
37 )
38
39 df = df.select(
40     f.from_json(f.decode(df.value, "utf-8"), schema=schema).alias("input")
41 ).select("input.*")
42
43 model_path = "gs://big-data-cs4830/lab-5/lab5_model"
44 model = PipelineModel.load(model_path)
45
46 df = df.withColumn("true_label", df["class"])
47 predictions = model.transform(df)
48
49 classes_map = dict(
50     zip([0.0, 1.0, 2.0], ["Iris-setosa", "Iris-versicolor", "Iris-virginica"])
51 )
52
53 map_op = f.create_map([f.lit(x) for x in chain(*classes_map.items())])
54 df = predictions.withColumn("predicted_label", map_op[f.col("prediction")])
55 df = df.withColumn("true_label", "prediction", "predicted_label")
56
57 df = df.withColumn(
58     "accuracy",
59     f.when(f.col("predicted_label") == f.col("true_label"), 100).otherwise(0),
60 )
61
62 df = df[["true_label", "predicted_label", "accuracy"]]
63 df.createOrReplaceTempView("output")
64
65 query = (
66     df.writeStream.queryName("output").outputMode("append").format("console").start()
67 )
68 query.awaitTermination()
69
```

Following is the screenshot of the outputs when subscriber.py is run

```
: query = df3.writeStream.queryName("output").outputMode('append').format('console').start()
query.awaitTermination()
```

Batch: 1

```
-----
+-----+-----+-----+
| true_label|predicted_label|accuracy|
+-----+-----+-----+
| Iris-setosa|      Iris-setosa|      100|
+-----+-----+-----+
```

Batch: 2

```
-----
+-----+-----+-----+
| true_label|predicted_label|accuracy|
+-----+-----+-----+
| Iris-setosa|      Iris-setosa|      100|
| Iris-setosa|      Iris-setosa|      100|
+-----+-----+-----+
```

```
: query = df3.writeStream.queryName("output").outputMode('append').format('console').start()
query.awaitTermination()
```

Batch: 148

```
-----
+-----+-----+-----+
|      true_label|predicted_label|accuracy|
+-----+-----+-----+
| Iris-versicolor|Iris-versicolor|      100|
+-----+-----+-----+
```

Batch: 149

```
-----
+-----+-----+-----+
|      true_label|predicted_label|accuracy|
+-----+-----+-----+
| Iris-versicolor|Iris-versicolor|      100|
+-----+-----+-----+
```

Screenshot of kafka and dataproc can also be found below:

[Cluster details](#) [SUBMIT JOB](#) [REFRESH](#) [START](#) [STOP](#) [DELETE](#) [VIEW LOGS](#)

i For PD-Standard without local SSDs, we strongly recommend provisioning 1TB or larger to ensure consistently high I/O performance. See <https://cloud.google.com/compute/docs/disks/performance> for information on disk I/O performance.

Name	me18b182-lab7
Cluster UUID	33709e0f-066a-4be8-9e1a-c600bceaa09f
Type	Dataproc Cluster
Status	Running

[MONITORING](#) [JOBS](#) [VM INSTANCES](#) [CONFIGURATION](#) [WEB INTERFACES](#)

[Filter](#) Filter instances

	Name ↑	Role	
✓	me18b182-lab7-m	Master	SSH

←

me18b182-lab7

DELETE

✓ me18b182-lab7 has been deployed

Overview - me18b182-lab7

▼ kafka-centos kafka-centos.jinja

▼ kafka-centos-vm-tmpl vm_instance.py

me18b182-lab7-vm vm instance

me18b182-lab7-tcp-9092 firewall

me18b182-lab7-tcp-6667 firewall

Apache Kafka Server on CentOS 8 Server

Solution provided by Cloud Infrastructure Services

Instance

me18b182-lab7-vm

Instance zone

europa-west4-a

Instance machine type

n1-standard-1

▼ MORE ABOUT THE SOFTWARE

Get started with Apache Kafka Server on CentOS 8 Server

SSH

▼

Suggested next steps

• Assign a static external IP address to your VM instance

An ephemeral external IP address has been assigned to the VM instance. If you require a static external IP address, you may promote the address to static. [Learn more](#)