

DELFT UNIVERSITY OF TECHNOLOGY

# LASER SWARM

MID TERM REVIEW

DESIGN SYNTHESIS EXERCISE

*Authors:*

S. BILLEMONT  
L.S. BOERSMA  
B. BUYENS  
S.R. FINCK  
J.P. FLORIJN  
T.C. GOOSSENS  
N.S. OBORIN  
A.J. VOROBIEV  
G.J. VAN DER WEL  
Z. ZHOU

*Tutor:*

BEN GORTE

*Coaches:*

PREM SUNDARAMOORTHY  
MATHIEU WILLAERT

May 3, 2010

## **Abstract**

In February 2010 the ICESat mission ended after 7 years of measuring ice sheet mass balance, cloud and aerosol heights, as well as land topography and vegetation characteristics using a space based Light Detection And Ranging (LiDAR) system. ICESat used only one of the possible approaches for LiDAR, namely the use of a high energy laser and a large receiver telescope. The other approach is using a high frequency, low energy laser and a single photon detector. The advantage of the latter approach is that it has a much lower mass, but it is uncertain if even a single photon per pulse reaches the receiver. One possible solution could be to use a swarm of satellites around the emitter, each equipped with a single photon detector. However, the technical feasibility of this concept has not yet been proven.

The baseline report provides an overview of the initial look into this concept. This document contains the requirements analysis, functional breakdowns, risk assessments and initial design options. A preliminary business assessment is also conducted at this stage. It provides the basis for the trade-off made later in the project to find the most feasible system, which incorporates this concept.

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Preliminary Pruning of the Design Option Tree</b>	<b>4</b>
<b>3</b>	<b>Sustainable Development Strategy</b>	<b>5</b>
3.1	Production and Logistics . . . . .	5
3.2	Operations . . . . .	5
3.3	End of Life . . . . .	6

## List of Acronyms

**GLAS** Geoscience Laser Altimeter System

**LiDAR** Light Detection And Ranging

**RAMS** Reliability, Availability, Maintainability and Safety

# Chapter 1

## Introduction

In February 2010 the ICESat mission ended after 7 years of measuring ice sheet mass balance, cloud and aerosol heights, as well as land topography and vegetation characteristics. To do all this, ICESat had only one instrument on board: a space based LiDAR system (Geoscience Laser Altimeter System (GLAS)), allowing for an unprecedented 3D view of the Earth's surface and atmosphere. The laser lifetimes, however, were severely limited because of manufacturing errors in one of the laser components.

ICESat followed only one of the possible approaches for LiDAR, namely the use of a high energy laser and a large receiver telescope. The other approach is using a high frequency low energy laser and a single photon detector. The advantage of the latter approach is that it has a much lower mass, but it is uncertain if even a single photon per pulse reaches the receiver. One possible solution could be the use of a swarm of satellites around the emitter, each equipped with a single photon detector. However the technical feasibility of this concept has not yet been proven.

This is the baseline report on the technical feasibility of this approach to achieve one or more applications of ICESat. It will mainly go into depth on the requirements, technical risks and define the initial design options. It will be the basis for the technical trade off to be made, which specifically requires the in-depth understanding of the subjects treated in this report.

Chapter ?? describes the functions and requirements of the system as a whole, whereas Chapter ?? shows the multiple budget breakdowns and resource allocation. In Chapter ?? the technical risks are investigated. Chapter ?? illustrates the different design options. Since sustainable engineering is an important factor, Chapter ?? is devoted to this subject. In Chapter ?? the return on investment and operational profit are discussed and finally in Chapter ?? the Reliability, Availability, Maintainability and Safety (RAMS) are studied.

## Chapter 2

# Preliminary Pruning of the Design Option Tree

In this chapter the Design Option Tree is pruned. This means that all options that can be dismissed off-hand are removed so as to end up with a table of only serious design options.

## Chapter 3

# Sustainable Development Strategy

In this chapter a Sustainable Development Strategy is discussed in the order of production (section 3.1, page 5), operations (section 3.2, page 5) and end of life (section 3.3, page 6).

### 3.1 Production and Logistics

The design is aimed at a swarm of mostly identical satellites. This may allow for series production which is more efficient in terms of resources than a one-of large satellite with a lot of unique components. This also implies that the number of different spare parts could be reduced. Smaller satellites could also use smaller facilities for production and testing.

Transportation can be split up into two parts: transportation to the launch site and the launch from the surface to the final orbit in space. On both occasions the system can again profit from its small size. If the satellites are not launched all together, they can piggyback on another satellite's launcher.

Spreading the swarm, i.e. piggybacking using different launchers, has several advantages. First of all the emissions are lower than in case of a dedicated launcher. Also, if the first satellite fails before the launch of the rest of the swarm, the others can be repaired and thus less resources are wasted.

### 3.2 Operations

Once in orbit, the satellite's influence on the Earth is very limited. The only real concern is the debris it leaves behind during launch and deployment, which can be dangerous to other satellites orbiting the Earth. The deployment mechanism however, which is responsible for most of the debris, is not included in this technical feasibility study. Later studies developing the ideas from this feasibility study should keep an eye on it, since more satellites could mean more deployment mechanisms and hence more waste. One aspect that can be dealt with is the efficient use of resources. The swarm can be designed in such a way that if one of the satellites fails a replacement satellite can be sent, whilst any remaining satellites can be reused.

### 3.3 End of Life

Each satellite will be at the end of its life if it cannot perform its function anymore. It is important that after the mission is over all satellites are removed from their orbit and burn up in the atmosphere so that they do not pose any danger to other satellites. Final decommissioning of the swarm will be more complex than for a regular satellite, since every individual satellite has to be decommissioned separately.



# Bibliography