

WIRELESS	
Standards and Protocols	IEEE 802.11ax 6 GHz, IEEE 802.11ax/ac/n/a 5 GHz, IEEE 802.11ax/n/b/g 2.4 GHz
WiFi Speeds	AXE7800 6 GHz: 2402 Mbps (802.11ax) 5 GHz: 4802 Mbps (802.11ax) 2.4 GHz: 574 Mbps (802.11ax)
WiFi Range	4 Bedroom Houses 8× Fixed High-Performance Antennas Multiple antennas form a signal-boosting array to cover more directions and large areas Beamforming Concentrates wireless signal strength towards clients to expand WiFi range High-Power FEM Improves transmission power to strengthen signal coverage 4T4R Multiple streams in the same band strengthen the fault tolerance in transmission
WiFi Capacity	Very High Tri-Band Allocate devices to different bands for optimal performance 4×4 MU-MIMO Simultaneously communicates with multiple MU-MIMO clients OFDMA Simultaneously communicates with multiple clients Airtime Fairness Improves network efficiency by limiting excessive occupation DFS Access an extra band to reduce congestion 8 Streams Connect your devices to more bandwidth

Chat Now

WIRELESS

Working Modes	Router Mode Access Point Mode
---------------	----------------------------------

SECURITY

Network Security	SPI Firewall Access Control IP & MAC Binding Application Layer Gateway HomeShield Security Real-Time IoT Protection Malicious Site Blocker Intrusion Prevention System DDoS Attack Prevention Home Network Scanner
Guest Network	1× 6 GHz Guest Network, 1× 5 GHz Guest Network, 1× 2.4 GHz Guest Network
VPN Server	OpenVPN Server PPTP VPN Server L2TP VPN Server
VPN Client	Open VPN Client PPTP VPN Client L2TP VPN Client
WiFi Encryption	WPA, WPA2, WPA3, WPA/WPA2-Enterprise (802.1x)

HARDWARE

Processor	1.7 GHz Quad-Core CPU
Ethernet Ports	1× 2.5 Gbps WAN/LAN Port 1× 1 Gbps WAN/LAN Port 3× 1 Gbps LAN Ports
USB Support	1× USB 3.0 Port 1× USB 2.0 Port Supported Partition Formats: NTFS, exFAT, HFS+, FAT32 Supported Functions:

Chat Now

HARDWARE

	Apple Time Machine FTP Server Media Server Samba Server
Buttons	Power On/Off Button Reset Button
Power	12 V = 3.3 A

SOFTWARE

Protocols	IPv4 IPv6
Service Kits	HomeShield Learn More>
OneMesh™	OneMesh™ Supported Without replacing your existing devices or buying a whole new WiFi ecosystem, OneMesh™ helps you create a more flexible network that covers your entire home with TP-Link OneMesh™ products. Learn More> All OneMesh Products>
Parental Controls	HomeShield Parental Controls Custom Profiles Professional Content Filter Library Family Time Bedtime Off Time Time Rewards Family Online Time Ranking Pause the Internet Weekly and Monthly Reports
WAN Types	Dynamic IP Static IP PPPoE PPTP L2TP
Quality of Service	QoS by Device
Cloud Service	Auto Firmware Upgrade TP-Link ID DDNS
NAT Forwarding	Port Forwarding Port Triggering DMZ

Chat Now

SOFTWARE

	UPnP Virtual Server
IPTV	IGMP Proxy IGMP Snooping Bridge Tag VLAN
DHCP	Address Reservation DHCP Client List Server
DDNS	TP-Link NO-IP DynDNS
Management Features	Tether App Webpage

OTHER

System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser Cable or DSL Modem (if needed) Subscription with an internet service provider (for internet access)
Certifications	FCC, RoHS
Environment	Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing

TEST DATA

WiFi Transmission Power	FCC: ≤29dBm (2.4 GHz), ≤28dBm (5 GHz), ≤22dBm (6 GHz) CE: ≤17dBm (2.4 GHz), ≤27dBm (5 GHz), ≤20dBm (6 GHz)
-------------------------	---

Chat Now

TEST DATA

WiFi Reception Sensitivity	2.4 GHz: 11ax HE20 MCS0:-95dBm, 11ax HE20 MCS11:-64dBm 11ax HE40 MCS0:-92dBm, 11ax HE40 MCS11:-62dBm 5 GHz: 11ax HE20 MCS0:-94dBm, 11ax HE20 MCS11:-63dBm 11ax HE40 MCS0:-91dBm, 11ax HE40 MCS11:-60dBm 11ax HE80 MCS0:-88dBm, 11ax HE80 MCS11:-57dBm 11ax HE160 MCS0:-85dBm, 11ax HE160 MCS11:-54dBm 6 GHz: 11ax HE20 MCS0:-93dBm, 11ax HE20 MCS11:-62dBm 11ax HE40 MCS0:-90dBm, 11ax HE40 MCS11:-59dBm 11ax HE80 MCS0:-87dBm, 11ax HE80 MCS11:-56dBm 11ax HE160 MCS0:-84dBm, 11ax HE160 MCS11:-53dBm
----------------------------	--

PHYSICAL

Dimensions (W×D×H)	12.2 × 8.1 × 6.8 in (311 × 207 × 174 mm)
Package Content	Wi-Fi Router Archer AXE95 Power Adapter RJ45 Ethernet Cable Quick Installation Guide

[For additional version information, please go to the support page.](#)

[†]Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location. The use of Wi-Fi 6 (802.11ax), Wi-Fi 6E, and features including OFDMA, 1024-QAM, and HE160 require clients to also support the corresponding features. Seven 160MHz channels may not be all available in the 6 GHz band in some regions/countries due to regulatory restrictions.

[△]Saving clients' battery power requires clients to also support the 802.11ax Wi-Fi standard. Actual power reduction may vary as a result of network conditions, client limitations, and environmental factors.

*HomeShield includes the Free Basic Plan. Fees apply for the Pro Plan. Visit tp-link.com/homeshield for more information.

**Use of WPA3 requires clients to also support the corresponding feature.

*** This router may not support all the mandatory features as ratified in the IEEE 802.11ax specification.

****Further software upgrades for feature availability may be required.

Actual network speed may be limited by the rate of the product's Ethernet WAN or LAN port, the rate supported by the network cable, Internet service provider factors and other environmental conditions.

Subscribe

Let's Connect

Be The First To Get Exclusive Deals & News

Email Address

Subscribe

Chat Now

About

- About Us
- Corporate Information
- Contact Us
- Sustainability
- Privacy Policy
- Your Privacy Choices
- Careers at TP-Link
- Accessibility
- Our Security Commitment

Press

- News
- Blog
- Security Advisory
- Security News
- Awards

Partners

- Partner Program
- Partner Deal Registration
- MAP Policy

Learning Center

- Technology Trends
- Training & Certification

Promotions

©2026 TP-Link Systems Inc. and its affiliated companies. All rights reserved. United States / English

TP-Link, Tapo, Kasa, Omada, VIGI, Aginet, HomeShield, and Tapo Care branded products are products of TP-Link Systems Inc. or its affiliates. Note: Some services and materials may require you to accept additional terms and conditions before access or use. References to "TP-Link" may include TP-Link Systems Inc., its subsidiaries, or business units within the TP-Link corporate structure, as applicable. The materials provided, including but not limited to press releases, presentations, blog posts, and webcasts, are current as of the date of publication and may be superseded by subsequent updates.

Chat Now