



HTML

Complete

Notes

HTML COMPLETE NOTES



HTML COMPLETE NOTES

Clean layout • Better alignment • Same original content

Designed for quick revision and classroom sharing.
Content is kept same as your original HTML notes. Only spacing, alignment and visual hierarchy are polished.

HTML

- HTML stands for hyper text markup language.
- It is used to create the structure of a webpage.

Types of HTML tags

- Paired tags (Container tags)
 - ❖ They have an opening tag and a closing tag (indicated by forward slash /).

❖ Structure: `<tagname> content </tagname>`

❖ Examples:

- `<p> This is a paragraph </p>`
- `<h1> This is a heading </h1>`
- `<html> ... </html>`

- Unpaired tags (self closing tags/ Empty tags)

❖ These tags do not wrap around text and that is why they do not require a closing tag.

❖ Structure: `<tagname>` or `<tagname />`

❖ Examples:

- `<br>` (Inserts a line break)
- `<img>` (Inserts an image)
- `<hr>` (Inserts a horizontal rule/line)

HTML Heading tags

- heading tags are used to define the headings and subheadings of a webpage.

- There are six levels of headings :

- `<h1>`: The most important heading.
- `<h2>`: Used for major sections or sub-titles.
- `<h3>`: Used for sub-sections under an `<h2>`.
- `<h4>` to `<h6>`: Used for further nested sub-headings.

HTML Formatting Tags

- Formatting tags are used to change the visual appearance of text to make it more readable

- Examples :

- `<b>` or `<strong>`: Makes text bold. (`<strong>` is preferred for SEO as it indicates importance).
- `<i>` or `<em>`: Makes text italic. (`<em>` indicates emphasis).
- `<u>`: Adds an `<u>underline</u>` to the text.
- `<mark>`: Highlights the text with a background color (usually yellow).
- `<sub>`: Subscript text (e.g., H₂O).
- `<sup>`: Superscript text (e.g., a₂ + b₂).

HTML List Tags

There are two types of lists in HTML:

1. Ordered List ()

- Used when the order of items matters (numbered lists).
- Example:
 - 1.Mango
 - 2.Apple

Type	Value	Description	Example
type="1"	numeric digits	1, 2, 3...	
type="A"	Uppercase letters	A, B, C...	
-type="a"	Lowercase letters	a, b, c...	
type="I"	Uppercase Roman numerals	I, II, III...	
type="i"	Lowercase Roman numerals	i, ii, iii...	

2. Unordered List ()

- Used for items where order doesn't matter (bullet points).
- Example:
 - Milk
 - Eggs

Value	Description	Visual
disc	Default solid circle	●
circle	Hollow circle	○
square	Solid square	■
none	No marker	

List Item ()

Every item inside a list must be wrapped in tag.

Description Lists (<dl>)

Aside from Ordered and Unordered, there is a third type used for terms and definitions (like a dictionary).

- <dl>: Definition List (The container)
- <dt>: Definition Term (The name/word)
- <dd>: Definition Description (The explanation)

HTML Anchor Tag (Links)

The <a> tag is used to create hyperlinks, which allow users to navigate from one page to another. It uses the href attribute to define the destination.

- Structure: Link Text

- Example: `<a href="https://www.google.com"> visit Google </a>`

1. The download Attribute

The download attribute tells the browser to download the file instead of opening it in the browser window (which is the default for images or PDFs).

- Syntax: `<a href="path/to/file.pdf" download> Download PDF </a>`

- Custom Name: You can give the file a new name when it downloads:

```
<a href="notes.pdf" download="HTML_Lesson_1"> Get Notes </a>
```

2. Call to actions

These are used inside the href attribute to trigger specific apps on a phone or computer.

Telephone (tel:)

This opens the dialer on mobile devices.

- Example: `<a href="tel:+919876543210"> Call Us Now </a>`

WhatsApp (wa.me)

To open a direct WhatsApp chat (with an optional pre-filled message).

- Example: `<a href="https://wa.me/919876543210"> Chat on WhatsApp </a>`

- With Message: `<a`

```
href="https://wa.me/919876543210?text=I%20want%20to%20join%20your%20whatsapp%20group"> Message </a>
```

Email (mailto:)

This opens the user's default email.

- Example: `<a href="mailto:abc@gmail.com"> Send Email </a>`

3. Essential <a> Tag Attributes

Attribute	Purpose	Example
-----------	---------	---------

target="_blank"	Open the link in a new tab.	<code></code>
-----------------	-----------------------------	---

title	Shows a "tooltip" (text) when you hover over the link.	<code></code>
-------	--	---

HTML Image Tag

The `<img>` tag is used to show images in a webpage. It is an unpaired tag (self-closing), meaning it does not have a closing `</img>` tag.

To display an image, you must use at least two essential attributes: `src` and `alt`.

Image tag Attributes

- **src** (Source): Specifies the path to the image file (URL or local file path).
- **alt** (Alternate Text): Provides a text description of the image when image is not working.
- **width**: Sets the width of the image (in pixels or percentage).
- **height**: Sets the height of the image.
- **title**: Adds a tooltip that appears when a user hovers over the image.

HTML Video Tag

`<video>` tag is used to show video content directly into a webpage.

Attribute Purpose

controls Adds play, pause, and volume buttons.

autoplay Starts playing the video as soon as the page loads.

muted Silences the audio.

loop Make the video keep playing again and again.

HTML iframe Tag

- The `<iframe>` tag (short for Inline Frame) is used to show external content within your current webpage. It essentially creates a "window" to another website or service.
- It is most commonly used for embedding YouTube videos, Google Maps, or

The `<iframe>` tag is a paired tag. While the content goes inside the `src` attribute, the closing tag `</iframe>` is required.

HTML Table Tags

Tables are used to arrange data like text, images, and links into rows and columns.

- `<table>`: The main container for the table.

1. Semantic Table Structure

A modern table is broken down into three main sections:

- `<thead>`: The header section (columns titles).
- `<tbody>`: The main content (the data).
- `<tfoot>`: The footer section (totals or summaries).

Inside these sections, we use:

- `<tr>`: Defines a Table Row.
- `<th>`: Defines a Table Header (bold and centered by default).
- `<td>`: Defines a Table Data (cell).

`<caption>`: Always add a caption to describe what the table is about.

3. Merging Cells (Rowspan & Colspan)

Sometimes you need a cell to span across multiple columns or rows.

- colspan: Merges columns (horizontal).

■ Example: `<td colspan="2">Merged Cells</td>`

- rowspan: Merges rows (vertical).

■ Example: `<td rowspan="2">Merged Rows</td>`

4. Attributes

- border="1"
- cellpadding="10"
- cellspacing="0"
- align="center"

HTML Paragraph Tag (<p>)

The `<p>` tag is used to define a block of text..

- Type: Block-level.
- Example:

The Division Tag (<div>)

The `<div>` tag is a container for other HTML elements. It is used to group large sections of a webpage together so they can be styled with CSS or manipulated with JavaScript.

- Type: Block-level (It always starts on a new line and takes up the full width available).

The Span Tag ()

The `<span>` tag is an inline container used to mark up a part of a text or a part of a document. It does not start on a new line and only takes up as much width as necessary.

- Type: Inline.
- Purpose: Usually used to style a specific word or phrase inside a paragraph.

Differences: Div vs. Span

Feature	<code><div></code>	<code></code>
Display Type	Block-level	Inline
New Line	Starts on a new line.	Does NOT start on a new line.
Width	Takes up 100% width of its parent. content.	Only takes width of its content.

Usage Creating layouts/sections. Styling specific text inside a block.

Form Tag (<form>)

Structure

The <form> tag is a paired tag. It acts as a container for various input elements like textboxes, checkboxes, and buttons.

```
<form action="/submit-data" > </form>
```

Form Elements

To make a form functional, you use these tags inside the <form> container:

A. The <label> Tag

Always use labels for accessibility. The for attribute should match the id of the input.

B. The <input> Tag (Unpaired)

The type attribute changes how the input looks and behaves:

- type="text": Basic one-line text box.
- type="password": Hides characters as they are typed.
- type="email": Validates that the input is a valid email format.
- type="radio": Circular buttons for selecting one option from a group.
- type="checkbox": Square boxes for selecting multiple options.
- type="submit": A button that sends the form data.
- type="tel": Used for telephone numbers (triggers the number pad on mobile).
- type="url": Validates that the input is a properly formatted web address.
- type="search": A text field specifically for searching. Shows (x) button to clear text.
- type="color": Opens a system color picker to select a hex code.
- type="file": Opens a dialog box to upload files from the device.
- type="range": Displays a slider for selecting a value between a min and max.
- type="date": Selects Day, Month, and Year.
- type="time": Selects Hour and Minutes.
- type="submit": Sends the form data to the action URL.
- type="reset": Clears all fields in the form to their default values.
- type="button": A clickable button with no default behavior (used with JavaScript).
- type="hidden": Stores data that the user cannot see or modify (sent with the form)

C. The <textarea> Tag (Paired)

Used for multi-line text input (like comments or messages).

D. The <select> & <option> Tags

Used to create a dropdown menu.

Input Attributes

- required: The field cannot be left empty.
- min / max: Sets the minimum and maximum values for number or date inputs.
- minlength / maxlength: Sets the number of characters allowed for text inputs.
- placeholder: Displays a temporary hint inside the box (disappears when typing).
- value: Sets a default value that is already filled in.
- Readonly: User can see it but can't change it.
- Disabled: User can't interact with it at all

E. The <fieldset> and <legend> Tags

Used to show borders around the form and caption of the form written on its boundary.

Follow for More Premium Notes

Web development • Interview preparation • Practical coding content

@the_yogeshpal01

Save it. Share it. Keep learning.