Cooperatio Manual

Architecture, capabilities and purpose of the method and of its instrument — method version 0.6.0

Contents

Preface **5**

I Purpose and scope 6

1 What cooperatio is **7**
1.1 The problem it addresses . . . 7
1.2 The idea in one sentence . . . 7
1.3 What the material distributes . . . 7
1.4 Who it is for . . . 9
1.5 The status of the evidence . . . 9

2 When to use it, and when not **11**
2.1 The four conditions . . . 11
2.2 Four situations that cost something . . . 11
2.3 What it costs . . . 12
2.4 What already exists, and what this adds . . . 12

3 The material at a glance **14**
3.1 Where to start . . . 14
3.2 What an adopter carries, and what is research . . . 14
3.3 Requirements . . . 14
3.4 Versioning and the freeze policy . . . 14
3.5 License . . . 15

II The method 16

4 The scheme and the loop **17**
4.1 The scheme . . . 17
4.2 The loop . . . 17
4.3 The orchestrator . . . 19

5 The eleven components **20**

6 Roles, artifacts and notes **22**
6.1 Roles and role cards . . . 22
6.2 Executors and families . . . 23
6.3 Artifacts . . . 24
6.4 Notes . . . 24
6.5 Sources of truth and the canon . . . 25

7 Gates, limits and the sensitivity test **26**
7.1 What a gate is . . . 26
7.2 Documentary gates and domain gates . . . 26
7.3 The sensitivity test . . . 27
7.4 The lifecycle of a gate . . . 27

8 The independent review **29**
8.1 Who reviews, with what . . . 29
8.2 The rubric . . . 29
8.3 The verdict rule . . . 30
8.4 The report format . . . 30
8.5 Freezing, and who writes the rubric . . . 31

9 The golden rules and the warning signs **32**
9.1 The ten golden rules . . . 32
9.2 Signs that an instance is wrong . . . 32

10 Evidence and epistemic discipline **33**
10.1 Prior instances and the `[prior:<id>]` mark . . . 33
10.2 Claims of efficacy and their labels . . . 33
10.3 The experiments . . . 34
10.4 What would promote or withdraw a claim . . . 34

III The material and the instrument 36

11 The reflexive application **37**
11.1 What it is, and what round counts as evidence . . . 37
11.2 The folder . . . 37
11.3 The artifact graph . . . 38
11.4 The canon's tables the validator reads . . . 39

12 The validator **40**
12.1 Purpose . . . 40
12.2 Inputs and the layout . . . 41
12.3 Architecture . . . 42
12.4 The report . . . 44
12.5 Exit codes . . . 44
12.6 The hash policy . . . 45
12.7 The self-test and the test suite . . . 45
12.8 The scaffold . . . 45

13 The gate catalogue **46**
13.1 Conventions shared by every gate . . . 46
13.2 Gates measured per document . . . 46
13.3 Gates measured once per run . . . 50
13.4 The measurement of the instrument . . . 51
13.5 Domain gates . . . 51
13.6 The false greens . . . 51

14 The sensitivity test **52**
14.1 Purpose . . . 52
14.2 A perturbation . . . 53
14.3 The copy is the material . . . 54
14.4 Specificity, coverage and the floor . . . 54
14.5 Provenance . . . 54
14.6 The synthetic prior, for a clone . . . 55
14.7 The attestation, and what it leaves . . . 55

15 Ledgers, records and integrity **56**
15.1 The three ledgers . . . 56
15.2 The hash chain . . . 56
15.3 The rules of the state of a note . . . 57
15.4 Frozen records . . . 57
15.5 The family map and its commitment . . . 57
15.6 What a clone verifies, and what rests on the owner . . . 58

16 The instances **59**
16.1 Instance 000: the audiovisual production method . . . 59
16.2 Instance 004: the adoption guide . . . 59
16.3 The three designed instances . . . 60
16.4 The registry as a contract . . . 61

IV Using the method 62

17 Quick start **63**
17.1 The ten-minute path . . . 63
17.2 What the scaffold writes . . . 63
17.3 The first run is red, by design . . . 64
17.4 The shortest path to green, verified . . . 64

18 Setting up a cell **65**
18.1 Step 0 — the folder . . . 66
18.2 Step 1 — the brief . . . 67
18.3 Step 2 — the sources of truth . . . 67
18.4 Step 3 — the canon . . . 67
18.5 Step 4 — the artifacts and the graph . . . 67
18.6 Step 5 — the role cards . . . 67
18.7 Step 6 — the contracts . . . 68
18.8 Step 7 — the gates . . . 68
18.9 Step 8 — the rubric, frozen . . . 68
18.10 Step 9 — the validator . . . 68
18.11 Step 10 — the assembly engine . . . 68
18.12 Step 11 — the quick first version and its review . . . 69
18.13 Step 12 — the round loop . . . 69
18.14 Step 13 — the stop . . . 69
18.15 Step 14 — the case method document and the registration . . . 69
18.16 Before handing over . . . 69

19 Running the instrument **70**
19.1 The commands of a cell . . . 70
19.2 The commands of the corpus . . . 70
19.3 The clone run . . . 71
19.4 Reading a report . . . 71
19.5 Troubleshooting . . . 71

20 Running a round **73**
20.1 Before the review . . . 75
20.2 The dispatch . . . 75
20.3 Importing and classifying . . . 75
20.4 Closing the round . . . 75
20.5 The stop . . . 75

21 Domain gates in a cell **76**
21.1 Declaring the gate . . . 76
21.2 Writing the result . . . 76
21.3 What the validator does with it . . . 76
21.4 The cell's own sensitivity . . . 77

22 Maintaining the material **78**
22.1 The order of a change . . . 78
22.2 Adding a gate or a perturbation . . . 78
22.3 Retiring a gate . . . 78
22.4 Re-freezing the rubric . . . 78
22.5 Ledgers and frozen records . . . 78

22.6 Migration notes . . . 79
22.7 The tests . . . 79
22.8 The freeze policy, restated . . . 79

V Appendices **81**

Appendix A — Glossary **82**

Appendix B — The contracts **85**

Appendix C — Command-line reference **86**
22.9 `validator.py` . . . 86
22.10 `sensitivity.py` . . . 86
22.11 `scaffold.py` . . . 87
22.12 The historical validator of instance 004 . . . 87

Appendix D — The false greens of the gates **88**

Appendix E — File index of the material **90**

Appendix F — Open owner decisions **91**

Appendix G — Building this manual **92**

Preface

This manual describes **cooperatio**, a method for organizing a team of people, language-model agents and code around a complex target, and the material that distributes it: the principle, the reflexive application (the method applied to itself), the validator and its sensitivity test, the agent skill that scaffolds a production cell, and the registry of executed instances. It is written for three readers:

- **the adopter**, a person or an orchestrator agent who wants to set up a production cell for a target of their own and run it to a verdict;
- **the maintainer**, who edits the material or the instrument and has to keep its provenance, ledgers and pins coherent;
- **the reviewer or auditor**, who wants to know what the material claims, what evidence stands behind each claim, and what a clone of the material can and cannot verify.

It is a manual, not a replacement for the material: every rule stated here is stated with more precision in the file it comes from, and the manual names that file. Where the manual and the material disagree, the material wins; please report the disagreement as a note.

Version. The manual describes method version 0.6.0, as recorded in `VERSION`. The counts it quotes (gates, perturbations, tests, files) were measured on that version; later versions change them, and the "Migration note" of each entry in `CHANGELOG.md` says what a cell has to change.

Conventions. File names and identifiers appear in `monospace`; paths are relative to the root of the material, or to the folder of the reflexive application (`02-reflexive-application/`) where the context says so. A term in **bold** at its first use is a term of the canon (`02-reflexive-application/01-canon.md`) and is defined in the glossary (appendix A). Claims the material itself labels as hypotheses are quoted with their label, `[hypothesis]`, because the material's own rule applies to the manual: a claim that the method works carries its evidence or its label.

Diagrams. Each diagram is written twice: as a Mermaid block in the Markdown source, which Markdown viewers that support Mermaid render in place, and as a Graphviz file under `diagrams/`, rendered to SVG and PDF. The PDF edition uses the Graphviz renders; the two are drawn from the same description and differ only in layout.

Status of the method, in the material's own words. A working hypothesis, with a documentary validator; the gates of a target's domain enter as results the cell's own code produces and the validator checks; two executed instances, one of them auditable from the material. The manual repeats this on purpose wherever a reader could take a described capability for a measured one.

Part I

Purpose and scope

Chapter 1

What cooperatio is

1.1 The problem it addresses

A complex target — a vehicle, a book, a software library, a long document — is produced today by teams in which people, language models and code all take part. The failure modes of such a team are familiar: one very capable agent does everything and checks its own work; a request is mistaken for a result ("I asked for medium quality, so it is medium quality"); the same number is stated three ways in three places; a reviewer invents a new grid every round, so nobody can say whether version 4 is better than version 3; an error that was found once comes back because nothing was built to detect it; and the work never ends, because every review finds something.

Cooperatio is a method that answers each of these with a named component and a rule, and a material that applies the method to itself so that the rules can be measured rather than trusted.

1.2 The idea in one sentence

The principle (`01-principle.md`, section 1) states it thus:

> Producing a complex artifact is compiling a graph of typed artifacts, each with an owner, a contract and a gate, in which separate roles communicate only through artifacts and notes, quality is measured by what the system delivered and not by what was asked for, each review is made by someone who did not produce, with a rubric frozen before it, so that rounds are comparable, and every error that escapes becomes a new gate, until a declared stopping criterion.

Put another way: it replaces "one very capable agent does everything" with "a small organization, with explicit contracts, in which intelligence is raw material and code is the glue that composes, checks and remembers".

The organization assembled for one target is a **production cell**. Its parts are typed **artifacts** (files with one **owner**, a **contract**, dependencies and **gates**), narrow **roles** described by **role cards**, a **canon** that is the single source of numbers and terms, a **validator** that reads every artifact against the canon, an **independent review** with a **rubric** frozen by hash, **notes** as the only change request between roles, and a **stopping criterion** declared by the owner before the last round.

1.3 What the material distributes

The material is a folder under version control. At version 0.6.0 it holds:

Part	Path	What it is for
The principle	`01-principle.md`	the method: idea, scheme, eleven components, ten golden rules, what changes by domain, the recipe in twelve steps, warning signs, limits, what would promote or withdraw a claim, ontological assumptions
The reflexive application	`02-reflexive-application/`	the method applied to itself: a brief, a canon, an artifact graph, four role cards, a gate table with a frozen rubric, a generic recipe in fifteen steps, three designed instances, the experiments about the method, the review of its first round, the lessons of every round, and the instrument
The instrument	`02-reflexive-application/80-validator/`	`validator.py` (the gates and the self-test), `sensitivity.py` (the gate on the gates), `perturbation_set.py` (the known defects), `test_validator.py` (the pytest suite), and the two published reports
The contracts	`02-reflexive-application/05-contracts/`	six JSON Schemas: note, state of a note, instance registry, round record, domain result, owner decision
The skill	`skills/cooperatio-teamwork/`	an agent skill that creates the teamwork files for a target, with a scaffold script, templates and a review checklist
The instances	`instances/`	`registry.json`, the record of the known instances pinned by sha256, and `004-adoption-guide/`, the cell of the second executed instance, distributed as a record
The owner records	`VERSION`, `CHANGELOG.md`, `LICENSE`, `.gitattributes`	the version of the method, its history with a migration note per version, the Apache License 2.0, and the rule that every text file checks out with LF line breaks




Figure 1.1: The folders of the material and what each one holds.

1.4 Who it is for

The brief of the reflexive application (`02-reflexive-application/00-brief.md`) names two readers: whoever is going to instantiate the method on a new target without having followed the first instance, and an orchestrator agent that receives the recipe as an instruction. Both have to be able to execute without asking what a term means — which is why the canon exists and why every document links to it.

The method is for a team, not for a single executor. With a single agent playing every role the separation is weak: it writes the rubric that will judge it. The material says so in its limits (`01-principle.md`, section 9) and in the skill: where there is only one agent, at least the rubric and the review have to come from outside the producing run.

1.5 The status of the evidence

The material calls itself a working hypothesis and says exactly what that covers. The reader of this manual should carry three facts throughout:

1. **Two executed instances, both documentary, both by the same owner.** Instance `000-av-production`, an audiovisual production method held by the owner and not distributable, from which the method was generalized; and instance `004-adoption-guide`, the adoption guide of the method itself, whose cell is distributed under `instances/` and whose method document is pinned by sha256. The three other instances in the registry (a car, a book about 2027, an HPC library) are designed sketches, not executions.
2. **One part of the scheme has never been exercised: the recompilation by hash.** In neither execution did an engine rebuild a stale artifact from the hash of its inputs; the validator resolves the command an artifact declares against the paths it names and does not run it.

3. **Efficacy is one-armed.** Everything the method found, it found under the method; no production of the same target ran without the gates, so there is no escape rate to compare. The counterfactual is experiment E2, designed and not run; the cheaper seeded-escape design is E4, designed and awaiting the owner's budget (chapter 10).

The principle keeps a table, written before any data, of what would promote each kind of claim to a result and what would withdraw it (section 9, "What would promote or withdraw a claim"); the manual reproduces it in chapter 10.

Chapter 2

When to use it, and when not

2.1 The four conditions

The method holds where the target has (`01-principle.md`, opening):

- (**a**) a brief that an owner can declare, with a stopping criterion;
- (**b**) a discrete artifact, assemblable from intermediate parts;
- (**c**) sources of truth separable per content type;
- (**d**) dependencies between those parts that can be kept acyclic.

The ontological assumptions behind the four (section 10 of the principle) tell which kinds of target fall outside:

Assumption	A target that violates it	What happens
the target is a discrete, assemblable artifact with a done moment	a continuous process or an ongoing service	the stopping criterion would be a fiction; a service is run, not compiled
the target decomposes into parts with acyclic dependencies	an exploratory target, whose next question is decided by the last result	it is a loop, not a graph; the method degrades to peer review with a rubric
quality is measurable by instruments that do not include the producer	a target where only taste decides	every gate becomes a contract and the independent review is the only instrument
the knowledge the target needs exists, or is produced by declared roles	an emergent target, whose content exists only after the audience reacts	its canon would be written after the fact, which is not a canon

2.2 Four situations that cost something

Inside the four conditions, the principle declares four recurring situations where the method still runs but loses part of what it promises (section 9, "When the method fits, and what each gap costs"). The table is a declaration of scope written before any of the cases was measured `[hypothesis]`:

Situation	What is lost	What it costs to run anyway
a single provider of models (every role from one family)	independence of family between producer and reviewer; what stays is independence of session and of reasoning, and the frozen rubric	record the relation in the round record (`reviewer_relation`), and get the rubric, or a reading review, from outside the run
a target without a registered prior	the facts about a prior that `p-prior` checks, and a recipe already executed once	the canon starts empty of recorded facts, and the first execution becomes a prior; budget an extra round for the gates that do not fit
a short target (a page, a note)	proportion: the cost per round is fixed and the target is small	below a few pages the method is dead weight; a checklist and one review cost less

Situation	What is lost	What it costs to run anyway
a target without an instrument of its domain	the domain gates: only the documentary gates run, so the method degrades to a review with a rubric	the owner writes the domain instrument first, or declares in the brief which non-negotiable no gate measures, and the verdict says so

2.3 What it costs

Per round: one production, one independent review and the maintenance of the instruments. The only costs measured so far are those of review runs, in experiments E1 and E3 of `02-reflexive-application/60-experiments.md`:

Experiment	Executor	Input tokens	Output tokens	Wall time
E1 (with the rubric)	X, the producer's family	about 58,000 (most of them the prior's method document)	55,000 to 66,000, 90 to 98 % of them reasoning	8 to 10 minutes
E1	Y, another family	not separable per call	not separable	about 4 minutes, indicative
E3 (without the rubric and the card)	X	about 56,000	41,000 to 46,000	10 to 13 minutes
E3	Y	not separable	not separable	about 4 minutes, indicative

The material is careful about these numbers: minutes taken in two sessions of different throughput are not comparable, so the measure is the tokens of each call, and a wall time is reported only beside the throughput of the same run. The cost of a production round and of the instruments has not been measured.

The method pays off when being wrong is expensive `[hypothesis]`; stated as a condition still unmeasured, the probability of an error times its cost has to exceed the cost per round times the rounds until the stop. For a throwaway draft the recipe prescribes only steps 1, 3 and 11 (brief, canon, one version and a read from outside).

2.4 What already exists, and what this adds

The method borrows from established practice and says so, so that a reader can tell the vocabulary from the claim (`01-principle.md`, section 9):

Here	Established practice	What this adds, if anything
artifact graph, rebuild by hash	build systems	the graph is of documents and decisions too, and an owner decision is a node
gate with magnitude and limit	quality gates of continuous integration; acceptance criteria	the limit carries its justification and origin label, and a gate counts only after its perturbation
gate sensitivity test	mutation testing; fault injection	a condition of every gate, recorded with its provenance; a noisy perturbation fails
frozen rubric, mechanical verdict	review checklists; scoring rubrics	frozen by hash before the review, so two rounds are comparable
notes routed to their origin	issue trackers; defect triage	a note aims at the artifact where the defect was born; an escaped regression becomes a gate or a reason
role cards	RACI matrices; job descriptions	the "does not decide" field, and the code-conversion degree per role

Here	Established practice	What this adds, if anything
failure analysis per gate	FMEA	done for the validator's gates, for one failure mode, the false green (chapter 13)

Chapter 3

The material at a glance

3.1 Where to start

The root `README.md` gives three entry points:

- to understand the method, read `01-principle.md`;
- to apply it to a new target, read `02-reflexive-application/10-generic-recipe.md`; the three instances there show what an artifact, a gate and a rubric are in each domain;
- to have an agent create the files, install the skill in `skills/cooperatio-teamwork/` and ask it to set up teamwork for the target.

Its "ten-minute path" is reproduced, with the commands verified, in chapter 17.

3.2 What an adopter carries, and what is research

The material separates the two. The fixed cost of a cell is the set of files the scaffold writes (24 with two roles; chapter 17 lists them), among them the instrument it copies: three Python scripts the adopter runs and does not have to read, about 5,700 lines at version 0.6.0 (`validator.py` 4,859, `sensitivity.py` 550, `perturbation_set.py` 333, measured by line count), plus one review per round. The history that matters to an adopter is the "Migration note" of each version in `CHANGELOG.md`; the rest of the changelog — the panels, the probes, the reworks — is the research.

3.3 Requirements

- Python 3.9 or later, standard library only, for the three scripts (they exit 2 below it; an interpreter older than 3.7 refuses the file before any line runs).
- `pytest` for the test suites, which are run with `python3 -B -m pytest -p no:cacheprovider` so that no bytecode cache lands in the material.
- A checkout with LF line breaks: `.gitattributes` enforces `* text eol=lf`, and every sha256 the instrument computes is taken over the text read as UTF-8, byte-order mark dropped, line breaks as LF, so a CRLF checkout keeps the pins.

3.4 Versioning and the freeze policy

`VERSION` holds the semantic version of the method; `CHANGELOG.md` has one entry per version, with a migration note. The round record (`02-reflexive-application/state/round-record.jsonl`) has one line per round, naming the executor of each role by **family** letter and effort, never by model identifier.

After 0.6.0 the instrument is frozen: the validator, the sensitivity test and the scaffold change only for a failure that changes a verdict, or for a new execution. The next budget goes to measuring value (experiment E4) and portability (an execution outside the documentary domain by someone who is not the owner, experiment E5), not to more instrument.

3.5 License

Apache License 2.0; the full text is in `LICENSE`.

Part II

The method

Chapter 4

The scheme and the loop

4.1 The scheme

The principle writes the method as a scheme — a naming of the parts and of the loop, not a formula with a testable property (`01-principle.md`, section 3). Let `A` be the target, `B` the brief and `F` the corpus:

```
A = Compile( Graph( Roles, Artifacts, Gates ), B, F )  until  Stop

where:
  Artifact   = (name, owner, schema, dependencies, paths, gates, hash)
  Role       = (responsibility, inputs, outputs, decides, does not decide,
                exit gate, notes it emits, code-conversion degree)
  Gate       = measurable function over an artifact that returns pass/reject
               with the magnitude measured, never only a signal
  Note       = (target_artifact, severity, text, origin, evidence, round)
  Canon      = single source of numbers, names, terms and decisions, with a
                version per section and an owner per section
  Review     = independent reading of the product with a fixed rubric,
               comparable between rounds, that returns notes and a verdict
  Stop       = criterion declared by the owner before the last round
```

4.2 The loop

```
compile(graph, brief, corpus):
    canon ← extract(brief, corpus)                  # numbers, terms, names, rules
    repeat:
        for each artifact in topological order:
            if inputs changed (hash) or there is a high/blocking note against it:
                output ← owner_role.produce(inputs, canon, open_notes)
                for each gate of the artifact:
                    measure ← gate(output)          # magnitude, not only a signal
                    if rejected: note(artifact, severity, measure) ; return to owner
                validator.check(output, canon)  # terms, numbers, names, assets
        product ← assemble(final artifacts)
        review ← independent_reviewer(product, fixed_rubric)
        for each finding of the review:
            if it is an instrument defect (false positive): fix the instrument at the root
            if it is a regression that no gate caught: create the gate, then fix
            otherwise: note to the originating artifact
        if stopping_criterion: record open notes and exit
    until stop
```




Figure 4.1: The compile loop of the method (principle, section 3).

Three features of the loop decide most of what follows in this manual:

- **Only what is stale is rebuilt.** An artifact is **stale** when the hash of an input changed since it passed its gates, or when a high or blocking note targets it. This is the design; as said in chapter 1, no execution has yet exercised an engine that rebuilds by hash.

- **A gate rejects with a magnitude.** The note it emits carries the measure, not a sign, so the owner of the artifact knows how far from the limit the output landed.
- **Each finding of the review has exactly three destinations.** Instrument defect, escaped regression, or product defect. The first fixes the instrument at the root; the second creates a gate *before* the fix; the third is a note to the artifact where the defect was born.

4.3 The orchestrator

The orchestrator is whoever executes the recipe: it passes paths (never summaries) to the roles, runs the engine and imports the notes. It is a **step, not a role**: it decides nothing that a card assigns to a role or to the owner (`10-generic-recipe.md`, "The orchestrator in pseudocode").

Chapter 5

The eleven components

The principle names eleven components that do not change from one domain to another (section 4; section 6 says what does change). The last column is the error each one prevents, with the example the material gives.




Figure 5.1: The eleven components of the method around the production cell.

Component	What it is	The error it prevents (example)
Artifact graph	each intermediate output is a typed file with an owner, schema, dependencies and hash; the core recompiles only what changed	work redone for nothing and, worse, work *not* redone when the input changed
Role cards	each role has a card: what it decides, what it does not decide, inputs, outputs, exit gate, notes it emits	one role compensating for the defect of another; the "does not decide" field returns the defect to its owner as a note
Contracts (schemas)	every artifact validates against a schema before being accepted; the schema refuses what is ambiguous	an ambiguous position key in a hand-off sheet; an unknown field accepted at assembly instead of at validation

Component	What it is	The error it prevents (example)
Gates with magnitude	a gate returns the measure, and the limit is declared with a justification; "greater than zero" lets a broken instrument pass	an offset measured against a reference that was itself wrong
Routed notes	a change request only by note, with target, severity, evidence and round; only high and blocking return the artifact; deduplication by hash	loose conversation between roles, a lost request, the same note three times
Canon	single source of numbers, names, terms to avoid, accepted variants, rules; each section with an owner and a version	a figure stated one way in one section and differently in another
Validator	a verifier that reads all artifacts against the canon and emits notes by itself	an old version of an asset cited by the canon while the sections used the new one
Independent review with a fixed rubric	another agent, with no access to the producers' reasoning, measures the product with the same grid each round; three verdicts	the team approving its own work; rounds that cannot be compared
Instrument fixed at the root	a false positive becomes a fix to the rule, with a test that reproduces the case, and the previous round is redone	an automatic reviewer of which 10 of 12 notes were false, in the second pilot of the first instance `[prior: 000-av-production]`
Stopping criterion	the owner declares when to stop: the review of the last version becomes a list of open notes, not a new version	endless rounds
Gate sensitivity test	before trusting a gate, inject a known defect and check that it rejects	a gate that checked numbers while the non-negotiable was about statements; the sensitivity test found a validator that read line by line and missed numbers in broken sentences

What changes by domain is: which roles there are, which artifacts, what each gate measures, what the review rubric is, which sources of truth exist for each type of content, and what code-conversion degree the domain already allows. The principle's table of three instantiations (car, text, HPC) calibrates what an "artifact", a "gate" and a "rubric" are in each; the manual summarizes the three designed instances in chapter 16.

Chapter 6

Roles, artifacts and notes

6.1 Roles and role cards

A **role** is a narrow responsibility exercised by an agent, a person or code, which communicates with other roles only through artifacts and notes. A role that neither emits notes nor has a gate is a step, not a role.

Every role has a **role card** with seven fixed fields, which the gate `p-card` reads as bold labels:

Field	What goes there
Decides	what the role settles alone
Does not decide	the neighboring decisions the role would be tempted to make, and whose they are
Inputs	the artifacts it reads
Outputs	the artifacts it writes
Exit gate	the gates its output has to pass
Notes it emits	the typical target and severity
Code-conversion degree	how much of the work the code does, and the executor of the role

The **code-conversion degree** has three values: (a) converted, the code does it and a person or a model decides exceptions; (b) partial under gate, the code does or measures a part; (c) contract and gate only, the role is exercised by an agent or a person and the code only validates the output. The degree is explicit per role and is expected to rise over time.

The reflexive application has four roles (`02-reflexive-application/03-roles/`):

Role	Mission	Degree	Executor
writer	turn the principle into documents an agent can execute; fill the instances	(c)	a language model
verifier	check facts about the priors; maintain the instrument; decide false positives; own the note ledgers	(b)	code for the number checks and the contracts, judgment for the false positives
runner	run the validator and route its notes; decide nothing beyond the rules it executes (named "validator" until v0.6.0)	(a)	the script `validator.py`
reviewer	read the whole product with the frozen rubric; return scores, findings and a verdict by the mechanical rule	(c)	an executor that did not take part, in a separate session, ideally of another family




Figure 6.1: Roles talk only through artifacts and notes; the four roles of the reflexive application.

6.2 Executors and families

Separating roles makes it possible to give each role a different executor: a person, code, or a language model of a chosen kind. The principle (section 2, "Using several models across the roles") gives the rules:

- **Capability follows the role.** A mechanical, fully specified role takes a fast, inexpensive model; a role that designs or weighs hard trade-offs takes the strongest available. The gate, not the model's confidence, decides whether the output is accepted.
- **Independence across families is recommended, not required** `[hypothesis]`. The review is best run on a model of another family than the producer's; the cost is a second provider. It is a recommendation because the one datum is against it as a rule: in experiment E1 the producer's own model, in another session, caught 2 of 2 injected defects, as the model of another family did (`[against: E1]`). What a pilot did show is the part a team can adopt without a second provider: a frozen rubric with a mechanical verdict rule turned a finding into a verdict (`[experiment:E3]`).
- **Code is not a model.** Whatever a gate can measure is measured by code, identically whichever model produced the artifact.
- **Contracts make models swappable.** Replacing the model behind a role must not change any other file; if it does, the contract is too loose.

- **The assignment is auditable, and anonymous.** The round record names the executor of each role by **family** — a letter kept stable across the material — and by effort, never by model identifier. The map from letter to family stays with the owner, outside the material, and since the rework of v0.6.0 each chained line of the round record carries a salted commitment to that map (chapter 15). A route or an alias is not a family: whether two executors differ is checked on what each name maps to, never on the name.

The round record also states, line by line, the reviewer's relation to the producer (`reviewer_relation`: `another family`, `same family, separate session`, `same model, separate route`, or `none`), so the recommendation can be checked against what was done.

6.3 Artifacts

An **artifact** is an intermediate or final output, typed, with a name, a single owner, paths, a schema, dependencies, gates and content identified by hash. An owner decision is also an artifact: it has a name, it is recorded as an open item for the owner, and the graph knows what depends on it (golden rule 7).

The record of an artifact, in the JSON form a cell uses (`03-artifacts.json`):

```
{ "name": "...", "owner": "ROLE", "paths": ["..."], "depends_on": ["..."],
  "schema": "05-contracts/....schema.json" or null, "command": "..." or null,
  "gates": ["..."], "resource": "code" | "agent" | "human" | "machine",
  "proposed": false }
```

Three rules about the record matter to the validator:

- the `gates` list is the **one source of the map from gate to artifact**: the validator runs each gate on the files of the artifacts that list it, and the gate table has to mirror that assignment (chapter 13);
- `paths` may carry globs, and since v0.6.0 each literal path has to exist and each glob has to match at least once (`p-declared`);
- `command`, when present, is resolved against the folder: every path it names has to exist, and the command is never run. Paths and commands may carry `{version}`, which takes the layout's `version-label`.

The **artifact graph** is the set of artifacts with the dependencies between them; it has to be acyclic, and the validator checks that on every pass (`p-references`). "Depends on" means: the artifact reads that input and becomes stale when it changes. A note is not a dependency.

6.4 Notes

A **note** is the only change request between roles. It has six fields, all required (`05-contracts/notes.schema.json`):

```
{ "target_artifact": "name in the graph", "severity": "low|medium|high|blocking",
  "text": "what is wrong and what is expected", "origin": "role or instrument",
  "evidence": "file, excerpt, measurement", "round": N }
```

Severity has four values. Only `high` and `blocking` send the artifact back to its owner; `low` and `medium` accumulate as debt that the stop records. A note aims at the artifact where the defect was born, not where it was seen; the note router refuses a target the graph does not know and deduplicates by identity (target, severity, text, origin, evidence).

An **open note** is a note recorded and not resolved when the production stops: written debt, not forgotten debt (golden rule 10). Since v0.6.0 the state of a note lives in a ledger of its own, append-only and chained (chapter 15).

6.5 Sources of truth and the canon

Every type of content has one declared **source of truth**, and it is never the writer (golden rule 2): a fact comes from the corpus or its primary source; a number comes from the canon or from the instrument that measured it; exact text comes from the original. The inventory is a table with content type, the source that errs least, who consults it and what is forbidden as a source (`01-sources-of-truth.md` in a cell).

The **canon** is the single source of numbers, names, terms to prefer and to avoid, accepted variants and rules, with an owner and a version per section. In the reflexive application it is a Markdown page whose tables the validator reads directly (`01-canon.md`); in a cell it is a JSON file (`02-canon.json`) with the lists the validator consumes. Everything that two roles could write differently goes into it. The canon is itself an artifact: it has an owner, a version and dependents, and the validator reads it on every pass.

A **contract** is the schema an artifact has to validate before it is accepted; it rejects the ambiguous before the expensive work (golden rule 5). The material's own contracts are listed in appendix B.

Chapter 7

Gates, limits and the sensitivity test

7.1 What a gate is

A **gate** is a measurable function over an artifact that returns pass or fail together with the measured **magnitude**. It has a **limit** and a written justification, and the justification starts with an **origin label**:

Label	Meaning
`[method]`	the limit follows from the method itself (for example, zero terms outside the canon)
`[brief]`	the limit was set by the owner in the brief
`[hypothesis]`	the limit is an assumption about the domain, plausible and justified, to be confirmed in a real instance

A row of a gate table has five columns: Gate, Artifact, Magnitude, Limit, Justification. The validator reads the justification's label and counts its words (at least six, read from the `p-limit` row itself), and compares the numbers of the Limit cell with the limit it applies.

Three distinctions the material insists on:

- **A tool that does not run is a tool failure, never a pass or a fail.** The validator exits 2 for it; the exit codes are in chapter 19.
- **A gate that was not measured is pending, neither a pass nor a fail.** A gate whose object is a list of the canon is pending when the list is empty, never "0 of 0 passed". A run with a pending the caller did not accept by name exits 4.
- **A signal gate** — one that only tests existence or "greater than zero" — lets a broken instrument through and has to gain a magnitude limit on both sides: an absurd value also rejects, because it signals a broken instrument.

A number taken from an earlier execution is a fact about it, never a limit a new one inherits: a `[hypothesis]` limit may cite a prior as support, never as the limit itself.

7.2 Documentary gates and domain gates

The validator that ships with the material measures documents: terms, sections, links, form, numbers stated about registered priors, the contracts and the chains of its ledgers (the `p-*` gates, chapter 13). A gate of a target's domain — the identity of a library's results, a speedup, a mass — is a **domain gate**, named `d-<name>` in the cell's gate table. The cell's own code measures it and writes a result file in the contract `domain-result.schema.json`; the validator reads the result, recomputes the sha256 of its inputs, refuses it when an input changed since it was written, turns a `fail` into a note and a missing result into a pending, never a pass. The validator does not run the cell's code (chapter 21).

7.3 The sensitivity test

Before trusting a gate, inject a known defect and check that the gate rejects it; a gate that never rejects proves nothing. The material makes this a condition of every gate: the **gate sensitivity test** (`sensitivity.py`) copies the whole material, injects one **perturbation** at a time, runs the validator on the copy and checks that the expected (document, gate) row went from pass to fail — and that no other row changed. A perturbation that changes another row is *noisy* and fails the report like a missed one, unless it declares the other gate it reaches by design. The report carries the provenance of what it was made against, and the validator's `p-sensitivity` gate refuses a report that the instrument cannot have produced. Chapter 14 describes the test in full.

7.4 The lifecycle of a gate

A gate is born from a regression that escaped every gate (golden rule 4), together with its perturbation. It lives while its object exists. It is retired deliberately, never by neglect: when its object is gone, or when its rule moved into a contract that refuses the defect earlier. The row of the gate table, its assignment in the artifact list and its perturbation leave together, and the changelog records "retired gate: `<id>`", the reason and the rounds the gate stayed silent. No gate was retired between v0.4.0 and v0.6.0.




Figure 7.1: The lifecycle of a gate (gate semantics, "Gate lifecycle").

The instrument detects half a retirement: removing a gate and keeping its perturbation makes the perturbation missed; removing the perturbation of a gate that still runs fails the test that every gate has one. Removing both and regenerating the sensitivity report passes everything; only the declaration in the changelog records that retirement.

Chapter 8

The independent review

8.1 Who reviews, with what

An **independent review** is a reading of the product by someone who did not produce it and has no access to the producer's reasoning, with the fixed rubric, returning notes and a verdict. The reviewer receives the files and the rubric — never drafts, conversation or summaries — and the dispatch records the effective output limit of the executor and the reason its generation ended. An ending for length, or a report that lacks a section of the format, is a tool failure and produces no verdict; the review runs again. This rule came from experiment E1, where one report stopped at a limit the dispatch had not declared and carried a verdict no reader could verify.

8.2 The rubric

The **rubric** is the fixed grid of dimensions, anchors and verdict rule that every review uses in every round; it is written before the first review and frozen by hash. The generic recipe (step 8) asks for six to ten dimensions with **rubric anchors** for scores 1, 3 and 5; a severity scale of the findings with examples from the domain; a mechanical verdict rule; and a report format.

The reflexive application's rubric (`04-gates-and-rubric.md`, section "Rubric") has eight dimensions:

Dimension	What is measured
D1 Fidelity to the principle	the eleven components and the golden rules applied without contradiction; nothing about the reference case invented
D2 Recipe executability	each step says what it reads, creates, does and when it is done
D3 Concreteness of instances	each element filled with domain content, not text that would serve any target
D4 Gates and numbers	gates with magnitude; plausible limits; justifications that say why that number; hypotheses marked
D5 Internal coherence	canon terms in their sense; the same number equal everywhere; references close
D6 Reflexivity	the production followed its own method and is honest where it did not
D7 Form	American English, plain Markdown, pseudocode in `text`, no path, date or machine, sizes in range
D8 Epistemic honesty	distinguishes method, prior instance and domain; marks hypotheses

Its severity scale: `blocking` for an invented fact about the prior instance, a contradiction with the principle that would change the application, a missing mandatory document, or an instance that cannot be executed; `high` for a gap that prevents an agent from executing a step, a signal gate or unjustifiable limit, a term

used in a sense different from the canon's, or an instance element filled with generic text; `medium` for a domain imprecision without a `[hypothesis]` mark; `low` for style.

8.3 The verdict rule

The **verdict** has three values — `rejected`, `accepted with conditions`, `accepted` — and the rule that produces it is mechanical:

```
if a blocking finding exists or some dimension has a score ≤ 2:
    verdict = rejected
else if no high finding and every dimension has a score ≥ 4:
    verdict = accepted
else:
    verdict = accepted with conditions
```




Figure 8.1: The mechanical verdict rule of the frozen rubric.

Experiment E3 is the measure of what this rule is worth: without the rubric and the severity table, two reviewers of different families still named both injected defects but classed an invented fact about a prior as `high` and accepted the product with conditions; with them, the same finding was `blocking` and the verdict was `rejected` (`[experiment:E3]`). That the severity table and the mechanical rule are the parts that did it is a hypothesis the design does not separate `[hypothesis]`.

8.4 The report format

1. **Verdict**, with the application of the rule.
2. **Scores by dimension**: table with dimension, score, evidence.

3. **Findings by severity**: each with target artifact (a name from the graph, or `corpus`), severity, text, evidence.
4. **Verified and correct.**
5. **Not verified**, and why.
6. **Out of scope.**
7. **Notes in JSON**, in the note contract (`origin = reviewer`).

From the second round on, the report adds the item-by-item table of the previous round (resolved, partial, remained, worsened).

8.5 Freezing, and who writes the rubric

The rubric is frozen with `validator.py --freeze-rubric FILE`, which writes the sha256 of the rubric as the layout resolves it (a dedicated `07-rubric.md` in a cell; the "Rubric" section of the gates file in the corpus). The command **refuses to overwrite an existing pin**: replacing a frozen rubric is a deliberate act via `--re-freeze-rubric`, with the reason recorded in the changelog, because re-freezing after a review would make the verdicts incomparable.

The provenance of the rubric matters. In the reflexive application the rubric was written by the producing agent in the first round, against step 8 of the recipe, which gives it to the owner and the reviewer; the deviation is recorded in the lessons, and the round record names the author of the rubric (`rubric_author`). A rubric written by the producer is recorded as such — a gap, not a neutral fact — and the validator adds a low note when a chained round line has `rubric_applied: true` and `rubric_author: producer`.

Chapter 9

The golden rules and the warning signs

9.1 The ten golden rules

From `01-principle.md`, section 5, each with its reason in short:

1. **Measure what the system delivered, not what was asked for.** The effective value comes from a named instrument applied to the produced artifact, never from the parameter that requested it.
2. **Every type of content has one declared source of truth, and it is never the writer.** A number taken from an earlier execution is a fact about it, never a limit a new one inherits.
3. **Every false positive is an instrument defect until proven otherwise.** The easy path is to loosen the limit; the right path is to understand why the instrument read wrongly. A third way out is legitimate when the instrument cannot accept exceptions: work around it and record the workaround as a note, so that it does not become a silent rule.
4. **Every regression that escaped all the gates becomes a gate, or a recorded decision not to make one.** Before fixing the defect, create the detector. Since v0.6.0 the state ledger records which (`escaped`, with `gate` or `no_gate`), and the validator refuses an escaped regression closed with neither.
5. **The contract refuses ambiguity before the expensive work starts.**
6. **Dates, machine names and absolute paths do not enter a durable artifact** if anonymity or reproducibility matters. The checking date is a command-line parameter, not content.
7. **A human decision is an artifact too.** What belongs to the owner is not invented.
8. **Convert judgment into code only when the criterion is measurable and the answer is unique.** The rest stays with an agent under a gate, or with a human under a contract.
9. **Version is method state; date of making is not.**
10. **What the review points out and the round does not fix is written down.**

9.2 Signs that an instance is wrong

The principle (section 8) and the recipe ("Signs that the instance is wrong, and which step catches them") give the same list from two sides:

Sign	Step of the recipe that should have caught it
a role approves its own artifact without a gate	5 (exit gate) and 7
the review of round N is not comparable with that of N−1	8 (frozen rubric)
a finding was "resolved" by loosening a limit	12 (root-cause fix)
two artifacts state different numbers for the same fact	3 and 9
the owner gets a question the brief already answered, or a role decided what its card said "does not decide"	1 and 5
the round gets longer and the notes do not fall	12 (origin, not symptom)
someone redid by hand what the graph should have recompiled	4 and 10 (hash)

Chapter 10

Evidence and epistemic discipline

The material applies its own doctrine of evidence to itself. Four mechanisms carry it: the registry of prior instances with its marks, the labels a claim of efficacy has to carry, the experiments with their provenance, and the table of what would promote or withdraw a claim.

10.1 Prior instances and the `[prior:<id>]` mark

A **prior instance** is an instance of the method that ran before the current one and is registered in the **instance registry** (`instances/registry.json`). A statement about a prior carries `[prior:<id>]`, and a number inside the marked unit is checked against that prior's method document (`p-prior`). A statement that uses one of the canon's prior-statement trigger phrases ("reference case", "prior instance", "of the case", "the executed instance", "instance 0") without the mark is a finding of `p-prior-mark`.

The registry at 0.6.0:

Id	Status	Document	Locator	Method version
`000-av-production`	executed	the owner's method document, pinned by sha256	owner-held, not distributable	—
`001-car`, `002-text-2027`, `003-hpc`	designed	none	none	—
`004-adoption-guide`	executed	`metodo-de-producao.md`, pinned by sha256	`instances/004-adoption-guide`	0.2.2

An executed entry carries `document`, `sha256`, `locator` and `number_format` (`point-decimal` or `comma-decimal`), none of them null; a designed entry keeps the four null, so it can never pass for a pinned prior. The entry of `000-av-production` also declares a `heading_style` (the shape of its section, subsection and step headings), which the synthetic prior of the sensitivity test follows (chapter 14).

Numbers about a prior do not enter the documents before they have a row in the canon's "Recorded facts" table, which names the number, its context (with the mark) and the sections of the prior's document where it lives. The canon also commits, by sha256, to the text of each cited section of the owner-held document, so that a later rewrite of a cited section is detectable without publishing the text (chapter 15).

10.2 Claims of efficacy and their labels

A unit that uses one of the canon's efficacy trigger phrases ("pays off", "the method found", "the gates caught", "the review found", "err less", "the only way", and the rest of the closed list) claims that the method works, and has to carry one of five labels outside code spans (`p-efficacy-mark`):

Label	Where the evidence is registered
`[prior:<id>]`	the method document of that registered prior
`[experiment:<id>]`	the section of that id in `60-experiments.md`, whose status is `executed` and whose "Provenance" table gives the sha256 of at least one input and one output
`[against:<id>]`	an executed experiment whose result goes against the claim: counter-evidence is labeled like evidence
`[lessons:<title>]`	the entry of `99-lessons.md` whose heading is that title
`[hypothesis]`	nowhere yet: an assumption, to be measured

The gate is lexical and says so: a paraphrase of a claim escapes it, and no list closes that gap; the mitigation is a review with a frozen rubric. A claim labeled `[hypothesis]` that states a number or a universal quantifier gets a low note: the label stays valid, the claim has the shape of a measurement with none behind it.

10.3 The experiments

`02-reflexive-application/60-experiments.md` registers the measurements about the method itself, each with its question, object, conditions, executors by family, protocol, predictions written before measuring, results, what it shows and does not show, cost, what became a gate or a lesson, and a provenance table. Only an executed experiment backs a claim.

Id	Status	Question	Result in one line
E1	executed	does the reviewer with the frozen rubric name two injected defects, and does a reviewer of another family differ?	both executors named 2 of 2 and gave `rejected` on the perturbed copy; one control run ended for length and is a tool failure, not a verdict
E2	designed	the counterfactual: the same target produced with and without the method	not run; two productions per target
E3	executed	the same reviewers without the rubric and the reviewer card	both still named 2 of 2, but classed the invented fact `high` and accepted with conditions: the apparatus turned the finding into a verdict
E4	designed	seeded escape: does the apparatus let fewer of ten seeded defects escape than a careful baseline, and does another family find more?	protocol and predictions written; awaits the owner's thresholds and budget
E5	designed	can a third party set up a cell for a target with domain measurements and reach a verdict without improvising instrument?	awaits the owner finding the third party

10.4 What would promote or withdraw a claim

Written before the data, as the gates are (`01-principle.md`, section 9), so that the material leaves the state of a working hypothesis by a measurement and not by a decision. The thresholds are the owner's to accept or adjust before E4 runs:

Claim	Promoted when	Withdrawn when
a reviewer of another family adds to one of the producer's family	in E4 or an equivalent design, the arm of the other family finds at least 1 more defect per 10 seeded, in at least 2 of 3 repetitions	the difference is nil in 3 repetitions
the review apparatus adds to a careful review without it	in E4, the escape rate of arm A is lower than that of arm B by at least 20 points	the difference is under 5 points
the method is portable outside the documentary domain	one execution outside it, by someone who is not the owner, with its domain gates read by the validator and a verdict of the canon	that execution cannot reach a verdict without improvising instrument

Part III

The material and the instrument

Chapter 11

The reflexive application

11.1 What it is, and what round counts as evidence

`02-reflexive-application/` is the method applied to itself: a production cell whose target is the set of documents that shows how to assemble a production cell. Its brief (`00-brief.md`) declares the target, the two readers, five non-negotiables with ids (`nn-method`, `nn-prior-facts`, `nn-hypothesis`, `nn-form`, `nn-anonymity`), the owner decisions, a budget (two returns per document per failed gate, then escalation) and the stopping criterion: **exactly one independent review round**.

That first round, and only that round, was a production under the method. The review gave `rejected` for the version it read (one blocking, two high); the blocking and high notes were fixed and checked by the gates, without a second review, as the brief prescribed; the 22 remaining notes are kept, frozen, in `90-review/notes.json`. Every round after it (v0.2 on) is a **maintenance round** of the material: recorded in the round record with `kind: maintenance`, its scope and the reviewer's relation to the producer, emitting no verdict of the canon, with its decisions in `CHANGELOG.md`. The reflexive application is evidence about the method only for round 1; the maintenance rounds are evidence about the material.

11.2 The folder

File or folder	Artifact	What it is
`00-brief.md`	`brief`	target, non-negotiables with ids, owner decisions, budget and stop, the protocol of the maintenance rounds
`01-canon.md`	`canon`	method terms, terms to avoid, the fixed lists the validator reads, form rules, recorded facts, section commitments, historical vocabulary
`02-artifacts.md`	`artifacts`	the artifact table (the one source of the gate map) and the graph
`03-roles/`	`cards`	the four role cards: writer, verifier, runner, reviewer
`04-gates-and-rubric.md`	`gates-and-rubric`	the gate table with magnitude, limit and justification; the measurement `m-determinism`; the size ranges; the frozen "Rubric" section
`05-contracts/`	`contracts`	six JSON Schemas (appendix B)
`06-gate-semantics.md`	`gate-semantics`	what each gate reads in detail; the hash policy; domain gates; the false greens table; the gate lifecycle; the provenance of the rubric
`10-generic-recipe.md`	`recipe`	the fifteen steps, with "Reads", "Creates", "Does" and "Done when" each

File or folder	Artifact	What it is
`20-instance-car.md`, `21-instance-text-2027.md`, `22-instance-hpc.md`	`instance-*`	the three designed instances
`60-experiments.md`	`experiments`	E1 to E5
`80-validator/`	`instrument-validator`, `validator-tests`, `validation-report`	the scripts, the test suite, `report.md` and `sensitivity.md`
`90-review/`	`review`, `replies`, `open-notes`	the frozen records of round 1: `rubric.sha256`, `auditor-report.md`, `auditor-notes.json`, `notes.json`, `replies.md`
`99-lessons.md`	`lessons`	one entry per round; append-only
`state/round-record.jsonl`	`round-record`	one line per round
`state/notes-status.jsonl`	`notes-status`	the state of each tracked note and panel finding
`state/owner-decisions.jsonl`	`owner-decisions`	the decisions only the owner can take
`README.md`	`readme`	the index and the runbook

Four artifacts live at the root and are declared in the same table: `version` (`VERSION`), `license`, `changelog`, `registry` (`instances/registry.json`), `readme-root` and `skill` (the three files of the skill). The gate `p-declared` checks that every Markdown document of the folder belongs to an artifact or is listed in the canon as outside the table; this production lists none.

11.3 The artifact graph

Each arrow is "is read by". The graph is acyclic and the validator checks it on every pass (`p-references`).




Figure 11.1: The artifact graph of the reflexive application; an arrow is "is read by".

Two things the graph says about the order of the work: the three instances only start after the recipe passes its gates, because it is the recipe that fixes what an instance has to fill in; and the review only starts after the validator passes on every document, so that the one review round is not spent on defects the code already finds.

11.4 The canon's tables the validator reads

The validator reads the tables of `01-canon.md` directly: changing a table changes what it checks, and the canon's "Canon schema" section is versioned (`v1`) so that a validator refuses a canon of another version.

Section of the canon	Read by
Method terms	the glossary; not a gate
Terms to avoid	`p-terms`
Instantiation table rows, Mandatory sections of an instance	`p-table`, `p-sections`
Role card fields	`p-card`
Origin labels of a limit	`p-limit`
Method components	`p-components`
Prior-statement triggers, Efficacy triggers and their labels	`p-prior-mark`, `p-efficacy-mark`
Efficacy mark in append-only documents	the heading from which `99-lessons.md` is measured
Documents outside the artifact table	`p-declared`
Chained ledgers	`p-contract-shape` (the lines before each chain)
Frozen records	`p-frozen-rubric`
Accepted paths, Month names, Machine roots	`p-anonymity`
Recorded facts, Section commitments	`p-prior`

A cell's JSON canon carries the same lists under the keys the scaffold writes (`terms to avoid`, `instantiation table rows`, `mandatory sections`, `role card fields`, `origin labels`, `method components`, `prior-statement triggers`, `recorded facts`, `efficacy triggers`, `documents outside the artifact list`), each a list of plain strings except the recorded facts, which are objects.

Chapter 12

The validator

12.1 Purpose

`validator.py` is the **runner**'s instrument: it reads every document the artifact list assigns a gate to, measures each gate on it, and writes a deterministic report with the magnitude, the limit and the result of each (document, gate) pair, plus the notes the failures produce. It also runs the global gates (the note ledgers, the frozen records, the sensitivity report, the declared files, the domain results), carries an embedded self-test, freezes the rubric, and measures its own determinism.




Figure 12.1: One run of the validator: inputs, the checker, the report and the exit code.

12.2 Inputs and the layout

The validator is written for the corpus's Markdown layout and remapped to a cell's JSON layout by `--layout layout.json`. The layout has a closed set of keys; a key the validator does not read is refused

(exit 2) instead of silently falling back to a default it meant to override.

Layout key	Meaning	Default (the corpus)	A scaffolded cell
`version`	the layout format	—	`1`
`artifacts.canon`	the canon	`01-canon.md`	`02-canon.json`
`artifacts.artifacts`	the artifact list	`02-artifacts.md`	`03-artifacts.json`
`artifacts.gates-and-rubric`	the gates file	`04-gates-and-rubric.md`	`06-gates.md`
`artifacts.roles-dir`	the role cards	`03-roles`	`04-roles`
`artifacts.rubric`	a dedicated rubric file (else the "Rubric" section of the gates file)	absent	`07-rubric.md`
`artifacts.sensitivity`	the sensitivity report	`80-validator/sensitivity.md`	`08-validator/sensitivity.md`
`artifacts.perturbations`	the perturbation data file of a cell	absent (the corpus keeps `perturbation_set.py`)	`08-validator/perturbations.json`
`artifacts.report`	the validator report	`80-validator/report.md`	`08-validator/report.md`
`artifacts.experiments`, `gate-semantics`, `notes-status`, `round-record`, `lessons`, `brief`, `owner-decisions`	the other documents the global gates read	the corpus's files	as the scaffold writes, or the defaults
`gates`	the parser of each gate: `builtin-markdown` or `builtin-json-canon`; every gate of the map has to use the same one	all `builtin-markdown`	all `builtin-json-canon`
`registry`	the instance registry, relative to the folder	`../instances/registry.json`	`priors.json`
`domain-results`	the result files of the `d-*` gates	`[]`	`[]`
`version-label`	what `{version}` expands to in paths and commands	absent	—

The other inputs are command-line options (appendix C): `--case` for each prior method document (repeatable; each is identified by its sha256 against the registry, and the number check of a `[prior:<id>]` unit reads the document identified as `<id>`, in the number format its registry entry declares); `--notes` for the note ledger; `--rubric-hash` for the frozen pin; `--forbidden` for the list of forbidden identifiers; `--allow-pending` for the gates whose pending rows the caller accepts by name.

12.3 Architecture

Since v0.6.0 the checker is one class per family of gates over a core that holds the state of a run and the interface every family uses. The split moved the methods unchanged, and the report of the corpus was byte-identical before and after it.




Figure 12.2: The classes of the validator: one family per kind of gate over a core.

A run proceeds as follows (`CheckerCore.run`):

1. The controls are loaded through the layout: the canon, the artifact list, the gates file (its merged gate tables, one row per gate, else exit 2; its size ranges), the registry. Every gate id of the table or of the map has to be a builtin, a global gate or a `d-*` gate, else exit 2.
2. The gate map is built from the artifact list: for each gate, the artifacts that list it; for each artifact, the files its paths resolve to. Domain gates are skipped here and read from their result files in the global pass.
3. The documents that carry `p-prior` are scanned for `[prior:<id>]` ids, so that `p-prior-pin` knows which executed priors it has to pin.
4. A run that measures no documents writes a blocking note on `artifacts`: a production with no documents is not green, so a freshly scaffolded cell fails until it has real artifacts.
5. For each document in sorted order, for each (gate, artifact) pair in sorted order, the handler of the gate records a measurement and its notes. A hit is a note of the gate's severity (high unless the gate says otherwise) and fails the row; an advisory is a low note that does not. Notes are capped at 50 per gate, with one note saying how many were omitted.
6. The global gates run once (`check_global`): the brief's languages, the frozen records, the declared files and documents, the sensitivity report, the note ledgers, the domain results.
7. The Limit column of the gate table is compared with the limits the validator applied (`check_limit_column`).

12.4 The report

`report.md` has three sections: **Measurements** (one row per document and gate, sorted, with magnitude, limit and `pass`, `fail` or `pending`, then the lines "Pending accepted by the caller", "Pending not accepted" and, when an accepted gate had nothing pending, "Accepted but not pending"); **Instrument measurement** (the `m-determinism` row, the count of the embedded self-test, and the sha256 of the test suite next to the validator); and **Notes** (the count by severity and a table with target, severity, text and evidence).

The report is deterministic by construction: no date, relative paths, rows sorted by document and gate, notes sorted and deduplicated. With `--output FILE` the report goes to the file and one summary line goes to the error stream (`validator: exit N; notes: ...; pending not accepted: ...`), so that a failing run with `--output` is never silent.

`--determinism` runs the validator twice more as child processes, with `PYTHONHASHSEED` set to 1 and 2 and, on the second run, `LC_ALL=C`, and compares the sha256 of the two reports; a difference is a high note. The working folder and the Python version (3.9 and 3.12) were varied by hand, not by the measurement, and gave the same report.

12.5 Exit codes




Figure 12.3: How the validator decides its exit code.

Code	Meaning
0	every gate was measured, or its pending was accepted by name, and no note is high or blocking
1	at least one high or blocking note (a `--determinism` mismatch included)

Code	Meaning
2	invalid input or tool failure: a layout key the validator does not read, a file that is not UTF-8, a truncated table row, a gate it does not implement, a gate with two rows, a gate named by `--allow-pending` outside its closed list, a domain result that breaks its contract, a Python older than 3.9, an unexpected exception
4	no such note, but a gate not measured that `--allow-pending` does not accept

`--allow-pending` accepts only four names: `p-anonymity`, `p-prior` and `p-prior-pin` (the halves that need an input the material does not distribute: the forbidden list, the owner-held prior document) and `p-sensitivity-synthetic` (a sensitivity report a clone regenerated with a synthetic prior). Any other name is exit 2, `p-sensitivity` included; a missing sensitivity report is blocking; and `p-anonymity-language` (a language the brief declares without month names) cannot be accepted either. The history behind the closed list: the panel that reviewed v0.5.0 deleted the sensitivity report, accepted the gate by name and got exit 0.

12.6 The hash policy

Every sha256 the instrument computes — the documents passed with `--case`, the rubric, the gate section, the canon, the resolved gate map, the validator itself, the inputs of a domain result and the lines of a chained ledger — is the sha256 of the text as the validator reads it: UTF-8, a byte-order mark dropped, every line break read as LF. A file that is not UTF-8 text (a domain input only) is hashed as its bytes. The scripts write UTF-8 to the console whatever its code page.

12.7 The self-test and the test suite

`validator.py --self-test` runs 185 checks (at 0.6.0) embedded in the script, with no inputs; the runbook and every cell use it without pytest, and the report prints its count. The pytest suite (`80-validator/test_validator.py`, 280 tests together with the scaffold's `test_scaffold.py` at 0.6.0) runs the self-test and one case per rule: one that passes and one that is rejected. Both are run with `python3 -B -m pytest -p no:cacheprovider`, because pytest imports the files before their own code can switch the bytecode cache off.

12.8 The scaffold

`skills/cooperatio-teamwork/scripts/scaffold.py` creates an empty production cell for a target, refusing to overwrite anything: it builds the cell in a staging folder and moves it into place, so a failure leaves no half-written cell. It copies the validator, the sensitivity script, the perturbation module and five contracts from the material, so it has to run from inside the material (or with the skill folder kept inside it); copied alone, the skill creates the cell without them, says so, and the cell has no validator until one is copied in. Chapter 17 lists what it writes.

Chapter 13

The gate catalogue

This chapter is the reference of the gates the validator implements at version 0.6.0: 17 builtin gates measured per document, 4 global gates measured once per run, one measurement of the instrument, and the family of domain gates a cell supplies. For each gate: the artifacts the reflexive application assigns it to, what it reads, its limit, when it is pending, and the semantics worth knowing before reading a note. The authoritative text is the gate table of `04-gates-and-rubric.md` and the declared semantics of `06-gate-semantics.md`.

13.1 Conventions shared by every gate

- **Units.** A gate reads a document in units: a paragraph, a list item, a table row or a heading. A mark or a label applies to the unit it sits in.
- **Code spans and fences.** Since v0.6.0 one tokenizer reads fenced blocks for every gate, in the CommonMark rules (three or more backticks or tildes, indented up to three spaces, closed by a line of the same character at least as long; an unclosed fence runs to the end and is a note). Marks, labels and triggers are read outside code spans: a mark between backticks is notation, not a mark.
- **Placeholders.** An angle-bracket word (`<fill in>`), `TBD` or `TODO` outside code spans is an unfilled field in exactly four places: a card (`p-card`), a gate row (`p-limit`), an instantiation cell (`p-table`) and an artifact record (`p-references`). A placeholder in prose passes every gate and is the review's to find.
- **Empty lists.** A gate whose object is a list of the canon is pending when that list is empty, never a pass of 0 of 0.
- **Severity.** A hit is a high note unless the gate's semantics say blocking (a cycle, an invented prior number, a malformed mark, a missing declared file, a broken chain, a changed frozen record, a stale domain result) or low (an advisory).
- **Cap.** 50 notes per gate; the 51st is replaced by a count.

13.2 Gates measured per document

13.2.1 `p-terms` — terms to avoid

- **Assigned to:** every prose document of the material, the changelog, the replies, the experiments and the skill's files.
- **Reads:** occurrences of each term of the canon's "Terms to avoid" table (`quality gate`, `checkpoint`, `pipeline`, `feedback`, `iteration`, `single source of truth`, `bible`, `ruler`, `review board`), as whole words, case-insensitive, with a plural suffix, outside code and link targets; in the canon, outside the table itself.
- **Limit:** 0. `[method]`: a synonym outside the canon is the first sign of drift, and replacing it costs one word.
- **Exempt:** the frozen ledger under `90-review/`, by design: vocabulary rules govern living documents.

13.2.2 `p-canon-link` — a link to the canon

- **Assigned to:** every document except the canon and the frozen records.
- **Reads:** links naming `01-canon.md` (or the cell's canon file) that resolve, relative to the document's own folder, to the canon of the layout; and links naming it that do not resolve.
- **Limit:** ≥ 1 resolved, 0 unresolved. `[method]`: a reader who lands on a loose document needs to know where the definitions are.

13.2.3 `p-anonymity` — paths, dates, identifiers

- **Assigned to:** every document, the registry, the three ledgers, the principle, the root README and the skill.
- **Reads, the path-and-date half:** absolute paths (a segment under a common root such as `/tmp`, `/home`, `/opt`; a path of two or more segments; file URLs; home folders by user name; UNC paths); dates in year-month-day, day/month/year, year/month/day and day.month.year formats; dates written with a month's name in English, Portuguese, Spanish, French, German or Italian, and in a language the canon's "Month names" table adds; the expressions "made on", "written on", "generated on" followed by a date; e-mail addresses; host names under a private suffix (`.local`, `.lan`, `.internal`, `.intranet`, `.corp`); a root of one segment the canon's "Machine roots" table names. A month and a year with no day, a version number, a relative path and a public domain name are not hits.
- **Reads, the identifier half:** the entries of the `--forbidden` list, by name or as `sha256:<hex>` entries compared with the sha256 of each lowercased word. Model identifiers belong to that list. The list is kept outside the material, since it contains what it forbids; the corpus runs with none, so this half is **pending by design** and accepted by name.
- **Limit:** 0. `[brief]`: the brief forbids absolute paths, authoring dates, machine names and user names; in the method the gate is an option of the instance.
- **Valves:** an interpreter line (`#!`) on line 1 is not read; a path hit equal to an entry of the canon's "Accepted paths" table for that document is dropped (the entry has to be a path and nothing else; the canon cannot accept a path for itself); a final period is not part of the path compared.
- **Languages:** the brief declares the languages of its documents on a line `Languages: en, pt`; a declared language with no built-in months and no row of the canon's table is pending on the brief under `p-anonymity-language`, which no caller accepts.

13.2.4 `p-form` — plain Markdown

- **Assigned to:** every prose document and the changelog.
- **Reads:** HTML tags and comments outside code; fenced blocks (backtick or tilde, indented up to three spaces) whose info string is not exactly `text`.
- **Limit:** 0. `[brief]`: plain Markdown and pseudocode only in `text` blocks are non-negotiables of the brief.

13.2.5 `p-size` — words in range

- **Assigned to:** the documents of the "Size ranges" table of the gates file.
- **Reads:** words separated by whitespace; since v0.6.0 the pipes and separators of a table are not words.
- **Limit:** within the range declared, before writing, in the "Size ranges" table. `[hypothesis]`: a range is raised before writing, never met by cutting text.

13.2.6 `p-table` — the instantiation table

- **Assigned to:** the three instances.
- **Reads:** the rows of the canon's "Instantiation table rows" list present in the two-column table that opens the instance; empty cells or cells holding a placeholder.
- **Limit:** 14 of 14, 0 empty. `[method]`: the table is the summary that makes instances comparable.

13.2.7 `p-sections` — the mandatory sections

- **Assigned to:** the three instances.

- **Reads:** the headings of the canon's "Mandatory sections of an instance" list.
- **Limit:** 14 of 14. `[method]`: each section corresponds to a step of the recipe.

13.2.8 `p-card` — the seven fields

- **Assigned to:** the role cards and the three instances (which carry cards of their own).
- **Reads:** per card, the fields of the canon's "Role card fields" list missing (as bold labels), and placeholders left in a field.
- **Limit:** 0 missing, 0 placeholders. `[method]`: a role without a gate and without a note is a step; the seven fields make that verifiable.

13.2.9 `p-limit` — justified limits

- **Assigned to:** the gates file and the three instances.
- **Reads:** gate table rows with an empty magnitude, limit or justification; a justification without an origin label or with fewer than 6 words (the number is read from the gate's own row); a placeholder in a field.
- **Limit:** 0. `[method]`: 6 words is the minimum to say where the number comes from and why not another one. It is a lexical proxy: six words of any kind pass, and the review reads whether they justify.

13.2.10 `p-references` — the graph closes

- **Assigned to:** the artifact table, the cards, the gates file and the three instances.
- **Reads:** artifacts cited in gates, dependencies or notes a card emits and not declared; owners that are neither a role nor `owner`; cycles in the graph (blocking); gates the artifact table assigns with no row in the gate table, or rows naming other artifacts than it assigns; placeholders in an artifact record; paths an artifact's `command` names that do not exist; Limit cells whose numbers are not the numbers of the limit the validator applied.
- **Limit:** 0. `[method]`: a loose reference is the written form of "the old text nobody knew had changed"; a cycle means a wrong graph.

13.2.11 `p-prior` — numbers about a registered prior

- **Assigned to:** the principle, the canon, the recipe, the three instances, the lessons and the experiments.
- **Reads:** prior labels whose id is not registered, or whose id breaks the grammar `[0-9a-z-]+` (a malformed mark, blocking); every number of a unit marked `[prior:<id>]`, code spans included, which needs a row of that prior in the canon's "Recorded facts" and is checked by presence in the union of the sections the row cites, in the method document passed with `--case` whose sha256 is the pin of `<id>`, read in the `number_format` the registry declares; section references ("section 2.1", "step 16") checked by the existence of that label; on the canon, the section commitments compared with the sections of the documents passed.
- **Limit:** 0. `[brief]`: a number absent from the prior's method document is an invented fact until proven otherwise.
- **Pending:** without a registry; without the `--case` document of a cited prior (pending by name: a cited owner-held prior reads "owner-held evidence, not measured here").
- **Exceptions:** the full id of a registered instance (`004-adoption-guide`) is a name, a bare `004` is a number; a digit attached to a letter (`p95`, `v7`) is a name; numbers written in words are not read. The check verifies the presence of the number's tokens in the cited sections, not the claim around it; the "Recorded facts" section of the canon is exempt by name.

13.2.12 `p-prior-mark` — statements about a prior carry the mark

- **Assigned to:** the principle, the recipe, the three instances and the experiments.
- **Reads:** paragraphs, list items and table rows that use a phrase of the canon's "Prior-statement triggers" without a `[prior:...]` mark outside code spans (a mark in a code span is no mark; a mark outside the grammar is no mark either).

- **Limit:** 0. `[method]`: created after the first review, where a qualitative statement about the prior, absent from its document, passed every gate because only numeric statements needed a mark.
- **Exempt:** the frozen "Rubric" section of the gates file, by design.

13.2.13 `p-prior-pin` — the pin of each executed prior

- **Assigned to:** the registry.
- **Reads:** for each executed prior cited in a document that carries `p-prior`, the registered sha256 compared with the documents passed with `--case`, prior by prior: a cited owner-held prior whose document was not passed is pending by name; a cited distributed prior whose pin matches none of the documents passed is blocking; a document passed that is the pin of no executed instance is blocking (with such a document even the owner-held prior is blocking, since the stray may be that prior, edited); a cited executed instance without a pin is blocking.
- **Limit:** equal. `[method]`: a pin nobody can re-verify is not a pin.

13.2.14 `p-contract-shape` — the contracts hold

- **Assigned to:** the artifact table, the contracts, the registry, the note ledger, the state ledger, the round record and the owner decisions.
- **Reads:** schema cells of the artifact table citing a `*.schema.json` file that is missing or does not parse; keywords of each contract outside the subset the validator applies, or a `contract_version` other than the one it reads (`1`); the registry, the note ledger, the state ledger, the round record and the owner decisions validated line by line against their schemas; registry entries that break the contract of their status; the hash chain of the three append-only ledgers (chapter 15) and the rules of a chained line of the round record (its `kind`, its `reviewer_relation`, no verdict on a maintenance line, a `rubric_hash` equal to the frozen rubric when `rubric_applied` is true, the form of `family_map_commitment`).
- **Limit:** 0. `[method]`: a contract that exists but is never applied is not a contract.

13.2.15 `p-recipe` — the steps of the recipe

- **Assigned to:** the recipe.
- **Reads:** steps missing one of the fields "Reads", "Creates", "Does", "Done when"; the number of steps (the minimum is read from the gate's row).
- **Limit:** 0 missing a field; ≥ 12 steps. `[method]`: 12 is the number of steps in the principle's recipe, which this one details.

13.2.16 `p-components` — the eleven components named

- **Assigned to:** the three instances.
- **Reads:** the method components of the canon's list named in the document (inflected forms accepted).
- **Limit:** 11 of 11. `[method]`: an instance without one of them is not the method.

13.2.17 `p-efficacy-mark` — claims of efficacy carry their evidence

- **Assigned to:** the principle, the brief, the recipe, the three instances, the lessons (from the heading the canon declares on), the README and the experiments.
- **Reads:** units that use a phrase of the canon's "Efficacy triggers" without one of the labels `[prior:<id>]`, `[experiment:<id>]`, `[against:<id>]`, `[lessons:<title>]`, `[hypothesis]` outside code spans; `[experiment:<id>]` and `[against:<id>]` labels that do not name an executed experiment with a "Provenance" table in `60-experiments.md` (a label citing a designed or pending experiment is a note; one without provenance reads as `[hypothesis]`, with a note); `[lessons:<title>]` labels that name no level-2 or level-3 heading of the lessons file; a `[hypothesis]` claim with a number or a universal quantifier (a low note).
- **Limit:** 0. `[method]`: a claim that the method itself works is a statement of the same kind as a statement about a prior, and exempting it was the double standard a critical panel found.

13.3 Gates measured once per run

13.3.1 `p-notes` — the note ledgers

- **Assigned to:** `open-notes` and `notes-status`.
- **Reads:** notes of the ledger passed with `--notes` missing one of the six fields, with a severity outside the four, or with a target outside the graph; notes without a line in the state ledger, or with two, or with a closing status and no version; evidence naming a file of the material (`.md`, `.json`, `.jsonl`, `.py`) that does not exist; the rules of the state (chapter 15): an escaped regression closed with neither a gate of the gate table nor a reason (high); an open high or blocking note that affects a non-negotiable and no decided owner decision covers (blocking); an open note older than 3 rounds and not scheduled (low).
- **Limit:** 0. `[hypothesis]`: a note aimed at an artifact the graph does not know is undeliverable; the note router of the first instance rejected such a target `[prior:000-av-production]`.
- **Pending:** without `--notes`; that pending cannot be accepted.

13.3.2 `p-frozen-rubric` — the rubric and the frozen records

- **Assigned to:** the gates file and the review.
- **Reads:** the sha256 recorded at the launch of the review (`--rubric-hash`) against the current sha256 of the rubric as the layout resolves it; and the sha256 of each record the canon's "Frozen records" table pins (the reviewer's report and notes of round 1, the derived note ledger, the replies, the pin of the rubric, and the part of the lessons above the heading the efficacy gate reads from).
- **Limit:** equal (blocking when a record changed). `[method]`: a rubric changed after the review makes the verdict incomparable. The panel that reviewed v0.5.0 rewrote "Rejected" as "Accepted" in the reviewer's report and no gate saw it; since v0.6.0 the records are pinned.

13.3.3 `p-sensitivity` — the gate on the gates

- **Assigned to:** `instrument-validator`.
- **Reads:** the sensitivity report named by the layout: a missing report (blocking); an incomplete one; a table that does not add up to its "Caught" line; a provenance that does not match (the running validator and the one next to the report, the "Gates" section, the canon, the resolved gate map, the perturbation set, the `case sha256` of each prior document and its `case attestation`); known defects the expected gate let through (missed) or that changed another row (noisy); an assigned gate without a perturbation, or fewer than 25 % of the (document, gate) pairs perturbed (pending with the reason, never a pass); a report made with a synthetic prior (pending under `p-sensitivity-synthetic` in a run without that prior's document, refused in a run with it).
- **Limit:** every gate covered, ≥ 25 % of pairs, 0 missed, 0 noisy. `[method]`: a gate that never fails proves nothing, and a report this instrument cannot have produced proves nothing either; `[hypothesis]`: the floor of a quarter of the pairs is the first this version commits to, above the 18 % a panel measured, to be raised and never lowered. The corpus covers 50 of 182 pairs.

13.3.4 `p-declared` — what is declared exists, and what exists is declared

- **Assigned to:** the artifact table.
- **Reads:** declared paths that match nothing on disk (each literal path, and each glob at least once; blocking, naming the path); Markdown documents of the folder no artifact declares and the canon does not list as outside the table; files that belong to two artifacts; documents of the "Size ranges" table no artifact declares; a declared artifact marked `proposed` (pending with its reason) or declared with no paths (pending).
- **Limit:** 0. `[method]`: a declared document that silently matches no file is a promise the instrument never kept.

13.4 The measurement of the instrument

13.4.1 `m-determinism`

Not a gate on a document: a measurement of the validator itself, which cannot fail a document. It is the equality of the report's sha256 across two consecutive runs on the same input, the second with another hash seed and the C locale; measured only with `--determinism`, and a difference is a high note. `[hypothesis]`: a report that changes by itself is not evidence; the continuity ledger the validator of the first instance wrote was deterministic `[prior:000-av-production]`.

13.5 Domain gates

13.5.1 `d-<name>`

A gate of the target's domain, declared as a row of the cell's gate table (every gate table of the gates file is read, so domain gates may keep a table of their own) and never run by the validator. The cell's own code measures it and writes a result file in the contract `domain-result.schema.json`; the layout lists the result files under `domain-results`. The validator reads each result and:

Case	What the validator does
an input changed or is missing since the result was written (its sha256 recomputed)	blocking: the result is stale
the result names no input	blocking
the inputs do not include every file of the artifacts the gate's row names	blocking (a result over the canon alone passed while the candidate changed)
the result's own numbers contradict it, when the limit starts with a comparison and a number (`≤ 2 s`, `at least 1.5 x`) or is a bare zero (`0 divergent`)	blocking
`result: fail`	a note with the severity of the gate's row (an optional Severity column, else high); a severity below high counts only for a gate a decided owner decision covers
`result: tool-failure`, or a result that breaks the contract	exit 2
a declared `d-*` gate with no result	pending, which no caller can accept

Declared reach: a result whose inputs were recomputed by hand, the candidate changed and its new sha256 written in, passes; it is the same act as running the gate again without running it, which the validator, reading results and never running the cell's code, cannot tell apart. The sensitivity of a domain gate is the cell's own (mutants, a reference with a known defect), and the coverage of `p-sensitivity` leaves domain gates out. Chapter 21 shows how a cell writes one.

13.6 The false greens

`06-gate-semantics.md` keeps a failure-mode analysis of the validator's gates for the one failure mode that matters to a verdict: the **false green**, a defect the gate lets through with a pass. For each gate it names the cause, what detects it today, the probe that first found it and the perturbation that covers it now. The table is reproduced in appendix D; the summary is that most of the causes found so far came from the critical panels that reviewed v0.4.2 and v0.5.0 and from the independent review of v0.6.0, each probe turned into a regression test and, where it is a defect of a document, a perturbation. The causes are the ones found so far, not an exhaustive list; a new probe that passes a gate adds a row and a perturbation.

Chapter 14

The sensitivity test

14.1 Purpose

A gate that never fails proves nothing. `sensitivity.py` is the gate on the gates: it injects known defects, one at a time, into a copy of the material and checks that the expected gate rejects each on the expected document, and nothing else moves. Its report, `sensitivity.md`, is an artifact the validator reads (`p-sensitivity`), with a provenance header that ties it to the exact validator, gate table, canon and gate map it was made against. The validator refuses a report that the instrument cannot have produced, so the test cannot be satisfied by an old report or a hand-written one.




Figure 14.1: One run of the sensitivity test, the gate on the gates.

14.2 A perturbation

The corpus keeps its set in `perturbation_set.py` (65 perturbations at 0.6.0), a module the validator reads without importing the sensitivity script; a cell keeps its own as data, `08-validator/perturbations.json`, named by the layout key `artifacts.perturbations`. The fields:

Field	Meaning
`name`	unique, without a comma (the report lists the names on one line)
`document`	the document to perturb, relative to the folder; `../instances/registry.json` is the copied registry
`old`, `new`	the text replaced once in the document; with `delete: true` the document is removed instead
`gate`	the gate that has to react on that document; one the validator implements, never a domain gate
`expect`	`fail` (default), or `pending` for a defect that empties what the gate reads (one perturbation of the corpus empties a list of the canon)
`needs_case`, `needs_rubric_hash`, `needs_notes`, `needs_registry`	the validator inputs the expected gate cannot run without; a row whose input was not passed is not measured, never missed
`prior`	the registered prior whose method document the gate needs; without a `--case` document identified as it, the row is not measured, whatever other prior was passed

Field	Meaning
`also`	gates the defect also reaches by design, comma-separated; their rows are not counted as noise, and the report lists them (eleven perturbations of the corpus declare one: a pin decides which document is the prior, a list of the canon feeds a gate on every document, a placeholder in angle brackets also reads as an HTML tag, an edited old line of a chained ledger breaks its chain)

Two examples from the corpus's set:

```
Perturbation("avoid-word inserted", "10-generic-recipe.md",
             "## The orchestrator in pseudocode",
             "## The orchestrator of the pipeline", "p-terms")
Perturbation("prior number altered", "10-generic-recipe.md",
             "the validator gave 38", "the validator gave 39", "p-prior",
             needs_case=True, prior="000-av-production")
```

14.3 The copy is the material

Since v0.6.0 each perturbation runs on a copy of the whole material the folder belongs to: the folder and everything its artifact table and registry reach above it (the principle, the root README, the skill, the changelog, the registry). Until then the copy was the folder alone, so no perturbation could reach those documents. The copies go to `--work SCRATCH_FOLDER`, or to a temporary folder; `.git`, `__pycache__` and `.pytest_cache` are not copied.

14.4 Specificity, coverage and the floor

The perturbed report is compared with the baseline row by row. A perturbation is **caught** when the expected (document, gate) row went from pass to fail (or to pending, when `expect` says so), **missed** when it did not, and **noisy** when another row changed its result — not counting the expected row, the row of `p-sensitivity` itself (which reads the provenance an edit of an input pins on purpose), the rows of a document that left the report, and the gates the perturbation declares in `also`. A noisy perturbation fails the gate like a missed one.

Coverage is measured twice: by gate (every gate the artifact table assigns, except `p-sensitivity`, the measurements and the domain gates, has at least one perturbation) and by pair (the (document, gate) rows of the baseline report that at least one measured perturbation targets). The magnitude reads "k of n gates covered, p of q pairs (r %), 0 missed of m, 0 noisy"; at 0.6.0 the corpus reads 20 of 20 gates and 50 of 182 pairs (27 %). An assigned gate without a perturbation, or fewer than 25 % of the pairs, leaves `p-sensitivity` pending with the reason, never a pass; the floor is a hypothesis, the first this version commits to, raised and never lowered. The three generic perturbations of a new cell cover three gates and three pairs; each gate a cell adds needs one of its own.

14.5 Provenance

The header of the report records what it was made against, and the validator recomputes every line and compares:

```
validator sha256: <sha of validator.py: the running one, and the one next to the report>
gates sha256: <sha of the "Gates" section; a cell's whole gates file>
canon sha256: <sha of the canon>
map sha256: <sha of the sorted (gate, document path) pairs of the gate map>
perturbations: <count> (<names, comma-separated>)
case sha256: <prior id> <sha of the document passed>   (one per prior; "none")
case attestation: <prior id> <sha of the text + the four digests above>
```

Editing the validator, the "Gates" section, the canon or the gate map makes the report stale: regenerate it (and then the validator report) before the next run, or `p-sensitivity` fails on provenance. Deleting the report does not help: a missing report is blocking, and `p-sensitivity` cannot be accepted by name.

14.6 The synthetic prior, for a clone

Five rows of the corpus's set need the method document of the first prior, which the owner keeps. A maintainer who edits the instrument without it regenerates a full report with `--synthetic-prior 000-av-production`: the script generates a document from the canon's recorded facts (one numbered section per label the facts cite, holding the facts' numbers in the prior's number format), in the `heading_style` the registry declares for the real document, passes it as `--case`, and patches its sha256 and its section digests into the registry and the canon of every copy, never of the material.

The validator tells a synthetic prior by its `case sha256` differing from the registry's pin, never by a line that declares it (the first draft's declaring line could be deleted, and the report then read as the owner's). A report made with a synthetic prior is never a pass: in a run without that prior's document its row is `p-sensitivity-synthetic`, pending, accepted only when the caller names that gate; in a run with the document it is refused. It shows that every gate fails its known defect; it does not show that the owner's document holds the facts, nor that the validator reads that document's format beyond what the registry declares.

14.7 The attestation, and what it leaves

The pin of the registry is public, so a `case sha256` line can be written by hand with the real pin over a report made with the synthetic document. Until the closing pass of v0.6.0 that forged line passed every run. Since then the report records, for each document it was made with, a `case attestation`: the sha256 of the document's text followed by the validator, gates, canon and map digests of the report, which only whoever holds the text can compute. A run that passes the document recomputes it and refuses a mismatch; that is the owner's run for `000` and every run for `004`. What it leaves, declared: a run without the document compares nothing, so **in a clone the forged line still passes**, and a frozen record re-pinned in the canon shows there only in the diff against a signed version.

Chapter 15

Ledgers, records and integrity

15.1 The three ledgers

Three append-only ledgers under `state/` hold the state the gates read, one JSON object per line, each with a contract (appendix B):

Ledger	One line per	Written by
`round-record.jsonl`	round: method version, round label, the executor of each role by family and effort, a summary, and since v0.6.0 its `kind`, the `reviewer_relation`, `rubric_applied`, `rubric_hash`, `rubric_author`, the `family_map_commitment`, and optional cost fields (tokens per role, calls, finish reason, `wall_seconds`, `notes_count`, `crew`, `rounds_to_stop`)	the verifier, at the close of a round
`notes-status.jsonl`	state change of a tracked note: `ref` (`notes:<n>` for the n-th note of the frozen ledger, `panel:<version>:<id>` for a panel finding), `status` (`open`, `fixed`, `disputed`, `out of scope`), `closed_in`, `summary`, and the fields of the state rules below	the verifier
`owner-decisions.jsonl`	decision only the owner can take: `name`, `status` (`open`, `decided`), `blocks`, `version`, `summary`, and once decided the notes it `covers`	the owner, through the orchestrator

15.2 The hash chain

Each line written from v0.6.0 on carries `prev`, the sha256 of every line above it, each followed by LF (for a file with no blank line, the sha256 of the file before the line was appended). `p-contract-shape` recomputes the chain: an earlier line edited, removed or reordered breaks the first chained line after it. The canon's "Chained ledgers" table counts the lines written before each chain (10 in the round record, 48 in the state ledger, 0 in the owner decisions), which are never edited, and every line after them has to carry `prev`, so stripping the chain is a finding too.

The reach is declared: the chain detects an edit made without recomputing it — the careless maintainer and the honest error. It does not detect an edit that recomputed it, which costs one sha256 per line, and it does not cover the last line of a ledger, which can be rewritten with no sign until a line is appended after it. Only an anchor outside the tree — a signed tag per version, which is the owner's to make — answers that.

15.3 The rules of the state of a note

Since v0.6.0 the last line of each tracked note is read against four rules (`p-notes`):

- **Golden rule 4.** A note that is a regression that escaped every gate (`escaped: true`) closes with the gate it became (`gate`, a row of the cell's gate table) or with the recorded reason not to make one (`no_gate`, at least 8 distinct words, or `decision` exactly the name of a decided owner decision); closed with neither, it is a high note. The count of words measures the form of the reason, not its content.
- **Age.** An open note is counted in rounds from the version it was opened in (`opened_in`, or the version of a panel ref, or 0.1.0 for the frozen ledger). Past 3 rounds, and not scheduled for a version still ahead (`due`), it is a low note: schedule it, dispute it or close it with the reason. Three rounds is a hypothesis: a panel counted 16 of the 22 notes of round 1 open nine rounds later.
- **Non-negotiables.** The brief gives each non-negotiable an id in a code span (`nn-<name>`); a note names those it affects (`affects`). An open note of severity high or blocking that affects one is blocking, unless a decided entry of the owner decisions covers it (`covers`). The fields a line's writer controls cannot undo the protection: the severity is the highest of the note ledger's and of every line of the ref; the non-negotiables are the union of every line's `affects`; a decision covers only while its last line is `decided`; a high or blocking note opened in 0.6.0 or later has to name what it affects (an empty list when nothing).
- **Evidence.** A note whose evidence names a file of the material needs that file to exist; the frozen ledger keeps the names of its time and is exempt.

15.4 Frozen records

The records of the first review and the history of the lessons are never edited. The canon's "Frozen records" table pins their sha256 (`90-review/auditor-report.md`, `auditor-notes.json`, `notes.json`, `replies.md`, `rubric.sha256`, and the part of `99-lessons.md` above the heading "The v0.5.0 round: exit 0 is not green"), and `p-frozen-rubric` compares them on every run. An append-only rule that no gate checked is how the panel that reviewed v0.5.0 rewrote a verdict unseen.

15.5 The family map and its commitment

The round record names the executors by family letter; the map from letter to family, and a salt, stay with the owner. Since the rework of v0.6.0 a chained line of the round record of method version 0.6.0 or later carries `family_map_commitment`, the sha256, over UTF-8, of

```
json.dumps(map, sort_keys=True, separators=(',', ':'), ensure_ascii=False) + '\n' + salt
```

where `map` is the object from letter to the description of the family and `salt` a string of 64 hex characters. `p-contract-shape` checks the form only (64 hex characters); the owner proves the commitment by revealing the map and the salt, and nothing in the material lets anyone else check it. A pseudonym made of the hash of a host name or a user name is not anonymity (a dictionary reverses it); this is why the material uses letters and a salted commitment.

15.6 What a clone verifies, and what rests on the owner




Figure 15.1: What pins what: the integrity structure of the material at version 0.6.0.

A clone verifies	Only the owner verifies
every gate on every document; the pin and the numbers of `004`, whose document is distributed; the frozen rubric; the provenance of the sensitivity report, the sha256 of each prior document included; the hash chain of the three ledgers	the numbers stated about `000`, whose document is owner-held (its cited sections are committed by sha256, so it cannot be swapped unseen, but a clone cannot read them); that the sensitivity report was made with that document, by regenerating it
that a ledger line written since v0.6.0 was not edited without recomputing the chain	an edit that recomputed the chain; the lines before the chain; the history of the lessons and the record of the experiments' raw files
the family letter each round line records, and the form of its salted commitment	the map from a family letter to a family, and its salt

The residual risks the material declares, as they stand at 0.6.0:

- in a clone without the owner's document, a forged `case sha256` line passes;
- the 8 distinct words of a `no_gate` reason measure form, not content;
- the attestation does not prove the perturbations actually ran, only that the report was made over those inputs;
- the git history distributes the name of the author and the dates of the commits; the gates measure the content, not the history;
- the anchor outside the tree, a signed tag per version, is recommended and not yet made (an open owner decision).

Chapter 16

The instances

16.1 Instance 000: the audiovisual production method

The first executed instance, from which the method was generalized: an audiovisual production method, written in Brazilian Portuguese, held by the owner and not distributable. The registry pins its method document by sha256 and declares its number format (`comma-decimal`) and its heading style (a section `## 6.`, a subsection `### 1.1`, a step `### Passo 15.`), and the canon commits, section by section, to the text of the twelve sections the recorded facts cite. The facts the material states about it are the rows of the canon's "Recorded facts" table — among them 18 roles with a card, 49 artifacts in the graph of its first pilot, 2 maximum rounds per artifact, the review of v1 with 3 blocking, 4 high, 12 medium and 12 low findings, 26 low notes open at v5, a drift gate whose wrong instrument read a p95 of 0.546 s at v1 and 0.10 s once fixed, and an automatic reviewer of which 10 of 12 notes were false `[prior:000-av-production]`. Several rules of the recipe carry the error of this instance that the step prevents, as a measured size of the error.

Its historical vocabulary is recorded in the canon so that the frozen records of round 1 can be read: the validator was its "continuity checker"; the verdicts were "publishable", "publishable with minor corrections" and "rejected"; the production cell carried a media term; the quarantine mark of a bracketed word became `[prior:<id>]`.

16.2 Instance 004: the adoption guide

The second executed instance: the adoption guide of the method itself, in Brazilian Portuguese, of 900 to 1,400 words by its brief, produced under method version 0.2.2 with a writer of one family and a review in a separate dispatch without the producer's reasoning, which gave `accepted` with no dimension below 4 and a guide of 1,054 words `[prior:004-adoption-guide]`. That review was first recorded as coming from another family; it came from the producer's own model through another route, so it separated the session and the reasoning, not the family.

Its cell is distributed under `instances/004-adoption-guide/` since v0.5.0, as a **record, not an example to copy**:

- it does not run under the current validator without a migration (the migration notes of `CHANGELOG.md`);
- its own copy of the validator, `08-validator/validator.py`, is the instrument of 0.2.2 and since v0.6.0 refuses to run unless called with `--historical`, because its exit 0 does not mean what the current validator's does (under 0.2.2 a gate that was not measured left the run with exit 0); that flag is the only change made to the cell since it was distributed;
- its `ERRATA.md` lists what the guide says that is no longer true when read against the material as it stands (the rubric is frozen before the first review, not before the production; the registry holds two executed instances; the skill copied alone creates a cell without the validator; independence across families is a recommendation, not a rule);
- its list of forbidden identifiers stayed with the owner, outside the material, since it contains what it forbids.

The cell shows the shape of a JSON-layout cell at 0.2.2: `00-brief.md`, `01-sources-of-truth.md`, `02-canon.json`, `03-artifacts.json`, `04-roles/` (four cards), `05-contracts/`, `06-gates.md`, `07-rubric.md` with its pin, `08-validator/` with its reports, `09-engine/`, `review/` (two wave reports and the round-1 notes), `state/`, `lessons.md`, `open-notes.json`, `priors.json`, `layout.json`, the guide, the method document and the errata.

Whether a new cell under 0.6.0 replaces it as the example is an open owner decision (appendix F).

16.3 The three designed instances

Three instances were chosen because they differ from each other, and each fills the fourteen rows of the instantiation table and the fourteen mandatory sections with domain content marked `[hypothesis]` where it is an assumption. They are designed sketches, not executions, and carry the design, not a result.

Element	Car (`20-instance-car.md`)	Text about 2027 (`21-instance-text-2027.md`)	HPC library (`22-instance-hpc.md`)
Target	the design of a battery-electric passenger vehicle released for tooling, with approved validation prototypes and a homologation dossier	a publishable nonfiction manuscript of about 90 thousand words in 12 chapters on the world in 2027, saying on every page which statement is fact, projection or opinion	a C++ library with a C interface that replaces the reference implementation of a 3D finite-difference operator, with measured speedup and byte-for-byte identical outputs
Owner	the program director	the author	the library's technical lead
Sources of truth	requirement → brief and regulatory matrix; geometry → released CAD; mass → weighing; cost → supplier quotation; physics → correlated simulation; standard → the regulation's text	fact → primary source; projection → declared model; number → claims register; quotation → original; figure → data plus script	correctness → oracle (frozen reference and hashed outputs); performance → measurement on a pinned node with the configuration obtained recorded; where the time goes → attribution instrument
Main artifacts	requirements, architecture, budgets, subsystem CAD, virtual vehicle, BOM, simulations, safety analysis, validation plan, test reports, homologation dossier	thesis, theme map, domain dossier, claims register, projections, outline, scenarios, chapters, figures, fact-check, manuscript	specification, interface, oracle, attribution report, lever decision, experiment plan, implementation, tests, build, equivalence, measurements, performance report, documentation
Main gates	mass against target with reserve, range with the real mass, charging time, clearances, crash margin, thermal propagation, traceability, coverage, quoted cost, simulation × test correlation	every claim with a register identifier, every projection marked, primary source, source density, readability, size per chapter, overlap, recheck of volatile claims	byte-for-byte equivalence, independence from order and thread count, sensitivity of the gate to mutations, configuration obtained, noise, speedup with confidence interval, size sweep, prediction written beforehand, sanitizers, third-party reproduction
Review rubric	a design review by a panel from outside the program	blind reading by readers from the target audience	code review and benchmark reproduction by someone who did not implement
What stays with the human	targets, styling, supplier choice, residual risk, safety sign-off, the decision to launch	thesis, tone, opinion, the label of projection or opinion, legal risk, release	what to optimize, the target, acceptable memory, new dependencies, the budget, the release

What each sketch adds to the method's vocabulary: the car shows the gates of a physical product and the fidelity ladder of its versions (paper, virtual, engineering prototype, validation prototype); the text shows the separation of fact, projection and opinion as a contract of the claims register and a gate on the chapters; the HPC library shows the danger moving from the role that writes badly to the instrument that measures wrongly and passes — the equivalence gate that never rejects, the benchmark that records the threads requested and not the threads obtained, the speedup measured at an extreme point and generalized — and makes "measure what the system gave, not what was asked for" the first gate of the loop.

16.4 The registry as a contract

`instances/registry.json` is one list; the status of an entry decides its fields, and `p-contract-shape` enforces that contract on every run. A cell keeps its own registry, `priors.json`, in the same contract, and registers itself in it at the close of its production (step 14 of the recipe), which is also what makes the token of its own id read as a name rather than as a number.

Part IV

Using the method

Chapter 17

Quick start

17.1 The ten-minute path

The root `README.md` gives a four-step path; here it is with the commands run from the root of the material.

1. Read the first section and section 7 of `01-principle.md` (the idea and the recipe).
2. Scaffold a cell:

```
python3 skills/cooperatio-teamwork/scripts/scaffold.py \
    --target "My target" --roles writer reviewer --out ./teamwork
```

3. Fill the brief, give each non-negotiable an id (`nn-<name>`), fill the lists of `02-canon.json` the validator reads and one card per role (the skill's `references/templates.md` has a filled example).
4. Freeze the rubric, run the sensitivity test, then the validator, with the commands of the skill ("The commands of a cell", reproduced in chapter 19); read every pending row before reading the exit code.

17.2 What the scaffold writes

With two roles the scaffold writes 24 files, refusing to overwrite anything that exists; of the folders it creates, `09-engine/` and `review/` stay empty:

File	What it is
`00-brief.md`	the brief template: target, audience, non-negotiables, owner decisions, budget and stop
`01-sources-of-truth.md`	the table of sources per content type
`02-canon.json`	the canon as data: four sections, the lists the validator reads (empty), the recorded facts (empty)
`03-artifacts.json`	one placeholder artifact record
`04-roles/<role>.md`	one card per role, seven bold fields with placeholders, a link to the canon
`05-contracts/02-canon.schema.json`	the contract of the JSON canon (written by the scaffold)
`05-contracts/notes.schema.json`, `notes-status.schema.json`, `round-record.schema.json`, `domain-result.schema.json`	copied from the material
`06-gates.md`	an empty gate table and an empty "Size ranges" table
`07-rubric.md`, `07-rubric.sha256`	the rubric template and the pin placeholder `not-frozen`
`08-validator/validator.py`, `sensitivity.py`, `perturbation_set.py`	copied from the material
`08-validator/perturbations.json`	three generic perturbations (an avoid-word, an absolute path, a deleted card field)
`layout.json`	the layout of the cell (chapter 12)
`lessons.md`, `open-notes.json`, `priors.json`	empty

File	What it is
`state/notes-status.jsonl`, `state/round-record.jsonl`	empty

17.3 The first run is red, by design

Verified on a cell scaffolded with three roles at 0.6.0: the self-test passes (185 checks), and the first validator run

```
python3 08-validator/validator.py --folder . --layout layout.json \
    --rubric-hash 07-rubric.sha256 --notes open-notes.json \
    --allow-pending p-anonymity
```

exits 1 with 3 blocking and 8 high notes: "no documents were measured; a production with no documents is not green" (the placeholder artifact matches no file), "declared artifact missing: `<relative path>`", "no sensitivity report at `08-validator/sensitivity.md`", and one high note per Markdown document of the cell that "belongs to no artifact and is not declared outside the artifact table". This is the contract: a newly scaffolded cell fails until it has real artifacts.

17.4 The shortest path to green, verified

The following edits, made on a cell scaffolded with `--roles writer reviewer`, took it from that red run to exit 0 with no notes in one pass (verified on 0.6.0; the full chapter 18 is the real procedure, this is the smallest cell the instrument accepts):

1. **`00-brief.md`**: a link to the canon (`Canon: [02-canon.json](02-canon.json)`), a `Languages: en` line, two non-negotiables with ids (`nn-source`, `nn-size`), one decided owner decision, a budget and a stop.
2. **`02-canon.json`**: `terms to avoid` (`pipeline`, `checkpoint`), the seven `role card fields`, the three `origin labels`, and `documents outside the artifact list` set to `01-sources-of-truth.md`, `07-rubric.md`, `lessons.md`, `08-validator/*.md`.
3. **`03-artifacts.json`**: three records — `brief` (`00-brief.md`, gates `p-terms`, `p-canon-link`, `p-anonymity`, `p-form`), `cards` (`04-roles/*.md`, those four plus `p-card`) and `gates` (`06-gates.md`, gates `p-limit`, `p-terms`, `p-canon-link`, `p-form`).
4. **`04-roles/writer.md`, `reviewer.md`**: the seven fields filled with one line each, the executor named by family and effort in the degree field.
5. **`06-gates.md`**: a link to the canon and one row per gate assigned above, each naming the same artifacts, with a magnitude, a limit and a justification of at least six words starting with an origin label; the "Size ranges" table left empty.
6. **`08-validator/perturbations.json`**: the three generic perturbations kept, plus one each for `p-form` (an HTML tag in the brief), `p-canon-link` (a broken link in a card) and `p-limit` (a justification deleted in the gates file), so that every assigned gate has one.

Then the four commands of the cell (chapter 19): the self-test (185 checks); the freeze, which printed the pin and replaced `not-frozen`; the sensitivity test, whose report read "Caught 6 of 6. Noisy: 0 of 6. Pairs covered: 6 of 22."; and the validator, which wrote a report of 23 rows with `p-sensitivity` at "6 of 6 gates covered, 6 of 22 pairs (27 %), 0 missed of 6, 0 noisy", three `p-anonymity` rows pending and accepted (the identifier half, with no forbidden list), `m-determinism` passed, and exit 0. Had the three generic perturbations been left alone, `p-sensitivity` would have been pending for the three uncovered gates and the run would have exited 4.

Chapter 18

Setting up a cell

This chapter condenses the fifteen steps of `02-reflexive-application/10-generic-recipe.md` and the procedure of the skill into one how-to. Each step says what it creates and when it is done; the recipe adds, for each, who performs it, what it reads and the trap the step exists to avoid.




Figure 18.1: The fifteen steps of the generic recipe and the file each one creates.

18.1 Step 0 — the folder

Create the tree (the scaffold does), decide where everything that stays out of version control goes and record it in the brief, and decide how machine-dependent paths enter: always as a command-line variable,

never written into an artifact. Done when the tree exists, the ledgers exist and are empty, and `priors.json` parses. Trap: starting to write the brief in a conversation. What is not in a file has no hash, and what has no hash makes nobody stale.

18.2 Step 1 — the brief

`00-brief.md`, with fixed sections: target; for whom; non-negotiables, each with an id in a code span (`nn-<name>`), written as sentences a gate could measure ("mass ≤ X kg", "no fact without a source", not "safe", "good", "fast"); owner decisions as a table with a status (and, since v0.6.0, as lines of `state/owner-decisions.jsonl`); available sources of truth; budget (maximum rounds per artifact, review rounds); a provisional stopping criterion; what is not an objective; assumptions labeled `[hypothesis]`. The brief also declares the languages of the documents on a line `Languages: en` (two-letter codes), which the anonymity gate reads. Done when every section is filled or says "owner decision pending", and the owner recorded the approval.

18.3 Step 2 — the sources of truth

`01-sources-of-truth.md`: a table with content type, the source that errs least, who consults it, and what is forbidden as a source. The writer is never a source of fact; a generative tool is never a source of exact text; a number never comes from the paragraph that cites it. Done when every content type of the brief has exactly one source.

18.4 Step 3 — the canon

`02-canon.json`, with its schema in `05-contracts/`. Sections with owner, version and state; canonical numbers (spelling by medium, unit, rounding, nature, source); accepted variants; names and terms; rules. Fill the lists the validator reads (a list left empty leaves its gate pending): `terms to avoid`, `role card fields`, `origin labels` (with their brackets), and the others the scaffold writes empty. List under `documents outside the artifact list` the Markdown documents of the cell that belong to no artifact (`01-sources-of-truth.md`, `07-rubric.md`, `lessons.md`, `08-validator/*.md`), or `p-declared` reports them. Every number the cell states about a registered prior gets a row of `recorded facts`:

```
{ "number": "18", "context": "roles with a card [prior:<id>]", "section": "1.1" }
```

Done when every section has an owner and a version, every number of the brief is in the canon, and the schema validates.

18.5 Step 4 — the artifacts and the graph

`03-artifacts.json`: one record per artifact (chapter 6). Start from the target and walk backward; give each artifact a single owner; turn every owner decision into an artifact with resource `human`; mark as `proposed` an artifact that has no file yet; compute the topological order. The `gates` field of each record is the one source of the gate map. Done when the graph is acyclic, every artifact has one owner, at least one gate and (except the target) at least one consumer. Trap: a finding that lands on the nearest artifact because the right target is not in the graph.

18.6 Step 5 — the role cards

`04-roles/<role>.md`, one per artifact owner, with the seven fields as bold labels (`**Decides:**`), plus "Questions it always asks" and the base prompt the orchestrator hands to the agent. In "Does not decide", write the neighboring decisions the role would be tempted to make and whose they are. In the degree field, name the executor: a person, code, or a kind of language model by family and effort; a role that audits another gets an executor different from the one that produced the artifact. Done when every

card has the seven fields, no decision appears in "Decides" of two cards, and no auditing role shares an executor with the role it audits.

18.7 Step 6 — the contracts

`05-contracts/<artifact>.schema.json` for each artifact that passes between roles, rejecting unknown fields and the domain's most likely ambiguity, with one valid and one invalid example; the invalid one has to fail. Done when validation runs in seconds, before any expensive work. Trap: the ambiguous position key.

18.8 Step 7 — the gates

`06-gates.md`: one row per gate of the artifact list, naming the same artifacts, with magnitude, limit and a justification that starts with an origin label and has at least six words; a "Size ranges" table with the word range of each document, declared before writing. Give every signal gate a magnitude limit on both sides; separate "rejects" from "tool failure"; never let a limit inherit a prior's number. A gate of the domain is a row `d-<name>` (chapter 21). The ids have to be ones the validator implements, or `d-*`: any other id exits 2. Done when every limit has a justification with an origin, and every code gate rejected its known perturbation.

18.9 Step 8 — the rubric, frozen

`07-rubric.md`: six to ten dimensions with anchors for 1, 3 and 5; the severity scale; the mechanical verdict rule; the report format. Then:

```
python3 08-validator/validator.py --folder . --layout layout.json \
    --freeze-rubric 07-rubric.sha256
```

The scaffold's pin holds the placeholder `not-frozen`, which the first freeze replaces; a real pin is refused, and a deliberate replacement goes through `--re-freeze-rubric`. Done when the hash is recorded before the first review and the round record will name who wrote the rubric. Written by the owner with whoever will review; never by whoever will produce, alone.

18.10 Step 9 — the validator

The scaffold copied `validator.py`, `sensitivity.py` and `perturbation_set.py` into `08-validator/`. Adapt the three generic perturbations of `perturbations.json` to the cell's text and add one per gate the cell assigns. Run the sensitivity test, then the validator (chapter 19). Done when two runs give an identical report, every gate has its perturbation caught, and the validator refuses a canon of another schema version.

18.11 Step 10 — the assembly engine

`09-engine/`: the graph core (state, hash per artifact, plan, execute), the note router, the assembly of the target and the tests. The content hash of an artifact is the sha256 over the canonical form of the file (UTF-8, the whitespace at the end of each line normalized, a single final newline). The plan marks each artifact `current`, `stale`, `missing`, `returned` or `escalated`; only what is stale runs, in topological order; the router refuses an unknown target, deduplicates, and only high and blocking return the artifact; the assembly validates every contract before the expensive work and names the output with the version label. Done when assembling twice with the same inputs gives the same product. Trap: the namesake file from an old version, which every reader silently picks.

18.12 Step 11 — the quick first version and its review

Produce every artifact, even bad, instead of polishing the first ones; assemble; hand the reviewer only the files and the rubric; record in the dispatch the output limit and the reason the generation ended; import the review's notes into the ledger. Done when every artifact exists, the report follows the rubric's format and the notes entered the ledger without refusal. Trap: polishing v1.

18.13 Step 12 — the round loop

Chapter 20.

18.14 Step 13 — the stop

The owner declares the criterion before the last round, in terms of rounds or verdict, never calendar; the review of the last version becomes open notes in `open-notes.json`, in the contract; a violated non-negotiable is not an open note but an undelivered target.

18.15 Step 14 — the case method document and the registration

`method-TARGET.md`: the ideas with the defect each prevents, the graph, the step by step with the real commands, the pseudocode per role with its degree, the owner decisions, the known false positives with a status, `[unverified]` on whatever was not checked. Register the instance in `priors.json` with id, status, the document's path relative to its own repository root, its sha256, its locator and its number format. Trap: a document that repeats the READMEs.

18.16 Before handing over

Run through `skills/cooperatio-teamwork/references/review-checklist.md`. At minimum: every document points to the canon; every gate has magnitude, limit and a justified origin label; the graph is acyclic; every owner is a role or the owner; every card has the seven fields; the rubric hash is recorded; every non-negotiable of the domain is a `d-*` gate whose result the cell's code writes; the validator exits 0 and every pending it reports is one of the four it accepts by name, with the reason; and the files do not claim the method has been validated on this target — the first review round does that.

Chapter 19

Running the instrument

19.1 The commands of a cell

From inside the cell, after the files are filled (the skill, "The commands of a cell"):

```
python3 08-validator/validator.py --folder . --layout layout.json --self-test
python3 08-validator/validator.py --folder . --layout layout.json \
    --freeze-rubric 07-rubric.sha256
python3 08-validator/sensitivity.py --folder . --layout layout.json \
    --rubric-hash 07-rubric.sha256 --notes open-notes.json --work SCRATCH_FOLDER
python3 08-validator/validator.py --folder . --layout layout.json \
    --rubric-hash 07-rubric.sha256 --notes open-notes.json \
    --allow-pending p-anonymity --determinism --output 08-validator/report.md
python3 -B -m pytest -p no:cacheprovider tests/
```

The last line only if the cell keeps a test suite. Add `--case` for each registered prior the cell cites, and `--forbidden` with the cell's list of forbidden identifiers kept outside the cell (then drop `--allow-pending`). Run the sensitivity test again after every change to the validator, the gates file, the canon, the artifact list's gate map or the perturbation set, and before the validator: the validator reads the report and fails `p-sensitivity` on provenance otherwise.

19.2 The commands of the corpus

From `02-reflexive-application/` (its README, "How to run the validator"):

```
python3 80-validator/sensitivity.py --folder . \
    --case PRIOR_000_DOCUMENT_PATH \
    --case ../instances/004-adoption-guide/metodo-de-producao.md \
    --rubric-hash 90-review/rubric.sha256 --notes 90-review/notes.json \
    --work SCRATCH_FOLDER --output 80-validator/sensitivity.md
python3 80-validator/validator.py --folder . \
    --case PRIOR_000_DOCUMENT_PATH \
    --case ../instances/004-adoption-guide/metodo-de-producao.md \
    --rubric-hash 90-review/rubric.sha256 --notes 90-review/notes.json \
    --allow-pending p-anonymity --determinism --output 80-validator/report.md
python3 80-validator/validator.py --self-test
python3 -B -m pytest -p no:cacheprovider 80-validator/test_validator.py \
    ../skills/cooperatio-teamwork/scripts/test_scaffold.py
```

The published report is made with exactly that command; at 0.6.0 it exits 0 with no notes, 27 rows of `p-anonymity` pending and accepted (the identifier half, with no forbidden list), `m-determinism` passed, the self-test at 185 checks; the sensitivity report reads 65 of 65 caught, 0 noisy, 50 of 182 pairs; the test suites pass 280 tests.

19.3 The clone run

The method document of instance 000 stays with the owner, so a clone of the material does not have it. The clone passes the document of 004 and accepts by name the gates that need the owner's:

```
python3 80-validator/validator.py --folder . \
    --case ../instances/004-adoption-guide/metodo-de-producao.md \
    --rubric-hash 90-review/rubric.sha256 --notes 90-review/notes.json \
    --allow-pending p-anonymity,p-prior,p-prior-pin --determinism
```

Expected: exit 0, no notes, the report on the standard output, the three gates listed as pending accepted by the caller, the pin and the numbers of 004 measured (its edited document, or an invented number about it, is a blocking note, exit 1), and the rows of 000 saying "owner-held evidence, not measured here". Without any `--case` the same run still exits 0, but measures neither pin.

A clone that edits the instrument cannot regenerate the sensitivity report with the owner's document; it regenerates one with a synthetic prior:

```
python3 80-validator/sensitivity.py --folder . \
    --case ../instances/004-adoption-guide/metodo-de-producao.md \
    --synthetic-prior 000-av-production \
    --rubric-hash 90-review/rubric.sha256 --notes 90-review/notes.json \
    --work SCRATCH_FOLDER --output 80-validator/sensitivity.md
```

and then adds `p-sensitivity-synthetic` to `--allow-pending` of the clone run. The report stays pending until the owner regenerates it with the document (chapter 14).

19.4 Reading a report

Read the pending rows before the exit code. A row is `pass`, `fail` or `pending`; the lines after the table say which pending gates the caller accepted, which it did not (the run exits 4 for those unless a note exits 1), and which accepted gates had nothing pending ("Accepted but not pending", so the caller sees that the acceptance covered nothing). The notes table gives, per note, the target artifact, the severity, the text (prefixed by the gate id) and the evidence (the document). With `--output`, one summary line goes to the error stream.


19.5 Troubleshooting

Message or symptom	Cause	What to do
`no documents were measured; a production with no documents is not green` (blocking, on `artifacts`)	the artifact list has no record whose paths match a file, or no gates	fill `03-artifacts.json` with real records and gates
`p-declared: declared artifact missing: <path>` (blocking)	a literal path of an artifact matches no file, or a glob matches nothing	create the file or fix the path
`p-declared: document X belongs to no artifact and is not declared outside the artifact table` (high)	a Markdown document of the folder is neither an artifact nor listed in the canon	add it to an artifact's paths, or list it under `documents outside the artifact list` with the reason
`p-sensitivity: no sensitivity report at ...` (blocking)	`sensitivity.py` has not run, or the layout key `artifacts.sensitivity` points elsewhere	run the sensitivity test
`p-sensitivity` fails on provenance (validator, gates, canon or map sha)	the instrument or its inputs changed after the report	regenerate the report, then the validator report
`p-sensitivity` pending: an assigned gate without a perturbation, or fewer than 25 % of pairs	the perturbation set does not cover the cell's gates	add one perturbation per gate the artifact list assigns

Message or symptom	Cause	What to do
exit 4 with `Pending not accepted: ...`	a gate was not measured and the caller did not accept it	supply the input (`--notes`, `--rubric-hash`, `--case`, the canon's list, the domain result), or accept it by name when it is one of the four
`--allow-pending accepts only p-anonymity, p-prior, p-prior-pin, p-sensitivity-synthetic ...` (exit 2)	the caller named a gate that has to be measured	measure it
`--allow-pending names gates this validator does not implement` (exit 2)	a typo in the gate name	fix the name
`the rubric is already frozen at ...` (exit 2)	`--freeze-rubric` on an existing pin	leave the pin, or `--re-freeze-rubric` deliberately with the reason in the changelog
`the gate table has more than one row for ...` (exit 2)	two rows for one gate	one row per gate
a gate id the validator does not implement (exit 2)	a placeholder row, a typo, or a cell-specific gate not named `d-*`	use a builtin id, or a `d-*` row with a result file
`layout: ...` or a layout key refused (exit 2)	a key the validator does not read (a typo such as `sensitivty`)	use the keys of chapter 12
`more than one parser` (exit 2)	a cell from before 0.4.0 whose layout lacks `p-efficacy-mark` in its gate map, so the merged map names two parsers	add the gate to the layout's map
`p-prior`: a number of a marked unit unverified (blocking)	the number has no row in the recorded facts, or is absent from the sections the row cites, or the prior's document was not passed	add the row and check the number; pass `--case`
`p-prior`: malformed mark (blocking)	a `[prior:...]` whose id is not lowercase letters, digits and hyphens	fix the id
`p-prior-pin` blocking on the registry	a document passed is the pin of no executed instance, or a distributed prior's pin matches no document	pass the right document; check the registry's sha256
`p-contract-shape`: a broken chain	an earlier chained line was edited, removed or reordered	restore the line; a state change is a new line
`p-notes`: an escaped regression closed with neither a gate nor a reason (high)	the ledger line has `escaped: true` and no `gate` of the gate table, no `no_gate` of 8 distinct words and no decided `decision`	name the gate, or write the reason
`p-anonymity-language` pending on the brief	the brief declares a language with no built-in months and no row in the canon's "Month names"	add the row with the twelve names
`Python 3.9 or later is required` (exit 2)	an older interpreter	use 3.9 or later

Chapter 20

Running a round



20.1 Before the review

The review only starts after the validator passes on every document and the sensitivity report is current: reviewing a text that the validator fails would spend a review round on defects the code already finds.

20.2 The dispatch

The reviewer receives the files and the rubric, never the reasoning of whoever produced them. The dispatch records the effective output limit of the executor and the reason its generation ended. A report that ended for length or lacks a section of the format is a tool failure and produces no verdict; the review runs again. The reviewer's relation to the producer is recorded in the round record (`reviewer_relation`), checked on what each alias or route maps to, not on its name: a second session of the producing model is `same family, separate session` or `same model, separate route`, never "independent".

20.3 Importing and classifying

Import the notes into the ledger (the router refuses an unknown target and deduplicates); only high and blocking return the artifact. Classify each finding:

- **product defect** — a note to the artifact where it originated;
- **regression that escaped every gate** — first create the gate (which has to reject the current version) with its perturbation, then fix; the state ledger records the note as `escaped`, and it closes with the `gate` it became or a `no_gate` reason;
- **false positive** — fix the instrument's rule at the root, with a test that reproduces the case, and redo the previous round to prove that no real finding disappeared; never loosen the limit.

Each owner answers note by note: done (where), partial (what is missing), contested (reason) or out of scope (for whom). A validator note the writer disputes goes to the verifier, who decides whether it is a false positive.

20.4 Closing the round

The engine recompiles what is stale; the gates run; the validator runs; the reviewer reviews with the same rubric and makes the item-by-item table of the previous round. The round's entry goes to `lessons.md` (what it taught and what became code, contract or gate), and a line goes to `state/round-record.jsonl`:

```
{"method_version": "0.6.0", "round": "v2", "kind": "production",
 "models": [{"role": "writer", "model": "family A, high effort"},
            {"role": "reviewer", "model": "family B, high effort"}],
 "reviewer_relation": "another family",
 "rubric_applied": true, "rubric_hash": "<the frozen sha256>", "rubric_author": "owner",
 "family_map_commitment": "<64 hex characters>",
 "summary": "...", "prev": "<sha256 of every line above>"}
```

A production line may carry a `verdict`; a maintenance line may not. The optional cost fields (per role: `tokens` with `input`, `output`, `reasoning`, `cached`; `calls`; `finish`) and the round's `wall_seconds`, `notes_count`, `crew` and `rounds_to_stop` are what the principle asks a round to measure, so that costs become comparable.

20.5 The stop

Done when the criterion is written in terms of rounds or verdict, the open notes validate against the contract with their state in the state ledger, no non-negotiable is among the open notes (an open high or blocking note that affects one is blocking at the stop unless a decided owner decision covers it), the lessons have the round's entry, and the instance is registered and pinned in `priors.json`.

Chapter 21

Domain gates in a cell

The distributed validator measures documents. A target whose non-negotiables are domain measurements — identity of results, a speedup, a mass — needs the cell's own code to write them as results the validator reads, or its exit 0 says nothing about them.

21.1 Declaring the gate

A row `d-<name>` in the cell's gate table, with its magnitude, limit and justification like any other; an optional Severity column sets the severity of a `fail` (high by default; a severity below high counts only for a gate a decided owner decision covers, so a failed identity of results cannot become a low note by the cell's own column). The artifact list assigns the gate to the artifacts it measures, and the result's inputs have to include every file of those artifacts.

21.2 Writing the result

The cell's code measures the gate and writes a result file in the contract `05-contracts/domain-result.schema.json`:

```
{
  "contract_version": "1",
  "gate": "d-identity",
  "magnitude": "0 divergent of 38 cases",
  "limit": "0 divergent",
  "result": "pass",
  "inputs": [ { "path": "v2/candidate.bin", "sha256": "<sha256 of that file>" },
              { "path": "oracle/reference.bin", "sha256": "<sha256 of that file>" } ]
}
```

`result` is `pass`, `fail` or `tool-failure`. The sha256 of an input is that of the file's text read as UTF-8 with LF line breaks (for a binary file, of its bytes). The layout lists the result files under `domain-results`.

21.3 What the validator does with it

It recomputes the sha256 of every input; an input changed or missing makes the result stale (blocking); a result that names no input, or whose inputs do not include every file of the gate's artifacts, is blocking; when the limit starts with a comparison and a number or is a bare zero, the first number of the magnitude is compared and a contradiction is blocking; `fail` is a note of the row's severity; `tool-failure` or a result outside the contract is exit 2; a declared `d-*` gate with no result is pending, which no caller can accept. The validator never runs the cell's code: a result whose inputs were recomputed by hand after the candidate changed passes, and the material says so.

21.4 The cell's own sensitivity

The sensitivity test perturbs documents and leaves domain gates out of its coverage; the sensitivity of a domain gate is the cell's own: mutants of the implementation, a reference with a known defect, a seeded regression that has to leave the run red. Experiment E5 is designed around exactly this (a candidate that breaks identity has to leave the validator at exit 1), and a failing test of the cell is a rejection of its gate, with a note to the implementation where the defect was born.

Chapter 22

Maintaining the material

For a maintainer of the material itself, or of a cell that carries a copy of the instrument.

22.1 The order of a change

Editing the validator, the "Gates" section of the gates file, the canon or the gate map of the artifact table changes a sha the sensitivity report records. The order that keeps the provenance coherent, as the changelog's "Round infra" entries record it: the scripts first; then the canon and the gate section the provenance pins; then the sensitivity report (regenerated with the owner's document, or with the synthetic prior in a clone); then the other documents and the validator report; then a round-record line, chained, with the executors by family and effort.

22.2 Adding a gate or a perturbation

A new gate needs, in the same change: its implementation and its handler in the family it belongs to; a row in the gate table; its assignment in the artifact list; its perturbation in `perturbation_set.py` (or the cell's `perturbations.json`); a test in the suite; its declared semantics in `06-gate-semantics.md` where a cell of the table is not enough; and a regenerated sensitivity report. The lesson of v0.6.0 is the rule: when a correction moves a definition, the place it moves to gets the pin, the completeness check and the perturbation in the same round, or the correction is declared incomplete.

22.3 Retiring a gate

The row, the assignment and the perturbation leave together, and the changelog records "retired gate: `<id>`", the reason and the rounds it stayed silent (chapter 7).

22.4 Re-freezing the rubric

Only when another review round opens: a new rubric is written by the reviewing side, frozen through `--re-freeze-rubric` with the reason in the changelog, and the round record names its author.

22.5 Ledgers and frozen records

A change of state is a new chained line, never an edit; the last line of a ledger is the one the chain does not yet cover, so append before relying on it. The records of `90-review/` and the history of the lessons above the measured heading are never edited; the append-only rule of the lessons is checked by hand at each round (the old file has to be a prefix of the new one), and the sweep for forbidden identifiers is run by hand each round, recorded outside the material.

22.6 Migration notes

Each entry of `CHANGELOG.md` carries a migration note for a cell that moves to that version. The ones a cell from an older validator meets, in order:

To version	A cell has to
0.3.0	re-run `sensitivity.py`, since reports without the provenance header fail `p-sensitivity` by design; name its rubric in the layout (`artifacts.rubric`)
0.4.0	add `p-efficacy-mark` to the gate map of its layout (else exit 2, "more than one parser"); give its executed priors a `number_format`; give every number it states about a prior a row of its JSON canon's recorded facts; register its own entry in its priors registry; make the card links resolve; regenerate the sensitivity report
0.4.1	cite an instance inside a marked unit by its full id; give every executed entry a `locator` and a `number_format`, and keep the four fields null on a designed one; cite only executed experiments; name executors by family and effort, model identifiers going to the forbidden list
0.4.2	replace a copy of the validator from before 0.4.2 (it wrote a bytecode cache); run pytest with `-B -p no:cacheprovider`
0.5.0	give its artifact records a `gates` list and keep the gate table in step; fill the canon's lists or accept their pending by name; remove placeholders; write cards in bold fields; add `contract_version` to its contracts; give each note a line in the state ledger; copy `sensitivity.py`, write `perturbations.json`, name it in the layout and regenerate the report
0.6.0	list its Markdown documents outside the artifact list in the canon; give every literal path a file; write its `d-*` gates as result files under `domain-results`; use `[lessons:<title>]` and a provenance table for each cited experiment; freeze its rubric and pass `--notes` (their pending can no longer be accepted); regenerate the report (map, specificity, pairs); copy `perturbation_set.py`; give its non-negotiables ids and keep the owner's decisions in `state/owner-decisions.jsonl`; schedule, dispute or close the open notes older than three rounds; declare `"version": "v1"` in its JSON canon

22.7 The tests

```
python3 02-reflexive-application/80-validator/validator.py --self-test
python3 -B -m pytest -p no:cacheprovider \
    02-reflexive-application/80-validator/test_validator.py \
    skills/cooperatio-teamwork/scripts/test_scaffold.py
```

The suite runs the self-test, one passing and one failing case per rule, the regression tests of the probes the panels found (a repointed file, a mark outside its grammar, a number between backticks, a deleted report accepted by name, a domain regression the validator never read), and the scaffold's integration test, which asserts that a fresh cell fails high.

22.8 The freeze policy, restated

After 0.6.0 the instrument changes only for a failure that changes a verdict, or for a new execution. A maintainer who finds a false green adds a row to the table of false greens, a regression test and, where it

is a defect of a document, a perturbation — and declares the change in the changelog with its migration note.

Part V

Appendices

Appendix A — Glossary

Condensed from the "Method terms" table of `02-reflexive-application/01-canon.md`, which is the authoritative definition of each term.

Term	Definition
accepted variant	another spelling of a number or term that the canon admits in a declared place and for a declared reason
artifact	an intermediate or final output, typed, with a name, a single owner, paths, a schema, dependencies, gates and content identified by hash; an owner decision is also an artifact
artifact graph	the set of artifacts with the dependencies between them; it has to be acyclic
assembly engine	the code that composes the artifacts into the target, rejects ambiguity, rebuilds by hash, routes notes and names the outputs by version label
brief	the owner's document: what the target is, for whom, what is non-negotiable, what is an owner decision, the round budget
canon	the single source of numbers, names, terms to prefer and to avoid, accepted variants and rules, with an owner and a version per section
case method document	the document that records, at the end, the ideas, graph, step by step, pseudocode per role with its degree, the owner's pending items and the known false positives of an instance
code-conversion degree	how much of a role's work the code does: (a) converted, (b) partial under gate, (c) contract and gate only
contract	the schema an artifact has to validate before it is accepted
corpus	the facts, materials, standards and references available before the production; read, never edited
dispatch	one call of an executor with its inputs, recorded with what the endpoint returned (tokens, the reason the generation ended)
domain gate	a gate of the target's domain, named `d-<name>`, measured by the cell's own code and read by the validator from a result file
escalated	the state of an artifact that exceeded its maximum rounds: nothing that depends on it runs until the owner decides
executor	whoever or whatever exercises a role: a person, code, or a language model of a declared kind
experiment	a measurement about the method itself, registered with its question, protocol and predictions written before measuring; `executed`, `pending` or `designed`
false negative	a real defect that no instrument reported
false positive	a note the instrument emits when there is no defect; an instrument defect until proven otherwise
family	the provider and line of models an executor belongs to, named by a stable letter

Term	Definition
first version	the v1: the whole target, end to end, made quickly to be reviewed, not to be good
gate	a measurable function over an artifact that returns pass or fail together with the measured magnitude; with a limit and a written justification
gate sensitivity test	injecting a known defect and checking that the gate rejects it, before trusting the gate
hand-off sheet	the artifact one role writes for another role to consume
independent review	a reading of the product by someone who did not produce it and has no access to the producer's reasoning, with the fixed rubric
instance registry	the record of the known instances, each with an id, a status, the path of its method document and the sha256 that pins it
instantiation table	the table of fourteen fixed rows that summarizes an instance
instrument	anything that measures: gate, validator, reviewer, simulation, benchmark
limit	the value that separates pass from fail, with the justification and the origin label next to it
magnitude	the measured value the gate returns, never just a sign
maintenance round	a round that corrects the material of the method itself after its stopping criterion, outside the reflexive production, with no verdict of the canon
maximum rounds	how many returns an artifact accepts before it is escalated to the owner
note	the only change request between roles: target artifact, severity, text, origin, evidence, round
open note	a note recorded and not resolved when the production stops
orchestrator	whoever executes the recipe: passes paths to the roles, runs the engine and imports notes; a step, not a role
owner	the person who commissions the target, approves the brief, makes the decisions no role can make and declares the stop
position key	the value that fixes where a part of the target lands during assembly; an ambiguous one is a contract error
prior instance	an instance of the method that ran before the current one and is registered in the registry
production cell	the organization assembled for one target: roles, artifacts, gates, canon, validator, review and assembly engine
regression	a defect that comes back or appears in a new version; if it escaped every gate, it gains a gate before it is fixed
retired gate	a gate removed deliberately, with its perturbation, because its object is gone or its rule moved into a contract
role	a narrow responsibility exercised by an agent, a person or code, which communicates only through artifacts and notes
role card	the sheet of a role with seven fixed fields
root-cause fix	handling a false positive by fixing the instrument's rule, with a test that reproduces the case, and redoing the previous round
round	one pass of the loop: produce, pass the gates, assemble, review, notes
rubric	the fixed grid of dimensions, anchors and verdict rule that every independent review uses in every round
rubric anchor	the written description of what a score of 1, 3 or 5 means in one rubric dimension
runner	the role that runs the validator and routes its notes; it decides nothing beyond the rules the validator executes
severity	`low`, `medium`, `high`, `blocking`; only the last two send the artifact back

Term	Definition
signal gate	a gate that only tests existence or “greater than zero”; it has to gain a magnitude limit
source of truth	for each content type, the only source accepted as origin; the writer is never a source of fact
stale	the state of an artifact whose input changed since it passed its gates
stopping criterion	the condition, declared by the owner before the last round, under which the review becomes a list of open notes
target	the final product that the production cell hands over
teamwork	the files that set up a production cell for a target; the name of the skill that creates them
unit	what a gate reads as one statement: a paragraph, a list item, a table row or a heading
validator	a checking instrument, preferably in code, that reads all artifacts against the canon and emits notes on its own
verdict	`rejected`, `accepted with conditions`, `accepted`
wave	a batch of dispatches run in parallel, whose outputs are read together before the next step

Appendix B — The contracts

Six JSON Schemas under `02-reflexive-application/05-contracts/`, each declaring `contract_version` `1` and rejecting unknown fields. The validator applies a closed subset of JSON Schema keywords and reports a contract that uses others.

Contract	File	Required fields	Optional fields
Note	`notes.schema.json`	`target_artifact`, `severity` (the four values), `text`, `origin`, `evidence`, `round` (string, or the legacy integer)	`status` (`open`, `fixed`, `disputed`, `out of scope`), `closed_in`
State of a note	`notes-status.schema.json`	`ref` (`notes:<n>` or `panel:<version>:<id>`), `status`, `summary`	`closed_in`, `prev`, `escaped`, `gate`, `no_gate`, `decision`, `opened_in`, `due`, `severity`, `affects`
Instance registry	`registry.schema.json`	`instances`: a list of entries with `id`, `status` (`executed`, `designed`)	per entry: `document`, `sha256`, `locator`, `number_format` (`point-decimal`, `comma-decimal`), `heading_style` (`section`, `subsection`, `step`), `method_version`; an executed entry carries the first four non-null, a designed one keeps them null
Round record	`round-record.schema.json`	`method_version`, `round`, `models` (a list of `role`, `model`, with optional `tokens` of `input`, `output`, `reasoning`, `cached`; `calls`; `finish`), `summary`	`verdict`, `rubric_hash`, `rubric_author`, `family_map_commitment`, `prev`, `kind` (`production`, `maintenance`), `reviewer_relation` (`another family`, `same family`, `separate session`, `same model, separate route`, `none`), `rubric_applied`, `rounds_to_stop`, `wall_seconds`, `notes_count`, `crew`
Domain result	`domain-result.schema.json`	`contract_version`, `gate`, `magnitude`, `limit`, `result` (`pass`, `fail`, `tool-failure`), `inputs` (a list of `path`, `sha256`)	—
Owner decisions	`owner-decisions.schema.json`	`name`, `status` (`open`, `decided`), `blocks`, `version`, `summary`	`covers`, `prev`

The scaffold writes a seventh, `02-canon.schema.json`, the contract of a cell's JSON canon, and copies the first five except the registry's (a cell's `priors.json` follows the same contract, enforced by the validator).

Appendix C — Command-line reference

22.9 `validator.py`

Option	Meaning
`--folder FOLDER`	the production folder (default `.`)
`--layout LAYOUT`	a `layout.json` that remaps artifacts to paths and gates to parsers; default is the Markdown layout of the corpus
`--registry REGISTRY`	the instance registry; default `../instances/registry.json` relative to the folder, when present; without a registry `p-prior` is pending
`--case CASE`	a prior method document, repeatable; each is identified by its sha256 against the registry
`--forbidden FORBIDDEN`	the list of forbidden identifiers, one per line (names or `sha256:<hex>`); without it that half of `p-anonymity` is pending
`--rubric-hash FILE`	the file with the frozen sha256 of the rubric
`--freeze-rubric FILE`	write the current sha256 of the rubric to the file and exit; refuses an existing pin (the scaffold's `not-frozen` placeholder excepted)
`--re-freeze-rubric FILE`	replace an existing frozen rubric deliberately; mutually exclusive with the previous
`--notes NOTES`	the note ledger to validate against the contract, with its state ledger
`--output FILE`	write the report to the file; one summary line goes to the error stream
`--determinism`	run twice more with different hash seeds (and the C locale) and compare the reports
`--allow-pending LIST`	the gates whose pending rows the caller accepts, comma-separated, from the closed list `p-anonymity`, `p-prior`, `p-prior-pin`, `p-sensitivity-synthetic`
`--self-test`	run the embedded checks and exit

Exit codes: 0, 1, 2, 4 (chapter 12).

22.10 `sensitivity.py`

Option	Meaning
`--folder FOLDER`	the production folder to copy and perturb
`--case CASE`	as in the validator, repeatable; without any, the rows that need a prior are not measured
`--forbidden FORBIDDEN`	the list of forbidden identifiers
`--registry REGISTRY`	the instance registry
`--rubric-hash FILE`	forwarded to the validator; without it the `p-frozen-rubric` row is not measured
`--notes NOTES`	forwarded; without it the `p-notes` row is not measured
`--work WORK`	the scratch folder for the copies (default: a temporary folder)

Option	Meaning
`--output FILE`	where the report is written (default: the layout key `artifacts.sensitivity`)
`--synthetic-prior ID`	an executed prior whose method document you do not have: a synthetic document is generated from the canon's recorded facts and pinned in the copies only
`--layout LAYOUT`	the cell's `layout.json`, which also names the cell's perturbation file

An empty perturbation set exits 4; a gate the validator does not implement in the set is a tool failure (exit 2).

22.11 `scaffold.py`

Option	Meaning
`--target TARGET`	the name of the target (required)
`--roles ROLE [ROLE ...]`	role ids, lowercase letters, digits and hyphens (required)
`--out OUT`	the destination folder (required); the scaffold refuses to overwrite

Run from inside the material, so that it finds the validator, the sensitivity script, the perturbation module and the contracts to copy.

22.12 The historical validator of instance 004

`instances/004-adoption-guide/08-validator/validator.py` is the instrument of 0.2.2 and refuses to run without `--historical`, since its exit 0 does not mean what the current validator's does.

Appendix D — The false greens of the gates

From the table of `06-gate-semantics.md`, "The false greens of the gates": for each gate, the cause of a false green found so far, what detects it today, and the perturbation that covers it. The causes are the ones found, not an exhaustive list.

Gate	Cause of a false green	Current detection	Perturbation that covers it
`p-terms`	a synonym written in a way the lexical match does not see	the canon's list and whole-word matching; the review reads the prose	avoid-word in the changelog
`p-canon-link`	a link that names the canon from the wrong folder	the target resolved relative to the document's folder	link to the canon does not resolve
`p-anonymity`	a path, a date or an identifier in a form the patterns do not know, or hidden by the valve	the patterns, the months of six languages and the canon's own, the forbidden list by name or sha256; an accepted path dropped only by equality	date written with the month's name
`p-form`	an HTML tag or comment hidden in a block the reader skips	one reader of fences, comments read	HTML comment
`p-size`	a document pushed past its range, or words counted wrong	the declared ranges; table pipes are no words	canon pushed above its size range
`p-table`	an instantiation table missing a row	the canon's fixed list of rows	instantiation table row deleted
`p-sections`	an instance missing a mandatory section	the canon's fixed list of sections	mandatory section heading removed
`p-card`	a card with a field empty, deleted or a placeholder	the seven fields, the placeholder detector	placeholder in a card field
`p-limit`	a justification of six words of any kind, or a limit raised in the table	the origin label and the word count; the Limit column compared	limit raised in the gate table
`p-references`	a reference to a role, an artifact or a gate that does not exist	the artifact table, the graph without cycles, the commands resolved	limit cell diverges from the applied limit
`p-prior`	an invented number about a prior: in a code span, under a malformed mark, in a section the reader does not find	each number checked in the sections its recorded fact cites; section commitments; the synthetic prior in the registry's heading style	prior number in a code span
`p-prior-mark`	a statement about a prior with no mark, or the mark in a code span	the canon's triggers, read outside code spans	prior mark inside a code span

Gate	Cause of a false green	Current detection	Perturbation that covers it
`p-prior-pin`	a prior document swapped or edited, or a pin no run compares	the registry's sha256 compared with each document passed, prior by prior	prior pin altered in the registry
`p-contract-shape`	a ledger line rewritten, a contract of another version, a registry entry that breaks its status	the schemas line by line, the hash chain (an edit that recomputes it is not detected)	old line of the round record edited
`p-recipe`	a step of the recipe without one of its fields	the canon's step fields	step field deleted
`p-components`	a component the principle names and an instance omits	the canon's list	method component omitted
`p-efficacy-mark`	a claim that the method works without a label, or with a label citing nothing executed	the canon's triggers (lexical), the provenance table of an experiment, a lessons title that resolves	claim backed by a designed experiment
`p-notes`	a note without a state, a regression closed with a gate that does not exist, a protection undone by a later line	the state ledger, golden rule 4 against the gate table, the highest severity and the union of `affects`	note without a status line
`p-frozen-rubric`	a rubric or a frozen record rewritten after the fact	the sha256 of the rubric and of each frozen record; the attestation in the owner's run	frozen review report rewritten
`p-sensitivity`	a report the instrument did not produce, a stale one, or one made without the owner's document read as made with it	the provenance header, the case lines against the pins, the attestation, a synthetic prior never a pass	none: the baseline reads the report; its defects are regression tests
`p-declared`	a declared path that matches nothing, a repointed file, a document no artifact declares	each literal path and each glob, the resolved map pinned in the sensitivity's provenance	file of an artifact repointed

Appendix E — File index of the material

The 79 files the material tracks at 0.6.0, grouped.

Path	Contents
`README.md`, `VERSION`, `CHANGELOG.md`, `LICENSE`, `.gitattributes`, `.gitignore`	the entry page, the version, the history, the license, the LF rule, the ignore list
`01-principle.md`	the method
`02-reflexive-application/README.md`	the index and the runbook of the reflexive application
`02-reflexive-application/00-brief.md` ... `06-gate-semantics.md`	brief, canon, artifacts, four role cards, gates and rubric, gate semantics
`02-reflexive-application/05-contracts/*.schema.json`	the six contracts
`02-reflexive-application/10-generic-recipe.md`	the fifteen steps
`02-reflexive-application/20-instance-car.md`, `21-instance-text-2027.md`, `22-instance-hpc.md`	the three designed instances
`02-reflexive-application/60-experiments.md`	E1 to E5
`02-reflexive-application/80-validator/validator.py`, `sensitivity.py`, `perturbation_set.py`, `test_validator.py`	the instrument and its suite
`02-reflexive-application/80-validator/report.md`, `sensitivity.md`	the published reports
`02-reflexive-application/90-review/rubric.sha256`, `auditor-report.md`, `auditor-notes.json`, `notes.json`, `replies.md`	the frozen records of round 1
`02-reflexive-application/99-lessons.md`	the lessons, one entry per round
`02-reflexive-application/state/round-record.jsonl`, `notes-status.jsonl`, `owner-decisions.jsonl`	the three chained ledgers
`skills/cooperatio-teamwork/SKILL.md`, `references/templates.md`, `references/review-checklist.md`, `scripts/scaffold.py`, `scripts/test_scaffold.py`	the skill
`instances/registry.json`	the instance registry
`instances/004-adoption-guide/`	the cell of the second executed instance: brief, sources of truth, JSON canon, artifacts, four cards, two contracts, gates, rubric and pin, the validator of 0.2.2 with its rules and reports, the engine's README, the two wave reports and the round-1 notes, the state ledgers, lessons, open notes, priors, layout, the guide (`guia-de-adocao.md`), the method document (`metodo-de-producao.md`) and `ERRATA.md`
`docs/manual/`	this manual: `src/`, `diagrams/`, `filters/`, `Makefile`, the built `manual.md`, `manual.pdf` and `build/manual.tex`

Appendix F — Open owner decisions

The lines of `02-reflexive-application/state/owner-decisions.jsonl` at 0.6.0, all `open`; each names what it blocks. Only the owner can close one, with a new chained line.

Decision	What it blocks
sign the tag of the version (create a signing key and sign `v0.6.0`)	the anchor of integrity outside the tree
publish an extract of the first prior, or not	a clone's check of the numbers about `000-av-production`
accept or adjust the thresholds to promote or withdraw a claim	experiment E4
approve the budget and run E4	the measure of value of the material
find the third party for E5	the measure of portability
promote independence across families to a rule	the rule of independence
open the next production of the material as a production, with its own brief, a rubric of the reviewing side and a stop	a new verdict of the canon on the material
replace the cell of 004 as the example (a new cell under 0.6.0 would be the third execution)	an executable example of a cell

Appendix G — Building this manual

The manual lives in `docs/manual/`:

Path	What it is
`src/*.md`	the source, one file per part, concatenated in order
`diagrams/*.dot`	the Graphviz twin of each Mermaid diagram; rendered to `.svg` and `.pdf`
`filters/mermaid.lua`	the pandoc filter that swaps a Mermaid block for its twin's PDF in the PDF build
`filters/header.tex`	the LaTeX preamble additions (fonts, shaded code blocks, table spacing)
`Makefile`	the build
`manual.md`	the concatenated Markdown, for viewers that render Mermaid
`build/manual.tex`, `manual.pdf`	the LaTeX and the PDF editions

Each Mermaid block opens with two Mermaid comments, `%% name:` (the twin under `diagrams/`) and `%% caption:`, which the filter reads; a Markdown viewer ignores them. The build needs pandoc 3 or later, Graphviz and LuaLaTeX with the TeX Gyre fonts (TeX Live 2025 was used); no Mermaid renderer is needed:

```
cd docs/manual
make            # manual.md, the diagrams, build/manual.tex, manual.pdf
make check      # margin overflow check of the PDF, where the local tool exists
```

The manual follows the form rules of the material where it can: no absolute path, machine name, user name, model identifier or authoring date; executors by family letter; claims of efficacy with their label.