From discharge alerts to follow-up work: design and retrospective evaluation of a local, human-in-the-loop AI agent for primary care

Thiago Batista Nunes Bandeira

Mendez Medical Center, Lauderhill, Florida, USA. Correspondence: thiagobandeira.ai@gmail.com

Abstract

Objective. Primary care practices learn about their patients' hospital discharges from payer alerts, but turning each alert into timely follow-up is manual work, and the hospital's discharge summary rarely reaches the practice. We designed an AI agent that runs on a practice's own hardware and evaluated its components retrospectively on public hospital data.

Materials and Methods. For each discharge, deterministic code scores readmission risk (LACE) and sets the follow-up dates. A local language model extracts structured facts from the discharge summary, when one exists, and drafts a coordinator call script and a provider brief; by design a person approves them, and this evaluation stopped before that step. On MIMIC-IV, we evaluated the risk tiers against 30-day unplanned readmission (an admission-type proxy) in 64,036 stays; extraction in 200 discharge summaries, comparing prompted Qwen3 8B and 14B models with QLoRA fine-tunes trained on rule-generated or teacher labels; and drafting in 195 discharges, with automated checks. Both extraction references started from the rule-generated labels: an author-corrected diagnosis reference (51 notes) and a language-model-corrected reference for all fields (200 notes).

Results. High-risk discharges were readmitted about twice as often as the rest (28.3% against 14.3%; LACE AUROC 0.638). Against the diagnosis reference, the fine-tuned models scored highest (micro F1 0.93-0.94, against 0.69-0.72 for prompted models zero-shot). Against the all-field reference, prompted models zero-shot scored 0.70-0.72 and the fine-tunes 0.58-0.60, similar to the rule-generated labels themselves (0.58), and the fine-tunes matched 243-299 of the rules' 301 potentially false "started" medications (by note and drug-name key), against 22-46 for prompted models. Drafting took 16.8 s per discharge on one consumer GPU, and the automated check found no medication names unmatched to the record.

Discussion. Deterministic rules can carry the time-critical scheduling while small local models handle text. Fine-tuning on rule-generated labels reproduced the labels' gaps and potential errors, and evaluation against those same labels concealed it.

Conclusion. A local, human-in-the-loop follow-up agent is computationally feasible on commodity hardware. On these benchmarks a prompted base model was the better default extractor; fine-tuning should be limited to fields whose labels have been checked against a reference other than the training labels. Human review, the clinical accuracy of the drafts and operational benefit remain to be evaluated.

1. Introduction

After a hospital stay, the primary care team has to act on what happened. It contacts the patient, reconciles medications, schedules a visit, follows up on results still pending, and watches for warning signs. Discharge information often reaches primary care late or incomplete,[1] and adverse events after discharge are common, many of them related to medications.[2] In the United States, transitional care management (TCM) adds requirements: an interactive contact within two business days of discharge, medication reconciliation by the face-to-face visit, and that visit within 7 days with high-complexity medical decision making (CPT 99496) or within 14 days with at least moderate complexity (99495).[3]

Many practices learn about discharges from payer encounter notifications, daily alerts that list which of their patients were admitted or discharged. An alert is not follow-up work. Someone still has to decide who is at high risk, what is due by when, what the hospital changed, and what to say on the phone. In a small practice that is usually one coordinator working through the list by hand.

Large language models (LLMs) can extract clinical information and draft text,[4] and agent systems chain such steps together. Three obstacles keep them out of small practices. Sending patient notes to a cloud service raises privacy and contractual questions. Open-weight models small enough to run on a single consumer GPU are weaker than the largest cloud models. And autonomous agents that choose their own actions are hard to make safe and auditable in clinical work.

We designed a care-transitions agent around these constraints: a fixed workflow, deterministic code for every rule-based decision, small local models only for reading and writing text, and a required human approval step. The work aims to help primary care practices adopt such tools on hardware they already own, so the code, the synthetic benchmark and every aggregate result are open. This paper describes the agent and evaluates its components retrospectively on public hospital data: the risk tiers, extraction and drafting. It also examines a question that arose while building it: what a small local model learns when it is fine-tuned on cheap, rule-generated labels, compared with prompting the same model. Human review and use were not evaluated.

2. Materials and methods

2.1 The agent

The agent runs one short, fixed-order workflow per discharge (Figure 1), built with LangGraph. Deterministic code makes every rule-based decision. The language model has narrow jobs inside specific steps and never chooses actions or tools.




Figure 1. One run per discharge alert, in a fixed order. Blue steps are deterministic code, orange steps use a local language model, and the green step is a person. Plan is rule-based; the model only writes a short explanation of the plan. Extraction is skipped when no discharge summary is available. A daily job starts a short new run for each patient with a check-in due, so no run stays open for the 30 days. This study evaluated steps 3, 4 and 6, and the workflow up to the review pause.

The workflow has eight steps. **Ingest** normalizes the day's payer discharge file to one event per stay, with dates, age, disposition, acuity and prior use. **EHR context** retrieves active problems and medications from the practice's record. **Score** computes the LACE index[5] (length of stay, acuity of admission, Charlson comorbidity, and emergency visits in the prior six months). It also flags Medicare coverage at an age under 65, a group that includes people entitled through disability or end-stage renal disease. High risk means LACE ≥ 10, or LACE ≥ 7 with Medicare coverage under 65. The lower threshold is a provisional policy rule, informed by the author's earlier operational work on payer notifications, which is unpublished and outside this study; both thresholds are to be calibrated on each practice's outcomes. We chose a published score over a trained model because, in that earlier work, machine-learning models did not outperform LACE. **Extract**, when a discharge summary is available, has a local model turn it into structured JSON: principal and secondary diagnoses, medication changes, follow-up appointments, pending tests and red-flag symptoms. **Plan** applies the rules in Table 1 and has the model write a two-to-three-sentence explanation for the coordinator. The risk tier sets the practice's scheduling targets; it does not determine the TCM code. The plan stores a candidate code with its window (99496 and 7 days for high risk, 99495 and 14 days otherwise), which the review screen labels as a candidate and the drafting prompt receives as context. Planning high-risk patients toward the shorter window is a conservative scheduling default. The agent assigns and submits no billing codes: the code billed depends on the provider's documented medical

decision making, which the agent does not assess. **Draft** has the model write a coordinator call script (opening, questions, medication review, warning signs, scheduling) and a one-page provider brief (reason for admission, key conditions, medication changes, what to watch for, risk summary). A deterministic check then flags any medication or condition a draft names that is not in the patient's record. **Human review** pauses the run, with its state saved in a local SQLite checkpointer, until a coordinator or provider approves, edits or rejects the drafts; by design, nothing reaches a patient or the record without that decision. **Track** stores decisions and outcomes locally.

Table 1. The follow-up plan's rules. Visit targets and check-ins are the practice's scheduling rules. The TCM window is a reminder of a billing requirement, not a billing decision.

	High risk	**Standard**
Tier (provisional)	LACE ≥ 10, or ≥ 7 with Medicare under 65	all other discharges
Interactive contact (TCM requirement for both codes)	within 2 business days	within 2 business days
Visit target (practice scheduling rule)	within 3 days	within 7 days
TCM face-to-face window the plan tracks	7 days (applies if billed as 99496)	14 days (applies if billed as 99495)
Check-ins (practice rule)	days 10 and 20	none

Every model output is validated against a schema and retried once. A second failure falls back to the rule text, or to an empty value, and flags the case for a person. Drafts have length limits, and a list that repeats an item is rejected as a runaway generation. The code refuses cloud model tags, remote endpoints and hosted tracing; models are served locally by Ollama. The review screen can time each review and record how much of each draft was edited and whether flags were real problems; these measures were not used in this study.

2.2 Data

MIMIC. We used the discharge summaries of MIMIC-IV-Note v2.2[6,7] (331,793 notes from 145,914 patients, 2008-2019) and the hospital module of MIMIC-IV v3.1[6,8] (patients admitted 2008-2022), both from the Beth Israel Deaconess Medical Center in Boston, on PhysioNet.[9] Notes were split by patient into training, validation and test sets (70/10/20, seed 13), so no patient appears in two splits. The 200 evaluation notes were a random sample of the test split (seed 21) and came from 200 different patients; the 51 hand-labeled notes were the first 51 in sampling order. The model reads seven sections of each summary in a fixed order: discharge diagnosis, admission medications, discharge medications, discharge instructions, follow-up instructions, pending results and hospital course. Inputs are capped at 14,000 characters, which 0.3% reach; the median input is about 1,050 tokens. MIMIC replaces the Follow-up Instructions section with a placeholder, so follow-ups have to come from other sections.

Synthetic benchmark. Qwen3-14B wrote 150 discharge summaries from Synthea patient records.[10] A note was kept only if it mentioned every reference fact, so every field has a known answer, by construction. The

notes are split by Synthea patient, 43 notes (40 patients) for few-shot examples and 107 (96 patients) for testing, and are public with the code.

2.3 Evaluating the risk tiers

This part evaluates a published score inside the agent's workflow; it does not develop a new prediction model.

Cohort. Every admission with a discharge summary in the test split, excluding deaths in hospital and discharges to hospice, for which the agent plans no follow-up.

Outcome. The primary outcome is an admission-type proxy for unplanned readmission: any later admission of the same patient anywhere in MIMIC-IV's hospital module (not only the note-linked cohort) that started after the index discharge time and within 30 × 24 hours of it, with an admission type other than elective or same-day surgery. A same-day return counts if it starts after discharge; an intervening elective admission neither counts nor blocks a later unplanned one; the outcome is binary. Follow-up is not censored at the end of a patient's record, and MIMIC records only its own hospital, so some readmissions are missed. The secondary outcome is death (from the date of death in the patients table) or readmission within 30 days, LACE's original outcome.

Score. LACE as the agent computes it at discharge: - **L:** calendar days from admission to discharge, scored 0 for less than one day, 1-3 for 1-3 days, 4 for 4-6, 5 for 7-13 and 7 for 14 or more. - **A:** 3 points for an emergency, urgent or emergency-observation admission type, or registration in the emergency department. - **C:** the Charlson score from the admission's billing diagnoses, using Quan's enhanced ICD-9-CM and ICD-10 coding algorithms[11] matched by code prefix (ICD-10-CM codes are matched with the ICD-10 prefixes), with severe liver disease, complicated diabetes and metastatic cancer superseding their milder forms; scored as is up to 3, and 5 for 4 or more. - **E:** one point per distinct ED registration day 2-182 days before admission (about six months, excluding the index visit), up to 4. MIMIC's hospital module has no ED-only visits, so these are ED-registered admissions and undercount ED use.

Missing diagnoses or visits score 0. Because billing diagnoses are coded after discharge and ED-only visits are absent, this is an operationalization of LACE on hospital data, not the score a practice would compute from its own record at discharge. The Medicare flag came from the admission's insurance.

Measures. The AUROC of the score; the share of stays in the high tier, the readmission rate in each tier, and the share of readmissions in the high tier (sensitivity); and the same measures for LACE ≥ 10 alone. 95% confidence intervals come from 1,000 bootstrap resamples of patients, each resampled patient contributing all of their stays.

2.4 Evaluating extraction

Task. Every key of the six-field JSON is required, and the prompt states each field's definition and conventions; without this guidance, zero-shot models skipped whole fields in early experiments on the synthetic notes. A note whose answer still fails validation after the retry counts as an empty prediction. Repeated list items are dropped before scoring, in predictions and references alike.

Training labels. Rule-generated "silver" labels come from each note's own structure. Diagnoses come from the Discharge Diagnosis section: the first line is the principal diagnosis and the rest are secondary (a principal diagnosis is found in 95.9% of notes). Medication changes compare the numbered or bulleted admission and discharge lists by drug name and dose: `started` if only on the discharge list, `stopped` if only on the admission list, and otherwise `dose_changed` or `continued`. Follow-ups come from the redacted section, so silver has none; pending tests are sentences containing "pending"; red flags are the list after phrases such as "call your doctor". As an alternative, Qwen3-14B with three training examples (the few-shot setting below) labeled follow-up, pending tests and red flags for 2,500 training and 300 validation notes (11.2 s per note, about 9 GPU hours), while diagnoses and medication changes stayed silver. This teacher listed follow-ups in 40% of notes, pending tests in 19% and red flags in 74%.

Models. We prompted Qwen3-8B and Qwen3-14B[12] zero-shot and with three fixed training examples, served by Ollama in 4-bit (Q4_K_M) with greedy decoding, a 16,384-token context and a 3,000-token answer cap. We fine-tuned Qwen3-8B with QLoRA:[13],[14] a 4-bit NF4 base, LoRA rank 16 (alpha 32) on all linear layers, one epoch at learning rate 2e-4 with cosine decay, an effective batch of 8, and loss on the answer only, using the zero-shot prompt. Examples longer than 3,072 tokens were dropped rather than truncated, keeping about 89% of notes. We trained four models (Table 2). Each adapter was merged, converted to GGUF with llama.cpp, quantized to Q4_K_M (5.0 GB) and served like the base models. The untouched base model went through the same conversion as a quantization control (Base-8B-local); its micro F1 was within 0.001 of the library model's on the synthetic notes and the 200-note reference, and 0.022 higher on the 51-note reference. Appendix A gives the remaining settings: seeds, sampling, model identifiers, decoding and training details.

Table 2. The fine-tuned models.

Model	Training labels	Training notes
Silver-8851	silver	8,851 (of 10,000 sampled; 4.4 h)
Silver-2500	silver	2,500 (71 min)
Teacher-2500	teacher for follow-up, pending tests and red flags; silver for the rest	the same 2,500 (74 min)
Teacher-1250	as Teacher-2500	the first 1,250 of them (37 min)

References. Training labels cannot serve as the reference, because a model trained on them is rewarded for imitation. We built two references on the 200 test notes in a local annotation tool that shows the note beside the silver labels as editable tables and saves only answers that pass the schema. Both references were therefore initialized from the silver labels: they are distinct from the training labels, but not independent of the rules that produced them. - **Author-corrected diagnosis reference.** The author, whose training is in data science and AI and who has five years of experience supervising clinical and operational work in primary care, corrected 51 notes (median 0.3 minutes per note) following a written guideline published with the code. Under it, the principal diagnosis is the main reason for the hospitalization as written under Discharge Diagnosis (the first or "primary" one), and secondary diagnoses are the other diagnoses listed there; past history not listed at discharge, and diagnoses mentioned only elsewhere in the note, are out of scope. This reference covers the two diagnosis fields only. Follow-up, pending tests and red flags were left

out before labeling, as too ambiguous for a quick single pass. Medication changes were labeled, then excluded after a check found a systematic error in them (Section 3.2); this decision was made after the hand pass and before any model was scored against the hand labels. - **Language-model-corrected reference.** Claude Opus 5.5 (Anthropic), a cloud service, filled in all six fields on all 200 notes on 1 November 2026, by operating the same tool through its browser extension under the author's account, whose model-training setting ("Help improve Claude") was turned off at the time (median 0.5 minutes per note). PhysioNet's guidance on online services lists Anthropic Claude among the services it suggests for credentialed data.[15] This was the only step in which note text left the local machine; every evaluated model, and every other step, ran locally. We treat these labels as model-made, not as hand annotation.

Metrics. List fields are scored as sets, with greedy pairing. A match is exact (normalized equality) or relaxed (token Jaccard overlap of at least 0.5); relaxed is the primary metric. A medication change matches only when the drug name and the change type both match, and change-type accuracy among matched drug names is reported separately. True positives, false positives and false negatives are summed over notes, and micro F1 pools the fields each reference covers; because medication entries make up 62% of the language-model-corrected reference's items, we also report the macro average over fields. Appendix A gives the normalization and pairing rules. Confidence intervals come from 1,000 bootstrap resamples of patients, each drawn patient contributing all of their notes; on MIMIC the 200 and 51 evaluation notes each come from a different patient, and on the synthetic notes 11 of the 96 test patients contribute two notes. For the comparisons the conclusions rest on, we report paired bootstrap differences (2,000 resamples of patients). All intervals are conditional on the fitted models and the reference labels; they do not capture annotation error, training-seed variability or the choice of prompts. Predictions were generated once and rescored against each reference.

2.5 Evaluating the drafts

On synthetic patients, the full workflow ran without a discharge summary, so extraction was skipped and the drafts came from the Synthea record alone: on 30 Synthea discharges with Qwen3-14B and Qwen3-8B on the GPU, and on 5 discharges with GPU offload disabled. Drafting used the Qwen3 model card's recommended non-thinking sampling with a fixed seed, because greedy decoding caused repetition loops in drafts.

On MIMIC, the full workflow ran up to the review pause on the 200 test notes. Five patients who died or went to hospice were skipped, leaving 195 discharges. Each discharge event came from the hospital module (times, age, disposition, acuity, prior emergency visits and Medicare), and the record stand-in held the admission's billing diagnoses plus the diagnoses and medications from the note's extraction. Extraction used the saved Qwen3-14B zero-shot predictions, and the same model drafted, so one model stays loaded.

This is a development evaluation, not an untouched test. The extractor was chosen as the best overall on the same 200 notes (Table 6), and the drafting prompt was revised after a first run on the same 195 discharges: the first run showed long condition lists and occasional validation failures, so the final prompt asks the brief for at most six conditions, most important first, and forbids placeholders such as "[Your Name]". We report both runs. The extraction prompt and its field guidance were developed on the synthetic notes, and all few-

shot examples come from training splits. A further 30 synthetic discharges, sampled separately (one overlaps the 30 above), were drafted with the practice's name in the prompt to check placeholders.

We measured by automated counts only; no draft was read. Record grounding is the agent's own check against the record, which includes the model's extraction, so a draft can repeat an extraction error and still pass it. Note grounding counts the medication names in the drafts that appear in the note text (the whole name, or every word of four or more letters in it), and the conditions in the brief that share at least one content word with the note, a permissive test. Completeness, measured against the extraction, counts the changed medications (started, stopped or dose changed) named in the brief, with the same change type, and in the call script, and the red flags covered by a warning sign in the call script (one sign holding at least half of the flag's content words). None of these checks assesses dose, timing, negation or clinical correctness. Seconds per discharge are wall-clock time for the three model calls, retries included, with the model already loaded except for the first discharge of a run.

2.6 Hardware and software

All local work (inference, fine-tuning and analyses) ran on one NVIDIA RTX 4080 (16 GB), an Intel i9-14900K CPU and 64 GB of RAM, under Windows. The agent uses Python 3.12.10, LangGraph 1.2.17 with langgraph-checkpoint-sqlite 3.1.2, LangChain Core 1.7.0, langchain-ollama 1.1.0, Pydantic 2.14.1 and Streamlit 1.66.1, with models served by Ollama 0.40.13. Fine-tuning used PyTorch 2.11.0 (CUDA 12.8), Transformers 5.20.2, TRL 1.16.0, PEFT 0.21.2, bitsandbytes 0.50.2 and Accelerate 1.15.0; conversion used llama.cpp release b11921. Analyses used pandas 3.1.0 and NumPy 2.5.4, and the figure matplotlib 3.11.2.

2.7 Ethics

MIMIC-IV and MIMIC-IV-Note are de-identified. Their collection was reviewed by the Institutional Review Board at the Beth Israel Deaconess Medical Center, which granted a waiver of informed consent and approved the data sharing, and we used them under the PhysioNet credentialed data use agreement. No separate ethics review was sought for this secondary analysis of de-identified data and synthetic records; the study involved no new human participants. Section 4.5 describes Mendez Medical Center's follow-up system, with the practice's written approval; no data from the practice were used. No MIMIC data, labels, predictions or drafts are in the public repository, which holds only code, the synthetic benchmark and aggregate metrics.

2.8 Reporting

Appendix C maps this report to the relevant items of TRIPOD+AI[16] (for the risk tiers) and TRIPOD-LLM[17] (for extraction, fine-tuning and drafting). The study had no registered protocol.

3. Results

3.1 Risk tiers

The cohort held 64,036 stays from 28,220 patients, after excluding 1,692 deaths in hospital and 671 hospice discharges. 12,601 stays (19.7%) were followed by an unplanned readmission within 30 days, and 1,332

stays by death within 30 days. 71.1% of stays had at least one Charlson condition, 29.2% a prior ED-registered admission and 80.9% an acute admission; the median LACE was 8 (interquartile range 6-11).

LACE discriminated modestly, with an AUROC of 0.638 for readmission and 0.654 for death or readmission (Table 3). The agent's high tier flagged 38.2% of stays; their readmission rate was 28.3%, about twice the standard tier's 14.3%, and the tier contained 55.1% of all readmissions. LACE ≥ 10 alone flagged 34.9% at a similar rate (28.9%) and contained 51.3%, so the under-65 Medicare rule added 3.3 points of stays and 3.8 points of sensitivity.

Table 3. The agent's risk tiers on MIMIC-IV, 64,036 stays from 28,220 patients, against 30-day unplanned readmission (admission-type proxy); 95% CIs from a patient bootstrap.

Measure	Estimate (95% CI)
LACE AUROC, 30-day readmission	0.638 (0.631-0.646)
LACE AUROC, 30-day death or readmission	0.654 (0.647-0.660)
Stays in the high tier	38.2% (37.5-39.0)
Readmission rate, high tier	28.3% (27.5-29.2)
Readmission rate, standard tier	14.3% (13.9-14.7)
Readmissions caught by the high tier	55.1% (53.6-56.6)
Stays with LACE ≥ 10	34.9% (34.3-35.6)
Readmission rate, LACE ≥ 10	28.9% (28.0-29.7)
Readmissions caught by LACE ≥ 10	51.3% (49.9-52.7)

3.2 Extraction

Synthetic notes: the label source shaped the prose fields. On notes with known answers (Table 4), the prompted models scored 0.948-0.979 micro F1 and the rules 0.696. The silver fine-tunes lost most of the base model's performance on follow-up: Silver-8851 scored 0.057, against 0.771 for the base model through the same conversion. On the same 2,500 notes, replacing silver with teacher labels raised micro F1 from 0.842 to 0.948 and follow-up from 0.190 to 0.797. Teacher-2500 had a point estimate similar to the base model's (0.948) and below its teacher's (0.979), and doubling the teacher-labeled notes from 1,250 to 2,500 gave similar micro F1 (0.949 and 0.948).

Table 4. Synthetic benchmark, 107 test notes from 96 patients, relaxed F1 (95% CI for micro F1 from a patient bootstrap).

Model	Principal	Secondary	Medications	Follow-up	Pending	Red flags	Micro F1
Rules	1.000	0.963	0.907	0.159	0.452	0.037	0.696 (0.678-0.716)
Base-8B-local, zero-shot	0.939	0.982	0.961	0.771	0.958	0.994	0.948 (0.936-0.959)
Qwen3-8B, few-shot	0.925	0.979	0.983	0.856	0.972	0.994	0.966 (0.956-0.974)
Qwen3-14B, few-shot (teacher)	0.935	0.981	0.981	0.981	0.928	0.994	0.979 (0.969-0.987)
Silver-8851	1.000	0.964	0.917	0.057	0.604	0.679	0.789 (0.766-0.811)
Silver-2500	1.000	0.963	0.942	0.190	0.609	0.902	0.842 (0.824-0.862)
Teacher-1250	1.000	0.995	0.975	0.752	0.892	0.960	0.949 (0.937-0.960)
Teacher-2500	1.000	0.995	0.949	0.797	0.905	0.978	0.948 (0.934-0.961)

MIMIC diagnoses: the fine-tunes agreed best with the section-based reference. Against the author-corrected reference (Table 5), the fine-tuned models scored 0.927-0.943 micro F1 on the diagnoses, against 0.695-0.724 for the prompted models zero-shot and 0.808-0.849 few-shot. The paired difference between Silver-8851 and Qwen3-14B zero-shot was 0.247 (95% CI 0.145 to 0.362). Between the best of each group, Teacher-1250 and Qwen3-8B few-shot, it was 0.095 (0.022 to 0.172); this pair was chosen after seeing the results, and the interval does not account for that choice. The principal diagnosis was easy for every model (0.91-0.98); the gap was in secondary diagnoses. The prompted models found most of them (recall 0.80-0.88 zero-shot) but listed many that the reference did not (precision 0.48-0.53), while the fine-tunes kept to the Discharge Diagnosis list (precision 0.87-0.91, recall 0.95-0.99). Under a broader definition, some of the prompted models' extra diagnoses could be legitimate. The rules agreed with this reference at 0.933 and the language-model-corrected reference at 0.845, and the latter ranked the models the same way.

Table 5. MIMIC-IV-Note, 51 notes from 51 patients, author-corrected diagnosis reference, relaxed F1 (95% CI for micro F1). The last row counts the reference items.

Model	Principal	Secondary	Micro F1
Rules (silver)	0.931	0.933	0.933 (0.889-0.970)
Silver-8851	0.950	0.937	0.942 (0.902-0.980)
Silver-2500	0.931	0.925	0.927 (0.877-0.970)
Teacher-1250	0.970	0.931	0.943 (0.894-0.984)
Teacher-2500	0.940	0.933	0.935 (0.891-0.979)
Base-8B-local, zero-shot	0.941	0.642	0.724 (0.619-0.821)
Qwen3-8B, zero-shot	0.911	0.625	0.702 (0.583-0.815)
Qwen3-8B, few-shot	0.961	0.800	0.849 (0.746-0.938)
Qwen3-14B, zero-shot	0.922	0.618	0.695 (0.580-0.793)
Qwen3-14B, few-shot	0.980	0.737	0.808 (0.700-0.909)
Reference items	51	106	157

MIMIC, all fields: the fine-tunes scored at the level of their training labels. Against the language-model-corrected reference on all six fields (Table 6), the prompted models zero-shot scored highest (0.703-0.723), while every fine-tune scored 0.583-0.600, against 0.584 for the rules themselves. The paired difference between Qwen3-14B zero-shot and Silver-8851 was 0.140 (0.108 to 0.173), and between Qwen3-14B zero-shot and Teacher-2500 0.135 (0.102 to 0.165). The macro average over fields kept the order: 0.609-0.622 for the prompted models zero-shot, 0.553-0.579 few-shot, 0.427-0.545 for the fine-tunes and 0.408 for the rules. On medication changes the prompted models reached 0.73-0.78 F1 with 0.85-0.89 change-type accuracy, and the fine-tunes 0.61-0.63 and 0.73-0.75, near the rules' 0.640 and 0.74. The silver fine-tunes never listed a follow-up; the teacher fine-tunes recovered part of it (0.30) but stayed below the prompted models zero-shot (0.40-0.49), and red flags showed the same order. Pending tests, with only 44 reference items, were hard for every model (0.10-0.30) and for the rules (0.08). At most one of 200 notes per model failed validation.

Table 6. MIMIC-IV-Note, 200 notes from 200 patients, language-model-corrected reference for all fields, relaxed F1 (95% CI for micro F1) and change-type accuracy among matched drug names. The last row counts the reference items.

Model	Principal	Secondary	Medications	Follow-up	Pending	Red flags	Micro F1	Change type acc.
Rules (silver)	0.838	0.833	0.640	0.000	0.083	0.056	0.584 (0.548-0.621)	0.74
Silver-8851	0.843	0.834	0.628	0.000	0.101	0.155	0.583 (0.546-0.622)	0.74
Silver-2500	0.833	0.827	0.634	0.000	0.102	0.318	0.593 (0.554-0.630)	0.75
Teacher-1250	0.841	0.842	0.625	0.303	0.304	0.357	0.600 (0.567-0.633)	0.75
Teacher-2500	0.835	0.831	0.610	0.300	0.203	0.366	0.588 (0.550-0.625)	0.73
Base-8B-local, zero-shot	0.852	0.749	0.725	0.416	0.225	0.754	0.704 (0.676-0.729)	0.85
Qwen3-8B, zero-shot	0.852	0.729	0.735	0.404	0.210	0.725	0.703 (0.672-0.727)	0.86
Qwen3-8B, few-shot	0.865	0.873	0.739	0.260	0.250	0.333	0.668 (0.640-0.694)	0.88
Qwen3-14B, zero-shot	0.845	0.704	0.776	0.492	0.234	0.683	0.723 (0.698-0.744)	0.89
Qwen3-14B, few-shot	0.877	0.808	0.729	0.357	0.293	0.412	0.675 (0.647-0.700)	0.86
Reference items	200	414	2,352	328	44	483	3,821	

The fine-tunes repeated the rules' potential false starts. The medication rule marks a drug `started` when it is not on a numbered admission list. In 22 of the 51 author-corrected notes, the admission section had no

numbered items (18) or was absent (4), so the rule saw no admission drugs. We screened every `started` drug by whether the first word of four or more letters in its name appears in the note's admission section, a heuristic screen rather than proof that the drug was taken before admission (Table 7). To compare sources case by case, each flagged row was keyed by its note and that word; the key can merge different medications that share a first word (two sodium salts, for example), so a match means agreement under this rule, not verified identity. 304 of the rules' 1,211 `started` rows (25.1%) were flagged, giving 301 keys. Each fine-tune flagged a similar share (25.3-27.3%) and matched most of the same keys: Silver-8851 matched 299 of the 301, and the other fine-tunes 243-272. The prompted models flagged 3.3-8.7% of their `started` rows and matched 22-46 of the keys, and the language-model-corrected reference flagged 2.6% (18 of 688 rows). The author-corrected labels still had 84 of 348 rows (24.1%) flagged, against the rules' 90 on the same 51 notes, which is why medication changes were left out of that reference.

Table 7. Potential false starts: `started` medications whose name's first word (four or more letters) appears in the note's admission-medication section, on the 200 MIMIC-IV-Note notes.

Source	Started rows	Flagged rows	Share	Rule-flagged note-drug keys matched (of 301)
Rules (silver)	1,211	304	25.1%	(301)
Language-model-corrected reference	688	18	2.6%	12
Silver-8851	1,219	316	25.9%	299
Silver-2500	1,201	304	25.3%	265
Teacher-1250	1,155	294	25.5%	243
Teacher-2500	1,222	333	27.3%	272
Base-8B-local, zero-shot	693	60	8.7%	42
Qwen3-8B, zero-shot	701	49	7.0%	35
Qwen3-8B, few-shot	843	70	8.3%	46
Qwen3-14B, zero-shot	765	25	3.3%	22
Qwen3-14B, few-shot	828	39	4.7%	35

Rows count `started` entries. A key is a note plus the first word of four or more letters in the drug's name, so flagged rows with the same key count once: the rules' 304 flagged rows give 301 keys. The key can merge different medications that share a first word, so the last column counts matches under this rule (each source's flagged keys that are also among the rules' 301), not verified medication identity.

Scored against their own training labels, the fine-tunes looked best. Against the silver labels of the same 200 notes, Silver-8851 reached 0.959 micro F1, against 0.566-0.638 for the prompted models. Its output matched silver's statistics closely: 2.25 secondary diagnoses per note with 36% of notes empty (silver: 2.25 and 36%), 11.3 medication entries per note (silver: 11.3), and no follow-ups.

3.3 Drafts and speed

On 30 synthetic discharges (Table 8), Qwen3-14B drafted the plan explanation, call script and provider brief in 15.8 s per discharge on the GPU, with no validation failures and no grounding flags. Qwen3-8B

was 2.5 times faster; its single flag was a real error, a misspelled condition. With GPU offload disabled, measured on 5 discharges each, a batch of 15 discharges would take about 47 minutes with 14B or 17 minutes with 8B (extrapolated).

Table 8. Drafting on Synthea discharges: three model calls per discharge, wall-clock seconds; CPU means GPU offload disabled.

Model	Device	n	Mean s / discharge	Median	Max	Schema failures	Discharges with grounding flags
Qwen3-14B	GPU	30	15.8	15.5	23.1	0	0
Qwen3-8B	GPU	30	6.2	5.5	10.9	0	1
Qwen3-14B	CPU	5	186.3	187.4	279.0	0	0
Qwen3-8B	CPU	5	69.2	67.7	96.7	0	0

On 195 MIMIC discharges (Table 9), the final run drafted each discharge in 16.8 s on average (median 16.1, maximum 31.3), and no document still failed validation after the retry. Zero observed failures does not mean a zero rate: under binomial assumptions, the rule of three gives an approximate one-sided 95% upper bound of 1.5% for this event, a bound that says nothing about clinical errors and ignores that the prompt was revised on these discharges. The automated record check found no unmatched medication names; 98.4% of the medication names in the drafts appeared in the note text, and the other 34 came from the extraction without appearing verbatim. Briefs listed 5.9 conditions on average; the record check flagged 3 of 1,144 (0.3%), in 2 discharges, and 65.2% shared a content word with the note, most of the rest coming from the admission's billing diagnoses. The provider brief named 93.6% of the extraction's changed medications (92.7% with the same change type), the call script 86.5%, and the call script covered 86.9% of the extraction's red flags. With comorbidity scored, 67 of the 195 discharges (34%) were high risk.

The first run, before the two prompt changes, listed 12.2 conditions per brief and had 16 of 2,371 flagged, 4 provider briefs that failed validation, and 18.2 s per discharge, with medication and red-flag completeness within 1.2 points of the final run. Whether the shorter condition lists dropped clinically important conditions was not measured. The MIMIC runs had no practice name to give, and despite the instruction every call script still contained a practice-name placeholder; with the name in the prompt, in the 30 further synthetic discharges, none did.

Table 9. The agent's drafts on 195 MIMIC-IV-Note discharges, automated counts only (Qwen3-14B extraction and drafting, final prompt; first run in brackets).

Measure	Count	Share
Discharges with a failed document after the retry	0 / 195 [4]	0.0% [2.1%]
Medication names in drafts not matched to the record	0 / 2,098	0.0% [0.0%]
Medications in drafts found in the note text	2,064 / 2,098	98.4% [98.3%]
Conditions in briefs not matched to the record	3 / 1,144	0.3% [0.7%]
Conditions in briefs sharing a word with the note	746 / 1,144	65.2% [61.8%]
Extracted changed medications named in the brief	1,075 / 1,149	93.6% [93.9%]
... with the same change type	1,065 / 1,149	92.7% [93.0%]
Extracted changed medications named in the call script	994 / 1,149	86.5% [86.4%]
Extracted red flags covered by the call script	615 / 708	86.9% [85.7%]

Extraction took 4.5-5.3 s per note for the fine-tuned models, 7.2-12.3 s for the prompted models zero-shot and 9.1-13.5 s few-shot. With 14B extraction (12.3 s) and drafting (16.8 s), the model time for a discharge with a summary is about 30 seconds on one consumer GPU, or about 7 minutes for a batch of 15. These are computation times; they exclude review and coordinator time.

4. Discussion

4.1 Principal findings

This retrospective evaluation tested three components of the agent on public hospital data, and each behaved differently. The rule-based risk tier discriminated modestly (AUROC 0.64): the high tier's readmission rate was about twice the standard tier's, which supports using the tier to order a coordinator's list, not as a prediction to act on alone; whether it improves decisions or workload was not tested. Extraction was the hardest component: the best prompted models reached about 0.70-0.72 micro F1 against the language-model-corrected reference. Drafting was consistent with its input under automated checks: on 195 real discharges the check found no unmatched medication names and few unsupported conditions, and the provider brief carried 94% of the extracted medication changes. These checks are lexical. They do not show that the drafts are clinically correct, and because the drafts follow their input, extraction errors can pass into documents that look grounded. The human review step is the design's answer to that; its effectiveness was not evaluated.

Two prompt changes made after the first drafting run halved the brief's condition list, removed the validation failures and reduced flagged conditions from 16 to 3, with similar medication and red-flag completeness; because they were tested on the same discharges, this is a development result. Placeholders disappeared only when the practice's name was in the prompt; an instruction alone did not remove them, so a deployment has to configure the practice's details.

4.2 Fine-tuning reproduced the rules' patterns

The evidence is consistent across both benchmarks and both references (Table 10). Where the rule-generated labels agreed with the reference convention, as for secondary diagnoses listed under Discharge Diagnosis, fine-tuning gave a clear gain over prompted models, which listed more diagnoses. Where the labels were likely wrong, as for `started` medications when the admission list was not numbered, the fine-tunes matched most of the same flagged cases note by note under a heuristic drug-name key (Table 7) and fell below the prompted models. Where the labels were empty, as for follow-up redacted in MIMIC, the silver fine-tunes produced none.

Table 10. What the fine-tunes did with rule-generated labels.

The rule-generated labels	Example	What the fine-tunes did
agreed with the reference convention	secondary diagnoses under Discharge Diagnosis	agreed best with the reference
were likely wrong	`started` medications with unnumbered admission lists	matched most of the same flagged cases (potential errors)
were empty	follow-up, redacted in MIMIC	silver-label fine-tunes produced none; teacher-label fine-tunes recovered some

The matched control isolates the label source: on the same notes, with the same training budget, changing only the labels moved follow-up from 0.19 to 0.80 on the synthetic notes. Rule-generated labels are a form of weak supervision,[18] and labels from a larger model a form of distillation;[19] both are cheap, and both strongly shape what the student learns. They are not a hard ceiling: on the synthetic notes the silver fine-tunes kept part of the base model's skill on red flags (0.679, against 0.037 for the rules). But on MIMIC, where the labels were likely wrong or empty, the fine-tunes followed the labels rather than the base model's behaviour, and the teacher-label models, whose medication labels were still silver, matched the same potential medication errors. Scoring against the training labels hid this: against silver, the silver fine-tune looked far better than the prompted models (0.959 against 0.57-0.64), but against references other than its training labels it was no better than the rules. Projects that train on weak labels and test on held-out labels of the same kind risk the same misreading.

For the agent, a prompted base model is therefore the preferred default extractor on these benchmarks. A fine-tuned model is worth using only for fields whose labels have been checked against a reference other than the training labels, here the section-based diagnoses, where it was also about twice as fast.

4.3 Building references from pre-filled labels

Both references were made by correcting the silver labels, so neither is independent of the rules. On medication changes, the author-corrected labels still had 84 potential false starts of the kind the rules made, against the rules' 90 on the same notes. This is consistent with anchoring on pre-annotation, which speeds up labeling but pulls annotators toward the suggestion.[20] A targeted check found it: the two references disagreed on medication change types, and a simple screen of the disagreeing rows located the pattern. Such checks are worth running whenever a reference is built from pre-filled labels. The diagnosis

comparison therefore measures agreement with a section-based, silver-initialized reference, not with an independently established clinical gold standard.

4.4 Why a fixed workflow rather than an autonomous agent

It is a design judgment, not a result of this study, that small local models should not choose actions while the tasks with deadlines and billing consequences (the TCM contact window, visit targets, check-in dates) have exact rules. Keeping those rules in deterministic code, and confining the model to reading and writing text that a person approves, makes every rule-based decision reproducible and auditable. Some model failures become visible flags: validation failures, runaway lists, and medication or condition names absent from the record. Errors these checks cannot detect, such as a wrong dose or a misleading sentence, are left to the reviewer.

4.5 In one practice, the discharge summary was the missing input

Mendez Medical Center, a multi-specialty primary care practice in Lauderhill, Florida, already runs the agent's deterministic steps in production, on a hospital follow-up board the author built in the practice's own dashboard. No data from the practice were used in this study; this section describes the system, not its patients. The payer's admission alert opens a card while the patient is still in the hospital, so follow-up is ready before discharge. Cards move through columns for new discharges, call again, visit scheduled and unreachable, and a daily overview counts open cards, contacts due or overdue, visits past the 14-day deadline and high-risk patients on the readmission protocol. Each card shows the LACE score stated as a frequency ("about N in 100 similar past stays were readmitted within 30 days", from the practice's own payer history), the high-risk rule with a coordinator override, the follow-up steps, and the call results; an appointment check looks for a booked visit in the practice's schedule.

The board has no language model, because the practice receives the payer's alert but not the hospital's discharge summary. This matches the long-standing gap in discharge communication to primary care,[1] and in this practice it decides where the agent can help. The rule-based half works with the alert alone, which is why the practice could deploy it. The language-model half needs the summary: without it, there is nothing to extract, and the call script and the brief lose the medication review and the hospital's warning signs. The agent runs either way, skipping extraction when no summary exists. The Synthea drafting runs used this mode, but measured only speed, validation and grounding, so what is lost without a summary was not evaluated, and the agent's full value depends on getting the summary to the practice, for example through a health information exchange or the hospital's patient portal. The board also suggests a change to the agent that remains untested: stating risk as a frequency from each practice's own history, which may be easier for a coordinator to use than a score.

4.6 Limitations

- **References.** The diagnosis reference is small and narrow: 51 notes and two fields, corrected quickly by one annotator from a pre-filled form, with no second annotator or agreement measure. Medication changes and the prose fields rest on a language-model-corrected reference that also started from the

pre-filled form; its accuracy is unmeasured, and the low scores of every model on pending tests may partly reflect it.

- **Development on the evaluation cases.** The extractor and the drafting prompt were chosen on the same notes they are evaluated on, and the extraction prompt on the synthetic notes, so the results are optimistic for a fixed, prospectively specified pipeline.
- **Data.** MIMIC comes from one academic center and redacts its follow-up section. Whether the Qwen3 models saw similar text in pre-training is unknown. The synthetic benchmark was written by Qwen3-14B, which may favor that model, and its notes were kept only if they contained every reference fact, which makes them easier than real notes.
- **Variability and subgroups.** Each fine-tune was trained once with one seed, and each model was run once, so training and generation variability are unmeasured. No subgroup, fairness or language analyses were done, including for the under-65 Medicare rule.
- **Matching.** Relaxed matching treats brand and generic names as different and needs only token overlap. The draft checks are lexical: grounding catches invented names, not every wrong statement; completeness is measured against the extraction rather than the note; and condition grounding needs only one shared word.
- **Risk score.** On MIMIC, the alert and record were stand-ins built from hospital tables, prior emergency visits were undercounted, readmissions to other hospitals were missed, follow-up was not censored at the end of the record, and billing diagnoses, coded after discharge, stood in for the problem list a practice would have at discharge. The thresholds are provisional and not calibrated on any practice's outcomes.
- **Human review and use.** No user evaluation was done. Human review is a design safeguard whose effectiveness is untested; reviewers may accept plausible errors (automation bias[21]). Latency measures computation only, not coordinator time. The no-summary mode was run only on synthetic records, with automated checks.

4.7 Next steps

The next evaluation is of use. The review screen already records decisions, edits, review time and the reviewer's verdict on flags, and a protocol is in the repository in which a practice's follow-up coordinator reviews 30 synthetic discharges and completes a short questionnaire; aggregate counts from the practice's live board would add how the rule-based steps are used day to day. Beyond that, the agent needs a clinician-read evaluation of drafts, an evaluation of the no-summary mode, a frequency statement of risk calibrated on each practice's history, and above all a route for the discharge summary to reach the practice.

5. Conclusion

This retrospective component evaluation shows that a local, human-in-the-loop agent for hospital follow-up is computationally feasible on a single consumer GPU, with deterministic rules for the time-critical scheduling and drafts that stayed consistent with their input under automated checks. Extraction was the weakest component, and fine-tuning a small model on rule-generated labels reproduced the rules' patterns, including their gaps and potential errors; on these benchmarks a prompted base model was the better

default, and fine-tuning should be limited to fields whose labels have been checked against a reference other than the training labels. In the one practice described, the scarce input was the discharge summary, not the model. Human review, the clinical accuracy of the drafts and operational benefit remain to be evaluated.

Declarations

Ethics. See Section 2.7.

Data availability. The code, the synthetic benchmark, the annotation guideline and tools, the review tool, the script for Figure 1 and every aggregate metric reported here are public at https://github.com/thiagobandeira1/care-transitions-agent (release v1-preprint). MIMIC-IV and MIMIC-IV-Note are available to credentialed users from PhysioNet. No MIMIC-derived data, labels, predictions, drafts or model weights are distributed, as the data use agreement requires. No data from Mendez Medical Center were used for training or evaluation.

Code availability. The author owns the code and releases it as open source. The repository's commands recompute every reported metric from the saved outputs (Appendix B maps each table to its results file) and rebuild this paper. Re-running the models may give slightly different outputs, and the hand and language-model annotations cannot be regenerated. Fine-tuned weights are not shared, because they were trained on MIMIC.

Author contributions. T.B.N.B. conceived the study, built the software, ran the analyses and wrote the manuscript.

Competing interests. The author is General Manager and Head of AI at Mendez Medical Center, where the follow-up board described in Section 4.5 runs. The author founded TH Intelligence, which builds AI and automation tools for healthcare organizations. The software is open source. The author declares no other competing interests.

Funding. This work received no specific funding.

Use of generative AI. Claude Opus 5.5 (Anthropic) produced the language-model-corrected reference labels (Section 2.4). Claude Code (Anthropic) assisted with software development, analysis scripts and the drafting and revision of this manuscript; it ran on the author's computer, where the analysis scripts printed aggregate results only, and it did not read note text, labels or drafts. The author reviewed all code, analyses and text and takes responsibility for them.

Acknowledgments. The author thanks Oscar Mendez, MD, and Mendez Medical Center for supporting this work and for testing the prototype of the hospital follow-up board described in Section 4.5 in the practice's daily work; that experience informed the design and is not an evaluation reported here.

References

1. Kripalani S, LeFevre F, Phillips CO, Williams MV, Basaviah P, Baker DW. Deficits in communication and information transfer between hospital-based and primary care physicians: implications for patient

safety and continuity of care. *JAMA*. 2007;297(8):831-841.

2. Forster AJ, Murff HJ, Peterson JF, Gandhi TK, Bates DW. The incidence and severity of adverse events affecting patients after discharge from the hospital. *Ann Intern Med*. 2003;138(3):161-167.
3. Centers for Medicare & Medicaid Services. Transitional care management services. MLN Booklet MLN908628. Baltimore, MD: CMS; August 2025.
4. Agrawal M, Hegselmann S, Lang H, Kim Y, Sontag D. Large language models are few-shot clinical information extractors. In: *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*. Abu Dhabi: Association for Computational Linguistics; 2022:1998-2022. doi:10.18653/v1/2022.emnlp-main.130
5. van Walraven C, Dhalla IA, Bell C, et al. Derivation and validation of an index to predict early death or unplanned readmission after discharge from hospital to the community. *CMAJ*. 2010;182(6):551-557.
6. Johnson AEW, Bulgarelli L, Shen L, et al. MIMIC-IV, a freely accessible electronic health record dataset. *Sci Data*. 2023;10:1. doi:10.1038/s41597-022-01899-x
7. Johnson A, Pollard T, Horng S, Celi LA, Mark R. MIMIC-IV-Note: deidentified free-text clinical notes (version 2.2). PhysioNet. 2023. doi:10.13026/1n74-ne17
8. Johnson A, Bulgarelli L, Pollard T, Gow B, Moody B, Horng S, Celi LA, Mark R. MIMIC-IV (version 3.1). PhysioNet. 2024. doi:10.13026/kpb9-mt58
9. Pollard T, Moody BE, et al. PhysioNet as a global platform for biomedical research. *Nature Health*. 2026. doi:10.1038/s44360-026-00096-z
10. Walonoski J, Kramer M, Nichols J, et al. Synthea: an approach, method, and software mechanism for generating synthetic patients and the synthetic electronic health care record. *J Am Med Inform Assoc*. 2018;25(3):230-238.
11. Quan H, Sundararajan V, Halfon P, et al. Coding algorithms for defining comorbidities in ICD-9-CM and ICD-10 administrative data. *Med Care*. 2005;43(11):1130-1139.
12. Yang A, et al. Qwen3 technical report. arXiv:2505.09388. 2025.
13. Hu EJ, Shen Y, Wallis P, et al. LoRA: low-rank adaptation of large language models. In: *ICLR*. 2022.
14. Dettmers T, Pagnoni A, Holtzman A, Zettlemoyer L. QLoRA: efficient finetuning of quantized LLMs. In: *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*. 2023.
15. PhysioNet. Responsible use of MIMIC data with online services like GPT. April 18, 2023. https://physionet.org/news/post/gpt-responsible-use
16. Collins GS, Moons KGM, Dhiman P, et al. TRIPOD+AI statement: updated guidance for reporting clinical prediction models that use regression or machine learning methods. *BMJ*. 2024;385:e078378.
17. Gallifant J, Afshar M, Ameen S, et al. The TRIPOD-LLM reporting guideline for studies using large language models. *Nat Med*. 2025;31(1):60-69.
18. Ratner A, Bach SH, Ehrenberg H, Fries J, Wu S, Ré C. Snorkel: rapid training data creation with weak supervision. *Proc VLDB Endowment*. 2017;11(3):269-282.
19. Hinton G, Vinyals O, Dean J. Distilling the knowledge in a neural network. arXiv:1503.02531. 2015.
20. Fort K, Sagot B. Influence of pre-annotation on POS-tagged corpus development. In: *Proceedings of the Fourth Linguistic Annotation Workshop*. Uppsala: Association for Computational Linguistics;

2010:56-63.

21. Goddard K, Roudsari A, Wyatt JC. Automation bias: a systematic review of frequency, effect mediators, and mitigators. *J Am Med Inform Assoc*. 2012;19(1):121-127.

Appendix A. Reproducibility details

A1. Sampling. The patient-level split sorts the unique patient identifiers, shuffles them with seed 13 and cuts them 70/10/20. The 200 evaluation notes were sampled from the test split with seed 21; they come from 200 patients. The author-corrected reference covers the first 51 of them in sampling order (51 patients). For fine-tuning, 10,000 training notes were shuffled with seed 3, and the 8,851 that fit 3,072 tokens were kept; the teacher-labeled notes are the first 2,500 training and 300 validation notes in that order. MIMIC few-shot examples were drawn from a pool of 5,000 training notes sampled with seed 5: notes of 1,500-4,000 characters whose silver labels fill the principal diagnosis, secondary diagnoses, medication changes and red flags, one of them with a pending test. The synthetic benchmark's 150 discharges were sampled with seed 11 and split by Synthea patient, 30% of patients for examples (43 notes from 40 patients) and the rest for testing (107 notes from 96 patients); its three few-shot examples were drawn from the 43 with seed 5.

A2. Models. Ollama models and their identifiers: qwen3:8b (500a1f067a9f), qwen3:14b (bdbd181c33f2), Base-8B-local (861ed60837c4), Silver-8851 (dd093221823a), Silver-2500 (07bf8bb6edfe), Teacher-1250 (0d4e129d8827) and Teacher-2500 (741950281678). The fine-tunes start from the Qwen/Qwen3-8B weights on Hugging Face and use the model's own chat template. Qwen3's thinking mode was off for every call.

A3. Decoding. Extraction and teacher labeling: temperature 0, JSON-schema-constrained output, a 16,384-token context, and a 3,000-token answer cap on MIMIC (1,500 on the synthetic notes). Drafting: temperature 0.7, top-p 0.8, top-k 20, seed 7 plus the call's index (so a retry samples a new answer), an 8,192-token context and a 1,500-token answer cap, with no repetition or presence penalty set (the served model's defaults applied); drafts are limited to 400 characters per list item and 1,000 per paragraph.

A4. Fine-tuning. 4-bit NF4 quantization with double quantization and bfloat16 compute; LoRA rank 16, alpha 32, dropout 0.05, on all linear layers; the Transformers default optimizer (AdamW) at learning rate 2e-4 with cosine decay and 3% warm-up; one epoch; batch 1 with 8 gradient-accumulation steps; maximum length 3,072 tokens; seed 3; loss on the answer tokens only. Validation loss was computed every 200 steps on the validation notes that fit (264 of 300 for Silver-8851); the final checkpoint was used, with no early stopping or checkpoint selection.

A5. Scoring. Text is normalized by lowercasing, replacing every character other than a-z and 0-9 with a space, and collapsing spaces. An exact match is equal normalized text; a relaxed match is an exact match or a Jaccard overlap of at least 0.5 between the two sets of normalized tokens. For each predicted item in output order, the first unmatched reference item that matches is paired with it. Medication changes are compared as name plus change type, relaxed on the name and exact on the type; follow-ups are compared on whom the follow-up is with; the principal diagnosis is a one-item list. True positives, false positives and

false negatives are summed over notes, and over fields for micro F1; a field with no reference items and no predictions contributes nothing. Repeated list items (ignoring case and spacing) are removed from predictions and references before scoring.

A6. Synthetic data. Synthea build d9d07a6, CSV export with 10 years of history. Discharges come from the agent's Medicare cohort builder; notes were written by Qwen3-14B and kept only if they mentioned every reference fact.

A7. Reproduction. The README and PROGRESS.md list the commands. Rescoring the saved predictions against the saved reference labels reproduces every reported metric exactly, but those files stay on the author's computer: MIMIC-derived predictions and labels cannot be distributed, and the synthetic predictions are not in the repository. The public release holds the code, the synthetic benchmark and the aggregate results files. Re-running the models may give slightly different outputs, and the author-corrected and language-model-corrected annotations cannot be regenerated. Prompts and instructions in the release: extraction, `src/ctagent/extractor.py`, with the schema and field definitions in `src/ctagent/extraction.py`; teacher labeling, `src/ctagent/teacher.py`; the plan explanation, drafting and the retry, `src/ctagent/graph.py`, `src/ctagent/drafts.py` and `src/ctagent/llm.py`; synthetic notes, `src/ctagent/notegen.py`; annotation guideline, `docs/ANNOTATION.md`.

Appendix B. Where each table comes from

Table	Results file in `evals/results/` (command)
1, 2	the rules module and PROGRESS.md (training logs)
3	`risk_mimic.json` (`mimic-risk`)
4	`extraction_synthetic_*.json` (`extract-bench`)
5	`extraction_mimic_gold_*.json` (`mimic-bench --ref gold --rescore`); rules row and support from `paper_extras.json`
6	`extraction_mimic_claude_*.json` (`mimic-bench --ref claude --rescore`); rules row and support from `paper_extras.json`
7, paired differences, support, macro F1	`paper_extras.json` (`scripts/paper_extras.py`)
8	`drafting_qwen3-14b_gpu.json`, `drafting_qwen3-8b_gpu.json` and the `_cpu` files (`bench`)
9	`drafting_mimic_qwen3-14b.json` (final run) and `drafting_mimic_qwen3-14b_run1.json` (first run) (`mimic-drafts`)

Appendix C. Reporting summary against TRIPOD+AI and TRIPOD-LLM

The relevant items of TRIPOD+AI[16] apply to the risk-tier evaluation, and those of TRIPOD-LLM[17] to extraction, fine-tuning and drafting. The table lists where each reporting area is addressed and what was not done.

Reporting area	Where	Status
Study type and intended use	Title, Abstract, 1, 2.1	Retrospective component evaluation of an intended workflow
Data sources, eligibility and flow	2.2, 2.3, 3.1, A1	Partial: sources, periods and flow reported; dates are shifted for de-identification, so the selected cohort's calendar period was not characterized
Outcome definition	2.3	Admission-type proxy for unplanned readmission
Score inputs and missing data	2.3	LACE mapping reported; missing inputs score 0
Sample size	2.2-2.4	Partial: the risk cohort is every eligible test-split stay; the 200-note sample was sized for feasible annotation, and the author corrected its first 51 notes; no sample-size calculation
Models, versions, settings and prompts	2.4, A2-A4	Reported; prompts in the repository
Reference construction	2.4, 4.3	Silver-initialized; one annotator; no agreement measure
Performance measures and uncertainty	2.4, 3, A5	Reported; intervals conditional on models and references
Development and evaluation data	2.2, 2.5, 4.6	Training and test splits are patient-disjoint; the evaluation cases were reused to select the extractor and revise the drafting prompt (disclosed)
Subgroups and fairness	4.6	Not performed
Human oversight and deployment	2.1, 4.6	Designed; not evaluated
Protocol and registration	2.8, 4.7	None for this study; a simulated-use protocol is in the repository
Data and code availability	Declarations, B	Reported
Ethics	2.7	Reported