

# Adequate and computational encodings in the logical framework Dedukti

Thiago Felicissimo ✉

Université Paris-Saclay, INRIA project Deducteam, Laboratoire de Méthodes Formelles, ENS  
Paris-Saclay, 91190 France

## Abstract

DEDUKTI is a very expressive logical framework which unlike most frameworks, such as the Edinburgh Logical Framework (ELF), allows for the representation of computation alongside deduction. However, unlike ELF encodings, DEDUKTI encodings proposed until now do not feature an adequacy theorem — *i.e.*, a bijection between terms in the encoded system and in its encoding. Moreover, many of them also do not have a conservativity one, which compromises the ability of DEDUKTI to check proofs written in such encodings. We propose a different approach for DEDUKTI encodings which do not only allow for simpler conservativity proofs, but which also restore the adequacy of encodings. More precisely, we propose in this work adequate (and thus conservative) encodings for Functional Pure Type Systems. However, in contrast with ELF encodings, ours is computational — that is, represents computation directly as computation. Therefore, our work is the first to present and prove correct an approach allowing for encodings that are both adequate and computational in DEDUKTI.

**2012 ACM Subject Classification** Theory of computation → Type theory; Theory of computation → Equational logic and rewriting

**Keywords and phrases** Type Theory, Logical Frameworks, Rewriting, Dedukti

**Digital Object Identifier** 10.4230/LIPIcs.CVIT.2016.23

**Acknowledgements** I would like to thank my PhD advisors Frédéric Blanqui and Gilles Dowek for the helpful discussions and comments on this paper.

## 1 Introduction

The research on proof-checking naturally leads to the proposal of many logical systems and theories. *Logical frameworks* are a way of addressing this heterogeneity by proposing a common foundation in which systems and theories can be defined. The *Edinburgh Logical Framework* (ELF)[17] is one of the milestones in the history of logical frameworks, and proposes the use of a dependently-typed lambda-calculus to express deduction. However, as modern proof assistants move from traditional logics to type theories, where computation plays an important role alongside deduction, it becomes essential for such frameworks to also be able to express computation, something that the ELF does not achieve.

The logical framework DEDUKTI[3] addresses this point by extending the ELF with rewriting rules, thus allowing for the representation of both deduction and computation. This framework has already proven itself as a very expressive system, and has been used to encode the logics of many proof assistants, such as COQ[14], AGDA[15], PVS[18] and others.

However, an unsatisfying aspect persists as, unlike ELF encodings, the DEDUKTI encodings proposed until now are not *adequate* — that is, feature a syntactical bijection between the terms of the encoded system and those of the encoding. Such property is key in ensuring that the framework faithfully represents the syntax on the encoded system. Moreover, proving that DEDUKTI encodings are *conservative* (*i.e.*, that if the translation of a type is inhabited, then this type is inhabited) is still a challenge, in particular for recent works such as [14][23][15][18]. This is a problem if one intends to use DEDUKTI to check the correctness of proofs coming from proof assistants: if conservativity does not hold then the fact that the translation of a



© Thiago Felicissimo;  
licensed under Creative Commons License CC-BY 4.0

42nd Conference on Very Important Topics (CVIT 2016).

Editors: John Q. Open and Joan R. Access; Article No. 23; pp. 23:1–23:28

Leibniz International Proceedings in Informatics



LIPICs Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl Publishing, Germany

45 proof is checked correct in DEDUKTI does not imply that this proof is correct.

46 In the specific case of Pure Type Systems (PTS), a class of type systems which generalizes  
 47 many others, [9] was the first to propose an encoding of functional PTSs into DEDUKTI. One  
 48 of their main contributions is that, differently from ELF encodings, theirs is *computational* —  
 49 that is, represents computation in the encoded system directly as computation. The authors  
 50 then show that the encoding was conservative under the hypothesis of normalization of their  
 51 rewrite rules.

52 To address the issue of this unproven assumption, [11] proposed a notion of model of  
 53 DEDUKTI and showed using the technique of *reducibility candidates* that the existence of  
 54 such a model entails the normalization of the encoding. Using this result, the author then  
 55 showed the conservativity of the encoding of Simple Type Theory and of the Calculus of  
 56 Constructions. This technique however is not very satisfying as the construction of such  
 57 models is a very technical task, and needs to be done case by case. One can also wonder why  
 58 conservativity should rely on normalization.

59 The cause of this difficulty in [9] and in all other traditional DEDUKTI encodings comes  
 60 from a choice made to represent the abstraction and application of the encoded system  
 61 directly by the abstraction and application of the framework. This causes a confusion as  
 62 redexes of the encoded system, that represent real computations, get confused with the  $\beta$   
 63 redexes of the framework, which in other frameworks such as the ELF are used exclusively  
 64 to represent binder substitution. As a non-normal term can contain both types of redexes,  
 65 it is impossible to inverse translate it as some of these redexes are ill-typed in the original  
 66 system, and the only way of eliminating these ill-typed redexes is by reducing all of them.  
 67 One then needs this process to be terminating, which is non-trivial to show as it involves  
 68 proving that the reduction of the redexes of the encoded system terminates.

69 The work of [2] first noted this problem and proposed a different approach to show  
 70 the conservativity of the encoding of PTSs. Instead of relying on the normalization of the  
 71 encoding, they proposed to directly inverse translate terms without normalizing them. As  
 72 this creates ill-typed terms, they then used reducibility candidates to show that these ill-typed  
 73 terms reduce to well-typed ones, thus proving conservativity for the encoding in [9]. Even  
 74 though this technique is a big improvement over [11], it is still unsatisfying that both of  
 75 them rely on involved arguments using reducibility, whereas the proofs of ELF encodings  
 76 were very natural. The technicality of these proofs may be a reason for recent works such as  
 77 [23], [18] and [15] to have left conservativity as conjecture. Moreover, none of these works  
 78 have addressed the lack of an adequacy theorem.

## 79 Our contribution

80 We propose to depart from the approach of traditional DEDUKTI encodings by restoring  
 81 the separation that existed in ELF encodings. Our paradigm represents the abstractions  
 82 and applications of the encoded system not by those of the framework, but by dedicated  
 83 constructions. Using this approach, we propose an encoding of functional PTSs that is not  
 84 only sound and conservative but also adequate. However, in contrast with ELF encodings,  
 85 ours is computational like other DEDUKTI encodings.

86 To show conservativity, we leverage the fact the computational rules of the encoded  
 87 system are not represented by  $\beta$  reduction anymore, but by dedicated rewrite rules. This  
 88 allows us to normalize only the framework's  $\beta$  redexes without touching those associated  
 89 with the encoded system, and thus performing no computation from its point of view.

90 To be able to  $\beta$  normalize terms, we generalize the proof in [17] to give a general criterion  
 91 for the normalization of  $\beta$  reduction in DEDUKTI. This criterion imposes rewriting rules

to be *arity preserving* (a definition we introduce). This is not satisfied by traditional DEDUKTI encodings, but poses no problem to ours. The proof uses the simple technique of defining an erasure map into the simply-typed lambda calculus, which is known to be normalizing.

## Outline

We start in Section 2 by recalling the preliminaries about DEDUKTI. We proceed in Section 3 by proposing a criterion for the normalization of  $\beta$  in DEDUKTI, which is used in our proofs of conservativity and adequacy. In Section 4 we introduce an explicitly-typed version of Pure Type Systems, which is used in our translation. We then present our encoding in Section 5, and proceed by showing it is sound in Section 6 and that it is conservative and adequate in Section 7. In Section 8 we discuss how our approach can be used together with already known techniques to represent systems with infinite sorts. Finally, in Section 10 we discuss more practical aspects by showing how our encoding can be instantiated and used in practice.

## 2 Dedukti

$$\begin{array}{c}
\frac{}{\Sigma; - \text{ well-formed}} \text{Empty} \quad x \notin \Gamma \frac{\Sigma; \Gamma \vdash A : \text{TYPE}}{\Sigma; \Gamma, x : A \text{ well-formed}} \text{Decl} \\
\\
c[\Delta] : A \in \Sigma \frac{\Sigma; \Delta \vdash A : s \quad \Sigma; \Gamma \vdash \vec{M} : \Delta}{\Sigma; \Gamma \vdash c[\vec{M}] : A\{\vec{M}\}} \text{Cons} \quad \frac{\Sigma; \Gamma \text{ well-formed}}{\Sigma; \Gamma \vdash \text{TYPE} : \text{KIND}} \text{Sort} \\
\\
x : A \in \Gamma \frac{\Sigma; \Gamma \text{ well-formed}}{\Sigma; \Gamma \vdash x : A} \text{Var} \quad A \equiv_{\beta\mathcal{R}} B \frac{\Sigma; \Gamma \vdash M : A \quad \Sigma; \Gamma \vdash B : s}{\Sigma; \Gamma \vdash M : B} \text{Conv} \\
\\
\frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s}{\Sigma; \Gamma \vdash \Pi x : A. B : s} \text{Prod} \quad \frac{\Sigma; \Gamma \vdash M : \Pi x : A. B \quad \Sigma; \Gamma \vdash N : A}{\Sigma; \Gamma \vdash MN : B\{N/x\}} \text{App} \\
\\
\frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s \quad \Sigma; \Gamma, x : A \vdash M : B}{\Sigma; \Gamma \vdash \lambda x : A. M : \Pi x : A. B} \text{Abs}
\end{array}$$

Figure 1 Typing rules for DEDUKTI

The logical framework DEDUKTI [3] has the syntax of the  $\lambda$ -calculus with dependent types [17] ( $\lambda\Pi$ -calculus). Like works such as [18], we consider here a version with arities, with the following syntax.

$$A, B, M, N ::= x \mid c[\vec{M}] \mid \text{TYPE} \mid \text{KIND} \mid MN \mid \lambda x : A. M \mid \Pi x : A. B$$

Here,  $c$  ranges in an infinite set of constants  $\mathcal{C}$ , and  $x$  ranges in an infinite set of variables  $\mathcal{V}$ . Each constant  $c$  is assumed to have a fixed arity  $n_c$  and for each occurrence of  $c[\vec{M}]$  we should have  $\text{length}(\vec{M}) = n_c$ . We denote  $\Lambda_{\text{DK}}$  the set of terms generated by this grammar. We call a term of the form  $\Pi x : A. B$  a *dependent product*, and we write  $A \rightarrow B$  when  $x$  does not appear free in  $B$ . We allow ourselves sometimes to write  $c \vec{M}$  instead of  $c[\vec{M}]$  to ease the notation.

A *context*  $\Gamma$  is a finite sequence of pairs  $x : A$  with  $A \in \Lambda_{\text{DK}}$ . A *signature*  $\Sigma$  is a finite set of triples  $c[\Delta] : A$  where  $A \in \Lambda_{\text{DK}}$  and  $\Delta$  is a context containing at least all free variables of  $A$ . The main difference between DEDUKTI and the  $\lambda\Pi$ -calculus is that we also consider a set  $\mathcal{R}$  of *rewrite rules*, that is, of pairs of the form  $c[\vec{l}] \hookrightarrow r$  with  $l_1, \dots, l_k, r \in \Lambda_{\text{DK}}$ . A *theory* is a pair  $(\Sigma, \mathcal{R})$  such that all constants appearing in  $\mathcal{R}$  are declared in  $\Sigma$ .

We write  $\hookrightarrow_{\mathcal{R}}$  for the context and substitution closure of the rules in  $\mathcal{R}$  and  $\hookrightarrow_{\beta\mathcal{R}}$  for  $\hookrightarrow_{\beta} \cup \hookrightarrow_{\mathcal{R}}$ . We also consider the equivalence relation  $\equiv_{\beta\mathcal{R}}$  generated by  $\hookrightarrow_{\beta\mathcal{R}}$ . Finally, we may refer to  $\hookrightarrow_{\beta\mathcal{R}}$  and  $\equiv_{\beta\mathcal{R}}$  by just  $\hookrightarrow$  and  $\equiv$ .

Typing in DEDUKTI is given by the rules in Figure 1. In rule **Conv** we use the usual notation  $\Sigma; \Gamma \vdash \vec{M} : \Delta$  meaning that  $\Delta = x_1 : A_1, \dots, x_n : A_n$  and  $\Sigma; \Gamma \vdash M_i : A_i\{M_1/x_1\}\dots\{M_{i-1}/x_{i-1}\}$  is derivable for  $i = 1, \dots, n$ . We then also allow ourselves to write  $A\{\vec{M}\}$  instead of  $A\{M_1/x_1\}\dots\{M_n/x_n\}$ .

We recall the following basic metatheorems.

► **Proposition 1** (Basic properties). *Suppose  $\hookrightarrow_{\beta\mathcal{R}}$  is confluent.*

1. *Weakening: If  $\Sigma; \Gamma \vdash M : A$  and  $\Gamma \sqsubseteq \Gamma'$  then  $\Sigma; \Gamma' \vdash M : A$*
2. *Well-typedness of contexts: If  $\Sigma; \Gamma$  well-formed then for all  $x : B \in \Gamma$ ,  $\Sigma; \Gamma \vdash B : \text{TYPE}$*
3. *Inversion of typing: Suppose  $\Sigma; \Gamma \vdash M : A$* 
  - *If  $M = x$  then  $x : A' \in \Gamma$  and  $A \equiv A'$*
  - *If  $M = c[\vec{N}]$  then  $c[\Delta] : A' \in \Sigma$ ,  $\Sigma; \Delta \vdash A' : s$ ,  $\Sigma; \Gamma \vdash \vec{N} : \Delta$  and  $A'(\vec{N}/\Delta) \equiv A$*
  - *If  $M = \text{TYPE}$  then  $A \equiv \text{KIND}$*
  - *$M = \text{KIND}$  is impossible*
  - *If  $M = \Pi x : A_1. A_2$  then  $\Sigma; \Gamma \vdash A_1 : \text{TYPE}$ ,  $\Sigma; \Gamma, x : A_1 \vdash A_2 : s$  and  $s \equiv A$*
  - *If  $M = M_1 M_2$  then  $\Sigma; \Gamma \vdash M_1 : \Pi x : A_1. A_2$ ,  $\Sigma; \Gamma \vdash M_2 : A_1$  and  $A_2(M_2/x) \equiv A$*
  - *If  $M = \lambda x : B. N$  then  $\Sigma; \Gamma \vdash B : \text{TYPE}$ ,  $\Sigma; \Gamma, x : B \vdash C : s$ ,  $\Sigma; \Gamma, x : B \vdash N : C$  and  $A \equiv \Pi x : B. C$*
4. *Uniqueness of types: If  $\Sigma; \Gamma \vdash M : A$  and  $\Sigma; \Gamma \vdash M : A'$  then  $A \equiv A'$*
5. *Well-sortedness: If  $\Sigma; \Gamma \vdash M : A$  then  $\Sigma; \Gamma \vdash A : s$  or  $A = \text{TYPE}$ ,  $s = \text{KIND}$*

► **Theorem 2** (Conv in context for DK). *Let  $A \equiv A'$  with  $\Sigma; \Gamma \vdash A' : s$ . We have*

- $\Sigma; \Gamma, x : A, \Gamma' \text{ WF} \Rightarrow \Sigma; \Gamma, x : A', \Gamma' \text{ WF}$
- $\Sigma; \Gamma, x : A, \Gamma' \vdash M : B \Rightarrow \Sigma; \Gamma, x : A', \Gamma' \vdash M : B$

**Proof.** Structural induction on the derivation tree, using weakening for the case **Var**. ◀

► **Proposition 3** (Reduce type in judgement). *Suppose  $\hookrightarrow_{\beta\mathcal{R}}$  is confluent. Then if  $\Sigma; \Gamma \vdash_{\lambda\Pi} M : A$  and  $A \hookrightarrow^* A'$  we have  $\Sigma; \Gamma \vdash_{\lambda\Pi} M : A'$ .*

**Proof.** By confluence,  $\beta$  satisfies subject reduction. Therefore, this is a direct consequence of well-sortedness and subject reduction. ◀

### 3 Strong Normalization of $\beta$ in Dedukti

In order to show the conservativity of encodings, one often needs to  $\beta$  normalize terms, thus requiring  $\beta$  to be normalizing for well-typed terms. In this section we generalize the proof of normalization of the  $\lambda\Pi$ -calculus given in [17] to DEDUKTI. More precisely, we show that, given that  $\beta\mathcal{R}$  is confluent and *arity preserving* (a definition we will introduce in this section), then  $\beta$  is SN (strongly normalizing) in DEDUKTI for well-typed terms.

Note that, unlike works such as [8], which provide syntactic criteria on the normalization of  $\beta\mathcal{R}$  in DEDUKTI, we only aim to show the normalization of  $\beta$ . In particular  $\beta\mathcal{R}$  may not be SN in our setting. Our work has more similar goals to [4], which provides criteria for the SN of  $\beta$  in the Calculus of Constructions when adding object-level rewrite rules. However, our work also allows for type-level rewrite rules, which will be needed in our encoding.

Our proof works by defining an erasure map into the simply-typed  $\lambda$ -calculus, which is known to be SN, and then show that this map preserves typing and non-termination of

$\beta$ , thus implying that  $\beta$  is SN in DEDUKTI. To do this, the erasure map must remove the dependency inside types, but as in DEDUKTI terms and types are all mixed together, we will first need to be able to separate them syntactically.

The syntactic stratification theorem (Theorem 9) is a standard property of DEDUKTI and is exactly what we need here. However, unlike the known variants in the literature, such as in [6], we prove a more general version not requiring subject reduction of  $\beta\mathcal{R}$ . The proof draws inspiration from a similar one in [4].

We proceed as follows. First we start by proving our generalization of the stratification theorem (Theorem 9). This is followed by the definition of the erasure function from DEDUKTI into the simply-typed  $\lambda$ -calculus (Definition 11). We then introduce our definition of *arity preserving* rewrite systems (Definition 13), and give some motivation of why the proof works. We then show that this function preserves both typing (Proposition 16) and non-termination (Proposition 17). Finally, by putting all this together, we will conclude by showing our main result (Theorem 18).

### 3.1 Syntactic stratification

► **Definition 4.** We introduce the following basic definitions.

1. Given a signature  $\Sigma$ , a constant  $c$  is type-level (and referred by  $\alpha, \gamma$ ) if  $c[\Delta] : A \in \Sigma$  with  $A$  of the form  $\Pi \vec{x} : \vec{B} : \text{TYPE}$ , otherwise it is object-level (and referred by  $a, b$ ).
2. A rewrite rule  $c[\vec{I}] \hookrightarrow r$  is type-level if its head symbol  $c$  is a type-level constant.

As previously mentioned, our proof of the stratification theorem will not need subject reduction of  $\mathcal{R}$ . Instead, we will only need the following syntactic property.

► **Definition 5.** We say that  $\mathcal{R}$  is well-formed (with respect to  $\Sigma$ ) if for all type-level rules, its right-hand side is in the following grammar, where  $\vec{M}, N, B$  are any.

$$R ::= \alpha[\vec{M}] \mid RN \mid \lambda x : B. R \mid \Pi x : R. R$$

We are now ready to define the syntactic classes of terms in DEDUKTI, through the following grammars. We will show in Theorem 9 that every typed term belong to one of these classes.

$$K ::= \text{TYPE} \mid \Pi x : T. K \quad (\text{Kinds})$$

$$T ::= \alpha[\vec{O}] \mid TO \mid \lambda x : T. T \mid \Pi x : T. T \quad (\text{Type Families})$$

$$O ::= x \mid a[\vec{O}] \mid OO \mid \lambda x : T. O \quad (\text{Objects})$$

These grammars can easily be shown closed under object-level substitution.

► **Lemma 6** (Closure under object-level substitution). For all objects  $O$ , we have

- If  $M$  is an object, then  $M\{O/x\}$  is an object
- If  $M$  is a type family, then  $M\{O/x\}$  is a type family
- If  $M$  is a kind, then  $M\{O/x\}$  is a kind

A property that one would find natural is for these grammars to be closed under reduction. However, as it is shown by the following example, this is not the case.

► **Example 7.** Consider the rule  $\alpha[\lambda x : y.x] \hookrightarrow \alpha[y]$ . With the substitution  $y \mapsto \gamma$  we have  $\alpha[\lambda x : \gamma.x] \hookrightarrow \alpha[\gamma]$ . The left-hand side is a type family, whereas the right-hand side is not in any of the grammars.

## 23:6 Adequate and computational encodings in the logical framework Dedukti

However, we can still define a weaker notion of pre-kinds and pre-type families for which closure under rewriting holds. This property will be key when proving the stratification theorem.

► **Lemma 8.** *Define the grammars*

$L ::= \text{TYPE} \mid \Pi x : R.L$  (Pre-Kinds)

$R ::= \alpha[\vec{M}] \mid RN \mid \lambda x : A.R \mid \Pi x : R.R$  (Pre-Type Families)

where  $A, N, \vec{M}$  are any. If  $\mathcal{R}$  is well-formed, then they are disjoint and closed under  $\beta\mathcal{R}$ .

**Proof.** The two grammars are clearly disjoint. Before showing closure under rewriting, we first show closure under substitution: for every pre-kind  $L$ , pre-type family  $R$  and term  $N$ ,  $L\{N/x\}$  is a pre-kind and  $R\{N/x\}$  is a pre-type family (by induction on  $R$  and  $L$ ). Then, by induction on the rewrite context and using closure under substitution we show the result. ◀

We are now ready to show the stratification theorem.

► **Theorem 9** (Syntactical stratification). *Suppose that  $\beta\mathcal{R}$  is confluent and  $\mathcal{R}$  is well formed. If  $\Sigma; \Gamma \vdash M : A$  then exactly one of the following hold:*

1.  $M$  is a kind and  $A = \text{KIND}$
2.  $M$  is a type family and  $A$  is a kind
3.  $M$  is an object and  $A$  is a type family

**Proof.** First note that the grammars are clearly disjoint, so only one of the cases can hold. We proceed by showing the rest by induction over  $\Sigma; \Gamma \vdash M : A$ .

**Sort:** Trivial.

**Var:** We have

$$x : A \in \Gamma \quad \frac{\Sigma; \Gamma \text{ well-formed}}{\Sigma; \Gamma \vdash x : A} \text{Var}$$

For some  $\Gamma' \sqsubseteq \Gamma$ , we have  $\Sigma; \Gamma' \vdash A : \text{TYPE}$  with a smaller derivation tree. By IH,  $A$  is a type family, hence the result follows.

**Cons:** We have

$$c[\Delta] : A \in \Sigma \quad \frac{\Sigma; \Delta \vdash A : s \quad \Sigma; \Gamma \vdash \vec{M} : \Delta}{\Sigma; \Gamma \vdash c[\vec{M}] : A\{\vec{M}\}} \text{Cons}$$

We first show the following claim.

► **Claim 10.**  $\vec{M}$  is made of objects.

**Proof.** Write  $\Delta = x_1 : A_1, \dots, x_n : A_n$ . First note that  $\Sigma; \Delta \vdash A : s$  implies  $\Sigma; x_1 : A_1, \dots, x_{i-1} : A_{i-1} \vdash A_i : \text{TYPE}$  with a smaller derivation tree, hence by the IH each  $A_i$  is a type family. We now show by induction on  $i$  that for  $i = 1, \dots, n$ ,  $M_i$  is an object<sup>1</sup>.

For the case  $i = 1$  this follows from  $\Sigma; \Gamma \vdash M_1 : A_1$ , by the outer IH and the fact that  $A_1$  is a type family. For the induction step, we have  $\Sigma; \Gamma \vdash M_i : A_i\{M_1/x_1\} \dots \{M_{i-1}/x_{i-1}\}$ . We know that  $A_i$  is a type family, and by the inner IH we have that  $M_1, \dots, M_{i-1}$  are objects. By closure under object-level substitution,  $A_i\{M_1/x_1\} \dots \{M_{i-1}/x_{i-1}\}$  is also a type family. Hence the outer IH implies that  $M_i$  is an object. ◀

<sup>1</sup> We will use the terms “inner IH” for the IH corresponding to this claim and “outer IH” for the IH corresponding to the whole theorem.

We now proceed with the main proof obligation. If  $s = \text{KIND}$  by IH  $A$  is a kind, of the form  $\Pi \vec{x} : \vec{B}. \text{TYPE}$ . Hence  $c$  is a type-level constant. Because  $c$  is type-level and  $\vec{M}$  is made of objects, then  $c[\vec{M}]$  is a type family. Finally, as  $\vec{M}$  are objects, then by closure under object-level substitution  $A\{\vec{M}\}$  is a kind. Hence we are in case 2.

If  $s = \text{TYPE}$  by IH  $A$  is a type family. Hence  $c$  is an object-level constant. Because  $c$  is object-level and  $\vec{M}$  is made of objects, then  $c[\vec{M}]$  is an object. Finally, as  $\vec{M}$  are objects, then by closure under object-level substitution  $A\{\vec{M}\}$  is a type family. Hence we are in case 3.

**Conv:** We have

$$A \equiv B \frac{\Sigma; \Gamma \vdash M : A \quad \Sigma; \Gamma \vdash B : s}{\Sigma; \Gamma \vdash M : B} \text{Conv}$$

By confluence, there is  $C$  with  $A \longleftrightarrow^* C \longleftrightarrow^* B$ . Note that type families and kinds are also respectively pre-type families and pre-kinds, which are disjoint and closed under rewriting. Therefore, an important remark is that both situations in which  $A$  is a type-family and  $B$  a kind, or  $A$  a kind and  $B$  a type family, are impossible.

We now proceed with the proof and consider the cases  $s = \text{TYPE}$  and  $s = \text{KIND}$ .

If  $s = \text{TYPE}$  then  $B$  is a type family. Applying the IH to  $M : A$ , then by the previous remark we only need to consider the case in which  $A$  is a type family, and thus  $M$  is an object as required.

If  $s = \text{KIND}$ , then  $B$  is a kind. Applying the IH to  $M : A$ , then by previous remark we only need to consider the case in which  $A$  is a kind, and thus  $M$  is a type family as required.

**Prod:** We have

$$\frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s}{\Sigma; \Gamma \vdash \Pi x : A. B : s} \text{Prod}$$

We have either  $s = \text{TYPE}$  or  $s = \text{KIND}$ .

If  $s = \text{TYPE}$ , then by IH both  $A, B$  are type families, hence  $\Pi x : A. B$  is a type family and we are in case (2).

If  $s = \text{KIND}$ , then  $A$  is a type family and  $B$  a kind, hence  $\Pi x : A. B$  is a kind and we are in case (1).

**Abs:** We have

$$\frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s \quad \Sigma; \Gamma, x : A \vdash M : B}{\Sigma; \Gamma \vdash \lambda x : A. M : \Pi x : A. B} \text{Abs}$$

We have either  $s = \text{TYPE}$  or  $s = \text{KIND}$ .

If  $s = \text{TYPE}$ , then by IH both  $A, B$  are type families and  $M$  is an object. Hence  $\lambda x : A. M$  is an object,  $\Pi x : A. B$  is a type family and we are in case (3).

If  $s = \text{KIND}$ , then  $B$  is a kind and  $A, M$  are type families. Hence  $\Pi x : A. M$  is a type family,  $\Pi x : A. B$  is a kind and we are in case (2).

**App:** We have

$$\frac{\Sigma; \Gamma \vdash M : \Pi x : A. B \quad \Sigma; \Gamma \vdash N : A}{\Sigma; \Gamma \vdash MN : B\{N/x\}} \text{App}$$

By the IH applied to  $M : \Pi x : A. B$ ,  $\Pi x : A. B$  is either a type family or a kind, hence in all cases  $A$  is a type family, and thus by the IH applied to  $N : A$ ,  $N$  is an object.

If  $\Pi x : A. B$  is a type family, then  $M$  is an object, and thus  $MN$  is also. As  $B$  is a type family and the grammars are closed by object-level substitution,  $B\{N/x\}$  is also a type family. Hence we are in case (2).

If  $\Pi x : A. B$  is a kind, then  $M$  is a type family, and thus  $MN$  is also. As  $B$  is a kind and the grammars are closed by object-level substitution,  $B\{N/x\}$  is a kind. Hence we are in case (1). ◀

### 3.2 Erasure map

We are now ready to give the definition of the erasure map into the simply-typed  $\lambda$ -calculus.

► **Definition 11** (Erasure map). *Consider the simple types generated by the grammar*

$$\sigma ::= * \mid \sigma \rightarrow \sigma.$$

Moreover, let  $\Gamma_\pi$  be the context containing for each  $\sigma$  the declaration  $\pi_\sigma : * \rightarrow (\sigma \rightarrow *) \rightarrow *$ .

We define the partial functions  $\|-\|, |-|$  by the following equations.

$$\begin{aligned} \|\text{TYPE}\| &= * & |x| &= x \\ \|\alpha[\vec{M}]\| &= * & |a[\vec{M}]| &= a \mid \vec{M} \\ \|\Pi x : A. B\| &= \|A\| \rightarrow \|B\| & |\alpha[\vec{M}]| &= \alpha \mid \vec{M} \\ \|AN\| &= \|A\| & |MN| &= |M| \|N\| \\ \|\lambda x : A. B\| &= \|B\| & |\lambda x : A. M| &= (\lambda z. \lambda x. |M|) |A| \text{ where } z \notin FV(M) \\ & & |\Pi x : A. B| &= \pi_{\|A\|} |A| (\lambda x. |B|) \end{aligned}$$

In particular, note that  $|-|$  is defined for all objects and type families, and that  $\|-\|$  is defined for all type-families and kinds. We also extend the definition of  $\|-\|$  (partially) on contexts and signatures by the following equations.

$$\begin{aligned} \|\Gamma\| &= \Gamma \\ \|x : A, \Gamma\| &= x : \|A\|, \|\Gamma\| \\ \|c[x_1 : A_1, \dots, x_n : A_n] : A; \Sigma\| &= (c : \|A_1\| \rightarrow \dots \rightarrow \|A_n\| \rightarrow \|A\|), \|\Sigma\| \end{aligned}$$

In order to show the normalization of  $\beta$ , we need the erasure to preserve typing. The main obstacle when showing this is dealing with the **Conv** rule. To make the proof go through, we would need to show that if  $A \equiv B$  then  $\|A\| = \|B\|$ . In the  $\lambda\Pi$ -calculus this can be easily shown, however because in **DEDUKTI** the relation  $\equiv$  also takes into account the rewrite rules in  $\mathcal{R}$ , we can easily build counterexamples in which this does not hold.

► **Example 12.** Let  $\text{El}$  be a type-level constant, and consider the rule

$$\text{El} (\text{Prod } A \ B) \longleftrightarrow \Pi x : \text{El } A. \text{El} (B \ x)$$

traditionally used to build **DEDUKTI** encodings (as in [9]). Note that here we write  $\alpha \tilde{I}$  for  $\alpha[\tilde{I}]$ , to ease the notation. We then have

$$\text{El} (\text{Prod Nat } (\lambda x. \text{Nat})) \equiv \Pi x : \text{El Nat}. \text{El} ((\lambda x. \text{Nat}) \ x) \equiv \text{El Nat} \rightarrow \text{El Nat}$$

but  $\|\text{El} (\text{Prod Nat } (\lambda x : \text{Nat}))\| = *$  and  $\|\text{El Nat} \rightarrow \text{El Nat}\| = * \rightarrow *$ .

If we were to define the arity of a type<sup>2</sup> as the number of consecutive arrows (that is, of  $\Pi$ s), then we realize that the problem here is that rules such as  $\text{El} (\text{Prod } A \ B) \longleftrightarrow \Pi x : \text{El } A. \text{El} (B \ x)$  do not preserve the arity. Indeed,  $\text{El} (\text{Prod } A \ B)$  has arity 0 because it has no arrows, whereas  $\Pi x : \text{El } A. \text{El} (B \ x)$  has arity 1 as it has one arrow<sup>3</sup>. As the left-hand side of a type-level rule always has arity 0 (because it is of the form  $\alpha[\tilde{I}]$ ), to remove these unwanted cases we need for their right-hand sides to also have arity 0. This motivates the following definition.

<sup>2</sup> Note that this concept is different from the notion of arity of constants, as defined in Section 2.

<sup>3</sup> Using a different notation for the dependent product, we can write this type as  $(x : \text{El } A) \rightarrow \text{El} (B \ x)$ , which may help to clarify this assertion.



317 ▶ **Definition 13** (Arity preserving).  $\mathcal{R}$  is said to be arity-preserving<sup>4</sup> if, for every type-level  
 318 rewrite rule in  $\mathcal{R}$ , the right-hand side is in the following grammar, where  $\vec{M}, N, A$  are any.

$$319 \quad R ::= \alpha[\vec{M}] \mid R \ N \mid \lambda x : A. R$$

320 It turns out that this definition, together with confluence of  $\beta\mathcal{R}$ , will be enough to show  
 321 that the translation preserves typing, and also non-termination. Therefore, throughout the  
 322 rest of this section we suppose the following assumptions.

323 ▶ **Assumption 14.**  $\beta\mathcal{R}$  is confluent and  $\mathcal{R}$  is arity preserving.

324 Note that if  $\mathcal{R}$  is arity preserving then it is also well-formed, and thus we can in particular  
 325 also use the stratification theorem.

### 326 3.3 Proof of Strong Normalization of $\beta$ in Dedukti

327 We start with the following key lemma, which ensures that convertible types are erased into  
 328 the same simple type by  $\|\cdot\|$ .

329 ▶ **Lemma 15** (Key property).

- 330 1. If  $\|A\|$  is defined, then for all  $N$ ,  $\|A(N/x)\|$  is also defined and  $\|A\| = \|A(N/x)\|$ .
- 331 2. If  $A \hookrightarrow A'$  and  $\|A\|$  is defined, then  $\|A'\|$  is also and  $\|A\| = \|A'\|$ .
- 332 3. If  $A \equiv A'$  and  $\|A\|, \|A'\|$  are well defined, then  $\|A\| = \|A'\|$ .

333 **Proof.** 1. By induction on  $A$ .

334 2. By induction on the rewrite context. For the base case of  $\beta$ , we use part 1. For the base  
 335 case of a rule in  $\mathcal{R}$ , this rule needs to be type-level, of the form  $\alpha[\vec{I}] \hookrightarrow r$ . Note that for  
 336 every substitution  $\sigma$ , we have  $\|\alpha[\vec{I}\{\sigma\}]\| = *$ . Thus, it suffices to show that for every  $\sigma$ ,  
 337  $\|r\{\sigma\}\|$  is defined and equal to  $*$ , which is done by induction on the grammar of Definition  
 338 13.

339 3. Follows from confluence and part 2. ◀

340 With the key property in hand, we can show that the erasure preserves typing.

341 ▶ **Theorem 16** (Preservation of typing). If  $\Sigma; \Gamma \vdash M : A$  and  $A \neq \text{KIND}$ , then there is  $\Sigma' \subseteq \Sigma$   
 342 such that  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda |M| : \|A\|$

343 **Proof.** First note that for all  $x : A \in \Gamma$ , we have  $\Sigma; \Gamma \vdash A : \text{TYPE}$ , thus by syntactic  
 344 stratification  $A$  is a type-family, and thus  $\|\Gamma\|$  is well-defined. We proceed by induction on  
 345 the derivation. The base cases Var and Sort are trivial.

346 **Cons:** We have

$$347 \quad c[\Delta] : A \in \Sigma \quad \frac{\Sigma; \Gamma \text{ well-formed} \quad \Sigma; \Delta \vdash A : s \quad \Sigma; \Gamma \vdash \vec{M} : \Delta}{\Sigma; \Gamma \vdash c[\vec{M}] : A\{\vec{M}\}} \text{Cons}$$

348 We first show that  $\|c[\Delta] : A\|$  is defined. Write  $\Delta = x_1 : A_1, \dots, x_n : A_n$ . First note that  
 349  $\Sigma; \Delta \vdash A : s$  implies that for all  $x_i : A_i \in \Delta$  we have  $A_i : \text{TYPE}$ , hence by stratification each  $A_i$   
 350 is a type family and  $\|\cdot\|$  is defined for all of them. Moreover, by stratification  $A : s$  implies  
 351 that  $A$  is either a type family or kind, hence  $\|A\|$  is defined. Hence,  $\|c[\Delta] : A\| = c : \|A_1\| \rightarrow$   
 352  $\dots \|A_n\| \rightarrow \|A\|$  is well-defined.

<sup>4</sup> More precisely, this definition also depends on the signature  $\Sigma$ , as this is used to define which constants are type-level.

353 We now proceed with the main proof obligation. By IH for  $i = 1, \dots, n$  we have  $\Sigma_i \subseteq \Sigma$   
 354 such that  $\Gamma_\pi, \|\Sigma_i\|, \|\Gamma\| \vdash |M_i| : \|A_i\{M_1/x_1\} \dots \{M_{i-1}/x_{i-1}\}\|$ . Then, by Lemma 15 we have  
 355  $\|A_i\{M_1/x_1\} \dots \{M_{i-1}/x_{i-1}\}\| = \|A_i\|$ . Therefore, by taking

$$356 \quad \Sigma' = c[\Delta] : A \cup \Sigma_1 \cup \dots \cup \Sigma_n$$

357 we can derive  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda c[\vec{M}] : \|A\|$ . Because  $\|A\| = \|A\{\vec{M}\}\|$ , the result follows.

358 **Conv:** We have

$$359 \quad \frac{\Sigma; \Gamma \vdash M : A \quad \Sigma; \Gamma \vdash B : s \quad A \equiv B}{\Sigma; \Gamma \vdash M : B} \text{Conv}$$

360 First note that  $A$  cannot be KIND. Indeed, by confluence we would have  $B \hookrightarrow^* \text{KIND}$ , but  
 361 by syntactic stratification  $B$  is either a kind or a type family. As kinds and type families are  
 362 in particular pre-kinds and pre-type families,  $B$  is one those. But as they are closed under  
 363 rewriting, this would imply that KIND is a pre-kind or a pre-type family, absurd.

364 Therefore, by IH we have  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda |M| : \|A\|$  for some  $\Sigma' \subseteq \Sigma$ . Moreover, by  
 365 syntactic stratification  $A, B$  are kinds or type families, thus  $\|- \|$  is defined for them. By the  
 366 Key Property  $A \equiv B$  implies  $\|A\| = \|B\|$  and thus the result follows.

367 **Prod:** We have

$$368 \quad \frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s}{\Sigma; \Gamma \vdash \Pi x : A. B : s} \text{Prod}$$

369 If  $s = \text{KIND}$  there is nothing to show, thus we consider  $s = \text{TYPE}$ . By IH, for some  $\Sigma', \Sigma'' \subseteq \Sigma$   
 370 we have  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda |A| : *$  and  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\|, x : \|A\| \vdash_\lambda |B| : *$ . We thus get  
 371  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\| \vdash_\lambda \lambda x. |B| : \|A\| \rightarrow *$ , and therefore  $\Gamma_\pi, \|\Sigma' \cup \Sigma''\|, \|\Gamma\| \vdash_\lambda \pi_{\|A\|} |A| (\lambda x. |B|) : *$

372 **Abs:** We have

$$373 \quad \frac{\Sigma; \Gamma \vdash A : \text{TYPE} \quad \Sigma; \Gamma, x : A \vdash B : s \quad \Sigma; \Gamma, x : A \vdash M : B}{\Sigma; \Gamma \vdash \lambda x : A. M : \Pi x : A. B} \text{Abs}$$

374 By IH, for some  $\Sigma', \Sigma'' \subseteq \Sigma$  we have  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda |A| : *$  and  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\|, x : \|A\| \vdash_\lambda$   
 375  $|M| : \|B\|$ , from which we deduce  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\| \vdash_\lambda \lambda x. |M| : \|A\| \rightarrow \|B\|$ . By adding some  
 376 spurious variable  $z$  of type  $*$  to the context and abstracting over it, we get  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\| \vdash_\lambda$   
 377  $\lambda z. \lambda x. |M| : * \rightarrow \|A\| \rightarrow \|B\|$ . Finally, we use application to conclude  $\Gamma_\pi, \|\Sigma' \cup \Sigma''\|, \|\Gamma\| \vdash_\lambda$   
 378  $(\lambda z. \lambda x. |M|)|A| : \|A\| \rightarrow \|B\|$ .

379 **App:** We have

$$380 \quad \frac{\Sigma; \Gamma \vdash M : \Pi x : A. B \quad \Sigma; \Gamma \vdash N : A}{\Sigma; \Gamma \vdash MN : B\{N/x\}} \text{App}$$

381 By IH, for some  $\Sigma', \Sigma'' \subseteq \Sigma$  we deduce  $\Gamma_\pi, \|\Sigma'\|, \|\Gamma\| \vdash_\lambda |M| : \|A\| \rightarrow \|B\|$  and  $\Gamma_\pi, \|\Sigma''\|, \|\Gamma\| \vdash_\lambda$   
 382  $|N| : \|A\|$ . By application, we get  $\Gamma_\pi, \|\Sigma' \cup \Sigma''\|, \|\Gamma\| \vdash_\lambda |N||M| : \|B\|$ , and as  $\|B\| = \|B\{N/x\}\|$   
 383 the result follows.  $\blacktriangleleft$

384 **► Proposition 17** (Preservation of non-termination). *Let  $M$  be an object or type family.*

- 385 1. *If  $N$  is an object, then  $M\{N/x\}$  is an object or type family and  $|M\{N/x\}| = |M|\{|N|/x\}$ .*
- 386 2. *If  $M \hookrightarrow_\beta N$  then  $N$  is an object or type family and  $|M| \hookrightarrow_\beta^+ |N|$ .*

387 **Proof.** 1. By induction on  $M$ , and using Lemma 15 for the case  $M = \Pi x : A. B$ .

388 2. By induction on the rewriting context. For the base case, we have  $M = (\lambda x : A. M_1)M_2 \hookrightarrow$   
 389  $M_1\{M_2/x\}$  and thus  $|M| = (\lambda z. \lambda x. |M_1|)|A||M_2|$ . As  $z$  is not free in  $|M_1|$ , we have  
 390  $|M| = (\lambda z. \lambda x. |M_1|)|A||M_2| \hookrightarrow (\lambda x. |M_1|)|M_2| \hookrightarrow |M_1|\{|M_2|/x\}$ . By part 1,  $|M_1\{M_2/x\}|$   
 391 is well-defined and equal to  $|M_1|\{|M_2|/x\}$ .

392 The induction steps are all similar, we present two of them to show the idea. If  $M = \lambda x : A.M'$  :  
 393  $A.M' \hookrightarrow \lambda x : A'.M' = N$ , where  $A \hookrightarrow A'$ , then by IH we have  $|A| \hookrightarrow^+ |A'|$ , and thus  
 394  $|M| = (\lambda z.\lambda x.|M'|)|A| \hookrightarrow^+ (\lambda z.\lambda x.|M'|)|A'| = |N|$ . If  $M = \Pi x : A.B \hookrightarrow \Pi x : A'.B = N$ ,  
 395 where  $A \hookrightarrow A'$ , then by IH we have  $|A| \hookrightarrow^+ |A'|$ . By the key property, this implies  
 396  $\|A\| = \|A'\|$ , and thus  $|M| = \pi_{\|A\|} |A| (\lambda x.|B|) \hookrightarrow^+ \pi_{\|A'\|} |A'| (\lambda x.|B|)$ . ◀

397 ▶ **Theorem 18** ( $\beta$  is SN in DEDUKTI). *If  $\beta\mathcal{R}$  is confluent and  $\mathcal{R}$  is arity-preserving, then  $\beta$*   
 398 *is strongly normalizing for well-typed terms in DEDUKTI.*

399 **Proof.** Suppose that  $M$  satisfies  $\Sigma; \Gamma \vdash_{\text{DK}} M : A$  and there is an infinite sequence  $M =$   
 400  $M_1 \hookrightarrow_{\beta} M_2 \hookrightarrow_{\beta} M_3 \hookrightarrow_{\beta} \dots$  starting from  $M$ . We now show that for some  $N$ ,  $|N|$  is  
 401 well-typed in the simply-typed  $\lambda$ -calculus and an infinite sequence starts from  $|N|$ .

402 If  $A \neq \text{KIND}$ , then this follows directly from Proposition 16 by taking  $N = M$ . If  $A = \text{KIND}$ ,  
 403 then  $M$  is of the form  $\Pi \vec{x} : \vec{B}.\text{TYPE}$ , and as there are finitely many  $B$ s and they are all type  
 404 families, we conclude that there is a type family  $B_i$  from which an infinite sequence starts.  
 405 We can thus take  $N = B_i$  and apply Proposition 16 to get the result.

406 Now note that as objects and type-families are closed under  $\beta$ , then  $|-|$  is defined for all  
 407 elements in the sequence. Therefore, by taking the image of this infinite sequence under  $|-|$   
 408 we also get an infinite sequence, by Proposition 17. This is a contradiction with the strong  
 409 normalization of  $\beta$  in the simply typed  $\lambda$ -calculus, hence the result follows. ◀

## 410 4 Pure Type Systems

411 Pure type systems (or PTSs) is a class of type systems that generalizes many other systems,  
 412 such as the Calculus of Constructions and System F. They are parameterized by a set of  
 413 sorts  $\mathcal{S}$  and two relations  $\mathcal{A} \subseteq \mathcal{S}^2, \mathcal{R} \subseteq \mathcal{S}^3$ . In this work we restrict ourselves to functional  
 414 PTSs, for which  $\mathcal{A}$  and  $\mathcal{R}$  are functional relations. This restriction covers almost all of PTSs  
 415 used in practice, and gives a much more well behaved metatheory.

416 In this paper we consider a variant of PTSs with explicit parameters. That is, just like  
 417 when taking the projection of a pair  $\pi^1(p)$  we can explicit all parameters and write  $\pi^1(A, B, p)$   
 418 where  $p : A \times B$ , we can also write  $\lambda(A, [x]B, [x]M)$  instead of  $\lambda x : A.M$  and  $\mathcal{O}(A, [x]B, M, N)$   
 419 instead of  $MN$ . Moreover, if  $(-) \times (-)$  is a universe-polymorphic definition, we should also  
 420 write  $\pi_{s_A, s_B}^1(A, B, p)$  to explicit the sort parameters. As in PTSs the dependent product is  
 421 used across multiple sorts, we then should also write  $\lambda_{s_A, s_B}(A, [x]B, [x]M)$ ,  $\mathcal{O}_{s_A, s_B}(A, [x]B, M, N)$   
 422 and  $\Pi_{s_A, s_B}(A, [x]B)$ . To be more technical, we render explicit the parameters on the dependent  
 423 product type and on its constructor (abstraction) and eliminator (application). Because of  
 424 this interpretation in which we are rendering the parameters of  $\lambda$  and  $\mathcal{O}$  explicit, we name  
 425 this version of PTSs as Explicitly-typed Pure Type Systems (EPTSs).

426 Reduction is then defined by the context closure of the  $\beta$  rules<sup>5</sup>

$$427 \quad \mathcal{O}_{s_1, s_2}(A, [x]B, \lambda_{s_1, s_2}(A', [x]B', [x]M), N) \hookrightarrow M\{N/x\}$$

428 given for each  $(s_1, s_2, s_3) \in \mathcal{R}$ . Typing is given by the rules in Figure 2.

429 This modification is just a technical change that will help us during the translation, as  
 430 our encoding needs the data of such parameters often left implicit. Other works such as [20]

<sup>5</sup> We consider a linearized variant of the expected non-left linear rule  $\mathcal{O}_{s_1, s_2}(A, [x]B, \lambda_{s_1, s_2}(A, [x]B, [x]M), N) \hookrightarrow M\{N/x\}$ , which is non-confluent in untyped terms. By linearizing it, we get a much more well-behaved rewriting system, where confluence holds for all terms. Moreover, whenever the left hand side is well-typed, the typing constraints impose  $A \equiv A'$  and  $B \equiv B'$ .

$$\begin{array}{c}
\frac{}{- \text{ well-formed}} \text{ EMPTY} \quad x \notin \Gamma \frac{\Gamma \vdash A : s}{\Gamma, x : A \text{ well-formed}} \text{ DECL} \\
\\
A \equiv B \frac{\Gamma \vdash M : A \quad \Gamma \vdash B : s}{\Gamma \vdash M : B} \text{ CONV} \quad (s_1, s_2) \in \mathcal{A} \frac{\Gamma \text{ well-formed}}{\Gamma \vdash s_1 : s_2} \text{ SORT} \\
\\
x : A \in \Gamma \frac{\Gamma \text{ well-formed}}{\Gamma \vdash x : A} \text{ VAR} \quad (s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2}{\Gamma \vdash \Pi_{s_1, s_2}(A, [x]B) : s_3} \text{ PROD} \\
\\
(s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2 \quad \Gamma, x : A \vdash M : B}{\Gamma \vdash \lambda_{s_1, s_2}(A, [x]B, [x]M) : \Pi_{s_1, s_2}(A, [x]B)} \text{ ABS} \\
\\
(s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2 \quad \Gamma \vdash N : A \quad \Gamma \vdash M : \Pi_{s_1, s_2}(A, [x]B)}{\Gamma \vdash \mathcal{O}_{s_1, s_2}(A, [x]B, M, N) : B\{N/x\}} \text{ APP}
\end{array}$$

■ **Figure 2** Typing rules for Explicitly-typed Pure Type Systems

and [21] also consider similar variants, though none of them correspond exactly to ours. Therefore, we had to develop the basic metatheory of our version in [13], and we have found that the usual meta-theoretical properties of functional PTSs are preserved when moving to the explicitly-typed version. More importantly, by a proof that uses ideas present in [21], we have shown the following equivalence.

Let  $| - |$  be the erasure map defined in the most natural way from an EPTS to its corresponding PTS. Moreover, for a system  $X$  let  $\Lambda(\Gamma \vdash_X - : A)$  be the set of  $M \in \Lambda_X$  with  $\Gamma \vdash_X M : A$ . Finally, let  $\equiv_I$  be defined by  $M \equiv_I N$  iff  $|M| = |N|$  and  $M \equiv N$ .

► **Theorem 19** (Equivalence between PTSs and EPTSs[13]). *Consider a functional PTS. If  $\Gamma \vdash_{PTS} A$  type, then there are  $\Gamma', A'$  with  $|\Gamma'| = \Gamma, |A'| = A$  such that we have a bijection*

$$\Lambda(\Gamma \vdash_{PTS} - : A) \simeq \Lambda(\Gamma' \vdash_{EPTS} - : A') / \equiv_I$$

We note that functional EPTSs satisfy the following basic properties, whose proofs can be found in [13].

► **Proposition 20** (Weakening). *Let  $\Gamma \sqsubseteq \Gamma'$ . We have*

- $\Gamma, x : A \text{ well-formed} \Rightarrow \Gamma', x : A \text{ well-formed}$  when  $x \notin \Gamma'$
- $\Gamma \vdash M : A \Rightarrow \Gamma' \vdash M : A$

► **Proposition 21** (Inversion). *If  $\Gamma \vdash M : C$  then*

- If  $M = x$ , then
  - $\Gamma \text{ well-formed}$  with a smaller derivation tree
  - there is  $x$  with  $x : A \in \Gamma$  and  $C \equiv A$
- If  $M = s$ , then there is  $s'$  with  $(s, s') \in \mathcal{A}$  and  $C \equiv s'$
- If  $M = \Pi_{s_1, s_2}(A, [x]B)$  then
  - $\Gamma \vdash A : s_1$  with a smaller derivation tree
  - $\Gamma, x : A \vdash B : s_2$  with a smaller derivation tree
  - there is  $s_3$  with  $(s_1, s_2, s_3) \in \mathcal{R}$  and  $C \equiv s_3$
- If  $M = \lambda_{s_1, s_2}(A, [x]B, [x]N)$  then
  - $\Gamma \vdash A : s_1$  with a smaller derivation tree
  - $\Gamma, x : A \vdash B : s_2$  with a smaller derivation tree
  - there is  $s_3$  with  $(s_1, s_2, s_3) \in \mathcal{R}$
  - $\Gamma, x : A \vdash N : B$  with a smaller derivation tree

- 461     $C \equiv \Pi_{s_1, s_2} (A, [x]B)$
- 462     $\dashv$  If  $M = \mathcal{O}_{s_1, s_2} (A, [x]B, N_1, N_2)$  then
- 463        $\Gamma \vdash A : s_1$  with a smaller derivation tree
- 464        $\Gamma, x : A \vdash B : s_2$  with a smaller derivation tree
- 465       there is  $s_3$  with  $(s_1, s_2, s_3) \in \mathcal{R}$
- 466        $\Gamma \vdash N_1 : A$  with a smaller derivation tree
- 467        $\Gamma \vdash N_2 : \Pi_{s_1, s_2} (A, [x]B)$  with a smaller derivation tree
- 468        $C \equiv B(N_2/x)$
  
- 469     $\triangleright$  **Proposition 22** (Conv in context). *Let  $A \equiv A'$  and  $\Gamma \vdash A' : s$ . We have*
- 470        $\Gamma, x : A, \Gamma'$  well-formed  $\Rightarrow \Gamma, x : A', \Gamma'$  well-formed
- 471        $\Gamma, x : A, \Gamma' \vdash M : B \Rightarrow \Gamma, x : A', \Gamma' \vdash M : B$
  
- 472     $\triangleright$  **Proposition 23** (Substitution in judgment). *Let  $\Gamma \vdash N : A$ . We have*
- 473        $\Gamma, x : A, \Gamma'$  well-formed  $\Rightarrow \Gamma, \Gamma'(N/x)$  well-formed
- 474        $\Gamma, x : A, \Gamma' \vdash M : B \Rightarrow \Gamma, \Gamma'(N/x) \vdash M(N/x) : B(N/x)$
  
- 475     $\triangleright$  **Proposition 24** (Uniqueness of types). *If  $\Gamma \vdash M : A$  and  $\Gamma \vdash M : B$  we have  $A \equiv B$ .*
- 476     $\triangleright$  **Corollary 25** (Uniqueness of sorts). *If  $\Gamma \vdash M : s$  and  $\Gamma \vdash M : s'$  we have  $s = s'$ .*

## 5 Encoding EPTSs in Dedukti

This section presents our encoding of functional EPTSs in DEDUKTI. In order to ease the notation, from now on we write  $c \vec{M}$  for  $c[\vec{M}]$ . The basis for the encoding is given by a theory  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$  which we will construct step by step here.

Pure Type Systems (explicitly-typed or not) feature two kinds of types: dependent products and universes. We start by building the representation of the latter. For each  $s \in \mathcal{S}$  we declare a type  $U_s$  to represent the type of elements of  $s$ . However, as the terms  $A$  with  $\Gamma \vdash_{\text{EPTS}} A : s$  are themselves types, we also need to declare a function  $El_{s_1}$  which maps each such  $A$  to its corresponding type. As for each  $(s_1, s_2) \in \mathcal{A}$  we have  $\vdash_{\text{EPTS}} s_1 : s_2$ , we also declare a constant  $u_{s_1}$  in  $U_{s_2}$  to represent this. Finally, as the sorts  $s_1$  with  $(s_1, s_2) \in \mathcal{A}$  now can be represented by both  $U_{s_1}$  and  $El_{s_2} u_{s_1}$ , we add a rewrite rule to identify these representations. This encoding resembles the definition of universes in type theories *à la* Tarski, and also follows traditional representations of universes in DEDUKTI as in [9].

$$\left| \begin{array}{l} U_s : \text{TYPE} \\ El_s[A : U_s] : \text{TYPE} \end{array} \right| \quad \text{for } s \in \mathcal{S} \quad \left| \begin{array}{l} u_{s_1} : U_{s_2} \\ El_{s_2} u_{s_1} \hookrightarrow_{u_{s_1}\text{-red}} U_{s_1} \end{array} \right| \quad \text{for } (s_1, s_2) \in \mathcal{A}$$

We now move to the representation of the dependent product type. We first declare a constant to represent the type formation rule for the dependent product.

$$\left| \text{Prod}_{s_1, s_2}[A : U_{s_1}; B : El_{s_1} A \rightarrow U_{s_2}] : U_{s_3} \right| \quad \text{for } (s_1, s_2, s_3) \in \mathcal{R}$$

Traditional DEDUKTI encodings would normally continue here by introducing the rule  $El_{s_3} (\text{Prod}_{s_1, s_2} A B) \hookrightarrow \Pi x : El_{s_1} A. El_{s_2} (B x)$ , identifying the dependent product of the encoded theory with the one of DEDUKTI, thus allowing for the use of the framework's abstraction, application and  $\beta$  to represent the ones of the encoded system. We instead keep them separate and declare constants representing the introduction and elimination rules for the dependent product being encoding, that is, representing abstraction and application.

$$\begin{array}{l}
\text{500} \quad \left| \begin{array}{l}
\text{abs}_{s_1, s_2} [A : U_{s_1}; B : El_{s_1} A \rightarrow U_{s_2}; M : \Pi x : El_{s_1} A. El_{s_2} (B \ x)] : El_{s_3} (Prod_{s_1, s_2} A B) \\
\text{app}_{s_1, s_2} [A : U_{s_1}; B : El_{s_1} A \rightarrow U_{s_2}; M : El_{s_3} (Prod_{s_1, s_2} A B); N : El_{s_1} A] : El_{s_2} (B \ N) \\
\text{app}_{s_1, s_2} A B (\text{abs}_{s_1, s_2} A' B' M) N \hookrightarrow_{\text{beta}_{s_1, s_2}} M N \quad \text{for } (s_1, s_2, s_3) \in \mathcal{R}
\end{array} \right|
\end{array}$$

501 We note that this idea is also hinted in [1], though they did not pursue it further.  
502 This approach also reassembles the one of the Edinburgh Logical Framework (ELF) [17] in  
503 which the framework's abstraction is used exclusively for binding. We are however able to  
504 encode computation directly as computation with the rule  $\text{beta}_{s_1, s_2}$ , whereas the ELF handles  
505 computation by encoding it as an equality judgment, thus introducing explicit coercions in  
506 the terms. Some other variants such as [16] prevent the introduction of such coercions, but  
507 computation is still represented by an equality judgment instead of being represented by  
508 computation.

509 We are now ready to define the translation function  $\llbracket - \rrbracket$ .

$$\begin{array}{l}
\text{510} \quad \llbracket x \rrbracket = x \\
\text{511} \quad \llbracket s \rrbracket = u_s \\
\text{512} \quad \llbracket \Pi_{s_1, s_2} (A, [x]B) \rrbracket = \text{Prod}_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \\
\text{513} \quad \llbracket \lambda_{s_1, s_2} (A, [x]B, [x]M) \rrbracket = \text{abs}_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket M \rrbracket) \\
\text{514} \quad \llbracket @_{s_1, s_2} (A, [x]B, M, N) \rrbracket = \text{app}_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \llbracket M \rrbracket \llbracket N \rrbracket
\end{array}$$

516 We also extend  $\llbracket - \rrbracket$  to well-formed contexts by the following definition. Note that because  
517 we are dealing with functional EPTSs, the sort of  $A$  in  $\Gamma$  is unique, hence the following  
518 definition makes sense.

$$\begin{array}{l}
\text{519} \quad \llbracket - \rrbracket = - \\
\text{520} \quad \llbracket \Gamma, x : A \rrbracket = \llbracket \Gamma \rrbracket, x : El_{s_A} \llbracket A \rrbracket \quad \text{where } \Gamma \vdash A : s_A
\end{array}$$

522 ▶ **Remark 26.** Note that in the definitions of  $\llbracket - \rrbracket$  it was essential for  $\lambda$  and  $@$  to explicit the  
523 types  $A$  and  $B$ , as the constants  $\text{abs}_{s_1, s_2}$  and  $\text{app}_{s_1, s_2}$  require their translations. Had we had  
524 for instance just  $\lambda x : A. M$ , we could then make the translation dependent on  $\Gamma$  and take a  
525  $B$  such that  $\Gamma, x : A \vdash M : B$ . However, because  $\llbracket - \rrbracket$  is defined by induction and  $B$  is not  
526 a subterm of  $\lambda x : A. M$ , we cannot apply  $\llbracket - \rrbracket$  to  $B$ . Therefore, when doing an encoding in  
527 DEDUKTI one should first render explicit the needed data before translating, and then show  
528 an equivalence theorem between the explicit and implicit versions (in our case, Theorem 19).

529 Moreover, note that by also making the sorts explicit in  $\lambda_{s_1, s_2}, @_{s_1, s_2}, \Pi_{s_1, s_2}$  our translation  
530 can be defined purely syntactically. If this information were not in the syntax, we could still  
531 define  $\llbracket - \rrbracket$  by making it dependent on  $\Gamma$ . Nevertheless, this complicates many proofs, as each  
532 time we apply  $\llbracket - \rrbracket_\Gamma$  to a term we need to know it is well-typed in  $\Gamma$ .

533 In order to understand more intuitively how the encoding works, let's look at an example.

534 ▶ **Example 27.** Recall that System F can be defined by the sort specification  $\mathcal{S} = \{\text{Type}, \text{Kind}\}$ ,  $\mathcal{A} =$   
535  $\{\text{Type} : \text{Kind}\}$ ,  $\mathcal{R} = \{(\text{Type}, \text{Type}, \text{Type}), (\text{Kind}, \text{Type}, \text{Type})\}$ . In this EPTS, we can express  
536 the polymorphic identity function, traditionally written as  $\lambda A : \text{Type}. \lambda x : A. x$ , by

$$\text{537} \quad \lambda_{\text{Kind}, \text{Type}} (\text{Type}, [A] \Pi (A, [x] A), [A] \lambda_{\text{Type}, \text{Type}} (A, [x] A, [x] x))$$

538 This term is represented in our encoding by

$$\text{539} \quad \text{abs}_{\text{Kind}, \text{Type}, u_{\text{Type}}} (\lambda A. \text{Prod}_{\text{Type}, \text{Type}} A (\lambda x. A)) (\lambda A. \text{abs}_{\text{Type}, \text{Type}} A (\lambda x. A) (\lambda x. x))$$

540 where we omit the type annotations in the abstractions, to improve readability.

## 6 Soundness

An encoding is said to be sound when it preserves the typing relation of the original system. In this section we will see that our encoding has this fundamental property. We start by establishing some conventions in order to ease notations.

► **Convention 28.** *We establish the following notations.*

- We write  $\Sigma; \Gamma \vdash_{\text{DK}} M : A$  for a DEDUKTI judgment and  $\Gamma \vdash M : A$  (not  $\vdash_{\text{EPTS}}$ ) for an EPTS judgment
- As the same signature  $\Sigma_{\text{EPTS}}$  is used everywhere, when writing  $\Sigma_{\text{EPTS}}; \Gamma \vdash_{\text{DK}} M : A$  we omit it and write  $\Gamma \vdash_{\text{DK}} M : A$ .

Before showing soundness, we start by establishing some basic results.

► **Proposition 29** (Basic properties). *We have the following basic properties.*

1. *Confluence:* The rewriting rules of the encoding are confluent with  $\beta$ .
2. *Well-formedness of the signature:* For all  $c[\Delta] : A \in \Sigma_{\text{EPTS}}$ , we have  $\Delta \vdash_{\text{DK}} A : s$ .
3. *Subject reduction for  $\beta$ :* If  $\Gamma \vdash_{\text{DK}} M : A$  and  $M \hookrightarrow_{\beta} M'$  then  $\Gamma \vdash_{\text{DK}} M' : A$ .
4. *Strong normalization for  $\beta$ :* If  $\Gamma \vdash_{\text{DK}} M : A$ , the  $\beta$  is strongly normalizing for  $M$ .
5. *Compositionality:* For all  $M, N \in \Lambda_{\text{EPTS}}$  we have  $\llbracket M \rrbracket \{ \llbracket N \rrbracket / x \} = \llbracket M \{ N / x \} \rrbracket$ .

**Proof.** 1. The considered rewrite rules form an orthogonal combinatory reduction system, and therefore are confluent[19].

2. Can be shown for instance with LAMBDAP1[10], an implementation of DEDUKTI.

3. Subject reduction of  $\beta$  is implied by confluence of  $\beta_{\mathcal{R}_{\text{EPTS}}}$ [6].

4.  $\mathcal{R}_{\text{EPTS}}$  is arity preserving and  $\beta_{\mathcal{R}_{\text{EPTS}}}$  is confluent, thus  $\beta$  is SN in DEDUKTI (Theorem 18) applies.

5. By induction on  $M$ . ◀

► **Remark 30.** We could also show subject reduction of our encoding, either using the method in [7] or LAMBDAP1[10]. However, we will see that our proof does not actually require subject reduction of  $\mathcal{R}_{\text{EPTS}}$ . Therefore, we conjecture that our proof method can also be adapted to systems that do not satisfy subject reduction.

► **Lemma 31** (Preservation of computation). *Let  $M, N \in \Lambda_{\text{EPTS}}$ . We have*

1.  $M \hookrightarrow N$  implies  $\llbracket M \rrbracket \hookrightarrow^* \llbracket N \rrbracket$
2.  $M \equiv N$  implies  $\llbracket M \rrbracket \equiv \llbracket N \rrbracket$

**Proof.** The first part is shown by induction on the rewriting context, using compositionality of  $\llbracket - \rrbracket$  for the base case. The second part follows by induction on  $\equiv$  and uses part 1. ◀

Recall that a sort  $s \in \mathcal{S}$  is said to be a top-sort if there is no  $s'$  with  $(s, s') \in \mathcal{A}$ . The following auxiliary lemma allows us to switch between sort representations and is heavily used in the proof of soundness.

► **Lemma 32** (Equivalence for sort representations). *If  $s$  is not a top-sort, then*

$$\Gamma \vdash_{\text{DK}} M : U_s \iff \Gamma \vdash_{\text{DK}} M : El_{s'} u_s$$

where  $(s, s') \in \mathcal{A}$ .

With all these results in hand, we can now show the soundness of our encoding.

► **Theorem 33** (Soundness). *Let  $\Gamma$  be a context and  $M, A$  terms in an EPTS. We have*



## 23:16 Adequate and computational encodings in the logical framework Dedukti

- 581 ■ If  $\Gamma$  well-formed then  $\llbracket \Gamma \rrbracket$  well-formed
- 582 ■ If  $\Gamma \vdash M : A$  then
  - 583 ■ if  $A$  is a top-sort then  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket M \rrbracket : U_A$
  - 584 ■ else  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket M \rrbracket : El_{s_A} \llbracket A \rrbracket$ , where  $\Gamma \vdash A : s_A$

585 **Proof.** By structural induction on the proof of the judgment. Easy for the cases EMPTY  
586 and VAR.

587 **Case Decl:** The proof ends with

$$588 \quad x \notin A \frac{\Gamma \vdash A : s}{\Gamma \vdash x : A} \text{DECL}$$

589 From the IH we can derive  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} El_s \llbracket A \rrbracket : \text{TYPE}$ , therefore we can apply Decl to get  
590  $\llbracket \Gamma \rrbracket, x : El_s \llbracket A \rrbracket$  well-formed.

591 **Case Sort:** The proof ends with

$$592 \quad (s_1, s_2) \in \mathcal{A} \frac{\Gamma \text{ well-formed}}{\Gamma \vdash s_1 : s_2} \text{SORT}$$

593 By IH we have  $\llbracket \Gamma \rrbracket$  well-formed, therefore we can show  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} u_{s_1} : U_{s_2}$  using Cons. If  
594  $s_2$  is not a top-sort, we use Lemma 32 to show  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} u_{s_1} : El_{s_3} u_{s_2}$ , where  $(s_2, s_3) \in \mathcal{A}$ .

595 **Case Prod:** The proof ends with

$$596 \quad (s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2}{\Gamma \vdash \Pi_{s_1, s_2}(A, [x]B) : s_3} \text{PROD}$$

597 By the IH and Lemma 32, we have  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket A \rrbracket : U_{s_1}$  and  $\llbracket \Gamma \rrbracket, x : El_{s_1} \llbracket A \rrbracket \vdash_{\text{DK}} \llbracket B \rrbracket : U_{s_2}$ .  
598 By Abs we get  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket : El_{s_1} \llbracket A \rrbracket \rightarrow U_{s_2}$ , therefore it suffices to apply Cons  
599 with  $Prod_{s_1, s_2}$  to conclude

$$600 \quad \llbracket \Gamma \rrbracket \vdash_{\text{DK}} Prod_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) : U_{s_3}$$

601 If  $s_3$  is not a top-sort, we then apply Lemma 32.

602 **Case App:** The proof ends with

$$603 \quad (s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2 \quad \Gamma \vdash M : \Pi_{s_1, s_2}(A, [x]B) \quad \Gamma \vdash N : A}{\Gamma \vdash \mathcal{O}_{s_1, s_2}(A, [x]B, M, N) : B(N/x)} \text{APP}$$

604 By the IH and Lemma 32, we have  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket A \rrbracket : U_{s_1}$ ,  $\llbracket \Gamma \rrbracket, x : El_{s_1} \llbracket A \rrbracket \vdash_{\text{DK}} \llbracket B \rrbracket : U_{s_2}$ ,  
605  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket M \rrbracket : El_{s_3} (Prod_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket))$  and  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket N \rrbracket : El_{s_1} \llbracket A \rrbracket$ . By Abs we  
606 get  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket : El_{s_1} \llbracket A \rrbracket \rightarrow U_{s_2}$ , therefore we can apply Cons with  $app_{s_1, s_2}$  to  
607 get

$$608 \quad \llbracket \Gamma \rrbracket \vdash_{\text{DK}} app_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \llbracket M \rrbracket \llbracket N \rrbracket : El_{s_2} ((\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \llbracket N \rrbracket)$$

609 Therefore, from *Reduce type in judgement* (Proposition 3) with  $(\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \llbracket N \rrbracket \hookrightarrow$   
610  $\llbracket B \rrbracket \{ \llbracket N \rrbracket / x \}$  and compositionality of  $\llbracket - \rrbracket$  we get

$$611 \quad \llbracket \Gamma \rrbracket \vdash_{\text{DK}} app_{s_1, s_2} \llbracket A \rrbracket (\lambda x : El_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) \llbracket M \rrbracket \llbracket N \rrbracket : El_{s_2} \llbracket B \{ N/x \} \rrbracket.$$

612 Finally, note that  $\Gamma \vdash N : A$  and  $\Gamma, x : A \vdash B : s_2$  imply  $\Gamma \vdash B\{N/x\} : s_2$ , thus  $B\{N/x\}$  is not  
613 a top-sort.

614 **Case Conv:** The derivation ends with

$$615 \quad A \equiv B \frac{\Gamma \vdash M : B \quad \Gamma \vdash A : s}{\Gamma \vdash M : A} \text{CONV}$$



First note that by confluence and subject reduction of rewriting in the EPTS,  $\Gamma \vdash B : s$ , thus  $B$  is not a top sort. Therefore, by the IH we have  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket M \rrbracket : \textcolor{blue}{El}_s \llbracket B \rrbracket$ . By the IH applied to  $\Gamma \vdash A : s$  we can show  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \textcolor{blue}{El}_s \llbracket A \rrbracket : \text{TYPE}$ , and by *Preservation of computation* (Lemma 31) applied to  $A \equiv B$  we get  $\llbracket A \rrbracket \equiv \llbracket B \rrbracket$ . Therefore, it suffices to apply *Conv* to conclude  $\llbracket \Gamma \rrbracket \vdash \llbracket M \rrbracket : \textcolor{blue}{El}_s \llbracket A \rrbracket$ .

**Case Abs:** The derivation ends with

$$(s_1, s_2, s_3) \in \mathcal{R} \frac{\Gamma \vdash A : s_1 \quad \Gamma, x : A \vdash B : s_2 \quad \Gamma, x : A \vdash N : B}{\Gamma \vdash \lambda_{s_1, s_2} (A, [x]B, [x]N) : \Pi_{s_1, s_2} (A, [x]B)} \text{ABS}$$

By the IH and Lemma 32, we have  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \llbracket A \rrbracket : \textcolor{blue}{U}_{s_1}$ ,  $\llbracket \Gamma \rrbracket, x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket \vdash_{\text{DK}} \llbracket B \rrbracket : \textcolor{blue}{U}_{s_2}$  and  $\llbracket \Gamma \rrbracket, x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket \vdash_{\text{DK}} \llbracket N \rrbracket : \textcolor{blue}{El}_{s_2} \llbracket B \rrbracket$ . By *Abs* we get  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket \rightarrow \textcolor{blue}{U}_{s_2}$  and  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket N \rrbracket : \Pi x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \textcolor{blue}{El}_{s_2} \llbracket B \rrbracket$ .

Using inversion of typing, it is not difficult to show that

$$\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \Pi x : \textcolor{blue}{El}_{s_1} A. \textcolor{blue}{El}_{s_2} ((\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) x) : \text{TYPE}.$$

Hence, because  $\Pi x : \textcolor{blue}{El}_{s_1} A. \textcolor{blue}{El}_{s_2} ((\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) x) \equiv \Pi x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \textcolor{blue}{El}_{s_2} \llbracket B \rrbracket$ , by *Conv* we can get

$$\llbracket \Gamma \rrbracket \vdash_{\text{DK}} \lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket N \rrbracket : \Pi x : \textcolor{blue}{El}_{s_1} A. \textcolor{blue}{El}_{s_2} ((\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket) x).$$

Therefore, we can apply *Conv* to conclude

$$\begin{aligned} \llbracket \Gamma \rrbracket \vdash_{\text{DK}} \textcolor{blue}{abs}_{s_1, s_2} \llbracket A \rrbracket (\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket_{\Gamma, x:A}) (\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket N \rrbracket) \\ : \textcolor{blue}{El}_{s_3} (\textcolor{blue}{Prod}_{s_1, s_2} \llbracket A \rrbracket (\lambda x : \textcolor{blue}{El}_{s_1} \llbracket A \rrbracket. \llbracket B \rrbracket)) \end{aligned}$$

## 7 Conservativity and Adequacy

Many works proposing DEDUKTI encodings often stop after showing soundness and leave conservativity as a conjecture. This is because, when mixing the rules  $\beta$  with *beta*, as done in traditional DEDUKTI encodings, one needs to show the termination of both, given that to show conservativity one often considers terms in normal form [9]. However this problem is non-trivial, and in particular the normalization of  $\beta \cup \textcolor{blue}{beta}$  implies the termination (and thus normally also the consistency) of the encoded system. This is also unnatural, as logical frameworks should be agnostic to the fact that a system is consistent or not, and thus this shouldn't be required to show conservativity.

In this section we will show how conservativity can be shown without difficulties when we distinguish the rules  $\beta$  and *beta*. In particular, our proof does not need  $\beta \cup \textcolor{blue}{beta}$  to be normalizing, and thus also applies to non-normalizing and non-consistent systems.

We start by defining a notion of invertible forms and an inverse translation which allows to invert them into the original system. After proving some basic properties about them, we then proceed with the proof of conservativity.

### 7.1 The inverse translation

► **Definition 34** (Invertible forms). *We call the terms generated by the following grammar the invertible forms. The  $s_i$  are any sorts in  $\mathcal{S}$ , whereas the  $T_1, T_2$  are any terms.*

$$\begin{aligned} M, N, A, B ::= x \mid c \mid u_s \mid \textcolor{blue}{abs}_{s_1, s_2} A (\lambda x : T_1. B) (\lambda x : T_2. M) \mid (\lambda x : T. M) N \\ \mid \textcolor{blue}{Prod}_{s_1, s_2} A (\lambda x : T_1. B) \mid \textcolor{blue}{app}_{s_1, s_2} A (\lambda x : T_1. B) M N \end{aligned}$$

Note that this definition includes some terms which are not in  $\beta$  normal form. The next definition justifies the name of invertible forms: we know how to invert them.

► **Definition 35.** We define the inverse translation function  $|-| : \Lambda_{\text{DK}} \rightarrow \Lambda_{\text{EPTS}}$  on invertible forms by structural induction.

$$\begin{array}{ll}
 |x| = x & |(\lambda x : \_ . M) N| = |M|\{|N|/x\} \\
 |c| = c & |\text{Prod}_{s_1, s_2} A (\lambda x : \_ . B)| = \Pi_{s_1, s_2} (|A|, [x]|B|) \\
 |u_s| = s & |\text{abs}_{s_1, s_2} A (\lambda x : \_ . B) (\lambda x : \_ . M)| = \lambda_{s_1, s_2} (|A|, [x]|B|, [x]|M|) \\
 & |\text{app}_{s_1, s_2} A (\lambda x : \_ . B) M N| = \mathcal{O}_{s_1, s_2} (|A|, [x]|B|, |M|, |N|)
 \end{array}$$

We can show, as expected, that the terms in the image of the translation are invertible forms and that  $|-|$  is a left inverse of  $\llbracket - \rrbracket$ . The proof is a simple induction on  $M$ .

► **Proposition 36.** For all  $M \in \Lambda_{\text{EPTS}}$ ,  $\llbracket M \rrbracket$  is an invertible form and  $\llbracket \llbracket M \rrbracket \rrbracket = M$ .

The following lemma shows that invertible forms are closed under rewriting and that this rewriting can also be inverted into the EPTS.

► **Proposition 37.** Let  $M$  be a invertible form.

1. If  $N$  is an invertible form, then  $M(N/x)$  is also and  $|M|\{|N|/x\} = |M\{N/x\}|$ .
2. If  $M \hookrightarrow_{\text{beta}_{s_1, s_2}} N$  then  $N$  is an invertible form and  $|M| \hookrightarrow_{\beta}^* |N|$ .
3. If  $M \hookrightarrow_{\beta, u_{s_1}\text{-red}} N$  then  $N$  is an invertible form and  $|M| = |N|$ .
4. If  $M \hookrightarrow^* N$  then  $N$  is an invertible form and  $|M| \hookrightarrow^* |N|$ .

**Proof.** 1. By induction on  $M$ .

2. By induction on the rewrite context. For the base case, we have

$$|\text{app}_{s_1, s_2} A_1 (\lambda x : T_1.B_1) (\text{abs}_{s_1, s_2} A_2 (\lambda x : T_2.B_2) (\lambda x : T_3.M')) N'| \hookrightarrow (\lambda x : T_3.M') N'$$

whose right hand side is in the grammar. Moreover, we have

$$\mathcal{O}_{s_1, s_2} (|A_1|, [x]|B_1|, \lambda_{s_1, s_2} (|A_2|, [x]|B_2|, [x]|M'|), |N'|) \hookrightarrow |M'|\{|N'|/x\} = |(\lambda x : T_3.M') N'|$$

and thus the reduction is reflected by the inverse translation.

3. By induction on the rewrite context. Note that there is no base case for  $u_{s_1}$ -red, as there is no term of the form  $\text{El}_{s_2} u_{s_1}$  in the grammar. For the base case of  $\beta$ , we have  $(\lambda x : T.M') N' \hookrightarrow M'\{N'/x\}$ . Hence the resulting term is in the grammar and we have  $|(\lambda x : T.M') N'| = |M'\{N'/x\}| = |M'\{N'/x\}|$  by part 1.

4. Immediate consequence of the previous parts. ◀

► **Remark 38.** Note that this last proposition explains the difference between the  $\beta$  and  $\text{beta}_{s_1, s_2}$  steps. Whereas  $\text{beta}_{s_1, s_2}$  steps represents the real computation steps that take place in the encoded system,  $\beta$  steps are invisible because they correspond to the framework's substitution, an administrative operation that is implicit in the encoded system. Therefore, it was expected that  $\text{beta}_{s_1, s_2}$  steps would be reflected into the original system, whereas  $\beta$  steps would be silent.

Putting all this together, we deduce that computation and conversion in DEDUKTI is reflected in the encoded system.

► **Corollary 39** (Reflection of computation). For  $M, N \in \Lambda_{\text{EPTS}}$ , we have

1. If  $\llbracket M \rrbracket \hookrightarrow^* \llbracket N \rrbracket$  then  $M \hookrightarrow^* N$ .

692 2. If  $\llbracket M \rrbracket \equiv \llbracket N \rrbracket$  then  $M \equiv N$ .

693 **Proof.** 1. Immediate consequence of Proposition 37 and Proposition 36.

694 2. Follows from confluence of  $\beta\mathcal{R}_{\text{EPTS}}$  and also Proposition 37 and Proposition 36.  $\blacktriangleleft$

695 Note that for part 2 we really need  $\beta\mathcal{R}_{\text{EPTS}}$  to be confluent. Indeed, If  $\llbracket M \rrbracket \longleftrightarrow N$  then  
 696 we cannot apply  $|-|$  to  $N$  because it might not be an invertible form.

## 697 7.2 Conservativity

698 Before showing conservativity, we show the following auxiliary result, saying that every  $\beta$   
 699 normal term  $M$  that has type  $\Pi x : A.B$  in  $\llbracket \Gamma \rrbracket$  is an abstraction.

700 **► Lemma 40.** *Let  $M$  be in  $\beta$ -normal form. If  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} M : \Pi x : A.B$  then  $M = \lambda x : A'.N$  with  
 701  $A' \equiv A$  and  $\llbracket \Gamma \rrbracket, x : A \vdash_{\text{DK}} N : B$ .*

702 **Proof.** By induction on  $M$ .  $M$  cannot neither be a variable or constant, as there is no  
 703  $x : C \in \llbracket \Gamma \rrbracket$  or  $c[\Delta] : C \in \Sigma_{\text{EPTS}}$  with  $C \equiv \Pi x : A.B$ . If  $M = M_1 M_2$ , then  $M_1$  has a type of the  
 704 form  $\Pi x' : A'.B'$ . By IH we get that  $M_1$  is an abstraction, which contradicts the fact that  $M$   
 705 is in  $\beta$  normal form.

706 Therefore,  $M$  is an abstraction, of the form  $M = \lambda x : A'.N$ . By inversion of typing, we  
 707 thus have  $\llbracket \Gamma \rrbracket, x : A' \vdash_{\text{DK}} N : B'$  with  $A' \equiv A$  and  $B' \equiv B$ . We can then use *Conv in context*  
 708 *for DK* (Theorem 2) and *Conv* to derive  $\llbracket \Gamma \rrbracket, x : A \vdash_{\text{DK}} N : B$ .  $\blacktriangleleft$

709 We are now ready to show conservativity for  $\beta$  normal forms. However, if we also want to  
 710 show adequacy latter, we also need to show that  $|-|$  is a kind of right inverse to  $\llbracket - \rrbracket$ . However,  
 711 because the inverse translation does not capture the information in the type annotations of  
 712 binders,  $\llbracket \llbracket M \rrbracket \rrbracket = M$  does not hold.

713 **► Example 41.** Take any invertible forms  $A, B$  and a term  $T$  with  $T \neq \text{El}_{s_1} A$ . Then the term  
 714  $M = \text{Prod}_{s_1, s_2} A (\lambda x : T.B)$  is sent by  $|-|$  into  $\Pi_{s_1, s_2} (|A|, [x]|B|)$ , which is then sent by  $\llbracket - \rrbracket$   
 715 into  $\text{Prod}_{s_1, s_2} \llbracket |A| \rrbracket (\lambda x : \text{El}_{s_1} \llbracket |A| \rrbracket. \llbracket |B| \rrbracket)$ . Therefore, even if have  $\llbracket |B| \rrbracket = B$  and  $\llbracket |A| \rrbracket = A$ ,  
 716 we still have  $T \neq \text{El}_{s_1} A$ , implying  $M \neq \llbracket \llbracket M \rrbracket \rrbracket$ . However, if  $M$  is typable, then by typing  
 717 constraints we should nevertheless have  $T \equiv \text{El}_{s_1} A$ .

718 Therefore, while proving conservativity we will show a weaker property: for the well-typed  
 719 terms we are interested in,  $|-|$  is a right inverse up to the following “hidden” conversion.

720 **► Definition 42** (Hidden step). *We say that a rewriting step  $M \longleftrightarrow N$  is hidden when it*  
 721 *happens on the type annotation of a binder. More formally, we should have a rewriting*  
 722 *context  $C(-)$  and terms  $A, A', P$  such that  $A \longleftrightarrow A'$ ,  $M = C(\lambda x : A.P)$  and  $N = C(\lambda x : A'.P)$ .*  
 723 *We denote the conversion generated by such rules by  $\equiv_H$ .*

724 We now have all ingredients to show that the encoding is conservative for  $\beta$  normal forms.

725 **► Theorem 43** (Conservativity of  $\beta$  normal forms). *Suppose  $\Gamma \vdash A$  type and let  $M \in \Lambda_{\text{DK}}$  be a*  
 726  *$\beta$  normal form st  $\llbracket \Gamma \rrbracket \vdash_{\text{DK}} M : T$ , with  $T = \text{El}_{s_A} \llbracket A \rrbracket$  or  $T = U_A$ . Then  $M$  is an invertible*  
 727 *form,  $\Gamma \vdash |M| : A$  and  $\llbracket \llbracket M \rrbracket \rrbracket \equiv_H M$ .*

728 **Proof.** By induction on  $M$ .

729 **Case**  $M = \lambda x : A'.M'$  : By inversion we have  $M : \Pi x : A'_1.A'_2$  with  $T \equiv \Pi x : A'_1.A'_2$ .  
 730 Because  $\mathcal{R}_{\text{EPTS}}$  is arity preserving, this implies that  $T$  is of the form  $\Pi x : A_1.A_2$ , which  
 731 cannot hold. Thus, this case is impossible.

732 **Case**  $M = M_1 M_2$  : As  $M$  is in beta normal form, its head symbol is a constant or  
 733 variable. However, there is no  $c[\Delta] : C \in \Sigma$  or  $x : C \in \Gamma$  with  $C$  convertible to a dependent  
 734 product type. Hence, this case is impossible.

735 **Case**  $M = x$  : If  $M = x$ , by inversion of typing there is  $x : El_{s_B} [B] \in [\Gamma]$  with  
 736  $T \equiv El_{s_B} [B]$ . Therefore, we deduce  $A \equiv B$  and thus we can derive  $\Gamma \vdash x : A$  by applying  
 737 VAR with  $x : B \in \Gamma$ , then CONV with  $A \equiv B$  and  $\Gamma \vdash A$  type.

738 **Case**  $M = c[\vec{M}]$  : We proceed by case analysis on  $c$ . Note that for  $c = El_s M'$  or  $c = U_s$   
 739 the resulting type is TYPE, which is not convertible to  $T$ . Hence, these cases are impossible.

740 ▶ **Note 44.** In the following, to improve readability we omit the typing hypothesis when  
 741 applying CONV. However, all such uses can be justified.

742 **Case**  $c = u_{s_1}$  : As we have  $[\Gamma] \vdash_{DK} u_{s_1} : U_{s_2}$ , by uniqueness of types we have  $T \equiv U_{s_2}$ , and  
 743 therefore we get  $A \equiv s_2$ . We can thus deduce  $\Gamma \vdash s_1 : A$  by using CONV with  $\Gamma \vdash s_1 : s_2$ .

744 **Case**  $c = Prod_{s_1, s_2}$  : By inversion of typing, we have

- 745 1.  $\vec{M} = M_1 M_2$
- 746 2.  $[\Gamma] \vdash_{DK} M_1 : U_{s_1}$
- 747 3.  $[\Gamma] \vdash_{DK} M_2 : El_{s_1} M_1 \rightarrow U_{s_2}$
- 748 4.  $T \equiv U_{s_3}$

749 As  $M_1$  is in  $\beta$  normal form, by IH  $M_1$  is an invertible form,  $\Gamma \vdash |M_1| : s_1$  and  $[[M_1]] \equiv_H M_1$ .

750 By Lemma 40 applied to 2, we get  $M_2 = \lambda x : B.N$  and  $B \equiv El_{s_1} M_2$  with  $[\Gamma], x : El_{s_1} M_1 \vdash$   
 751  $N : U_{s_2}$ . Because  $M_1 \equiv [[M_1]]$ , we have  $[\Gamma], x : El_{s_1} [[M_1]] \vdash N : U_{s_2}$ . As  $\Gamma \vdash |M_1| : s_1$  we  
 752 have  $\Gamma, x : |M_1|$  well-formed and thus by IH  $N$  is an invertible form and we have  $[[N]] \equiv_H N$   
 753 and  $\Gamma, x : |M_1| \vdash |N| : s_2$ .

754 Therefore, by PROD we have  $\Gamma \vdash \Pi_{s_1, s_2}(|M_1|, [x]|N|) : s_3$ , and then by CONV with  
 755  $A \equiv s_3$  we conclude  $\Gamma \vdash \Pi_{s_1, s_2}(|M_1|, [x]|N|) : A$ . Finally, as  $M_1 \equiv_H [[M_1]]$ ,  $N \equiv_H [[N]]$  and  
 756  $B \equiv El_{s_1} M_1 \equiv El_{s_1} [[M_1]]$ , we conclude

$$\begin{aligned} 757 M &= Prod_{s_1, s_2} M_1 M_2 = Prod_{s_1, s_2} M_1 (\lambda x : B.N) \\ 758 &\equiv_H Prod_{s_1, s_2} [[M_1]] (\lambda x : El_{s_1} [[M_1]]. [[N]]) = [[\Pi_{s_1, s_2}(|M_1|, [x]|N|)]] = [[M]] \end{aligned}$$

760 **Case**  $c = abs_{s_1, s_2}$  : By inversion of typing, we have

- 761 1.  $\vec{M} = M_1 M_2 M_3$
- 762 2.  $[\Gamma] \vdash M_1 : U_{s_1}$
- 763 3.  $[\Gamma] \vdash M_2 : El_{s_1} M_2 \rightarrow U_{s_2}$
- 764 4.  $[\Gamma] \vdash M_3 : \Pi x : El_{s_1} M_1. El_{s_2} (M_2 x)$
- 765 5.  $T \equiv El_{s_3} (Prod_{s_1, s_2} M_1 M_2)$

766 By the same arguments as in case  $M = Prod_{s_1, s_2} \vec{M}$ , we have that

- 767 ■  $M_1$  is an invertible form,  $[[M_1]] \equiv_H M_1$  and  $\Gamma \vdash |M_1| : s_1$ .
- 768 ■  $M_2 = \lambda x : B.N$ ,  $N$  is an invertible form,  $[[N]] \equiv_H N$ ,  $\lambda x : El_{s_1} [[M_1]]. [[N]] \equiv_H \lambda x : B.N$   
 769 and  $\Gamma, x : |M_1| \vdash |N| : s_2$ .

770 By Lemma 40 applied to 4 we have  $M_3 = \lambda x : C.P$ ,  $C \equiv El_{s_1} M_1$  and  $[\Gamma], x : El_{s_1} M_1 \vdash_{DK}$   
 771  $P : El_{s_2} (M_2 x)$ . Using  $M_2 = \lambda x : B.N$  and *Reduce type in judgement* (Proposition 3), we  
 772 get  $[\Gamma], x : El_{s_1} M_1 \vdash_{DK} P : El_{s_2} N$ . Because  $M_1 \equiv [[M_1]]$  and  $N \equiv [[N]]$ , we then get  
 773  $[\Gamma], x : El_{s_1} [[M_1]] \vdash_{DK} P : El_{s_2} [[N]]$ .

774 Therefore, by IH  $P$  is an invertible form,  $\Gamma, x : |M_1| \vdash |P| : |N|$  and  $[[P]] \equiv_H P$ .  
 775 Putting this together with  $\Gamma \vdash |M_1| : s_1$  and  $\Gamma, x : |M_1| \vdash |N| : s_2$  we can derive  $\Gamma \vdash$

776  $\lambda_{s_1, s_2}(|M_1|, [x]|N|, [x]|P|) : \Pi_{s_1, s_2}(|M_1|, [x]|N|)$ . From 5 we can also show  $\Pi_{s_1, s_2}(|M_1|, [x]|N|) \equiv A$ ,  
 777 which allows us to apply CONV to get  $\Gamma \vdash \lambda_{s_1, s_2}(M_1, [x]|N|, [x]|P|) : A$ . Finally, from  
 778  $\llbracket |M_1| \rrbracket \equiv_H M_1$ ,  $\lambda x : B.N \equiv_H \lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket$ ,  $P \equiv_H \llbracket |P| \rrbracket$  and  $C \equiv El_{s_1} M_1 \equiv El_{s_1} \llbracket |M_1| \rrbracket$   
 779 we get

$$\begin{aligned} 780 \quad M &= abs_{s_1, s_2} M_1 M_2 M_3 = abs_{s_1, s_2} M_1 (\lambda x : B.N) (\lambda x : C.P) \\ 781 \quad &\equiv_H abs_{s_1, s_2} \llbracket |M_1| \rrbracket (\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket) (\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |P| \rrbracket) \\ 782 \quad &= \llbracket \lambda_{s_1, s_2}(|M_1|, [x]|N|, [x]|P|) \rrbracket = \llbracket |M| \rrbracket \end{aligned}$$

784 **Case  $c = app_{s_1, s_2}$ :** By inversion of typing, we have

- 785 1.  $\vec{M} = M_1 M_2 M_3 M_4 M_5$
- 786 2.  $\llbracket \Gamma \rrbracket \vdash_{DK} M_1 : U_{s_1}$
- 787 3.  $\llbracket \Gamma \rrbracket \vdash_{DK} M_2 : El_{s_1} M_1 \rightarrow U_{s_2}$
- 788 4.  $\llbracket \Gamma \rrbracket \vdash_{DK} M_3 : El_{s_3} (Prod_{s_1, s_2} M_1 M_2)$
- 789 5.  $\llbracket \Gamma \rrbracket \vdash_{DK} M_4 : El_{s_1} M_1$
- 790 6.  $T \equiv El_{s_2} (M_2 M_4)$

791 By the same arguments as in case  $M = Prod_{s_1, s_2} \vec{M}$ , we have that

- 792 ■  $M_1$  is an invertible form,  $\llbracket |M_1| \rrbracket \equiv_H M_1$  and  $\Gamma \vdash |M_1| : s_1$ .
- 793 ■  $M_2 = \lambda x : B.N$ ,  $N$  is an invertible form,  $\llbracket |N| \rrbracket \equiv_H N$ ,  $\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket \equiv_H \lambda x : B.N$   
 794 and  $\Gamma, x : |M_1| \vdash |N| : s_2$ .

795 As  $Prod_{s_1, s_2} M_1 M_2 \equiv \llbracket \Pi_{s_1, s_2}(|M_1|, [x]|M_2|) \rrbracket$ , from 4 we get  $\llbracket \Gamma \rrbracket \vdash_{DK} M_3 : El_{s_3} \llbracket \Pi_{s_1, s_2}(|M_1|, [x]|M_2|) \rrbracket$ .  
 796 Therefore, we deduce by the IH that  $M_3$  is an invertible form,  $\Gamma \vdash |M_3| : \Pi_{s_1, s_2}(|M_1|, [x]|N|)$   
 797 and  $\llbracket |M_3| \rrbracket \equiv_H M_3$ .

798 Moreover, as  $M_1 \equiv \llbracket |M_1| \rrbracket$ , from 5 we get  $\llbracket \Gamma \rrbracket \vdash_{DK} M_4 : El_{s_1} \llbracket |M_1| \rrbracket$ , therefore by IH we  
 799 deduce that  $M_4$  is an invertible form,  $\Gamma \vdash |M_4| : |M_1|$  and  $\llbracket |M_4| \rrbracket \equiv_H M_4$ .

800 Putting together  $\Gamma \vdash |M_1| : s_1$ ,  $\Gamma, x : |M_1| \vdash |N| : s_2$ ,  $\Gamma \vdash |M_3| : \Pi_{s_1, s_2}(|M_1|, [x]|N|)$  and  
 801  $\Gamma \vdash |M_4| : |M_1|$  we derive  $\Gamma \vdash \mathcal{C}_{s_1, s_2}(|M_1|, [x]|N|, |M_3|, |M_4|) : |N|(|M_4|/x)$ .

802 From 8 we get  $T \equiv El_{s_2} (M_2 M_4) \equiv El_{s_2} ((\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket) \llbracket |M_4| \rrbracket) \equiv El_{s_2} \llbracket |N|(|M_4|/x) \rrbracket$ ,  
 803 thus we deduce  $A \equiv |N|(|M_4|/x)$ . Hence, we can apply CONV to get  $\Gamma \vdash \mathcal{C}_{s_1, s_2}(|M_1|, [x]|N|, |M_3|, |M_4|) : A$ .  
 804

805 From  $\llbracket |M_1| \rrbracket \equiv_H M_1$ ,  $\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket \equiv_H \lambda x : B.N$ ,  $\llbracket |M_4| \rrbracket \equiv_H M_4$  and  $\llbracket |M_3| \rrbracket \equiv_H M_3$   
 806 we can then conclude

$$\begin{aligned} 807 \quad M &= app_{s_1, s_2} M_1 M_2 M_3 M_4 = app_{s_1, s_2} M_1 (\lambda x : B.N) M_3 M_4 \\ 808 \quad &\equiv_H app_{s_1, s_2} \llbracket |M_1| \rrbracket (\lambda x : El_{s_1} \llbracket |M_1| \rrbracket. \llbracket |N| \rrbracket) \llbracket |M_3| \rrbracket \llbracket |M_4| \rrbracket \\ 809 \quad &= \llbracket \mathcal{C}_{s_1, s_2}(|M_1|, [x]|N|, |M_3|, |M_4|) \rrbracket = \llbracket |M| \rrbracket \end{aligned}$$

811 By *Basic properties* (Proposition 29),  $\beta$  is strongly normalizing and type preserving.  
 812 Therefore from the previous result we can immediately get full conservativity.

813 ► **Theorem 45 (Conservativity).** Let  $\Gamma \vdash A$  type,  $M \in \Lambda_{DK}$  such that  $\llbracket \Gamma \rrbracket \vdash_{DK} M : T$ , with  
 814  $T = El_{s_A} \llbracket |A| \rrbracket$  or  $T = U_A$ . We have  $\Gamma \vdash |NF_\beta(M)| : A$  and  $M \hookrightarrow_\beta^* NF_\beta(M) \equiv_H \llbracket |NF_\beta(M)| \rrbracket$ .

815 Note that this also gives us a straightforward algorithm to invert terms: it suffices to  
 816 normalize with  $\beta$  and then apply  $|-|$ .

### 7.3 Adequacy

If we write  $\Lambda(\Gamma \vdash_{EPTS} \_ : A)$  for the set of  $M \in \Lambda_{EPTS}$  st  $\Gamma \vdash M : A$  and  $\Lambda_{NF}(\Gamma \vdash_{DK} \_ : T)$  for the set of  $M \in \Lambda_{DK}$  in  $\beta$  normal form st  $\Gamma \vdash_{DK} M : T$ , we can show our adequacy theorem. This result follows by simply putting together *Basic properties* (Proposition 29), *Preservation of computation* (Lemma 31), *Soundness* (Theorem 33), *Reflection of computation* (Corollary 39) and *Conservativity* (Theorem 45).

► **Theorem 46** (Computational adequacy). *For  $A, \Gamma$  with  $\Gamma \vdash A$  type, let  $T = U_A$  if  $A$  is a top sort, otherwise  $T = El_{s_A} \llbracket A \rrbracket$ . We have a bijection*

$$\Lambda(\Gamma \vdash_{EPTS} \_ : A) \simeq \Lambda_{NF}(\llbracket \Gamma \rrbracket \vdash_{DK} \_ : T) / \equiv_H$$

given by  $\llbracket - \rrbracket$  and  $|-|$ . It is compositional in the sense that  $\llbracket - \rrbracket$  commutes with substitution. It is computational in the sense that  $M \hookrightarrow^* N$  iff  $\llbracket M \rrbracket \hookrightarrow^* \llbracket N \rrbracket$ . Moreover, any  $M$  satisfying  $\llbracket \Gamma \rrbracket \vdash_{DK} M : T$  has such a  $\beta$  normal form.

## 8 Representing systems with infinite sorts

We have presented an encoding of EPTSs in DEDUKTI that is sound, conservative and adequate. However when using it in practice with DEDUKTI implementations we run into problems when representing systems with infinite sorts, such as in Martin-Löf's Type Theory or the Extended Calculus of Constructions. Indeed, in this case our encoding needs an infinite number of constant and rule declarations, which cannot be made in practice.

One possible solution is to approximate the infinite sort structure by a finite one. Indeed, every proof in an infinite sort systems only use a finite number of sorts, and thus does not need all of them to be properly represented.

A different approach proposed in [1][23] is to internalize the indices of  $Prod_{s_1, s_2}, El_{s_1}, \dots$  and represent them inside DEDUKTI. In order to apply this method, we chose to stick with systems in which  $\mathcal{A}, \mathcal{R}$  are total functions  $\mathcal{S} \rightarrow \mathcal{S}$  and  $\mathcal{S} \times \mathcal{S} \rightarrow \mathcal{S}$  respectively. Note that this is true for almost all infinite sort systems used in practice, and this will greatly simplify our presentation.

We can now declare a constant  $\hat{\mathcal{S}}$  to represent the type of sorts in  $\mathcal{S}$  and two constants  $\hat{\mathcal{A}}, \hat{\mathcal{R}}$  to represent the functions  $\mathcal{A}, \mathcal{R}$ . Then, each of our previously declared families of constants now becomes a single one, by taking arguments of type  $\hat{\mathcal{S}}$ . The same happens with the rewrite rules. This leads to the theory presented in Figure 3, which we call  $(\Sigma_{EPTS}^{\mathcal{S}}, \mathcal{R}_{EPTS}^{\mathcal{S}})$ .

This theory needs of course to be completed case by case, so that  $\hat{\mathcal{S}}, \hat{\mathcal{A}}, \hat{\mathcal{R}}$  correctly represent  $\mathcal{S}, \mathcal{A}, \mathcal{R}$ . For this to hold, each sort  $s \in \mathcal{S}$  should have a representation  $\dot{s} : \hat{\mathcal{S}}$ , and this should restrict to a bijection when considering only the closed normal forms of type  $\hat{\mathcal{S}}$ . Moreover, we should add rewrite rules such that  $\mathcal{A}(s_1) = s_2$  iff  $\hat{\mathcal{A}} \dot{s}_1 \equiv \dot{s}_2$  and  $\mathcal{R}(s_1, s_2) = s_3$  iff  $\hat{\mathcal{R}} \dot{s}_1 \dot{s}_2 \equiv \dot{s}_3$ .

In order to understand intuitively these conditions, let's look at an example.

► **Example 47.** The sort structure of Martin-Löf's Type Theory is given by the specification  $\mathcal{S} = \mathbb{N}$ ,  $\mathcal{A}(x) = x + 1$  and  $\mathcal{R}(x, y) = \max\{x, y\}$ . We can represent this in DEDUKTI by declaring constants  $z : \hat{\mathcal{S}}, s[n : \hat{\mathcal{S}}] : \hat{\mathcal{S}}$  and rewrite rules  $\hat{\mathcal{A}} x \hookrightarrow s x$ ,  $\hat{\mathcal{R}} z x \hookrightarrow x$ ,  $\hat{\mathcal{R}} x z \hookrightarrow x$  and  $\hat{\mathcal{R}} (s x) (s y) \hookrightarrow s (\hat{\mathcal{R}} x y)$ .

With this representation, we can revisit the example of the polymorphic identity function.

$$\begin{array}{ll}
\hat{S} : \text{TYPE} & U[s : \hat{S}] : \text{TYPE} \\
\hat{A}[s_1 : \hat{S}] : \hat{S} & El[s : \hat{S}; A : U s] : \text{TYPE} \\
\hat{R}[s_1 : \hat{S}; s_2 : \hat{S}] : \hat{S} & u[s : \hat{S}] : U(\hat{A} s) \\
& El s' (u s) \hookrightarrow_{u\text{-red}} U s \\
\\ 
Prod[s_1 : \hat{S}; s_2 : \hat{S}; A : U s_1; B : El s_1 A \rightarrow U s_2] : U(\hat{R} s_1 s_2) \\
abs[s_1 : \hat{S}; s_2 : \hat{S}; A : U s_1; B : El s_1 A \rightarrow U s_2; N : \Pi x : El s_1 A. El s_2 (B x)] \\
\quad : El(\hat{R} s_1 s_2) (Prod s_1 s_2 A B) \\
app[s_1 : \hat{S}; s_2 : \hat{S}; A : U s_1; B : El s_1 A \rightarrow U s_2; M : El(\hat{R} s_1 s_2) (Prod s_1 s_2 A B); N : El s_1 A] \\
\quad : El s_2 (B N) \\
app s_1 s_2 A B (abs s'_1 s'_2 A' B' M) N \hookrightarrow_{beta} M N
\end{array}$$

■ **Figure 3** Definition of the theory  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$

► **Example 48.** The (predicative and at sort 0) polymorphic identity function in Martin L f’s Type Theory is given by the term

$$\lambda_{1,0}(0, [A]\Pi_{0,0}(A, [x]A), [A]\lambda_{0,0}(A, [x]A, [x]x)).$$

It can be represented in the encoding by

$$abs(s z) z (u z) (\lambda A. Prod z z A (\lambda x. A)) (\lambda A. abs z z A (\lambda x. A) (\lambda x. x)).$$

Let us now define the encoding function formally, by the following equations.

$$\begin{array}{ll}
\llbracket x \rrbracket_s = x & \\
\llbracket s \rrbracket_s = u \dot{s} & \\
\llbracket \Pi_{s_1, s_2}(A, [x]B) \rrbracket_s = Prod \dot{s}_1 \dot{s}_2 \llbracket A \rrbracket_s (\lambda x : El \dot{s}_1 \llbracket A \rrbracket_s. \llbracket B \rrbracket_s) & \\
\llbracket \lambda_{s_1, s_2}(A, [x]B, [x]M) \rrbracket_s = abs \dot{s}_1 \dot{s}_2 \llbracket A \rrbracket_s (\lambda x : El \dot{s}_1 \llbracket A \rrbracket_s. \llbracket B \rrbracket_s) (\lambda x : El \dot{s}_1 \llbracket A \rrbracket_s. \llbracket M \rrbracket_s) & \\
\llbracket @_{s_1, s_2}(A, [x]B, M, N) \rrbracket_s = app \dot{s}_1 \dot{s}_2 \llbracket A \rrbracket_s (\lambda x : El \dot{s}_1 \llbracket A \rrbracket_s. \llbracket B \rrbracket_s) \llbracket M \rrbracket_s \llbracket N \rrbracket_s & \\
\llbracket - \rrbracket_s = - & \\
\llbracket \Gamma, x : A \rrbracket_s = \llbracket \Gamma \rrbracket_s, x : El \dot{s}_A \llbracket A \rrbracket_s \quad \text{where } \Gamma \vdash A : s_A &
\end{array}$$

Now one can proceed as before with the proofs of soundness, conservativity and adequacy, which follow the same idea as the previously presented ones. However, it is quite unsatisfying that we have to redo all the work of Sections 6 and 7 another time, and therefore one can wonder if we can reuse the results we already have about the first encoding.

Note that one may intuitively think of the  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$  as a “hidden implementation” of  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$ . In this case, it should be possible to take a proof written in the  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$  and “implement” it in the  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$ . To formalize this intuition, we will define a notion of *theory morphism* which will allow us to establish the soundness of this new encoding using a morphism from  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$  to  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$ .

## 9 Theory morphisms

To define our notion of theory morphism, we start by defining an auxiliary weaker notion of pre-morphism. In the following, we write  $\mathcal{C}(\Sigma_i)$  for the constants appearing in  $\Sigma_i$  and  $\Lambda(\Sigma_i)$

885 for the terms built using such constants.

886 ▶ **Definition 49** (Theory pre-morphism). *A theory pre-morphism  $F : (\Sigma_1, \mathcal{R}_1) \rightarrow (\Sigma_2, \mathcal{R}_2)$  is*  
 887 *for each  $c \in \mathcal{C}(\Sigma_1)$  a term  $F_c \in \Lambda(\Sigma_2)$  with free variables in  $\Delta_c$ . Each such  $F$  defines a map*  
 888 *on terms  $|-|_F$  given by*

$$\begin{aligned}
 |c[\vec{M}]|_F &= F_c\{|\vec{M}|_F\} & |\Pi x : A.B|_F &= \Pi x : |A|_F. |B|_F \\
 |x|_F &= x & |\lambda x : A.M|_F &= \lambda x : |A|_F. |M|_F \\
 |\text{TYPE}|_F &= \text{TYPE} & |MN|_F &= |M|_F |N|_F \\
 |\text{KIND}|_F &= \text{KIND}
 \end{aligned}$$

890 Given a term  $c[\vec{M}]$  defined in the signature  $\Sigma_1$ , one should understand  $F_c\{|\vec{M}|_F\}$  as the  
 891 implementation in  $\Sigma_2$  of this term. With this interpretation, we can see  $F_c$  as the body of  
 892 the implementation. This also explains why  $F_c$  should have free variables in  $\Delta_c$ , as these  
 893 corresponds to the arguments that are supplied to  $c$ .

894 In order to understand intuitively the definition, let's define a theory pre-morphism from  
 895  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$  to  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$ , which will then be used to show soundness of  $\llbracket - \rrbracket_S$ .

896 ▶ **Example 50.** We define the pre-morphism  $\phi : (\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}}) \rightarrow (\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$  by the  
 897 following data. We recall in the right the variables in the context of each constant (we write  
 898  $\mathcal{V}(\Delta)$  for the variables in  $\Delta$ ).

$$\begin{aligned}
 \phi_{U_s} &= U \dot{s} & \mathcal{V}(\Delta_{U_s}) &= - \\
 \phi_{E_{I_s}} &= E_{I_s} \dot{s} A & \mathcal{V}(\Delta_{E_{I_s}}) &= A \\
 \phi_{u_s} &= u \dot{s} & \mathcal{V}(\Delta_{u_s}) &= - \\
 \phi_{\text{Prod}_{s_1, s_2}} &= \text{Prod } \dot{s}_1 \dot{s}_2 A B & \mathcal{V}(\Delta_{\text{Prod}_{s_1, s_2}}) &= A, B \\
 \phi_{\text{abs}_{s_1, s_2}} &= \text{abs } \dot{s}_1 \dot{s}_2 A B N & \mathcal{V}(\Delta_{\text{abs}_{s_1, s_2}}) &= A, B, N \\
 \phi_{\text{app}_{s_1, s_2}} &= \text{app } \dot{s}_1 \dot{s}_2 A B M N & \mathcal{V}(\Delta_{\text{app}_{s_1, s_2}}) &= A, B, M, N
 \end{aligned}$$

906 We can then calculate for instance the value of  $|\text{Prod}_{s_1, s_2} T_1 T_2|_\phi$  as

$$907 \quad |\text{Prod}_{s_1, s_2} T_1 T_2|_\phi = (\text{Prod } \dot{s}_1 \dot{s}_2 A B)\{ |T_1|_\phi / A, |T_2|_\phi / B \} = \text{Prod } \dot{s}_1 \dot{s}_2 |T_1|_\phi |T_2|_\phi$$

908 More generally, we can prove that  $\llbracket M \rrbracket_\phi = \llbracket M \rrbracket_S$  by induction on  $M \in \Lambda_{\text{EPTS}}$ .

909 Not every theory pre-morphism should be called a morphism, as there are some properties  
 910 which one should enforce. In the following, we write  $\vdash_i$  for a judgment in the theory  $(\Sigma_i, \mathcal{R}_i)$ .

911 ▶ **Definition 51** (Theory morphism). *A theory morphism  $F : (\Sigma_1, \mathcal{R}_1) \rightarrow (\Sigma_2, \mathcal{R}_2)$  is a theory*  
 912 *pre-morphism satisfying the following conditions*

- 913 1. *for all  $c[A_c] : \Delta_c \in \Sigma_1$ , we have  $|\Delta_c|_F \vdash_2 F_c : |A_c|_F$*
- 914 2. *for all  $l \hookrightarrow_1 r \in \mathcal{R}_1$  we have  $|l|_F \hookrightarrow_2^* |r|_F$*

915 We have the following basic properties about compositionality and preservation of com-  
 916 putation and of conversion.

917 ▶ **Lemma 52.** *For each morphism  $F$ , we have the following properties.*

- 918 1. *Compositionality:*  $|M|_F\{|N|_F/x\} = |M\{N/x\}|_F$
- 919 2. *Preservation of computation:* if  $M \hookrightarrow_1 N$  then  $|M|_F \hookrightarrow_2^* |N|_F$
- 920 3. *Preservation of conversion:* if  $M \equiv_1 N$  then  $|M|_F \equiv_2 |N|_F$



921 We can now show the main result about theory morphisms.

922 ▶ **Theorem 53** (Preservation of typing). *Let  $F : (\Sigma_1, \mathcal{R}_1) \rightarrow (\Sigma_2, \mathcal{R}_2)$  be a theory morphism.*

923 1. *If  $\Gamma$  well-formed<sub>1</sub> then  $\vdash_2 |\Gamma|_F$  well-formed<sub>2</sub>*

924 2. *If  $\Gamma \vdash_1 M : A$  then  $|\Gamma|_F \vdash_2 |M|_F : |A|_F$*

925 **Proof.** By induction on the judgment tree. We do only cases **Conv** and **Cons**, as they are  
926 the only interesting ones.

927 **Case Cons:** The proof ends with

$$928 \quad c[\Delta_c] : A_c \in \Sigma_1 \quad \frac{\Delta_c \vdash_1 A_c : s \quad \Gamma \vdash_1 \vec{M} : \Delta_c}{\Gamma \vdash_1 c[\vec{M}] : A_c\{\vec{M}\}} \text{Cons}$$

929 By IH we have  $|\Gamma| \vdash_2 |\vec{M}| : |\Delta_c|$ . Moreover, because  $F$  is a morphism we have  $|\Delta_c| \vdash_2$   
930  $F_c : |A_c|$ . By substitution we thus deduce  $|\Gamma| \vdash_2 F_c\{|\vec{M}|\} : |A_c\{\vec{M}\}|$ . Finally, as  $|A_c\{\vec{M}\}| =$   
931  $|A_c\{\vec{M}\}|$  we get the result.

932 **Case Conv:** The proof ends with

$$933 \quad A \equiv_1 B \quad \frac{\Gamma \vdash_1 M : A \quad \Gamma \vdash_1 B : s}{\Gamma \vdash_1 M : B} \text{Conv}$$

934 By the IH, we have  $|\Gamma| \vdash_2 |M| : |A|$  and  $|\Gamma| \vdash_2 |B| : s$ . Moreover, as  $A \equiv_1 B$ , by Lemma  
935 52 we have  $|A| \equiv_2 |B|$ , and thus we can apply **Conv** to conclude. ◀

936 Using this result, one can also show, as expected, that theories and their morphisms  
937 assemble into a category. However, as we will not need this result here, we will not show it.  
938 Instead, let's now come back to our pre-morphism  $\phi$  and show that it is indeed a morphism.

939 ▶ **Example 54.** We show that  $\phi$  verifies the conditions of Definition 51, and is thus a morphism.  
940 Condition 2 can be easily verified, so we concentrate in the first one. As an example, we  
941 show the property only for constant  $\text{Prod}_{s_1, s_2}$ . We need to show

$$942 \quad A : |U_{s_1}|_\phi, B : |El_{s_1} A|_\phi \vdash U \dot{s}_1 \dot{s}_2 A B : |U_{s_3}|$$

943 where  $(s_1, s_2, s_3) \in \mathcal{R}$ . Because  $|U_{s_1}|_\phi = U \dot{s}_1$  and  $|El_{s_1} A|_\phi = El \dot{s}_1 A$  we can show, using rule  
944 **Cons**, that  $A : U \dot{s}_1, B : El \dot{s}_1 A \vdash U \dot{s}_1 \dot{s}_2 A B : U (\widehat{\mathcal{R}} \dot{s}_1 \dot{s}_2)$ . However, as we have  $\widehat{\mathcal{R}} \dot{s}_1 \dot{s}_2 \equiv \dot{s}_3$   
945 and  $U \dot{s}_3 : \text{TYPE}$ , using **Conv** we deduce the required result.

946 We can now use this to show that  $\llbracket - \rrbracket_S$  is sound. Indeed, because  $\llbracket - \rrbracket$  is sound and we  
947 have  $\llbracket M \rrbracket_\phi = \llbracket M \rrbracket_S$ , by Theorem 53 we immediately get the following result.

948 ▶ **Corollary 55** ( $\llbracket - \rrbracket_S$  is sound). *Let  $\Gamma$  be a context and  $M, A$  terms in an EPTS. We have*

- 949 ■ *If  $\Gamma$  well-formed then  $\llbracket \Gamma \rrbracket_S$  well-formed<sub>2</sub>*
- 950 ■ *If  $\Gamma \vdash M : A$  then*
  - 951 ■ *if  $A = s$  is a top-sort then  $\llbracket \Gamma \rrbracket_S \vdash_2 \llbracket M \rrbracket_S : U \dot{s}$*
  - 952 ■ *else  $\llbracket \Gamma \rrbracket_S \vdash_2 \llbracket M \rrbracket_S : El \dot{s}_A \llbracket A \rrbracket_S$ , where  $\Gamma \vdash A : s_A$*

953 In a sense, our notion of theory morphism allows us to embed a theory that is more  
954 fined grained into a theory that is less. For instance, to build our morphism  $\phi$ , we map all  
955 the constants of the form  $\text{Prod}_{s_1, s_2}$  to the same one. We then could try to build an inverse  
956 morphism  $\phi^{-1}$  to show conservativity of  $\llbracket - \rrbracket_S$ , but this is not possible with our definition.  
957 Indeed, the same constant  $\text{Prod}$  should be sent into  $\text{Prod}_{s_1, s_2}$  when it is applied to  $\dot{s}_1, \dot{s}_2$  and  
958 into  $\text{Prod}_{s_3, s_4}$  when it is applied to  $\dot{s}_3, \dot{s}_4$ . However, in our definition the body of the  
959 implementation  $F_c$  only depends on the initial constant  $c$ , and not on its arguments  $\vec{M}$ .

Therefore, it is still an open problem for us to find a notion of morphism that would allows to build morphisms in both directions between  $(\Sigma_{\text{EPTS}}, \mathcal{R}_{\text{EPTS}})$  and  $(\Sigma_{\text{EPTS}}^S, \mathcal{R}_{\text{EPTS}}^S)$ , and then show the equivalence between the encodings. For the time being, in order to show conservativity (and then adequacy) of  $\llbracket - \rrbracket_5$  one basically has to redo the work of Section 7.

We note nevertheless that our definition of morphism can have many other applications. For instance, if we consider two DEDUKTI theories that express classical logic, one using the axiom of the excluded middle  $A \vee \neg A$  and the other using the double negation axiom  $A \Leftrightarrow \neg \neg A$ , one could define morphisms in both directions in order to be able to transport proofs from a theory to another. It would suffice to map the constant representing the excluded middle *exm* to a proof of it  $F_{\text{exm}}$  which uses the double negation, and map the constant representing the double negation axiom *nnpp* to a proof of it  $F_{\text{nnpp}}$  which uses the excluded middle.

## 10 The encoding in practice

Our encoding satisfies nice theoretical properties, but when using it in practice it becomes quite annoying to have to explicit all the information needed in *app*<sub>*s*<sub>1</sub>,*s*<sub>2</sub></sub> and *abs*<sub>*s*<sub>1</sub>,*s*<sub>2</sub></sub>. Worst, when performing translations from other systems where those parameters are not explicit we would then have to compute them during the translation. Thankfully, LAMBDAP1[10], an implementation of DEDUKTI, allows us to solve this by declaring some arguments as implicit, so they are only calculated internally.

Using the encoding of Figure 3 we can mark for instance the arguments *s*<sub>1</sub>, *s*<sub>2</sub>, *A* of *Prod* as implicit. We can then also rename *Prod* into  $\Pi'$ , *abs* into  $\lambda'$ , *app* into  $\blacksquare$  and use another LAMBDAP1 feature allowing to mark  $\Pi'$ ,  $\lambda'$  as quantifier and  $\blacksquare$  as infix left. This then allows us to represent  $\Pi x : A.B$  as  $\Pi'x : \text{El } [A]. [B]$ ,  $\lambda x : A.B$  as  $\lambda'x : \text{El } [A]. [B]$  and  $M N$  as  $[M] \blacksquare [N]$ . Using these notations, we can write terms in the encoding in a natural way, and we refer to <sup>6</sup> for a set of examples of this.

However, as DEDUKTI also aims to be used in practice for sharing real libraries between proof assistants, we also tested how our approach copes with more practical scenarios. We provide a benchmark<sup>7</sup> of Fermat's little theorem library in DEDUKTI[22], where we compare the traditional encoding with an adequate version that applies the ideas of our approach<sup>8</sup>. As we can see, the move from the traditional to the adequate version introduces a considerable performance hit. The standard DEDUKTI implementation, which is our reference here, takes 16 times more time to typecheck the files. This is probably caused by the insertion of type parameters *A* and *B* in *abs*<sub>*s*<sub>A</sub>,*s*<sub>B</sub></sub> and *app*<sub>*s*<sub>A</sub>,*s*<sub>B</sub></sub>, which are not needed in traditional encodings.

Nevertheless, DEDUKTI is still able to typecheck our encoding in a reasonable time, showing that our approach is indeed usable in practical scenarios, even if it is not the most performing one. Moreover, as our encoding is mainly intended to be used to check proofs, and not with interactive proof development, immediacy of the result is not essential and thus it can be reasonable to trade performance for better theoretical properties. Still, we plan in the future to look at techniques to improve our performances. In particular, using more sharing in DEDUKTI would probably improve our performances, as the parameter annotations in *app*<sub>*s*<sub>A</sub>,*s*<sub>B</sub></sub> and *abs*<sub>*s*<sub>A</sub>,*s*<sub>B</sub></sub> carry a lot of repetition.

<sup>6</sup> <https://github.com/thiagofelicissimo/examples-encodigs>

<sup>7</sup> <https://github.com/thiagofelicissimo/encoding-benchmarking>

<sup>8</sup> Because the underlying logic of the library is not a PTS, this encoding is not exactly the one we present here. However, it uses the same ideas discussed, and the same proof strategy to show adequacy applies.

## 11 Conclusion

By separating the framework's abstraction and application from the ones of the encoded system, we have proposed a new paradigm for DEDUKTI encodings. Our approach offers much more well-behaved encodings, whose conservativity can be showed in a much more straightforward way and which feature adequacy theorems, something that was missing from traditional DEDUKTI encodings. However, differently from the ELF approach, our encoding is also computational. Therefore, our method combines the adequacy of ELF encodings with the computational aspect of DEDUKTI encodings.

By decoupling the framework's  $\beta$  from the rewriting of the encoded system, our approach allows to show the expected properties of the encoding without requiring to show that the encoded system terminates. Indeed, our adequacy result concerns all functional EPTS, even non terminating ones, such as the one with  $Type : Type$ . This sets our work apart from [9], whose conservativity proof requires the encoded system to be normalizing.

This work opens many other directions we would like to explore. We believe that our technique can be extended to craft adequate and computational encodings of type theories with much more complex features, such as (co)inductive types, universe polymorphism, predicate subtyping and others. For instance, in the case of inductive types no type-level rewriting rules need to be added, thus  $\beta$  is SN in DEDUKTI (Theorem 18) would apply. Therefore, we could repeat the same technique of normalizing only with  $\beta$  to show conservativity.

However, we would be particularly interested to see if we could take a general definition of type theories covering most of these features (maybe in the lines of [5]). This would allow us to define a single encoding which could be applied to encode various features, and thus would save us from redoing similar proofs multiple times.

## References

- 1 Ali Assaf. *A framework for defining computational higher-order logics*. Theses, École polytechnique, September 2015. URL: <https://pastel.archives-ouvertes.fr/tel-01235303>.
- 2 Ali Assaf. Conservativity of embeddings in the lambda pi calculus modulo rewriting. In *13th International Conference on Typed Lambda Calculi and Applications (TLCA 2015)*. Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, 2015.
- 3 Ali Assaf, Guillaume Burel, Raphaël Cauderlier, D Delahaye, G Dowek, C Dubois, F Gilbert, P Halmagrand, O Hermant, and R Saillard. Dedukti: a logical framework based on the  $\lambda$   $\pi$ -calculus modulo theory. Manuscript, 2016.
- 4 Gilles Barthe. The relevance of proof-irrelevance. In Kim G. Larsen, Sven Skyum, and Glynn Winskel, editors, *Automata, Languages and Programming*, pages 755–768, Berlin, Heidelberg, 1998. Springer Berlin Heidelberg.
- 5 Andrej Bauer, Philipp G. Haselwarter, and Peter LeFanu Lumsdaine. A general definition of dependent type theories, 2020. [arXiv:2009.05539](https://arxiv.org/abs/2009.05539).
- 6 Frédéric Blanqui. *Théorie des types et réécriture. (Type theory and rewriting)*. PhD thesis, University of Paris-Sud, Orsay, France, 2001. URL: <https://tel.archives-ouvertes.fr/tel-00105522>.
- 7 Frédéric Blanqui. Type safety of rewrite rules in dependent types. In *FSCD 2020 - 5th International Conference on Formal Structures for Computation and Deduction*, volume 167, page 14, Paris, France, June 2020. URL: <https://hal.inria.fr/hal-02981528>, doi: 10.4230/LIPIcs.FSCD.2020.13.
- 8 Frédéric Blanqui, Guillaume Genestier, and Olivier Hermant. Dependency pairs termination in dependent type theory modulo rewriting. In Herman Geuvers, editor, *4th International*

- 1047 *Conference on Formal Structures for Computation and Deduction, FSCD 2019, June 24-*  
 1048 *30, 2019, Dortmund, Germany*, volume 131 of *LIPIcs*, pages 9:1–9:21. Schloss Dagstuhl -  
 1049 Leibniz-Zentrum für Informatik, 2019. doi:10.4230/LIPIcs.FSCD.2019.9.
- 1050 9 Denis Cousineau and Gilles Dowek. Embedding pure type systems in the lambda-pi-calculus  
 1051 modulo. In Simona Ronchi Della Rocca, editor, *Typed Lambda Calculi and Applications*, pages  
 1052 102–117, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg.
- 1053 10 Deducteam. Lambdapi. <https://github.com/Deducteam/lambdapi>.
- 1054 11 Gilles Dowek. Models and termination of proof reduction in the lambda pi-calculus modulo  
 1055 theory. In *ICALP*, 2017.
- 1056 12 Thiago Felicissimo. Adequate and computational encodings in the logical framework Dedukti.  
 1057 Draft at <https://lmf.cnrs.fr/Perso/ThiagoFelicissimo>, 2022.
- 1058 13 Thiago Felicissimo. No need to be implicit! Draft at [https://lmf.cnrs.fr/Perso/](https://lmf.cnrs.fr/Perso/ThiagoFelicissimo)  
 1059 [ThiagoFelicissimo](https://lmf.cnrs.fr/Perso/ThiagoFelicissimo), 2022.
- 1060 14 Gaspard Ferey. *Higher-Order Confluence and Universe Embedding in the Logical Framework*.  
 1061 Theses, Université Paris-Saclay, June 2021. URL: [https://tel.archives-ouvertes.fr/](https://tel.archives-ouvertes.fr/tel-03418761)  
 1062 [tel-03418761](https://tel.archives-ouvertes.fr/tel-03418761).
- 1063 15 Guillaume Genestier. *Dependently-Typed Termination and Embedding of Extensional Universe-*  
 1064 *Polymorphic Type Theory using Rewriting*. PhD thesis, 2020. Thèse de doctorat dirigée  
 1065 par Blanqui, Frédéric et Hermant, Olivier Informatique université Paris-Saclay 2020. URL:  
 1066 <http://www.theses.fr/2020UPASG045>.
- 1067 16 Robert Harper. An equational logical framework for type theories. *arXiv preprint*  
 1068 *arXiv:2106.01484*, 2021.
- 1069 17 Robert Harper, Furio Honsell, and Gordon Plotkin. A framework for defining logics. *J. ACM*,  
 1070 40(1):143–184, January 1993. doi:10.1145/138027.138060.
- 1071 18 Gabriel Hondet and Frédéric Blanqui. Encoding of Predicate Subtyping with Proof Irrelevance  
 1072 in the  $\lambda\Pi$ -Calculus Modulo Theory. In Ugo de'Liguoro, Stefano Berardi, and Thorsten  
 1073 Altenkirch, editors, *26th International Conference on Types for Proofs and Programs (TYPES*  
 1074 *2020)*, volume 188 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 6:1–6:18,  
 1075 Dagstuhl, Germany, 2021. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: <https://drops.dagstuhl.de/opus/volltexte/2021/13885>, doi:10.4230/LIPIcs.TYPES.2020.6.
- 1076 19 Jan Willem Klop, Vincent van Oostrom, and Femke van Raamsdonk. Combinatory reduction  
 1077 systems: introduction and survey. *Theoretical Computer Science*, 121(1):279–308, 1993. URL:  
 1078 <https://www.sciencedirect.com/science/article/pii/0304397593900917>, doi:[https://doi.org/10.1016/0304-3975\(93\)90091-7](https://doi.org/10.1016/0304-3975(93)90091-7).
- 1080 20 Paul-André Melliès and Benjamin Werner. A generic normalisation proof for pure type systems.  
 1081 In Eduardo Giménez and Christine Paulin-Mohring, editors, *Types for Proofs and Programs*,  
 1082 pages 254–276, Berlin, Heidelberg, 1998. Springer Berlin Heidelberg.
- 1083 21 Vincent Siles and Hugo Herbelin. Pure type system conversion is always typable. *Journal of*  
 1084 *Functional Programming*, 22:153 – 180, 2012.
- 1085 22 François Thiré. Sharing a library between proof assistants: Reaching out to the HOL family. In  
 1086 Frédéric Blanqui and Giselle Reis, editors, *Proceedings of the 13th International Workshop on*  
 1087 *Logical Frameworks and Meta-Languages: Theory and Practice, LFMTP@FSCD 2018, Oxford,*  
 1088 *UK, 7th July 2018*, volume 274 of *EPTCS*, pages 57–71, 2018. doi:10.4204/EPTCS.274.5.
- 1089 23 François Thiré. *Interoperability between proof systems using the logical framework Dedukti*.  
 1090 PhD thesis, ENS Paris-Saclay, 2020.