

# Generic Bidirectional Typing for Dependent Type Theories

Thiago Felicissimo

Proofs and algorithms seminar

16 December 2024

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

**Fully-annotated syntax** keeps track of all annotations

$$t @_{A,x.B} u \quad \langle t, u \rangle_{A,x.B} \quad t ::_A l \quad \dots$$

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

**Fully-annotated syntax** keeps track of all annotations

$$t @_{A,x.B} u \quad \langle t, u \rangle_{A,x.B} \quad t ::_A l \quad \dots$$

What one gets when looking at semantics of type theory

Arguably the most canonical choice

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

**Fully-annotated syntax** keeps track of all annotations

$$t @_{A,x.B} u \quad \langle t, u \rangle_{A,x.B} \quad t ::_A l \quad \dots$$

What one gets when looking at semantics of type theory

Arguably the most canonical choice, but the syntax is unusable in practice...

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

**Fully-annotated syntax** keeps track of all annotations

$$t @_{A,x.B} u \quad \langle t, u \rangle_{A,x.B} \quad t ::_A l \quad \dots$$

What one gets when looking at semantics of type theory

Arguably the most canonical choice, but the syntax is unusable in practice...

**Non-annotated syntax** restores usability by eliding parameter annotations

$$t u \quad \langle t, u \rangle \quad t :: l \quad \dots$$

# The syntax of type theory

When defining syntax of programming languages and type theories, many choices:

**Fully-annotated syntax** keeps track of all annotations

$$t @_{A,x.B} u \quad \langle t, u \rangle_{A,x.B} \quad t ::_A l \quad \dots$$

What one gets when looking at semantics of type theory

Arguably the most canonical choice, but the syntax is unusable in practice...

**Non-annotated syntax** restores usability by eliding parameter annotations

$$t u \quad \langle t, u \rangle \quad t :: l \quad \dots$$

Syntax so common that many don't realize that an omission is being made

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash A \text{ type} \quad \Gamma, x : A \vdash B \text{ type} \quad \Gamma \vdash t : \Pi x : A. B \quad \Gamma \vdash u : A}{\Gamma \vdash t \ u : B[u/x]}$$



# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C \quad C \longrightarrow^* \Pi x : A. B \quad \Gamma \vdash u \Leftarrow A}{\Gamma \vdash t u \Rightarrow B[u/x]}$$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow ?}{\Gamma \vdash t u \Rightarrow ?}$$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C}{\Gamma \vdash t u \Rightarrow ?}$$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C \quad C \longrightarrow^* \Pi x : A. B}{\Gamma \vdash t u \Rightarrow ?}$$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C \quad C \longrightarrow^* \Pi x : A.B \quad \Gamma \vdash u \Leftarrow A}{\Gamma \vdash t u \Rightarrow ?}$$

# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C \quad C \longrightarrow^* \Pi x : A. B \quad \Gamma \vdash u \Leftarrow A}{\Gamma \vdash t u \Rightarrow B[u/x]}$$



# Typechecking without annotations

**Omission has a cost** Knowing annotations is needed for typing

$$\frac{\Gamma \vdash ? \text{ type} \quad \Gamma, x : ? \vdash ? \text{ type} \quad \Gamma \vdash t : ? \quad \Gamma \vdash u : ?}{\Gamma \vdash t u : ?}$$

How to find  $A$  and  $B$  if they're not stored in syntax?

**Bidirectional typing** Decompose  $t : A$  in modes check  $t \Leftarrow A$  and infer  $t \Rightarrow A$

Allow specify flow of type information in typing rules, explain how to use them

$$\frac{\Gamma \vdash t \Rightarrow C \quad C \longrightarrow^* \Pi x : A. B \quad \Gamma \vdash u \Leftarrow A}{\Gamma \vdash t u \Rightarrow B[u/x]}$$

Complements unannotated syntax, *locally* explains how to recover annotations

# Contribution

Bidirectional type systems have been studied and proposed for many theories

However, general guidelines have remained informal, no unified framework

# Contribution

Bidirectional type systems have been studied and proposed for many theories

However, general guidelines have remained informal, no unified framework

**This work** *Generic* account of bidirectional typing for class of type theories

# Contribution

Bidirectional type systems have been studied and proposed for many theories

However, general guidelines have remained informal, no unified framework

**This work** *Generic* account of bidirectional typing for class of type theories

## Roadmap

# Contribution

Bidirectional type systems have been studied and proposed for many theories

However, general guidelines have remained informal, no unified framework

**This work** *Generic* account of bidirectional typing for class of type theories

## Roadmap

1. We give a general definition of bidirectional type theory

# Contribution

Bidirectional type systems have been studied and proposed for many theories  
However, general guidelines have remained informal, no unified framework

**This work** *Generic* account of bidirectional typing for class of type theories

## Roadmap

1. We give a general definition of bidirectional type theory
2. For each theory, we define declarative and bidirectional type systems

# Contribution

Bidirectional type systems have been studied and proposed for many theories  
However, general guidelines have remained informal, no unified framework

**This work** *Generic* account of bidirectional typing for class of type theories

## Roadmap

1. We give a general definition of bidirectional type theory
2. For each theory, we define declarative and bidirectional type systems
3. We show, in a theory-independent fashion, their equivalence

# BiTTs: A theory-independent bidirectional type-checker

Our framework not only of theoretic interest, also has practical applications



# BiTTs: A theory-independent bidirectional type-checker

Our framework not only of theoretic interest, also has practical applications

Implemented in the theory-independent bidirectional type-checker BiTTs

```
(* Equality *)
constructor Eq () (A : Ty, x : Tm(A), y : Tm(A)) : Ty

constructor refl (A : Ty, x : Tm(A), y : Tm(A)) () (x = y : Tm(A)) : Tm(Eq(A, x, y))

destructor J (A : Ty, x : Tm(A), y : Tm(A))
  [t : Tm(Eq(A, x, y))]
  (P{y : Tm(A), e : Tm(Eq(A, x, y))} : Ty, p : Tm(P{x, refl}))
  : Tm(P{y, t})

equation J(refl, y e. P{y, e}, p) --> p

(* some basic properties of equality *)
let sym : Tm(Π(U, a. Π(El(a), x. Π(El(a), y. Π(Eq(El(a), x, y), _. Eq(El(a), y, x))))))
  := λ(a. λ(x. λ(y. λ(p. J(p, z q. Eq(El(a), z, x), refl)))))

let trans : Tm(Π(U, a. Π(El(a), x. Π(El(a), y. Π(El(a), z. Π(Eq(El(a), x, y), _. Π(Eq(El(a), y, z), _. Eq(El(a), x, z)))))))
  := λ(a. λ(x. λ(y. λ(z. λ(p. λ(q. J(q, k r. Eq(El(a), x, k), p)))))

let transp : Tm(Π(U, a. Π(U, b. Π(Eq(U, a, b), _. Π(El(a), _. El(b)))))
  := λ(a. λ(b. λ(p. λ(x. J(p, z q. El(z), x)))))
```

# The theories

## The theories

A *bidirectional theory*  $\mathbb{T}^b$  is made of *schematic typing rules* and *rewrite rules*

## The theories

A *bidirectional theory*  $\mathbb{T}^b$  is made of *schematic typing rules* and *rewrite rules*

Three kinds of schematic typing rules: *sort rules*, *constructor rules*, *destructor rules*

## The theories

A *bidirectional theory*  $\mathbb{T}^b$  is made of *schematic typing rules* and *rewrite rules*

Three kinds of schematic typing rules: *sort rules*, *constructor rules*, *destructor rules*

**Sort rules**<sup>1</sup> Sorts are terms  $T$  that can appear to the right in judgment  $t : T$

Used to define the *judgment forms* of the theory

---

<sup>1</sup>We use the name "sort" instead of "type" to avoid a name clash with the types of the theory

## The theories

A *bidirectional theory*  $\mathbb{T}^b$  is made of *schematic typing rules* and *rewrite rules*

Three kinds of schematic typing rules: *sort rules*, *constructor rules*, *destructor rules*

**Sort rules**<sup>1</sup> Sorts are terms  $T$  that can appear to the right in judgment  $t : T$

Used to define the *judgment forms* of the theory

Example: In MLTT, 2 judgment forms: " $\Box$  type" and " $\Box : A$ " for a type  $A$ .

---

<sup>1</sup>We use the name "sort" instead of "type" to avoid a name clash with the types of the theory

# The theories

A *bidirectional theory*  $\mathbb{T}^b$  is made of *schematic typing rules* and *rewrite rules*

Three kinds of schematic typing rules: *sort rules*, *constructor rules*, *destructor rules*

**Sort rules**<sup>1</sup> Sorts are terms  $T$  that can appear to the right in judgment  $t : T$

Used to define the *judgment forms* of the theory

Example: In MLTT, 2 judgment forms: " $\Box$  type" and " $\Box : A$ " for a type  $A$ .

$$\frac{}{\mathbf{Ty} \text{ sort}}$$
$$A \text{ type} \quad \rightsquigarrow \quad A : \mathbf{Ty}$$
$$\frac{A : \mathbf{Ty}}{\mathbf{Tm}(A) \text{ sort}}$$
$$t : A \quad \rightsquigarrow \quad t : \mathbf{Tm}(A)$$

---

<sup>1</sup>We use the name "sort" instead of "type" to avoid a name clash with the types of the theory

# Constructor rules

Term-level rules split between *constructors* and *destructors*



## Constructor rules

Term-level rules split between *constructors* and *destructors*

**Constructor rules** In bidirectional typing, constructors support *checking*

Missing information recovered from the sort given as input

The sort of the rule should be a linear (Miller) *pattern*  $T^P$  on the missing arguments

## Constructor rules

Term-level rules split between *constructors* and *destructors*

**Constructor rules** In bidirectional typing, constructors support *checking*

Missing information recovered from the sort given as input

The sort of the rule should be a linear (Miller) *pattern*  $T^P$  on the missing arguments

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty}}{\Pi(A, x.B\{x\}) : \mathbf{Ty}}$$

## Constructor rules

Term-level rules split between *constructors* and *destructors*

**Constructor rules** In bidirectional typing, constructors support *checking*

Missing information recovered from the sort given as input

The sort of the rule should be a linear (Miller) *pattern*  $T^P$  on the missing arguments

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty}}{\Pi(A, x.B\{x\}) : \mathbf{Ty}}$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))}$$

## Destructor rules & Rewrite rules

**Destructor rules** In bidirectional typing, destructors support *inference*

Missing arguments are recovered by inferring the *principal argument*  $t : T^P$

Sort of the principal argument  $t : T^P$  should be a pattern on the missing arguments

## Destructor rules & Rewrite rules

**Destructor rules** In bidirectional typing, destructors support *inference*

Missing arguments are recovered by inferring the *principal argument*  $t : T^P$

Sort of the principal argument  $t : T^P$  should be a pattern on the missing arguments

$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad t : \text{Tm}(\Pi(A, x.B\{x\})) \quad u : \text{Tm}(A)}{@(t, u) : \text{Tm}(B\{u\})}$$

## Destructor rules & Rewrite rules

**Destructor rules** In bidirectional typing, destructors support *inference*

Missing arguments are recovered by inferring the *principal argument*  $t : T^P$

Sort of the principal argument  $t : T^P$  should be a pattern on the missing arguments

$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad t : \text{Tm}(\Pi(A, x.B\{x\})) \quad u : \text{Tm}(A)}{@(t, u) : \text{Tm}(B\{u\})}$$

Destructors written in **orange**, constructors and sorts written in **blue**

## Destructor rules & Rewrite rules

**Destructor rules** In bidirectional typing, destructors support *inference*

Missing arguments are recovered by inferring the *principal argument*  $t : T^P$

Sort of the principal argument  $t : T^P$  should be a pattern on the missing arguments

$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad t : \text{Tm}(\Pi(A, x.B\{x\})) \quad u : \text{Tm}(A)}{@(t, u) : \text{Tm}(B\{u\})}$$

Destructors written in orange, constructors and sorts written in blue

**Rewrite rules** Specify the conversion of the theory

$$@(\lambda(x.t\{x\}), u) \longmapsto t\{u\}$$

In general, of the form  $l^P \longmapsto r$

## Full example, in the *formal* notation

Previous inference-rule notation can be desugared into a formal notation



## Full example, in the *formal* notation

Previous inference-rule notation can be desugared into a formal notation

**Theory**  $\mathbb{T}_{\lambda\Pi}^b$  A minimalistic type theory with only dependent functions

$\mathbf{Ty}(\cdot)$  sort

$\mathbf{Tm}(A : \mathbf{Ty})$  sort

$\Pi(\cdot; A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}) : \mathbf{Ty}$

$\lambda(A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}; t\{x : \mathbf{Tm}(A)\} : \mathbf{Tm}(B\{x\})) : \mathbf{Tm}(\Pi(A, x.B\{x\}))$

$@(A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}; t : \mathbf{Tm}(\Pi(A, x.B\{x\})); u : \mathbf{Tm}(A)) : \mathbf{Tm}(B\{u\})$

$@(\lambda(x.t\{x\}), u) \longmapsto t\{u\}$

## Full example, in the *formal* notation

Previous inference-rule notation can be desugared into a formal notation

**Theory**  $\mathbb{T}_{\lambda\Pi}^b$  A minimalistic type theory with only dependent functions

$\mathbf{Ty}(\cdot)$  sort

$\mathbf{Tm}(A : \mathbf{Ty})$  sort

$\Pi(\cdot; A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}) : \mathbf{Ty}$

$\lambda(A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}; t\{x : \mathbf{Tm}(A)\} : \mathbf{Tm}(B\{x\})) : \mathbf{Tm}(\Pi(A, x.B\{x\}))$

$@(A : \mathbf{Ty}, B\{x : \mathbf{Tm}(A)\} : \mathbf{Ty}; t : \mathbf{Tm}(\Pi(A, x.B\{x\})); u : \mathbf{Tm}(A)) : \mathbf{Tm}(B\{u\})$

$@(\lambda(x.t\{x\}), u) \longmapsto t\{u\}$

In the rest of the talk, we use the inference-rule notation for readability ☺

# **Declarative type system**

# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

## Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad x : \text{Tm}(A) \vdash t : \text{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \text{Tm}(\Pi(A, x.B\{x\}))}$$

# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{\begin{array}{c} A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \\ x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\}) \end{array}}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\begin{array}{c} \Gamma \vdash A : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \\ \Gamma, x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B) \end{array}}{\Gamma \vdash \lambda(x.t) : \mathbf{Tm}(\Pi(A, x.B))}$$

# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad x : \text{Tm}(A) \vdash t : \text{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \text{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\Gamma \vdash A : \text{Ty} \quad \Gamma, x : \text{Tm}(A) \vdash B : \text{Ty} \quad \Gamma, x : \text{Tm}(A) \vdash t : \text{Tm}(B)}{\Gamma \vdash \lambda(x.t) : \text{Tm}(\Pi(A, x.B))}$$
$$\frac{A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \quad t : \text{Tm}(\Pi(A, x.B\{x\})) \quad u : \text{Tm}(A)}{@(t, u) : \text{Tm}(B\{u\})}$$



# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\begin{array}{c} \frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))} \\ \sim \frac{\Gamma \vdash A : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B)}{\Gamma \vdash \lambda(x.t) : \mathbf{Tm}(\Pi(A, x.B))} \end{array}$$
  
$$\begin{array}{c} \frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Pi(A, x.B\{x\})) \quad u : \mathbf{Tm}(A)}{@(t, u) : \mathbf{Tm}(B\{u\})} \\ \sim \frac{\Gamma \vdash A : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad \Gamma \vdash t : \mathbf{Tm}(\Pi(A, x.B)) \quad \Gamma \vdash u : \mathbf{Tm}(A)}{\Gamma \vdash @(t, u) : \mathbf{Tm}(B[u/x])} \end{array}$$

# Declarative type system

Each  $\mathbb{T}^b$  defines a declarative type system, with main judgment  $\Gamma \vdash t : T$

Main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\Gamma \vdash A : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B)}{\Gamma \vdash \lambda(x.t) : \mathbf{Tm}(\Pi(A, x.B))}$$
$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Pi(A, x.B\{x\})) \quad u : \mathbf{Tm}(A)}{@(t, u) : \mathbf{Tm}(B\{u\})} \quad \rightsquigarrow \quad \frac{\Gamma \vdash A : \mathbf{Ty} \quad \Gamma, x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad \Gamma \vdash t : \mathbf{Tm}(\Pi(A, x.B)) \quad \Gamma \vdash u : \mathbf{Tm}(A)}{\Gamma \vdash @(t, u) : \mathbf{Tm}(B[u/x])}$$

**Note that** typing terms bottom-up requires guessing  $A$  and  $B$

# Meta-theory of the declarative system

We establish basic metaproperties of the declarative system, such as:

## Meta-theory of the declarative system

We establish basic metaproperties of the declarative system, such as:

**Weakening** The following rule is admissible

$$\frac{\Delta \vdash t : T \quad \Gamma \vdash}{\Gamma \vdash t : T} \Delta \sqsubseteq \Gamma$$

## Meta-theory of the declarative system

We establish basic metaproperties of the declarative system, such as:

**Weakening** The following rule is admissible

$$\frac{\Delta \vdash t : T \quad \Gamma \vdash \Delta \sqsubseteq \Gamma}{\Gamma \vdash t : T}$$

**Substitution property** The following rule is admissible

$$\frac{\Gamma \vdash \vec{u} : \Delta \quad \Delta \vdash t : T}{\Gamma \vdash t[\vec{u}/\vec{x}_\Delta] : T[\vec{u}/\vec{x}_\Delta]}$$

## Meta-theory of the declarative system

We establish basic metaproperties of the declarative system, such as:

**Weakening** The following rule is admissible

$$\frac{\Delta \vdash t : T \quad \Gamma \vdash}{\Gamma \vdash t : T} \Delta \sqsubseteq \Gamma$$

**Substitution property** The following rule is admissible

$$\frac{\Gamma \vdash \vec{u} : \Delta \quad \Delta \vdash t : T}{\Gamma \vdash t[\vec{u}/\vec{x}_\Delta] : T[\vec{u}/\vec{x}_\Delta]}$$

Not shown for one theory, but generically for all bidirectional theories  $\mathbb{T}^b$

# **Bidirectional type system**

## Matching modulo for recovering arguments

In bidirectional typing, we need matching modulo to recover missing arguments

$$\frac{\Gamma \vdash t \Rightarrow U \quad \dots}{\Gamma \vdash @ (t, u) \Rightarrow}$$



## Matching modulo for recovering arguments

In bidirectional typing, we need matching modulo to recover missing arguments

$$\frac{\Gamma \vdash t \Rightarrow U \quad \dots}{\Gamma \vdash @ (t, u) \Rightarrow}$$

If  $@ (t, u)$  is well-typed (in the declarative system), for some  $A, B$  we have

$$U \equiv \mathbf{Tm}(\Pi(A, x.B\{x\}))[A/A, x.B/B]$$

but how to recover  $A$  and  $B$  from  $U$ ?

## Matching modulo for recovering arguments

In bidirectional typing, we need matching modulo to recover missing arguments

$$\frac{\Gamma \vdash t \Rightarrow U \quad \dots}{\Gamma \vdash @ (t, u) \Rightarrow}$$

If  $@ (t, u)$  is well-typed (in the declarative system), for some  $A, B$  we have

$$U \equiv \mathbf{Tm}(\Pi(A, x.B\{x\}))[A/A, x.B/B]$$

but how to recover  $A$  and  $B$  from  $U$ ?

**Solution** Given  $T^P$  and  $U$ , we have an algorithmic matching judgment

$$T^P < U \rightsquigarrow \vec{x}_1.t_1/x_1, \dots, \vec{x}_k.t_k/x_k$$

that tries to compute  $t_1, \dots, t_k$  s.t.  $T^P[\vec{x}_1.t_1/x_1, \dots, \vec{x}_k.t_k/x_k] \equiv U$

## Bidirectional syntax

Not all unannotated terms can be algorithmically typed

$$\frac{\begin{array}{c} ? \\ \hline \Gamma \vdash \lambda(x.t) \Rightarrow ? \end{array} \quad \dots}{\Gamma \vdash @(\lambda(x.t), u) \Rightarrow ?}$$

## Bidirectional syntax

Not all unannotated terms can be algorithmically typed

$$\frac{\frac{?}{\Gamma \vdash \lambda(x.t) \Rightarrow ?} \quad \dots}{\Gamma \vdash @(\lambda(x.t), u) \Rightarrow ?}$$

Limitation not specific to bidirectional typing, undecidable in general!

## Bidirectional syntax

Not all unannotated terms can be algorithmically typed

$$\frac{\begin{array}{c} ? \\ \hline \Gamma \vdash \lambda(x.t) \Rightarrow ? \end{array} \quad \dots}{\Gamma \vdash @(\lambda(x.t), u) \Rightarrow ?}$$

Limitation not specific to bidirectional typing, undecidable in general!

Bidirectional system defined over *inferred* and *checkable* terms

$$\boxed{\text{Tm}^i} \ni \quad t^i, u^i ::= x \mid d(t^i, \vec{x}_1.u_1^c, \dots, \vec{x}_k.u_k^c) \mid t^c :: T^c$$
$$\boxed{\text{Tm}^c} \ni \quad t^c, u^c ::= c(\vec{x}_1.u_1^c, \dots, \vec{x}_k.u_k^c) \mid \underline{\quad}^i$$

## Bidirectional syntax

Not all unannotated terms can be algorithmically typed

$$\frac{\begin{array}{c} ? \\ \hline \Gamma \vdash \lambda(x.t) \Rightarrow ? \end{array} \quad \dots}{\Gamma \vdash @(\lambda(x.t), u) \Rightarrow ?}$$

Limitation not specific to bidirectional typing, undecidable in general!

Bidirectional system defined over *inferred* and *checkable* terms

$$\begin{array}{l} \boxed{Tm^i} \ni \quad t^i, u^i ::= x \mid d(t^i, \vec{x}_1.u_1^c, \dots, \vec{x}_k.u_k^c) \mid t^c :: T^c \\ \boxed{Tm^c} \ni \quad t^c, u^c ::= c(\vec{x}_1.u_1^c, \dots, \vec{x}_k.u_k^c) \mid \underline{\quad}^i \end{array}$$

When destructor meets a constructor, we need an *ascription*, in the style of McBride:

$$@(\lambda(x.t^c) :: T^c, u^c)$$

## Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

## Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :



## Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{\begin{array}{l} A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \\ x : \text{Tm}(A) \vdash t : \text{Tm}(B\{x\}) \end{array}}{\lambda(x.t\{x\}) : \text{Tm}(\Pi(A, x.B\{x\}))}$$

## Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{\begin{array}{l} A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \\ x : \text{Tm}(A) \vdash t : \text{Tm}(B\{x\}) \end{array}}{\lambda(x.t\{x\}) : \text{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\begin{array}{l} \text{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \\ \Gamma, x : \text{Tm}(A) \vdash t^c \Leftarrow \text{Tm}(B) \end{array}}{\Gamma \vdash \lambda(x.t^c) \Leftarrow T}$$

# Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\begin{array}{c}
 A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \\
 x : \text{Tm}(A) \vdash t : \text{Tm}(B\{x\}) \\
 \hline
 \lambda(x.t\{x\}) : \text{Tm}(\Pi(A, x.B\{x\}))
 \end{array}
 \quad \rightsquigarrow \quad
 \begin{array}{c}
 \text{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \\
 \Gamma, x : \text{Tm}(A) \vdash t^c \Leftarrow \text{Tm}(B) \\
 \hline
 \Gamma \vdash \lambda(x.t^c) \Leftarrow T
 \end{array}$$

$$\begin{array}{c}
 A : \text{Ty} \quad x : \text{Tm}(A) \vdash B : \text{Ty} \\
 t : \text{Tm}(\Pi(A, x.B\{x\})) \quad u : \text{Tm}(A) \\
 \hline
 @ (t, u) : \text{Tm}(B\{u\})
 \end{array}$$

# Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\mathbf{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \quad \Gamma, x : \mathbf{Tm}(A) \vdash t^c \Leftarrow \mathbf{Tm}(B)}{\Gamma \vdash \lambda(x.t^c) \Leftarrow T}$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Pi(A, x.B\{x\})) \quad u : \mathbf{Tm}(A)}{@(t, u) : \mathbf{Tm}(B\{u\})} \quad \rightsquigarrow \quad \frac{\Gamma \vdash t^i \Rightarrow T \quad \mathbf{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \quad \Gamma \vdash u^c \Leftarrow \mathbf{Tm}(A)}{\Gamma \vdash @(t^i, u^c) \Rightarrow \mathbf{Tm}(B[\ulcorner u^c \urcorner / x])^2}$$

<sup>2</sup>Given  $t^i$  or  $u^c$ , I write  $\ulcorner t^i \urcorner$  or  $\ulcorner u^c \urcorner$  for the underlying regular term.

# Bidirectional typing rules

Each  $\mathbb{T}^b$  defines a bid. type system with judgments  $\Gamma \vdash t^c \Leftarrow T$  and  $\Gamma \vdash t^i \Rightarrow T$

The main typing rules instantiate the schematic rules of  $\mathbb{T}^b$ :

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash t : \mathbf{Tm}(B\{x\})}{\lambda(x.t\{x\}) : \mathbf{Tm}(\Pi(A, x.B\{x\}))} \quad \rightsquigarrow \quad \frac{\mathbf{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \quad \Gamma, x : \mathbf{Tm}(A) \vdash t^c \Leftarrow \mathbf{Tm}(B)}{\Gamma \vdash \lambda(x.t^c) \Leftarrow T}$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Pi(A, x.B\{x\})) \quad u : \mathbf{Tm}(A)}{@(t, u) : \mathbf{Tm}(B\{u\})} \quad \rightsquigarrow \quad \frac{\Gamma \vdash t^i \Rightarrow T \quad \mathbf{Tm}(\Pi(A, x.B\{x\})) < T \rightsquigarrow A/A, x.B/B \quad \Gamma \vdash u^c \Leftarrow \mathbf{Tm}(A)}{\Gamma \vdash @(t^i, u^c) \Rightarrow \mathbf{Tm}(B[\ulcorner u^c \urcorner / x])^2}$$

**Note that** no more need to guess  $A$  and  $B$ !

<sup>2</sup>Given  $t^i$  or  $u^c$ , I write  $\ulcorner t^i \urcorner$  or  $\ulcorner u^c \urcorner$  for the underlying regular term.

# Equivalence with declarative typing

(Suppose underlying  $\mathbb{T}^b$  is *valid*)

# Equivalence with declarative typing

(Suppose underlying  $\mathbb{T}^b$  is *valid*)

**Soundness** If  $\Gamma \vdash$  and  $\Gamma \vdash t^i \Rightarrow T$  then  $\Gamma \vdash \ulcorner t^i \urcorner : T$

If  $\Gamma \vdash T$  sort and  $\Gamma \vdash t^c \Leftarrow T$  then  $\Gamma \vdash \ulcorner t^c \urcorner : T$

# Equivalence with declarative typing

(Suppose underlying  $\mathbb{T}^b$  is *valid*)

**Soundness** If  $\Gamma \vdash$  and  $\Gamma \vdash t^i \Rightarrow T$  then  $\Gamma \vdash \ulcorner t^i \urcorner : T$

If  $\Gamma \vdash T$  sort and  $\Gamma \vdash t^c \Leftarrow T$  then  $\Gamma \vdash \ulcorner t^c \urcorner : T$

**Annotability** If  $\Gamma \vdash t : T$  then for some  $u^c$  with  $\ulcorner u^c \urcorner = t$  we have  $\Gamma \vdash u^c \Leftarrow T$



# Equivalence with declarative typing

(Suppose underlying  $\mathbb{T}^b$  is *valid*)

**Soundness** If  $\Gamma \vdash$  and  $\Gamma \vdash t^i \Rightarrow T$  then  $\Gamma \vdash \ulcorner t^i \urcorner : T$

If  $\Gamma \vdash T$  sort and  $\Gamma \vdash t^c \Leftarrow T$  then  $\Gamma \vdash \ulcorner t^c \urcorner : T$

**Annotability** If  $\Gamma \vdash t : T$  then for some  $u^c$  with  $\ulcorner u^c \urcorner = t$  we have  $\Gamma \vdash u^c \Leftarrow T$

**Decidability** If  $\mathbb{T}$  normalizing, then inference is decidable for inferable terms, and checking is decidable for checkable terms

# Equivalence with declarative typing

(Suppose underlying  $\mathbb{T}^b$  is *valid*)

**Soundness** If  $\Gamma \vdash$  and  $\Gamma \vdash t^i \Rightarrow T$  then  $\Gamma \vdash \ulcorner t^i \urcorner : T$

If  $\Gamma \vdash T$  sort and  $\Gamma \vdash t^c \Leftarrow T$  then  $\Gamma \vdash \ulcorner t^c \urcorner : T$

**Annotability** If  $\Gamma \vdash t : T$  then for some  $u^c$  with  $\ulcorner u^c \urcorner = t$  we have  $\Gamma \vdash u^c \Leftarrow T$

**Decidability** If  $\mathbb{T}$  normalizing, then inference is decidable for inferable terms, and checking is decidable for checkable terms

Not shown for one particular theory, but for *all* instances of our framework

**More examples**

# Dependent sums

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty}}{\Sigma(A, x.B\{x\}) : \mathbf{Ty}}$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Sigma(A, x.B\{x\}))}{\mathbf{proj}_1(t) : \mathbf{Tm}(A)}$$

$$\mathbf{proj}_1(\mathbf{pair}(t, u)) \mapsto t$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(A) \quad u : \mathbf{Tm}(B\{t\})}{\mathbf{pair}(t, u) : \mathbf{Tm}(\Sigma(A, x.B\{x\}))}$$

$$\frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \vdash B : \mathbf{Ty} \quad t : \mathbf{Tm}(\Sigma(A, x.B\{x\}))}{\mathbf{proj}_2(t) : \mathbf{Tm}(B\{\mathbf{proj}_1(t)\})}$$

$$\mathbf{proj}_2(\mathbf{pair}(t, u)) \mapsto u$$

# Lists

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\begin{array}{c} \frac{A : \mathbf{Ty}}{\mathbf{List}(A) : \mathbf{Ty}} \qquad \frac{A : \mathbf{Ty}}{\mathbf{nil} : \mathbf{Tm}(\mathbf{List}(A))} \qquad \frac{A : \mathbf{Ty} \quad x : \mathbf{Tm}(A) \quad l : \mathbf{Tm}(\mathbf{List}(A))}{\mathbf{cons}(x, l) : \mathbf{Tm}(\mathbf{List}(A))} \\[2ex] \frac{A : \mathbf{Ty} \quad l : \mathbf{Tm}(\mathbf{List}(A)) \quad x : \mathbf{Tm}(\mathbf{List}(A)) \vdash P : \mathbf{Ty} \quad \mathbf{pnil} : \mathbf{Tm}(P\{\mathbf{nil}\}) \quad x : \mathbf{Tm}(A), y : \mathbf{Tm}(\mathbf{List}(A)), z : \mathbf{Tm}(P\{y\}) \vdash \mathbf{pcons} : \mathbf{Tm}(P\{\mathbf{cons}(x, y)\})}{\mathbf{ListRec}(l, x.P\{x\}, \mathbf{pnil}, xyz.\mathbf{pcons}\{x, y, z\}) : \mathbf{Tm}(P\{l\})} \\[2ex] \mathbf{ListRec}(\mathbf{nil}, x.P\{x\}, \mathbf{pnil}, xyz.\mathbf{pcons}\{x, y, z\}) \longmapsto \mathbf{pnil} \\ \mathbf{ListRec}(\mathbf{cons}(x, l), x.P\{x\}, \mathbf{pnil}, xyz.\mathbf{pcons}\{x, y, z\}) \longmapsto \\ \mathbf{pcons}\{x, l, \mathbf{ListRec}(l; x.P\{x\}, \mathbf{pnil}, xyz.\mathbf{pcons}\{x, y, z\})\} \end{array}$$

# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)$

$\text{Eq}(A, a, b) : \text{Ty}$

$A : \text{Ty} \quad a : \text{Tm}(A)$

$\text{refl} : \text{Tm}(\text{Eq}(A, a, a))$

$A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b)$

$x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\})$

$J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})$

$J(\text{refl}, xy.P\{x, y\}, p) \mapsto p$

# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)$

$\text{Eq}(A, a, b) : \text{Ty}$

$A : \text{Ty} \quad a : \text{Tm}(A)$

$\text{refl} : \text{Tm}(\text{Eq}(A, a, a))$

$A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b)$

$x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\})$

$J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})$

$J(\text{refl}, xy.P\{x, y\}, p) \mapsto p$

# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)}{\text{Eq}(A, a, b) : \text{Ty}} \qquad \frac{A : \text{Ty} \quad a : \text{Tm}(A)}{\text{refl} : \text{Tm}(\text{Eq}(A, a, a))}$$

$$\frac{\begin{array}{l} A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b) \\ x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\}) \end{array}}{J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})}$$

$$J(\text{refl}, xy.P\{x, y\}, p) \longmapsto p$$

Constructor rules need to be extended to account for *indexed* types:



# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)}{\text{Eq}(A, a, b) : \text{Ty}} \qquad \frac{A : \text{Ty} \quad a : \text{Tm}(A)}{\text{refl} : \text{Tm}(\text{Eq}(A, a, a))}$$

$$\frac{\begin{array}{l} A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b) \\ x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\}) \end{array}}{J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})}$$

$$J(\text{refl}, xy.P\{x, y\}, p) \longmapsto p$$

Constructor rules need to be extended to account for *indexed* types:

- Solution 1: Ad-hoc treatment of indices (see the TOPLAS paper)

# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)}{\text{Eq}(A, a, b) : \text{Ty}} \qquad \frac{A : \text{Ty} \quad a : \text{Tm}(A)}{\text{refl} : \text{Tm}(\text{Eq}(A, a, a))}$$
$$\frac{\begin{array}{l} A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b) \\ x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\}) \end{array}}{J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})}$$
$$J(\text{refl}, xy.P\{x, y\}, p) \longmapsto p$$

Constructor rules need to be extended to account for *indexed* types:

- Solution 1: Ad-hoc treatment of indices (see the TOPLAS paper)
- Solution 2: Equational premises (see my PhD thesis & implementation)

# Equality

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A)}{\text{Eq}(A, a, b) : \text{Ty}} \qquad \frac{A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad a \equiv b}{\text{refl} : \text{Tm}(\text{Eq}(A, a, b))}$$

$$\frac{\begin{array}{l} A : \text{Ty} \quad a : \text{Tm}(A) \quad b : \text{Tm}(A) \quad t : \text{Eq}(A, a, b) \\ x : \text{Tm}(A), y : \text{Tm}(\text{Eq}(A, a, x)) \vdash P : \text{Ty} \quad p : \text{Tm}(P\{a, \text{refl}\}) \end{array}}{J(t, xy.P\{x, y\}, p) : \text{Tm}(P\{b, t\})}$$

$$J(\text{refl}, xy.P\{x, y\}, p) \longmapsto p$$

Constructor rules need to be extended to account for *indexed* types:

- Solution 1: Ad-hoc treatment of indices (see the TOPLAS paper)
- Solution 2: Equational premises (see my PhD thesis & implementation)

# Vectors

Extends  $\mathbb{T}_{\lambda\Pi}^b$  with

$$\frac{A : \text{Ty} \quad n : \text{Tm}(\text{Nat})}{\text{Vec}(A, n) : \text{Ty}} \quad \frac{A : \text{Ty} \quad n : \text{Tm}(\text{Nat}) \quad n \equiv 0 : \text{Tm}(\text{Nat})}{\text{nil} : \text{Tm}(\text{Vec}(A, n))} \quad \frac{A : \text{Ty} \quad n, m : \text{Tm}(\text{Nat}) \quad x : \text{Tm}(A) \quad l : \text{Tm}(\text{Vec}(A, m)) \quad n \equiv S(m) : \text{Tm}(\text{Nat})}{\text{cons}(m, x, l) : \text{Tm}(\text{Vec}(A, n))}$$

$$\frac{\begin{array}{l} A : \text{Ty} \quad n : \text{Tm}(\text{Nat}) \quad l : \text{Tm}(\text{Vec}(A, n)) \\ x : \text{Tm}(\text{Nat}), y : \text{Tm}(\text{Vec}(A, x)) \vdash P : \text{Ty} \quad \text{pnil} : \text{Tm}(P\{0, \text{nil}\}) \\ x : \text{Tm}(\text{Nat}), y : \text{Tm}(A), z : \text{Tm}(\text{Vec}(A, x)), w : \text{Tm}(P\{x, z\}) \vdash \text{pcons} : \text{Tm}(P\{S(x), \text{cons}(x, y, z)\}) \end{array}}{\text{VecRec}(l, xy.P\{x, y\}, \text{pnil}, xyzw.\text{pcons}\{x, y, z, w\}) : \text{Tm}(P\{n, l\})}$$

$$\text{VecRec}(\text{nil}, x.P\{x\}, \text{pnil}, xyzw.\text{pcons}\{x, y, z, w\}) \mapsto \text{pnil}$$

$$\text{VecRec}(\text{cons}(n, x, l), x.P\{x\}, \text{pnil}, xyzw.\text{pcons}\{x, y, z, w\}) \mapsto \text{pcons}\{n, x, l, \text{VecRec}(l, x.P\{x\}, \text{pnil}, xyzw.\text{pcons}\{x, y, z, w\})\}$$

## Other examples

In the implementation at

`https://github.com/thiagofelicissimo/BiTTs`

you can also find:

- Tarski-, Russell- and Coquand-style universes, with/without cumulativity and universe polymorphism
- Flavours of Observational Type Theory
- A variant of Exceptional Type Theory (type theory with exceptions)

## Conclusion

## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

Beyond theoretic interest of understanding bidirectional typing formally,  
implementation BiTTs can also be used in practice for rechecking proofs



## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

Beyond theoretic interest of understanding bidirectional typing formally, implementation BiTTs can also be used in practice for rechecking proofs

**Future work**

## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

Beyond theoretic interest of understanding bidirectional typing formally, implementation BiTTs can also be used in practice for rechecking proofs

## Future work

1. Remove reliance on rewriting, to allow for  $\eta$ -rules and proof irrelevance  
Implementation would require a generic type-directed equality-checker

## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

Beyond theoretic interest of understanding bidirectional typing formally, implementation BiTTs can also be used in practice for rechecking proofs

## Future work

1. Remove reliance on rewriting, to allow for  $\eta$ -rules and proof irrelevance  
Implementation would require a generic type-directed equality-checker
2. Develop a framework for formalizing decidability of typing proofs  
Derivation of syntax, substitution, typing rules, etc automatic from  $\mathbb{T}^b$   
To prove decidability of typing, only need to show  $\mathbb{T}^b$  is valid and s.n.

## Conclusion

We have given a generic account of bidirectional typing for a class of type theories

Beyond theoretic interest of understanding bidirectional typing formally, implementation BiTTs can also be used in practice for rechecking proofs

## Future work

1. Remove reliance on rewriting, to allow for  $\eta$ -rules and proof irrelevance  
Implementation would require a generic type-directed equality-checker
2. Develop a framework for formalizing decidability of typing proofs  
Derivation of syntax, substitution, typing rules, etc automatic from  $\mathbb{T}^b$   
To prove decidability of typing, only need to show  $\mathbb{T}^b$  is valid and s.n.

Thank you for your attention!