

Using Formal Verification to Prove Properties of Lists Recursively Defined

Thiago Henrique Mata
Independent Researcher
thiago.henrique.mata@gmail.com
<https://thiagomata.com/>
<https://github.com/thiagomata>

Abstract

We define finite integer lists recursively and verify a property calculus for their structural and arithmetic operations in Scala Stainless. The verified results establish identities for indexed access and slicing, sum and product laws under concatenation, divisibility of list products by their elements, and preservation of element bounds through append and split. We also verify shifted-list laws preserving the period and relating adjacent values to gaps, together with rotation laws preserving membership, size, sum, and element bounds. Collectively, these properties describe how recursive finite sequences behave under decomposition, composition, aggregation, bounds, periodic shifts, and rotation.

Licensed under the Creative Commons Attribution 4.0 International License (CC BY 4.0):
<https://creativecommons.org/licenses/by/4.0/>.

1 Introduction

Lists are finite sequences of values that support a wide range of operations in functional and declarative programming. When combined with summation, they form the backbone for definitions of sequences, recurrence, accumulation, and integration in the discrete domain.

Our approach mirrors traditional recursive definitions but is formally verified using [Scala Stainless \[1\]](#), a verification framework for pure Scala programs that uses formal verification to ensure user-defined functions satisfy given preconditions, postconditions, and invariants through automated proofs under all valid inputs.

Formal verification is the act of proving or disproving the correctness of intended algorithms underlying a system with respect to a certain formal specification or property, using formal methods of mathematics. — Wikipedia on Formal Verification [4]

This article verifies:

- Index and access: tail shift, last element (Section 3).
- Slice: recursive, index-range, append consistency (Section 4).
- Sum: definition, concatenation, commutativity, positivity (Section 5).
- Product: definition, concatenation, commutativity, positivity (Section 6).

- Product divisibility: head, all elements, inserted element (Section 7).
- Bound and order: lower- and upper-bound propagation through append and split (Section 8).
- Slice equivalence (Section 9).
- Shifted list: period, gap identity, gap translation (Section 10).
- Rotation: permutation invariants (size, sum, bounds, membership) (Section 11).

Related work

Recursive lists, indexed access, and list splitting are long-established parts of formal libraries. The Rocq/Coq standard list library defines indexed access, prefix and suffix operations, and proves their reconstruction law `firstn n l ++ skipn n l = l` [3]. Lean’s mathematical library also formalizes list rotation through splitting and concatenation, including reduction of a rotation index modulo the list length [2].

These prior developments are useful points of contact for the present work. They show how a mature formal-mathematical setting treats familiar list structure, while this article develops and verifies the stated property package for a minimal recursive `BigInt` implementation in Scala Stainless. In particular, the article brings structural operations into the same checked development as product divisibility, numeric bounds, shifted-list gaps, and rotation invariants. The comparison is contextual rather than competitive: it locates the Stainless proofs in the wider body of formal work and makes both the overlap and the scope of this implementation clear.

2 Definitions

This section defines the list model itself. A list is either empty or a single value paired with a smaller list, and every operation used later in the article — size, append, slicing, indexing, sum, and product — is defined by recursion on that same head/tail decomposition.

2.1 List Construction

Let $\mathbb{L}$ be the set of all lists over a set S . A list is either the empty L_e or a non-empty list L_{node} , as follows:

2.2 Empty List

Let’s define an empty list L_e :

$$\begin{aligned} L_e &\in \mathbb{L} \\ L_e &= [] \end{aligned}$$

2.3 Recursive Definition of List

A non-empty list packages one value, its **head**, together with the remainder of the list, its **tail**, which is itself a smaller list. Every list in $\mathbb{L}$ is either the single empty list or one of these head/tail pairings, so the definition below builds the whole set $\mathbb{L}$ out of the already-defined L_e plus this one construction rule:

$$\begin{aligned}
\text{head} & \in \mathbb{S} \\
\text{tail} & \in \mathbb{L} \\
L_{\text{node}}(\text{head}, \text{tail}) & \in \mathbb{L}_{\text{node}} \\
\mathbb{L} = \{L_e\} \cup \{L_{\text{node}}(\text{head}, \text{tail}) \mid \text{head} \in \mathbb{S}, \text{tail} \in \mathbb{L}\}
\end{aligned}$$

Termination and cyclic references. Because all lists in this model are immutable, each application of $L_{\text{node}}(\text{head}, \text{tail})$ produces a distinct structural value without the possibility of cyclic references. Recursive functions over $\mathbb{L}$ terminate naturally, as a strictly decreasing structure defines size.

2.4 Elements Access and Indexing

The head/tail decomposition gives direct access to a list's first element and its remaining sublist. Indexing extends this one step at a time: position 0 is the head, and position $n > 0$ is found by re-indexing the tail at position $n - 1$, so reaching index n costs n recursive tail steps. The last element is the value at the final valid index, $|L| - 1$.

$$\begin{aligned}
\text{if } L_{\text{node}} = [v_0, v_1, \dots, v_{n-1}] & \implies L_{\text{node}} = (\text{head} : v_0, \text{tail} : [v_1, \dots, v_{n-1}]) \\
\text{head}(L_{\text{node}}) & = v_0 \\
\text{tail}(L_{\text{node}}) & = [v_1, \dots, v_{n-1}] \\
\text{last}(L_{\text{node}}) & = L_{\text{node}}(|L| - 1) \\
L_{\text{node}}(0) & = L_{(0)} = \text{head}(L_{\text{node}}) \\
L_{\text{node}}(n) & = L_{(n)} = \text{tail}(L_{\text{node}})(n - 1) \quad \forall n > 0
\end{aligned}$$

2.5 List Size

With the structure of lists defined, we now introduce a recursive definition for their size (or length). We define the size of a list L , $|L|$ as follows:

$$|L| = \begin{cases} 0 & \text{if } L = L_e \\ 1 + |\text{tail}(L)| & \text{otherwise} \end{cases}$$

The size of a list is zero for the empty list, or one plus the size of its tail otherwise. Proved in the native stainless library in `stainless.collection.List`.

2.6 List Append

Let $A, B \in \mathbb{L}$ over some set S . The append operation $A ++ B$ is defined recursively as:

$$A ++ B = \begin{cases} B & \text{if } A = L_e \\ L_{\text{node}}(\text{head}(A), \text{tail}(A) ++ B) & \text{otherwise} \end{cases}$$

Appending B onto an empty list yields B ; appending it onto a non-empty list keeps A 's head in place and appends B onto A 's tail. Proved in the native stainless library in `stainless.collection.List`.

2.7 List Slice

Let $L = [v_0, v_1, \dots, v_{n-1}]$, $i, j \in \mathbb{N}$, with $i \leq j < n$.

$$L[i \dots j] := [L_k \mid k \in \mathbb{N}, i \leq k \leq j]$$

The slice from i to j keeps exactly the elements at positions i through j , in order. The implementation of `slice` is available in [ListUtils](#). The full Scala verification code is in Appendix A.3.

2.8 List Sum

Let $\text{sum} : \mathbb{L} \Rightarrow \mathbb{S}$ be a recursively defined function:

$$\text{sum}(L) = \begin{cases} 0 & \text{if } L = L_e \\ \text{head}(L) + \text{sum}(\text{tail}(L)) & \text{otherwise} \end{cases}$$

The sum of an empty list is zero; the sum of a non-empty list is its head plus the sum of its tail. The implementation of `sum` is available in [ListUtils](#). The full Scala verification code is in Appendix A.7.

2.9 List Product

Let $\text{product} : \mathbb{L} \Rightarrow \mathbb{S}$ be a recursively defined function:

$$\text{product}(L) = \begin{cases} 1 & \text{if } L = L_e \\ \text{head}(L) \cdot \text{product}(\text{tail}(L)) & \text{otherwise} \end{cases}$$

The product of an empty list is one; a non-empty list's product is its head times the product of its tail. The implementation of `product` is available in [ListProduct](#). The full Scala verification code is in Appendices A.11 through A.15.

3 Index and Access Properties

How positions shift when the list is decomposed into head and tail, and how the last element relates to its index.

- [Tail access shift](#): $\text{tail}(L)[i] = L[i + 1]$ for $i < |\text{tail}(L)|$
- [Last element identity](#): $L[|L| - 1] = \text{last}(L)$

3.1 Tail Access Shift

Lemma: For any list L with at least two elements, accessing the i -th element of its tail is equivalent to accessing the $(i + 1)$ -th element of the list.

$$\forall L, i, \quad 1 < |L|, \quad 0 \leq i < |\text{tail}(L)| \implies \text{tail}(L)_{(i)} = L_{(i+1)}$$

Since:

$$\begin{array}{ll}
L = [x_0, x_1, x_2, \dots, x_{n-1}] & \text{[List definition]} \\
L = x_0 :: [x_1, x_2, \dots, x_{n-1}] & \text{[Cons definition]} \\
L = \text{head}(L) :: \text{tail}(L) & \text{[Head and Tail definition]} \\
\text{tail}(L) = [x_1, x_2, \dots, x_{n-1}] & \text{[Tail definition]} \\
\text{tail}(L)_i = x_{i+1} = L_{i+1} \quad \forall 0 \leq i < |\text{tail}(L)| & \blacksquare \quad \text{[Q.E.D.]}
\end{array}$$

This forward shift is verified in `ListUtilsProperties::accessTailShiftRight`. The reverse indexing form, $L_i = \text{tail}(L)_{i-1}$ for $i > 0$, is verified in `ListBoundUtils::assertTailShiftLeft`. The full Scala verification code is in Appendix A.1.

3.2 Last Element Identity

Lemma: The last element of a non-empty list is equal to the element at position $n - 1$, where $n = |L|$.

$$\forall L, |L| > 0 \implies \text{last}(L) = L_{(n-1)}$$

$$L = [x_0, x_1, \dots, x_{n-1}] \quad \text{[List definition]}$$

Base case: $|L| = 1$

$$\begin{array}{ll}
L = [x_0] & \text{[Singleton list]} \\
\text{last}(L) = x_0 = L_0 = L_{(n-1)} & \text{[Definition of last]}
\end{array}$$

Inductive step: $|L| > 1$

$$\begin{array}{ll}
L = x_0 :: \text{tail}(L) & \text{[Decomposition]} \\
\text{last}(L) = \text{last}(\text{tail}(L)) & \text{[Definition of last]} \\
\text{last}(\text{tail}(L)) = \text{tail}(L)_{(|\text{tail}(L)|-1)} & \text{[Inductive hypothesis]} \\
\text{tail}(L)_{(|\text{tail}(L)|-1)} = L_{(|L|-1)} & \text{[Tail Shift Position]} \\
\implies \text{last}(L) = L_{(|L|-1)} & \text{[By substitution]}
\end{array}$$

$\therefore$

$$\forall L, |L| > 0 \implies \text{last}(L) = L_{(|L|-1)} \quad \blacksquare$$

This property is verified in `ListUtilsProperties::assertLastEqualsLastPosition`. The full Scala verification code is in Appendix A.2.

3.3 Indexed Access Under Concatenation

Accessing a concatenated list at a given index routes to the matching side: an index inside the left list's range reads from the left list at that same index, and an index at or past the left list's size reads from the right list, offset by the left list's size.

$$\begin{array}{ll}
0 \leq k < |A| \implies (A ++ B)_k = A_k \\
|A| \leq k < |A| + |B| \implies (A ++ B)_k = B_{(k-|A|)}
\end{array}$$

Both directions are proved by induction on k : the left case peels one head element at a time until k reaches 0; the right case peels elements off A until it is exhausted, then indexes directly into B .

This property is verified in `ListUtilsProperties::assertAppendApplyLeft` and `ListUtilsProperties::assertAppendApplyRight`.

4 Slice Properties

Four constructions for extracting a sublist by index range — all equivalent.

- **Tail-recursive slice**: builds from the end by prepending
- **Head-recursive slice**: builds from the front
- **Index-range slice**: accumulates by position within a range
- **Slice append consistency**: appending a singleton preserves the slice structure

4.1 Tail-Recursive Slice

The tail-recursive slice builds the sublist from the end, prepending elements as it recurses backward.

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L|$$

$$\text{slice}(L, i, j) := \begin{cases} L_j :: L_e & \text{if } i = j \\ \text{slice}(L, i, j - 1) ++ (L_j :: L_e) & \text{if } i < j \end{cases}$$

Goal:

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L| \implies \text{slice}(L, i, j) = L[i \dots j]$$

Proof by induction on j , with fixed i

Base case: $j = i$

$$\text{slice}(L, i, i) = L_i :: L_e = L[i \dots i]$$

Inductive step: Assume

$$\text{slice}(L, i, j - 1) = [L_k \mid i \leq k \leq j - 1]$$

Show:

$$\begin{aligned} \text{slice}(L, i, j) &= \text{slice}(L, i, j - 1) ++ (L_j :: L_e) && \text{[by definition of slice]} \\ &= [L[i \dots (j - 1)] ++ (L_j :: L_e) && \text{[by Inductive Hypothesis]} \\ &= [L_k \mid i \leq k \leq j - 1] ++ (L_j :: L_e) && \text{[by Specification]} \\ &= [L_k \mid i \leq k \leq j] && \text{[by definition of Concatenation]} \\ &= L[i \dots j] && \text{[Q.E.D]} \end{aligned}$$

$\therefore$

$$\forall 0 \leq i \leq j < |L|, \text{slice}(L, i, j) = L[i \dots j] \quad \blacksquare$$

This property is verified in `ListUtils::slice`. The implementation and verification code are in Appendix A.3.

4.2 Head-Recursive Slice

The head-recursive slice builds the sublist from the front, cons-ing elements as it recurses forward.

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L|$$

$$\text{headRecursiveSlice}(L, i, j) := \begin{cases} L_i :: L_e & \text{if } i = j \\ L_i :: \text{headRecursiveSlice}(L, i + 1, j) & \text{if } i < j \end{cases}$$

Goal:

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L| \implies \text{headRecursiveSlice}(L, i, j) = L[i \dots j]$$

Proof by induction on $j - i$

Base case: $i = j$

$$\text{headRecursiveSlice}(L, i, i) = L_i :: L_e = L[i \dots i]$$

Inductive step: Assume

$$\text{headRecursiveSlice}(L, i + 1, j) = [L_k \mid i + 1 \leq k \leq j]$$

Show:

$$\begin{aligned} \text{headRecursiveSlice}(L, i, j) &= L_i :: \text{headRecursiveSlice}(L, i + 1, j) && \text{[by definition]} \\ &= L_i :: L[i + 1 \dots j] && \text{[by Inductive Hypothesis]} \\ &= [L_k \mid i \leq k \leq j] = L[i \dots j] && \text{[by specification]} \end{aligned}$$

$\therefore$

$$\forall 0 \leq i \leq j < |L|, \text{headRecursiveSlice}(L, i, j) = L[i \dots j] \quad \blacksquare$$

This property is verified in `SliceEquivalenceLemmas::headRecursiveSlice`. The full Scala verification code is in Appendix A.4.

4.3 Index-Range Slice

The index-range slice builds the sublist by direct index access, recursing forward through the index range.

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L|$$

$$\text{indexRangeValues}(L, i, j) := \begin{cases} L_i :: L_e & \text{if } i = j \\ L_i :: \text{indexRangeValues}(L, i + 1, j) & \text{if } i < j \end{cases}$$

Goal:

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L| \implies \text{indexRangeValues}(L, i, j) = L[i \dots j]$$

Proof by induction on $j - i$

Base case: $i = j$

$$\text{indexRangeValues}(L, i, i) = L_i :: L_e = L[i \dots i]$$

Inductive step: Assume

$$\text{indexRangeValues}(L, i + 1, j) = [L_k \mid i + 1 \leq k \leq j]$$

Show:

$$\begin{aligned} \text{indexRangeValues}(L, i, j) &= L_i :: \text{indexRangeValues}(L, i + 1, j) && \text{[by definition]} \\ &= L_i :: L[i + 1 \dots j] && \text{[by Inductive Hypothesis]} \\ &= [L_k \mid i \leq k \leq j] = L[i \dots j] && \text{[by specification]} \\ &\therefore \end{aligned}$$

$$\forall 0 \leq i \leq j < |L|, \text{indexRangeValues}(L, i, j) = L[i \dots j] \quad \blacksquare$$

This property is verified in [SliceEquivalenceLemmas::indexRangeValues](#). The full Scala verification code is in Appendix A.5.

4.4 Slice Append Consistency

Lemma: A slice of a list from index f to t can be expressed as the slice from f to $t - 1$ concatenated with the element at index t , for $f \leq t < |L|$.

$$\begin{aligned} L[f \dots t] &= \text{slice}(L, f, t) \\ &= \text{slice}(L, f, t - 1) ++ (L_t :: L_e) \\ &= L[f \dots t - 1] ++ (L_t :: L_e) \quad \blacksquare \end{aligned}$$

This property is verified in [ListUtilsProperties::assertAppendToSlice](#). The full Scala verification code is in Appendix A.6.

5 Sum Properties

The recursive `sum` matches the mathematical summation, and addition commutes over concatenation.

- [Sum matches summation](#): $\text{sum}(L) = L[0] + \dots + L[|L| - 1]$
- [Left append preserves sum](#): $\text{sum}(x :: L) = x + \text{sum}(L)$
- [Sum over concatenation](#): $\text{sum}(A ++ B) = \text{sum}(A) + \text{sum}(B)$
- [Commutativity of sum](#): $\text{sum}(A ++ B) = \text{sum}(B ++ A)$

5.1 Sum matches Summation

We can prove that the recursive `sum` function over a list L matches the mathematical definition of the summation $\sum_{i=0}^{n-1} x_i$, where $L = [x_0, x_1, \dots, x_{n-1}]$, $|L| = n$.

Base case: $|L| = 0$

$$\begin{aligned} \text{sum}(L) &= 0 && \text{[by definition of sum]} \\ \sum L &= 0 && \text{[summation over empty list]} \\ \implies \text{sum}(L) &= \sum L \in \mathbb{L} \end{aligned}$$

$\therefore$

$$\forall L \in \mathbb{L}$$

$$|L| = 0 \implies \text{sum}(L) = \sum L$$

Inductive step: $|L| > 0$

Let $P \in \mathbb{L}$, with $P = [x_1, x_2, \dots, x_{n-1}] \in \mathbb{L}$, and assume:

$$\begin{aligned} \text{sum}(P) &= \sum_{i=1}^{n-1} x_i && \text{[by Inductive Hypothesis]} \\ L = x_0 :: P &= [x_0, x_1, \dots, x_{n-1}] && \text{[by Definition of Cons]} \end{aligned}$$

We can ensure termination, since:

$$\begin{aligned} |L| &= |P| + 1 && \text{[by Size Definition]} \\ |P| &< |L| && \text{[Size Decreases Ensures Termination]} \end{aligned}$$

Let's calculate the sum of L :

$$\begin{aligned} \text{sum}(L) &= \text{head}(L) + \text{sum}(\text{tail}(L)) && \text{[by definition of the recursive function sum]} \\ &= x_0 + \text{sum}(P) && \text{[by definition of head and P]} \\ &= x_0 + \sum_{i=1}^{n-1} x_i && \text{[by Inductive Hypothesis]} \\ &= \sum_{i=0}^{n-1} x_i = \sum L \end{aligned}$$

$\therefore$

$$\forall L \in \mathbb{L}$$

$$|L| > 0 \implies \text{sum}(L) = \sum L$$

Hence, by induction on the size of L :

$$\forall L \in \mathbb{L}$$

$$\text{sum}(L) = \sum L = \sum_{i=0}^{n-1} x_i \in \mathbb{S} \quad \blacksquare \quad [\text{Q.E.D.}]$$

This property is verified in `ListUtils::sum`. The implementation and verification code are in Appendix A.7.

5.2 Left Append Preserves Sum

The sum of a list with an element prepended equals the element plus the sum of the original list.

$$\forall x \in \mathbb{S}$$

$$\text{sum}(x :: L) = x + \text{sum}(L)$$

Proof:

$$\begin{aligned} A &= x :: L && [\text{Cons}] \\ \text{sum}(A) &= \text{head}(A) + \text{sum}(\text{tail}(A)) && [\text{By recursive definition of sum}] \\ &= x + \text{sum}(L) && [\text{By recursive definition of head and tail}] \\ &\therefore \end{aligned}$$

$$\text{sum}(x :: L) = x + \text{sum}(L) \quad \blacksquare \quad [\text{Q.E.D.}]$$

This property is verified in `ListUtils::listSumAddValue`. The full Scala verification code is in Appendix A.8.

5.3 Sum over Concatenation

The sum of two concatenated lists equals the sum of each list added together.

$$\text{sum}(A ++ B) = \text{sum}(A) + \text{sum}(B)$$

If list A is empty:

$$\begin{aligned} A ++ B &= L_e ++ B && [\text{A is empty list}] \\ &= B && [\text{By definition of concatenation}] \\ \text{sum}(A) &= 0 && [\text{By definition of sum}] \\ \text{sum}(A ++ B) &= \text{sum}(B) && [\text{Since } A ++ B \text{ equals } B] \\ &= 0 + \text{sum}(B) \\ &= \text{sum}(A) + \text{sum}(B) && [\text{Since sum}(A) \text{ is zero}] \end{aligned}$$

If list A is non-empty:

$$\begin{aligned}
C &= \text{tail}(A) ++ B \\
\text{sum}(A) &= \text{head}(A) + \text{sum}(\text{tail}(A)) && [\text{By definition of sum}] \\
\text{sum}(C) &= \text{sum}(\text{tail}(A)) + \text{sum}(B) && [\text{Inductive Step}] \\
A ++ B &= \text{head}(A) :: (\text{tail}(A) ++ B) && [\text{By definition of head and tail}] \\
\text{sum}(A ++ B) &= \text{head}(A) + \text{sum}(\text{tail}(A) ++ B) && [\text{By definition of sum}] \\
&= \text{head}(A) + \text{sum}(\text{tail}(A)) + \text{sum}(B) && [\text{By definition of C}] \\
&= \text{sum}(A) + \text{sum}(B) && [\text{Substituting}]
\end{aligned}$$

$\therefore$

$$\text{sum}(A ++ B) = \text{sum}(A) + \text{sum}(B) \quad \blacksquare \quad [\text{Q.E.D.}]$$

This property is verified in `ListUtils::listCombine`. The full Scala verification code is in Appendix A.9.

5.4 Commutativity of Sum over Concatenation

The order of concatenation does not affect the total sum.

$$\text{sum}(A ++ B) = \text{sum}(B ++ A)$$

Since:

$$\begin{aligned}
\text{sum}(A ++ B) &= \text{sum}(A) + \text{sum}(B) && [\text{Sum over Concatenation}] \\
\text{sum}(B ++ A) &= \text{sum}(B) + \text{sum}(A) && [\text{Sum over Concatenation}] \\
\text{sum}(B) + \text{sum}(A) &= \text{sum}(A) + \text{sum}(B) && [\text{Distributive}] \\
\text{sum}(B ++ A) &= \text{sum}(A ++ B) \quad \blacksquare && [\text{Q.E.D.}]
\end{aligned}$$

This property is verified in `ListUtils::listSwap`. The full Scala verification code is in Appendix A.10.

5.5 Sum Positivity

If every element of a non-empty list is greater than zero, the sum of the list is greater than zero.

$$(\forall x \in L, x > 0) \wedge L \neq L_e \implies \text{sum}(L) > 0$$

The base case is the singleton list, where the sum is just the one positive element. The inductive step adds a positive head to a tail whose sum is already known to be positive by the inductive hypothesis.

This property is verified in `ListUtilsProperties::assertSumPositive`.

6 Product Properties

The product operation, from singleton identity through concatenation distributivity to positivity.

- **Singleton product:** $\text{product}(x :: \text{empty}) = x$
- **Product pull-out element:** $\text{product}(x :: L) = x \cdot \text{product}(L)$
- **Product over concatenation:** $\text{product}(A ++ B) = \text{product}(A) \cdot \text{product}(B)$
- **Commutativity of product:** $\text{product}(A ++ B) = \text{product}(B ++ A)$
- **Positive product:** product of all-positive list is positive

6.1 Singleton Product

The product of a singleton list containing x is x .

$$\forall x \in \mathbb{S}$$

$$\text{product}(x :: L_e) = x$$

Proof:

$$\begin{aligned} \text{product}(x :: L_e) &= \text{head}(x :: L_e) \cdot \text{product}(\text{tail}(x :: L_e)) && \text{[by definition of product]} \\ &= x \cdot \text{product}([]) && \text{[by definition of head and tail]} \\ &= x \cdot 1 && \text{[product of empty list is 1]} \\ &= x \quad \blacksquare && \text{[Q.E.D.]} \end{aligned}$$

This property is verified in `ListProduct::singletonProduct`. The full Scala verification code is in Appendix A.11.

6.2 Product Pull-Out Element

A single element can be factored out of the product of a concatenated list.

$$\forall listA, listB \in \mathbb{L}, \forall e \in \mathbb{S}$$

$$\text{product}(listA ++ (e :: listB)) = e \cdot \text{product}(listA ++ listB)$$

Proof by induction on $listA$

Base case: $listA = L_e$

$$\begin{aligned} \text{product}(L_e ++ (e :: listB)) &= \text{product}(e :: listB) && \text{[by definition of append and cons]} \\ &= e \cdot \text{product}(listB) && \text{[by definition of product]} \\ &= e \cdot \text{product}(L_e ++ listB) \quad \blacksquare && \text{[Q.E.D.]} \end{aligned}$$

Inductive step: Assume for $listA$, prove for $\text{head}(A) :: listA$.

This property is verified in `ListProduct::productPullOutElement`. The full Scala verification code is in Appendix A.12.

6.3 Product over Concatenation

Product distributes over list concatenation.

$$\forall listA, listB \in \mathbb{L}$$

$$\text{product}(listA ++ listB) = \text{product}(listA) \cdot \text{product}(listB)$$

Proof by induction on $listA$

Base case: $listA = L_e$

$$\begin{aligned} \text{product}(L_e ++ listB) &= \text{product}(listB) && [\text{by definition of append}] \\ &= 1 \cdot \text{product}(listB) && [1 \text{ is multiplicative identity}] \\ &= \text{product}(L_e) \cdot \text{product}(listB) && \blacksquare [\text{Q.E.D.}] \end{aligned}$$

Inductive step: For $\text{head}(A) :: listA$, the recursive definition of product and the inductive hypothesis give the result.

This property is verified in [ListProduct::productConcatLemma](#). The full Scala verification code is in Appendix A.13.

6.4 Commutativity of Product

Product is invariant under swapping concatenated blocks.

$$\forall listA, listB \in \mathbb{L}$$

$$\text{product}(listA ++ listB) = \text{product}(listB ++ listA)$$

Proof:

$$\begin{aligned} \text{product}(listA ++ listB) &= \text{product}(listA) \cdot \text{product}(listB) && [\text{Product over Concatenation}] \\ \text{product}(listB ++ listA) &= \text{product}(listB) \cdot \text{product}(listA) && [\text{Product over Concatenation}] \\ &= \text{product}(listA) \cdot \text{product}(listB) && [\text{Commutativity of multiplication}] \\ &= \text{product}(listA ++ listB) && \blacksquare [\text{Q.E.D.}] \end{aligned}$$

This property is verified in [ListProduct::productConcatCommutative](#). The full Scala verification code is in Appendix A.14.

6.5 Positive Product

If every element of a list is strictly positive, then the product is strictly positive.

$$\forall elements \in \mathbb{L}$$

$$(\forall x \in elements, x > 0) \implies \text{product}(elements) > 0$$

Proof by induction on $elements$

Base case: $elements = L_e$

$$\text{product}(L_e) = 1 > 0 \quad \blacksquare$$

Inductive step: For $\text{head}(e) :: \text{tail}$, we have $e > 0$ and $\text{product}(\text{tail}) > 0$ by inductive hypothesis. The product of two positive numbers is positive.

This property is verified in [ListProduct::positiveProduct](#). The full Scala verification code is in Appendix A.15.

7 Product Divisibility Properties

Every element of a list divides its total product. The proofs below apply the quotient-invariance-under-shift law $\text{mod}(a + m \cdot b, b) = \text{mod}(a, b)$ at $a = 0$ to derive $(a \cdot b) \text{ mod } a = 0$; that law is verified in the companion article [Division and Modulo from Recursive Normalization](#) and reused here as a foundational primitive.

- [Head divides product](#): $\text{product}(L) \text{ mod } \text{head}(L) = 0$
- [All elements divide product](#): every element divides $\text{product}(L)$
- [Inserted element divides product](#): x divides $\text{product}(x :: L)$

7.1 Head Divides Product

The head of a positive list divides the product of the entire list.

$$\forall \text{elements} \in \mathbb{L}, \text{elements} \neq L_e$$

$$(\forall x \in \text{elements}, x > 0) \implies \text{product}(\text{elements}) \text{ mod } \text{head}(\text{elements}) = 0$$

Proof:

$$\text{product}(\text{elements}) = \text{head}(\text{elements}) \cdot \text{product}(\text{tail}(\text{elements})) \quad [\text{by definition of product}]$$

$$\begin{aligned} & \text{product}(\text{elements}) \text{ mod } \text{head}(\text{elements}) \\ &= (\text{head}(\text{elements}) \cdot \text{product}(\text{tail}(\text{elements}))) \text{ mod } \text{head}(\text{elements}) \\ &= 0 \quad \blacksquare \quad [\text{by modulo identity}] \end{aligned}$$

This property is verified in [ListProductDiv::ListProductDiv](#). The full Scala verification code is in Appendix A.16.

7.2 All Elements Divide Product

Every element of a positive list divides the product of the list.

$$\forall \text{elements} \in \mathbb{L}$$

$$(\forall x \in \text{elements}, x > 0) \implies (\forall x \in \text{elements}, \text{product}(\text{elements}) \text{ mod } x = 0)$$

Proof by induction on elements

Base case: $elements = L_e$ — vacuously true.

Inductive step: For $head(p) :: tail$, we have $product(elements) = p \cdot product(tail)$. By modulo identity, p divides the product. By the inductive hypothesis, every element of $tail$ appears as the head of some recursive sublist and divides that sublist's product. Multiplying that sublist product by the preceding positive factors preserves divisibility, so every tail element also divides $p \cdot product(tail) = product(elements)$.

This property is verified in `ListProductDiv::allElementsDivideProduct`. The full Scala verification code is in Appendix A.17.

7.3 Inserted Element Divides Product

Inserting an element into a list guarantees that the resulting product is divisible by that element.

$$\forall prefix, suffix \in \mathbb{L}, \forall e \in \mathbb{S}, e > 0$$

$$(\forall x \in prefix, x > 0), (\forall x \in suffix, x > 0)$$

$$\implies product(prefix ++ (e :: suffix)) \bmod e = 0$$

Proof:

$$product(prefix ++ (e :: suffix)) = e \cdot product(prefix ++ suffix) \quad [\text{Product Pull-Out Element}]$$

$$= e \cdot k \quad [\text{where } k = product(prefix ++ suffix)]$$

$$\begin{aligned} & product(prefix ++ (e :: suffix)) \bmod e \\ &= (e \cdot k) \bmod e = 0 \quad \blacksquare \quad [\text{Q.E.D.}] \end{aligned}$$

This property is verified in `ListProductDiv::insertedElementDividesProduct`. The full Scala verification code is in Appendix A.18.

8 Bound and Order Properties

How the property $\forall x \in L, x > v$ propagates from a whole list to its elements and through concatenation.

- **All greater than at index:** $(\forall x \in L, x > v) \implies L(pos) > v$
- **Append preserves all greater than:** $(\forall x \in A, x > v) \wedge (\forall x \in B, x > v) \implies \forall x \in (A ++ B), x > v$
- **All greater than head and tail:** the head/tail decomposition propagates the bound
- **Index checking lemmas:** efficient bound verification

8.1 All Greater Than at Index

For every list where all elements are greater than a value, any element at a valid position is also greater than that value.

$$\forall list \in \mathbb{L}, \forall value \in \mathbb{S}, \forall pos \in \mathbb{N}$$

$$(\forall x \in list, x > value) \wedge pos < |list| \implies list(pos) > value$$

This property is verified in [ListBoundUtils::assertGreaterThanAtIndex](#). The full Scala verification code is in Appendix A.19.

8.2 Append Preserves All Greater Than

If both lists have all elements greater than a value, then their concatenation also has all elements greater than that value.

$$\forall listA, listB \in \mathbb{L}, \forall value \in \mathbb{S}$$

$$(\forall x \in listA, x > value) \wedge (\forall x \in listB, x > value)$$

$$\implies \forall x \in (listA ++ listB), x > value$$

This property is verified in [ListBoundUtils::assertAppendGreaterThen](#). The full Scala verification code is in Appendix A.20.

8.3 All Greater Than Head and Tail

For a non-empty list where all elements are greater than a value, the head is greater than that value and the tail also satisfies the property.

$$\forall list \in \mathbb{L}, list \neq L_e, \forall value \in \mathbb{S}$$

$$(\forall x \in list, x > value) \implies list.head > value \wedge (\forall x \in list.tail, x > value)$$

This property is verified in [ListBoundUtils::assertGreaterThanHeadTail](#). The full Scala verification code is in Appendix A.21.

8.4 Check All Bigger at Index

For every list where all elements are bigger than a value, any element at a valid position is also bigger.

$$\forall list \in \mathbb{L}, \forall value \in \mathbb{S}, \forall pos \in \mathbb{N}$$

$$checkAllBiggerThanValue(list, value) \wedge pos < |list| \implies list(pos) > value$$

This property is verified in [ListUtilsProperties::checkAllBiggerThanValueAtIndex](#). The full Scala verification code is in Appendix A.22.

8.5 Check All Bigger Head and Tail

For a non-empty list where all elements are bigger than a value, the head is bigger and the tail also satisfies the property.

$$\forall list \in \mathbb{L}, list \neq L_e, \forall value \in \mathbb{S}$$

$$checkAllBiggerThanValue(list, value) \implies list.head > value$$

$$\wedge checkAllBiggerThanValue(list.tail, value)$$

This property is verified in `ListUtilsProperties::checkAllBiggerThanValueHeadTail`. The full Scala verification code is in Appendix A.23.

8.6 Split Preserves All Greater Than

Splitting a lower-bounded list at any valid index preserves the bound on both halves.

$$\forall list \in \mathbb{L}, \forall value \in \mathbb{S}, 0 \leq index \leq |list|$$

$$(\forall x \in list, x > value) \implies (\forall x \in front, x > value) \wedge (\forall x \in back, x > value)$$

$$\text{where } (front, back) = splitAt(list, index)$$

This property is verified in `ListBoundUtils::assertSplitAtPreservesAllGreaterThan`.

8.7 The All Less Than Family

The upper-bound mirror of the property above, $\forall x \in L, x < b$, satisfies the same shape of properties: append preservation, split preservation, and transitivity across a looser bound.

$$\begin{aligned} & (\forall x \in listA, x < bound) \wedge (\forall x \in listB, x < bound) \\ & \implies \forall x \in (listA ++ listB), x < bound & \text{[Append]} \\ & (\forall x \in list, x < bound) \wedge 0 \leq index \leq |list| \\ & \implies (\forall x \in front, x < bound) \wedge (\forall x \in back, x < bound) & \text{[Split]} \\ & (\forall x \in list, x < bound) \wedge bound \leq bound_2 \\ & \implies \forall x \in list, x < bound_2 & \text{[Transitivity]} \\ & (\forall x \in list, x < bound) \wedge 0 \leq pos < |list| \\ & \implies list(pos) < bound & \text{[At Index]} \end{aligned}$$

These properties are verified in `ListBoundUtils::assertAppendLessThan`, `ListBoundUtils::assertSplitAtPreservesAllLessThan`, `ListBoundUtils::assertTransitiveLessThan`, and `ListBoundUtils::assertLessThanAtIndex`.

9 Equivalence Properties

All three slice constructions produce identical results for every valid input.

- [Slice equivalence](#): tail-recursive, head-recursive, and index-range slices are identical for all valid inputs

9.1 Slice Equivalence Lemma

All three slice implementations — tail-recursive, head-recursive, and index-range — produce the same result for any valid input.

$$\forall L \in \mathbb{L}, \forall i, j \in \mathbb{N}, i \leq j < |L|$$

$$\text{slice}(L, i, j) = \text{headRecursiveSlice}(L, i, j) = \text{indexRangeValues}(L, i, j)$$

Proof by induction on $j - i$

Base case: $i = j$ — all three produce $L_i :: L_e$.

Inductive step: For $i < j$, each function decomposes into a head element plus a recursive call on $(i + 1, j)$ or $(i, j - 1)$. By the inductive hypothesis, the recursive calls produce equal sublists, and the head element is the same, so the results are equal.

This property is verified in [SliceEquivalenceLemmas::tailHeadAndIndexRangeSlicesAreEqual](#). The full Scala verification code is in Appendix A.24.

10 Shifted List Properties

A shifted list advances the head by one gap and re-indexes positions. Three lemmas characterize this operation.

- [Same period](#): shifting does not change the period (gap list length)
- [Adjacent difference equals gap](#): consecutive shifted-list values differ by the corresponding gap
- [Gap translation](#): shifting translates the gap sequence by one index

A shifted list is a value sequence viewed one position later, with the head advanced by the first gap. Unlike rotation (which re-indexes without changing values), a shift changes the head and re-indexes positions.

Shifting is the list-level operation that advances a position in a cumulative value sequence. When a sequence of adjacent differences is known (the gap list), advancing the head by the first gap and rotating the gap list yields the view from the next position — without recomputing the cumulative sums.

$$\begin{aligned} \text{ShiftedList}(h, [g_0, \dots, g_{n-1}]) : \text{head} &= h, \text{ gaps} = [g_0, \dots, g_{n-1}] \\ \text{value}_{h,G}(0) &= h \\ \text{value}_{h,G}(i + 1) &= \text{value}_{h,G}(i) + G_i \\ \text{shift}(h, [g_0, \dots, g_{n-1}]) &= \text{ShiftedList}(h + g_0, [g_1, \dots, g_{n-1}, g_0]) \end{aligned}$$

10.1 Same Period

Shifting does not change the period: the gap list remains the same length. The structural property $\text{size} = |\text{gaps}|$ is an invariant of the case class.

$$\text{period}(\text{shifted}) = \text{period}(\text{original}) \quad [\text{Q.E.D.}]$$

Source: [ShiftedList::assertSamePeriod](#)

```
def assertSamePeriod(otherSize: BigInt): Boolean = {
  require(otherSize == gaps.size)
  size == otherSize
}.holds
```

10.2 Adjacent Difference Equals Gap

For any valid position, the difference between consecutive shifted-list values equals the gap at that position. This is a direct consequence of the cumulative value definition above.

$$\text{value}_{h,G}(i+1) - \text{value}_{h,G}(i) = G_i \quad \text{for } 0 \leq i < \text{size} - 1 \quad [\text{Q.E.D.}]$$

Source: [ShiftedList::assertAdjacentDifferenceEqualsGap](#)

```
def assertAdjacentDifferenceEqualsGap(position: BigInt): Boolean = {
  require(position >= 0)
  require(position + 1 < size)
  apply(position + 1) - apply(position) == gaps(position)
}.holds
```

10.3 Gap Translation

Shifting the head and rotating the gaps by one translates the adjacent-gap sequence by one index: the shifted sequence's gap at i equals the original sequence's gap at $i+1$. Both sides reduce to G_{i+1} because the gap list is rotated by one position.

$$\begin{aligned} & \text{value}_{\text{shift}(h,G)}(i+1) - \text{value}_{\text{shift}(h,G)}(i) \\ &= \text{value}_{h,G}(i+2) - \text{value}_{h,G}(i+1) \quad [\text{Gap translation}] \\ &= \text{gaps}(i+1) \quad [\text{By adjacent-difference identity for both views}] \end{aligned}$$

Source: [ShiftedList::assertGapTranslation](#)

```
def assertGapTranslation(
  origHead: BigInt, gaps: List[BiGInt], i: BigInt
): Boolean = {
  require(gaps.nonEmpty)
  require(i >= 0)
  require(i + 2 < gaps.size)
  val shifted = shift(origHead, gaps)
  val orig = ShiftedList(origHead, gaps)
  shifted.apply(i + 1) - shifted.apply(i) ==
    orig.apply(i + 2) - orig.apply(i + 1)
}.holds
```

These properties are verified in `ShiftedList::assertSamePeriod`, `ShiftedList::assertAdjacentDifferenceEqualsGap`, and `ShiftedList::assertGapTranslation`.

11 Rotation Properties

Cyclic permutation preserves every structural invariant: the same elements, same size, same sum, and same bounds.

- **Same elements:** $\text{rotateAt}(L, k).contains(x) \iff L.contains(x)$
- **Same size and sum:** $|\text{rotateAt}(L, k)| = |L|$, $\sum \text{rotateAt}(L, k) = \sum L$
- **Bound preservation:** $(\forall x \in L, x > v) \implies \forall x \in \text{rotateAt}(L, k), x > v$, and likewise for the upper bound $\forall x \in L, x < b$
- **Index shift by one:** $\text{rotateAt}(L, 1)(i) = L(i + 1)$

Rotating a list at index k swaps the front (first k elements) and back (remaining elements) — a cyclic permutation. Rotation preserves every structural invariant: size, sum, element membership, and bound properties are unchanged, because the multiset of elements is the same under any cyclic reordering.

Cyclic permutations arise whenever a fixed set of values is viewed from a different starting position — for example, shifting a circular buffer or aligning a periodic sequence. Rotation invariance means no structural property is lost when the viewing window moves.

$$\begin{aligned} \text{rotateAt}(L, k) &= \text{back} ++ \text{front} \quad \text{where } (\text{front}, \text{back}) = \text{splitAt}(L, k) \\ &= [L_k, L_{k+1}, \dots, L_{n-1}, L_0, L_1, \dots, L_{k-1}] \end{aligned}$$

11.1 Permutation Invariants

Rotation is a permutation of the underlying multiset: the same elements appear, and every structural quantity derived from the list is preserved.

Membership. An element belongs to the original list if and only if it belongs to the rotated list. Since `append` order doesn't affect membership, swapping `front` and `back` preserves the element set.

$$\text{rotateAt}(L, k).contains(x) \iff L.contains(x) \quad [\text{Q.E.D.}]$$

Size and sum. The rotated list has the same length and the same total sum. Sum over `append` is additive and commutative.

$$\begin{aligned} |\text{rotateAt}(L, k)| &= |L| \quad [\text{Same size}] \\ \sum \text{rotateAt}(L, k) &= \sum L \quad [\text{Same sum}] \end{aligned}$$

Bound preservation. If every element of L is strictly greater than v (or strictly less than b), the same holds after rotation.

$$\begin{aligned} (\forall x \in L, x > v) &\implies \forall x \in \text{rotateAt}(L, k), x > v \\ (\forall x \in L, x < b) &\implies \forall x \in \text{rotateAt}(L, k), x < b \end{aligned}$$

11.2 Index Shift Under Rotation by One

Rotating by one position and looking up index k gives the original list's element at index $k + 1$. This is the lemma that underlies gap translation in `ShiftedList`.

$$\text{rotateAt}(L, 1)(k) = L(k + 1) \quad \text{for } k + 1 < |L| \quad [\text{Q.E.D.}]$$

Source: [RotationProperties](#)

```
def assertRotateContainsForward(
  list: List[BigInt], index: BigInt, x: BigInt
): Boolean = {
  require(index >= 0); require(list.contains(x))
  ListUtils.rotateAt(list, index).contains(x)
}.holds

def assertRotateSameSize(list: List[BigInt], index: BigInt): Boolean = {
  require(index >= 0)
  ListUtils.rotateAt(list, index).size == list.size
}.holds

def assertRotateSameSum(list: List[BigInt], index: BigInt): Boolean = {
  require(index >= 0)
  ListUtils.sum(ListUtils.rotateAt(list, index)) == ListUtils.sum(list)
}.holds

def assertRotateSameLowerBound(
  list: List[BigInt], index: BigInt, value: BigInt
): Boolean = {
  require(index >= 0); require(ListBoundUtils.allGreaterThan(list, value))
  ListBoundUtils.allGreaterThan(ListUtils.rotateAt(list, index), value)
}.holds

def assertRotatedAtIndexPlusOne(list: List[BigInt], k: BigInt): Boolean =
{
  require(k + 1 < list.size)
  ListUtils.rotateAt(list, BigInt(1)).apply(k) == list.apply(k + 1)
}.holds
```

These properties are verified in the [RotationProperties](#) module (11 lemmas total). The forward/backward membership pair and the upper/lower bound pair cover all permutation invariants; the remaining lemmas (`assertAppendContainsLeft/Right/Decompose/Swap`) are structural helpers consumed by the main rotation proofs.

12 Conclusion

This article established a formally verified property calculus for finite integer lists represented by recursive head–tail decomposition.

The core proved properties can be summarized as follows, for lists $L, A, B, P, S \in \mathbb{L}$, values $x, e, v \in \mathbb{S}$, and valid natural indices.

$$\begin{aligned}
|L| > 0 &\implies L_{|L|-1} = \text{last}(L) && [\text{Last Element Identity}] \\
0 < i < |L| &\implies L_i = \text{tail}(L)_{i-1} && [\text{Tail Access Shift}] \\
0 \leq f < t < |L| &\implies L[f \dots t] = L[f \dots (t-1)] ++ (L_t :: L_e) && [\text{Slice Append Consistency}]
\end{aligned}$$

$$\begin{aligned}
\text{sum}(L) &= \sum_{i=0}^{|L|-1} L_i && [\text{Sum Matches Summation}] \\
\text{sum}(x :: L) &= x + \text{sum}(L) && [\text{Left Append Preserves Sum}] \\
\text{sum}(A ++ B) &= \text{sum}(A) + \text{sum}(B) && [\text{Sum over Concatenation}] \\
\text{sum}(A ++ B) &= \text{sum}(B ++ A) && [\text{Commutativity of Sum}] \\
(\forall x \in L, x > 0) \wedge L \neq L_e &\implies \text{sum}(L) > 0 && [\text{Sum Positivity}] \\
\text{product}(x :: L_e) &= x && [\text{Singleton Product}] \\
\text{product}(A ++ (e :: B)) &= e \cdot \text{product}(A ++ B) && [\text{Product Pull-Out Element}] \\
\text{product}(A ++ B) &= \text{product}(A) \cdot \text{product}(B) && [\text{Product over Concatenation}] \\
\text{product}(A ++ B) &= \text{product}(B ++ A) && [\text{Commutativity of Product}] \\
(\forall x \in L, x > 0) &\implies \text{product}(L) > 0 && [\text{Positive Product}]
\end{aligned}$$

$$L \neq L_e \wedge (\forall x \in L, x > 0) \implies \text{product}(L) \bmod \text{head}(L) = 0 \quad [\text{Head Divides Product}]$$

$$(\forall x \in L, x > 0) \implies \forall x \in L, \text{product}(L) \bmod x = 0 \quad [\text{All Elements Divide Product}]$$

$$\begin{aligned}
e > 0 \wedge (\forall x \in P, x > 0) \wedge (\forall x \in S, x > 0) \\
\implies \text{product}(P ++ (e :: S)) \bmod e = 0 && [\text{Inserted Element Divides Product}]
\end{aligned}$$

$$(\forall x \in L, x > v) \wedge 0 \leq i < |L| \implies L_i > v \quad [\text{Bound at Index}]$$

$$(\forall x \in A, x > v) \wedge (\forall x \in B, x > v) \implies \forall x \in A ++ B, x > v \quad [\text{Bound over Concatenation}]$$

$$\begin{aligned}
(\forall x \in L, x > v) \wedge 0 \leq k \leq |L| \\
\implies (\forall x \in \text{front}, x > v) \wedge (\forall x \in \text{back}, x > v) && [\text{Split Preserves Lower Bound}]
\end{aligned}$$

$$(\forall x \in A, x < b) \wedge (\forall x \in B, x < b) \implies \forall x \in A ++ B, x < b \quad [\text{Bound over Concatenation, Upper}]$$

$$\begin{aligned}
(\forall x \in L, x < b) \wedge 0 \leq k \leq |L| \\
\implies (\forall x \in \text{front}, x < b) \wedge (\forall x \in \text{back}, x < b) && [\text{Split Preserves Upper Bound}]
\end{aligned}$$

$$\text{slice}(L, f, t) = \text{headRecursiveSlice}(L, f, t) = \text{indexRangeValues}(L, f, t) \quad [\text{Slice Equivalence}]$$

$$\text{value}_{h,G}(i+1) - \text{value}_{h,G}(i) = G_i \quad [\text{Adjacent Difference}]$$

$$\text{value}_{\text{shift}(h,G)}(i+1) - \text{value}_{\text{shift}(h,G)}(i) = \text{value}_{h,G}(i+2) - \text{value}_{h,G}(i+1) \quad [\text{Gap Translation}]$$

$$\text{rotateAt}(L, k). \text{contains}(x) \iff L. \text{contains}(x) \quad [\text{Rotation Same Elements}]$$

$$|\text{rotateAt}(L, k)| = |L| \quad [\text{Rotation Same Size}]$$

$$\text{sum}(\text{rotateAt}(L, k)) = \text{sum}(L) \quad [\text{Rotation Same Sum}]$$

All of these properties are verified in the source references cited throughout the article. Appendix A collects the Scala excerpts that are useful to keep near the text; each excerpt links back to its maintained source file.

Collectively, these results give one verified calculus for decomposing and composing finite lists, aggregating and bounding their values, relating their elements to list products, preserving period while tracking adjacent values and gaps under shifted-list transformations, and preserving membership, size, sum, and element bounds under rotation.

13 Future Work

Extending lists via integration (cumulative sums) and derivation (gap extraction) would formalize two dual operations that map between a list and its accumulated or decomposed form. These operations connect the finite list algebra presented here to the theory of discrete sequences and differences.

Two related list disciplines have verified source proofs but are not developed here as headline properties: maintaining ascending order under insertion and filtering (**SortedList**), and preserving a lower or upper numeric bound under filtering alone rather than the append/split operations covered in Section 8 (**MinBoundList**, **MaxBoundList**). A dedicated treatment of ordered and bounded-filter list variants is left as future work.

14 Limitations

This article restricts the implementation and verification to immutable, finite lists of integers represented using the `stainless.collection.List` data type. The focus is on **correctness**, not on performance or scalability. Our summation and accumulation models follow a **recursive definition**, aligned with mathematical formalism. However, this approach may introduce performance limitations in practical applications involving large lists.

14.1 Overflow and Memory Limits Are Out of Scope

By using `BigInt` and immutable lists, the model assumes unbounded integer arithmetic and infinite list capacity. This choice avoids overflow and out-of-memory errors, but it does not reflect the constraints of fixed-size integer types or limited system memory in real-world environments.

14.2 Side Effects Are Excluded

All list operations are pure and referentially transparent. Mutation, I/O, and performance overhead are outside the scope of this model.

14.3 No Parallelism or Laziness

Unlike streaming libraries or lazy sequences, this model is strictly eager and sequential, without support for parallel computation or lazy evaluation.

14.4 Limitations Imposed by Stainless Verification Tool

Due to current limitations in the Scala Stainless verifier (version 0.9.8.8), formal proofs must often rely on concrete numeric types such as `BigInt`. Stainless does not yet fully support generic numeric abstractions or type classes like `Numeric[T]`, which hinders verification of implementations parameterized over arbitrary numeric types.

As a result, while the mathematical properties in this work conceptually apply to any numeric domain satisfying the required algebraic laws, practical verification is constrained to `BigInt`. Overcoming these tool limitations is an important direction for future enhancements, enabling broader generality and more flexible formal verification.

14.5 Scope of Correctness

This article emphasizes the **mathematical correctness** of recursive definitions and verified properties, rather than runtime behavior or system-level efficiency.

The use of `BigInt` and conceptually unbounded lists abstracts away concerns like stack overflows, memory usage, and execution time. It also circumvents limitations of the current version of Scala Stainless with respect to generic numeric reasoning.

While limiting practical use in some contexts, these assumptions maintain the focus on proving functional correctness as defined by recursive specifications.

Future work may include developing alternative implementations of these data structures that explicitly address real-world constraints, such as bounded memory and side effects, alongside formal proofs establishing their equivalence with the current, mathematically rigorous model.

References

- [1] Jad Hamza, Nicolas Voirol, and Viktor Kuncak. System FR: Formalized Foundations for the Stainless Verifier. In *Object-Oriented Programming, Systems, Languages & Applications (OOPSLA)*, 2019. <https://lara.epfl.ch/~kuncak/papers/HamzaETAL19SystemFR.pdf>.
- [2] The Lean Community. Mathlib: List Rotation. https://leanprover-community.github.io/mathlib_docs/data/list/rotate.html.
- [3] The Rocq Development Team. The Rocq Standard Library: Lists. <https://docs.rocq-prover.org/v8.16/stdlib/Coq.Lists.List.html>.
- [4] Wikipedia contributors. Formal verification. Wikipedia, The Free Encyclopedia. https://en.wikipedia.org/wiki/Formal_verification, 2026.

A Scala Verification Code

A.1 Tail Access Shift — accessTailShiftRight

Source: [ListUtilsProperties.scala](#)

```
def accessTailShiftRight[T](list: List[T], position: BigInt): Boolean =
{
  require(list.nonEmpty && position >= 0 && position < list.tail.size)
  list.tail(position) == list(position + 1)
}.holds
```

Source: [ListBoundUtils.scala](#)

```
def assertTailShiftLeft[T](list: List[T], position: BigInt): Boolean = {
  require(list.nonEmpty)
  require(position >= 0 && position < list.size)
  decreases(position)

  if (position == 0) {
    list(position) == list.head
  } else {
    assert(list == List(list.head) ++ list.tail)
    assert(list(position) == list.apply(position))
    assert(assertTailShiftLeft(list.tail, position - 1))
    assert(list.apply(position) == list.tail.apply(position - 1))
    list(position) == list.tail(position - 1)
  }
}.holds
```

A.2 Last Element Identity — assertLastEqualsLastPosition

Source: [ListUtilsProperties.scala](#)

```
def assertLastEqualsLastPosition[T](list: List[T]): Boolean = {
  require(list.nonEmpty)
  decreases(list.size)

  if (list.size == 1) {
    assert(list.head == list.last)
  } else {
    assert(assertLastEqualsLastPosition(list.tail))
    assertTailShiftLeft(list, list.size - 1)
    assert(list.last == list(list.size - 1))
  }
  list.last == list(list.size - 1)
}.holds
```

A.3 Tail-Recursive Slice — slice

Source: [ListUtils.scala](#)

```
def slice(list: List[BIGInt], from: BIGInt, to: BIGInt): List[BIGInt] =
{
```

```

require(from >= 0)
require(to >= from)
require(to < list.size)
decreases(to)

val current: BigInt = list(to)
if (from == to) {
  List(current)
} else {
  val prev = slice(list, from, to - 1)
  ListUtilsProperties.listAddValueTail(prev, current)
  prev ++ List(current)
}
}

```

A.4 Head-Recursive Slice — headRecursiveSlice

Source: [SliceEquivalenceLemmas.scala](#)

```

def headRecursiveSlice[A](list: List[A], from: BigInt, to: BigInt):
  List[A] = {
    require(0 <= from && from <= to && to < list.length)
    decreases(to - from)
    if (from == to) List(list(from))
    else Cons(list(from), headRecursiveSlice(list, from + 1, to))
  }

```

A.5 Index-Range Slice — indexRangeValues

Source: [SliceEquivalenceLemmas.scala](#)

```

def indexRangeValues[A](list: List[A], from: BigInt, to: BigInt): List[A]
  = {
    require(0 <= from && from <= to && to < list.length)
    decreases(to - from)
    if (from == to) List(list(from))
    else Cons(list(from), indexRangeValues(list, from + 1, to))
  }

```

A.6 Slice Append Consistency — assertAppendToSlice

Source: [ListUtilsProperties.scala](#)

```

def assertAppendToSlice(list: List[BigInt], from: BigInt, to: BigInt):
  Boolean = {
    require(from >= 0)
    require(from < to)
    require(to < list.size)

    listSumAddValue(list, list(to))

    ListUtils.slice(list, from, to) ==

```

```
ListUtils.slice(list, from, to - 1) ++ List(list(to))
}.holds
```

A.7 Sum Implementation — sum

Source: [ListUtils.scala](#)

```
def sum(loopList: List[BigInt]): BigInt = {
  if (loopList.isEmpty) {
    BigInt(0)
  } else {
    loopList.head + sum(loopList.tail)
  }
}
```

A.8 Left Append Preserves Sum — listSumAddValue

Source: [ListUtils.scala](#)

```
def listSumAddValue(list: List[BigInt], value: BigInt): Boolean = {
  ListUtils.sum(List(value) ++ list) == value + ListUtils.sum(list)
}.holds
```

A.9 Sum over Concatenation — listCombine

Source: [ListUtils.scala](#)

```
def listCombine(listA: List[BigInt], listB: List[BigInt]): Boolean = {
  decreases(listA.size)

  if (listA.isEmpty) {
    assert(ListUtils.sum(listA) == BigInt(0))
    assert(ListUtils.sum(listB) == BigInt(0) + ListUtils.sum(listB))
    assert(ListUtils.sum(listB) == ListUtils.sum(listA) +
      ListUtils.sum(listB))
    assert(listA ++ listB == listB)
  } else {
    listCombine(listA.tail, listB)
    val bigList = listA ++ listB
    assert(bigList == List(listA.head) ++ listA.tail ++ listB)
    listSumAddValue(listA.tail ++ listB, listA.head)
  }
  ListUtils.sum(listA ++ listB) == ListUtils.sum(listA) +
  ListUtils.sum(listB)
}.holds
```

A.10 Commutativity of Sum — listSwap

Source: [ListUtils.scala](#)

```
def listSwap(listA: List[BigInt], listB: List[BigInt]): Boolean = {
  listCombine(listA, listB)
  listCombine(listB, listA)
  assert(ListUtils.sum(listA ++ listB) == ListUtils.sum(listA) +
    ListUtils.sum(listB))
  assert(ListUtils.sum(listB ++ listA) == ListUtils.sum(listB) +
    ListUtils.sum(listA))
  assert(ListUtils.sum(listA) + ListUtils.sum(listB) ==
    ListUtils.sum(listB) + ListUtils.sum(listA))
  ListUtils.sum(listA ++ listB) == ListUtils.sum(listB ++ listA)
}.holds
```

A.11 Singleton Product — singletonProduct

Source: [ListProduct.scala](#)

```
def singletonProduct(x: BigInt): Boolean = {
  product(List(x)) == x
}.holds
```

A.12 Product Pull-Out Element — productPullOutElement

Source: [ListProduct.scala](#)

```
def productPullOutElement(
  listA: List[BigInt],
  e: BigInt,
  listB: List[BigInt]): Boolean = {
  decreases(listA.size)

  if (listA.isEmpty) {
    product(List(e) ++ listB) == e * product(listB)
  } else {
    productPullOutElement(listA.tail, e, listB)
    product(listA ++ List(e) ++ listB) ==
      e * product(listA ++ listB)
  }
}.holds
```

A.13 Product over Concatenation — productConcatLemma

Source: [ListProduct.scala](#)

```
def productConcatLemma(
  listA: List[BigInt],
  listB: List[BigInt]
): Boolean = {
  decreases(listA.size)

  if (listA.isEmpty) {
    assert(product(listA) == BigInt(1))
    assert(product(listB) == product(listA) * product(listB))
  }
}
```

```

    assert(listA ++ listB == listB)
  } else {
    productConcatLemma(listA.tail, listB)

    val concatenated = listA ++ listB

    assert(
      concatenated ==
        List(listA.head) ++ listA.tail ++ listB
    )

    assert(
      product(concatenated) ==
        listA.head * product(listA.tail ++ listB)
    )
  }

  product(listA ++ listB) ==
    product(listA) * product(listB)
}.holds

```

A.14 Commutativity of Product — productConcatCommutative

Source: [ListProduct.scala](#)

```

def productConcatCommutative(
    listA: List[BigInt],
    listB: List[BigInt]
): Boolean = {

  productConcatLemma(listA, listB)
  productConcatLemma(listB, listA)

  assert(
    product(listA ++ listB) ==
      product(listA) * product(listB)
  )

  assert(
    product(listB ++ listA) ==
      product(listB) * product(listA)
  )

  assert(
    product(listA) * product(listB) ==
      product(listB) * product(listA)
  )

  product(listA ++ listB) ==
    product(listB ++ listA)
}.holds

```

A.15 Positive Product — positiveProduct

Source: [ListProduct.scala](#)

```
def positiveProduct(elements: List[BigInt]): Boolean = {
  decreases(elements.size)

  require(ListBoundUtils.allGreaterThan(elements, 0))

  if (elements.isEmpty) {
    product(elements) > 0
  } else {
    positiveProduct(elements.tail)
    assert(product(elements.tail) > 0)
    product(elements) > 0
  }
}.holds
```

A.16 Head Divides Product — ListProductDiv

Source: [ListProductDiv.scala](#)

```
def ListProductDiv(
    elements: List[BigInt]
): Boolean = {

  require(elements.nonEmpty)
  require(ListBoundUtils.allGreaterThan(elements, 0))

  val p = elements.head
  val tailProduct = ListProduct.product(elements.tail)

  assert(
    ListProduct.product(elements) ==
      p * tailProduct
  )

  assert(ModIdentity.modIdentity(p))

  assert(
    ATimesBSameMod(
      BigInt(0),
      p,
      tailProduct
    )
  )

  Calc.mod(
    ListProduct.product(elements),
    p
  ) == BigInt(0)
}.holds
```

A.17 All Elements Divide Product — allElementsDivideProduct

Source: [ListProductDiv.scala](#)

```
def allElementsDivideProduct(
    elements: List[BigInt]
): Boolean = {

    require(ListBoundUtils.allGreaterThan(elements, 0))

    decreases(elements.size)

    if (elements.isEmpty) {
        true
    } else {

        val p = elements.head
        val tailProduct = ListProduct.product(elements.tail)

        assert(
            ListProduct.product(elements) ==
                p * tailProduct
        )

        assert(ModIdentity.modIdentity(p))

        assert(
            ATimesBSameMod(
                BigInt(0),
                p,
                tailProduct
            )
        )

        assert(
            Calc.mod(
                ListProduct.product(elements),
                p
            ) == BigInt(0)
        )

        allElementsDivideProduct(elements.tail)
    }
}.holds
```

A.18 Inserted Element Divides Product — insertedElementDividesProduct

Source: [ListProductDiv.scala](#)

```
def insertedElementDividesProduct(
    prefix: List[BigInt],
    e: BigInt,
    suffix: List[BigInt]
): Boolean = {
```

```

require(e > 0)
require(ListBoundUtils.allGreaterThan(prefix, 0))
require(ListBoundUtils.allGreaterThan(suffix, 0))

ListProduct.productPullOutElement(
  prefix,
  e,
  suffix
)

assert(
  ListProduct.product(
    prefix ++ List(e) ++ suffix
  ) ==
  e * ListProduct.product(
    prefix ++ suffix
  )
)

assert(ModIdentity.modIdentity(e))

assert(
  ATimesBSameMod(
    BigInt(0),
    e,
    ListProduct.product(prefix ++ suffix)
  )
)

Calc.mod(
  ListProduct.product(
    prefix ++ List(e) ++ suffix
  ),
  e
) == BigInt(0)
}.holds

```

A.19 All Greater Than at Index — `assertGreaterThanAtIndex`

Source: [ListBoundUtils.scala](#)

```

def assertGreaterThanAtIndex(list: List[BigInt], value: BigInt, pos:
  BigInt): Boolean = {
  require(allGreaterThan(list, value))
  require(pos >= 0 && pos < list.size)
  decreases(pos)
  if (pos == BigInt(0)) {
    list.head > value
  } else {
    assert(assertGreaterThanAtIndex(list.tail, value, pos - 1))
    assert(assertTailShiftLeft(list, pos))
    list(pos) > value
  }
}

```



```
}.holds
```

A.20 Append Preserves All Greater Than — `assertAppendGreaterThan`

Source: [ListBoundUtils.scala](#)

```
def assertAppendGreaterThan(listA: List[BigInt], listB: List[BigInt],
  value: BigInt): Boolean = {
  require(allGreaterThan(listA, value))
  require(allGreaterThan(listB, value))
  decreases(listA.size)
  if (listA.isEmpty) {
    allGreaterThan(listA ++ listB, value)
  } else {
    assert(assertAppendGreaterThan(listA.tail, listB, value))
    assert(allGreaterThan(listA.tail ++ listB, value))
    assert(listA.head > value)
    allGreaterThan(listA ++ listB, value)
  }
}.holds
```

A.21 All Greater Than Head and Tail — `assertGreaterThanHeadTail`

Source: [ListBoundUtils.scala](#)

```
def assertGreaterThanHeadTail(list: List[BigInt], value: BigInt):
  Boolean = {
    require(allGreaterThan(list, value))
    require(list.nonEmpty)
    list.head > value && allGreaterThan(list.tail, value)
  }.holds
```

A.22 Check All Bigger at Index — `checkAllBiggerThanValueAtIndex`

Source: [ListUtilsProperties.scala](#)

```
def checkAllBiggerThanValueAtIndex(list: List[BigInt], value: BigInt,
  pos: BigInt): Boolean = {
  require(ListUtils.checkAllBiggerThanValue(list, value))
  require(pos >= 0 && pos < list.size)
  ListBoundUtils.assertGreaterThanAtIndex(list, value, pos)
}.holds
```

A.23 Check All Bigger Head and Tail — `checkAllBiggerThanValueHeadTail`

Source: [ListUtilsProperties.scala](#)

```
def checkAllBiggerThanValueHeadTail(list: List[BigInt], value: BigInt):
  Boolean = {
    require(ListUtils.checkAllBiggerThanValue(list, value))
    require(list.nonEmpty)
    ListBoundUtils.assertGreaterThanHeadTail(list, value)
  }.holds
```

A.24 Slice Equivalence — tailHeadAndIndexRangeSlicesAreEqual

Source: [SliceEquivalenceLemmas.scala](#)

```
def tailHeadAndIndexRangeSlicesAreEqual(list: List[BigInt], from:
  BigInt, to: BigInt): Boolean = {
  require(0 <= from && from <= to && to < list.length)
  decreases(to - from)

  val indexSlice = indexRangeValues(list, from, to)
  val tailSlice = ListUtils.slice(list, from, to)
  val headSlice = headRecursiveSlice(list, from, to)

  if (from == to) {
    assert(indexSlice == List(list(from)))
    assert(tailSlice == List(list(from)))
    assert(headSlice == List(list(from)))
  } else {
    assert(tailHeadAndIndexRangeSlicesAreEqual(list, from, to - 1))
    assert(tailHeadAndIndexRangeSlicesAreEqual(list, from + 1, to))
    val reconstructedTail = ListUtils.slice(list, from, to - 1) ++
List(list(to))
    assert(tailSlice == reconstructedTail)
    assert(tailSlice == indexSlice)
    assert(headSlice == indexSlice)
    assert(tailSlice == headSlice)
  }
  (
    tailSlice == headSlice &&
    tailSlice == indexSlice &&
    headSlice == indexSlice
  )
}.holds
```

B Stainless Verification Log Output

All formally verified results in this article were checked with Stainless 0.9.8.8, compiling with its standard Scala 3.3.3 front end, by running `just verify-ch 3` on the exact sources tagged `list-article-v1.0.0`. The run reported 1,602 valid, 0 invalid, and 0 unknown verification conditions. The pinned verification log is [logs/verify-ch-3-v1-chapter3-_.log](#).