

Formal Verification of Discrete Integration Properties from First Principles

Thiago Henrique Mata

Independent Researcher

thiago.henrique.mata@gmail.com

<https://thiagomata.com/>

<https://github.com/thiagomata>

Abstract

We define a recursive discrete integral over finite integer lists and verify its principal properties in Scala Stainless. At every valid position, the integral equals the initial value plus the corresponding prefix sum; its final value equals the initial value plus the total sum; and consecutive differences recover the corresponding input values. We prove pointwise, final-value, and length agreement between recursive lookup and the accumulated-list representation. We also verify that positive input values imply a strictly increasing integral, while a positive consecutive integral gap implies that the corresponding input value is positive. Together, these results characterize the discrete integral as a length-preserving cumulative-sum construction with verified representation agreement and value recovery.

Licensed under the Creative Commons Attribution 4.0 International License (CC BY 4.0):

<https://creativecommons.org/licenses/by/4.0/>.

1 Introduction

Accumulation is a central operation in mathematics and computing — from prefix sums in algorithms to integral transforms in signal processing. In functional programming, accumulation often appears as a fold or scan, but such constructs are rarely defined from first principles in a formally verified setting.

In this article, we define a recursive discrete integral over finite integer lists and verify its cumulative-sum, difference-recovery, monotonicity, and representation-agreement properties using Scala Stainless. The recursive lookup and accumulated-list representations agree pointwise and in length, and consecutive differences recover the corresponding input values.

This article verifies:

- Core integral properties: head value, cumulative sum, incremental change, final sum, strictly increasing, gaps positivity — Sections 4.1–4.6.
- Implementation consistency: element/acc/delta/last/size agreement between the recursive and accumulated representations — Sections 5.2–5.5.

Related work

The cumulative-sum construction is the list instance of a prefix scan or accumulation. In Rocq/Coq, the standard list library defines `fold_left` and proves its composition across concatenation; its natural-number list library also defines list sum as a fold and proves sum over concatenation [2]. Those formally checked results give a useful established setting for recursive accumulation.

The present article develops that setting for a recursive `BigInt` integral in Scala Stainless. Its focus is the agreement of two concrete representations — recursive lookup and an accumulated list — and the accompanying cumulative-sum, difference-recovery, length, and monotonicity properties. The citation places these proofs in a broader formal treatment of list accumulation; it does not replace the specific representation-agreement results verified here.

2 Preliminaries and Notation

Let $L = [x_0, x_1, \dots, x_{n-1}] \in \mathbb{Z}^n$ be a finite, non-empty list of n integers, where $n = |L|$, and let $init \in \mathbb{Z}$ be an initial value.

We reuse several basic list operations and their verified properties from a companion article on recursive list construction — [Using Formal Verification to Prove Properties of Lists Recursively Defined](#) [1]. These include the following functions:

- $\text{sum}(L)$: recursively computes the total sum of elements in a list.
- $\text{head}(L)$: returns the first element of a non-empty list.
- $\text{tail}(L)$: returns the list without its first element.
- $A ++ B$: concatenates two lists A and B .

These operations were defined and verified using the same zero-prior-knowledge methodology [1], and are treated here as foundational primitives.

Proofs in this article are written in Scala and verified using the Stainless system with `BigInt` used to represent unbounded integers.

3 Definition of Discrete Integral

The discrete integral accumulates list values into partial sums from a given initial value. Two representations are equivalent.

- Mathematical: $I_k = init + \sum_{i=0}^k L_i$ — the specification
- Recursive: $I_0 = L_0 + init$, $I_{k+1} = I_k + L_{k+1}$ — the implementation

3.1 Mathematical Definition

We define the **discrete integral** $I = \text{Integral}(L, init)$ as a list of partial sums such that:

$$\begin{aligned} &\text{for } k \in [0, n-1] \\ I_k &:= init + \sum_{i=0}^k L_i \end{aligned}$$

3.2 Recursive Definition

The implementation computes the same partial sums by peeling one head from the list at each recursive step and carrying the current accumulated value.

$$\begin{aligned} I &:= \text{Integral}(L, \text{init}) \\ n &:= |L| \\ k &\in [0, n - 1] \end{aligned}$$

The value of the k -th element in the integral I is defined recursively as:

$$I_k := \begin{cases} L_0 + \text{init} & \text{if } k = 0 \\ \text{Integral}(\text{tail}(L), \text{head}(L) + \text{init})_{(k-1)} & \text{if } k > 0 \end{cases}$$

In Scala, this is encoded at [Integral.scala](#):

```
case class Integral(list: List[BigInt], init: BigInt = 0) {
  def apply(position: BigInt): BigInt = {
    require(list.nonEmpty)
    require(position >= 0 && position < list.size)
    if (position == 0) this.head else Integral(list.tail,
    this.head).apply(position - 1)
  }
  def head: BigInt = {
    require(list.nonEmpty)
    list.head + init
  }
  // ... additional methods omitted
}
```

4 Core Integral Properties

These identities connect each recursively defined integral value to the finite list of values it accumulates.

- Head value: $I_0 = L_0 + \text{init}$ — Section 4.1
- Cumulative sum: $I_k = \text{init} + \sum_{i=0}^k L_i$ — Section 4.2
- Incremental change: $I_{p+1} - I_p = L_{p+1}$ — Section 4.3
- Final sum: $I_{n-1} = \text{init} + \text{sum}(L)$ — Section 4.4

4.1 Head Value Matches Definition

The first element of the Integral equals the first element of the original list plus the initial value.

$$I_0 = x_0 + \text{init}$$

Since:

$I \neq L_e$	[By definition: Integral is not an empty list]
$I_0 = \text{head}(I)$	[List element access and indexing]
$\text{head}(I) = \text{head}(L) + \text{init}$	[By definition of Integral]
$L_0 = \text{head}(L)$	[List element access and indexing]
$L_0 = x_0$	[By definition of List]
$\text{head}(I) = L_0 + \text{init}$	[Substitute $\text{head}(L)$ by L_0]
$I_0 = L_0 + \text{init}$	[Substitute $\text{head}(I)$ by I_0]
$I_0 = x_0 + \text{init}$	[Substitute L_0 by x_0]
$I_0 = x_0 + \text{init}$ ■	[Q.E.D.]

This property is verified in the `IntegralProperties::assertHeadValueMatchDefinition`. The full Scala verification code is in Appendix A.1.

4.2 Integral Equals Sum Until Position

The integral at position k equals the sum of all elements in the list up to that position, plus the initial value:

$$\forall k \in [0, n-1] : I_k = \text{init} + \sum_{i=0}^k x_i$$

Proof by Induction on k

Base case: $k = 0$

$$\begin{aligned} \sum_{i=0}^0 x_i &= x_0 && \text{[By definition of sum]} \\ I_0 &= \text{init} + x_0 && \text{[By definition of integral]} \\ &= \text{init} + \sum_{i=0}^0 x_i && \text{[Substituting } x_0\text{]} \\ &\therefore \end{aligned}$$

$$I_0 = \text{init} + \sum_{i=0}^0 x_i \quad \text{[Q.E.D.]}$$

Inductive step: Assume the property holds for $k-1$

$$I_{k-1} = \text{init} + \sum_{i=0}^{k-1} x_i \implies I_k = \text{init} + \sum_{i=0}^k x_i$$

$$\begin{aligned}
I_{k-1} &= \text{init} + \sum_{i=0}^{k-1} x_i && \text{[By induction]} \\
I_k &= I_{k-1} + L_k && \text{[By definition of integral]} \\
&= \left(\text{init} + \sum_{i=0}^{k-1} x_i \right) + x_k && \text{[By induction and } L_k = x_k \text{]} \\
&= \text{init} + \left(\sum_{i=0}^{k-1} x_i + x_k \right) && \text{[Distributivity]} \\
&= \text{init} + \sum_{i=0}^k x_i && \text{[By definition of sum]}
\end{aligned}$$

$\therefore$

$$I_k = \text{init} + \sum_{i=0}^k x_i \quad \blacksquare \quad \text{[Q.E.D.]}$$

This property is verified in the [IntegralProperties::assertIntegralEqualsSum](#). The full Scala verification code is in Appendix A.2.

4.3 Incremental Change Matches List Value

The difference between two consecutive values in the Integral equals the corresponding value in the original list L .

$$\begin{aligned}
&\forall p \in [0, n-2] : \\
&I_{p+1} - I_p = L_{p+1}
\end{aligned}$$

Proof of the Base Case $I_1 - I_0 = x_1$

$$\begin{aligned}
I_1 &= \text{Integral}(\text{tail}(L), I_0)_0 && \text{[By recursive definition for a non-first element]} \\
&= \text{Integral}([x_1, \dots, x_n], I_0)_0 && \text{[By tail definition]} \\
&= \text{head}([x_1, \dots, x_n]) + I_0 && \text{[By recursive Integral definition for the first element]} \\
&= x_1 + I_0 && \text{[By head definition]} \\
I_1 - I_0 &= (x_1 + I_0) - I_0 && \text{[Substituting for } I_1, I_0 \text{]} \\
&= x_1 + I_0 - I_0 && \text{[Distributivity]} \\
&= x_1 && \text{[Cancellation of terms]} \\
&\therefore \\
I_1 - I_0 &= x_1 && \text{[Q.E.D.]}
\end{aligned}$$

Proof of the Inductive Step $I_{p+1} - I_p = L_{p+1}$

$$\begin{array}{ll}
L = x_0 :: \text{tail}(L) & [\text{List decomposition}] \\
I = I_0 :: \text{tail}(I) & [\text{Integral decomposition}] \\
I_{p+1} = I_{\text{tail}, p} & [\text{By indexing: tail of } I \text{ at position } p] \\
I_{p+2} = I_{\text{tail}, p+1} & [\text{By indexing: tail of } I \text{ at position } p+1] \\
I_{\text{tail}, p+1} = L_{\text{tail}, p+1} + I_{\text{tail}, p} & [\text{By recursive definition of Integral}] \\
I_{p+2} - I_{p+1} = I_{\text{tail}, p+1} - I_{\text{tail}, p} & [\text{Substituting for } I_{p+2}, I_{p+1}] \\
= (L_{\text{tail}, p+1} + I_{\text{tail}, p}) - I_{\text{tail}, p} & [\text{Substituting for } I_{\text{tail}, p+1}] \\
= L_{\text{tail}, p+1} & [\text{Cancellation of terms}] \\
L_{p+2} = L_{\text{tail}, p+1} & [\text{By indexing: tail of } L \text{ at position } p+1] \\
\therefore & \\
I_{p+2} - I_{p+1} = L_{p+2} & \blacksquare \quad [\text{Q.E.D.}]
\end{array}$$

This property is verified in the `IntegralProperties::assertAccDiffMatchesList`. The full Scala verification code is in Appendix A.3.

4.4 Final Element Equals Full Sum

The last element of the Integral equals the sum of all elements in the List plus the initial value.

$$I_{n-1} = \text{init} + \sum_{i=0}^{n-1} x_i$$

Mathematically, this is the $k = n - 1$ instance of Section 4.2, which proves $I_k = \text{init} + \sum_{i=0}^k x_i$ for all k :

$$\begin{array}{l}
k = n - 1 \implies I_{n-1} = \text{init} + \sum_{i=0}^{n-1} x_i \\
\therefore \\
I_{n-1} = \text{init} + \sum_{i=0}^{n-1} x_i \quad \blacksquare
\end{array}$$

This property is verified in the `IntegralProperties::assertLastEqualsSum`. The Stainless proof is a self-contained structural induction on the list size — single-element base case, tail-integral inductive step — giving an independent, machine-checked argument for the same identity. The full Scala verification code is in Appendix A.4.

4.5 Strictly Increasing Integral

When every value in the list is positive, the integral is strictly increasing: a later position always produces a larger value. This is the monotonicity theorem — the integral grows with every step.

$$(\forall x \in L, x > 0) \wedge 0 \leq a < b < n \implies I_b > I_a$$

Proof. Induct on $b - a$. The base case follows from the consecutive difference law; the step combines the induction hypothesis with the next positive list value.

$$\begin{aligned}
b = a + 1 &\implies I_{a+1} - I_a = L_{a+1} > 0 \quad [\S 4.3] \\
&\implies I_{a+1} > I_a, \\
I_{b-1} > I_a, \quad I_b - I_{b-1} = L_b > 0 &\implies I_b > I_{b-1} > I_a \\
&\therefore I_b > I_a. \quad \blacksquare \text{ [Q.E.D.]}
\end{aligned}$$

Stainless verification.

```
def assertIntegralStrictlyIncreasing(
  integral: Integral, a: BigInt, b: BigInt
): Boolean = {
  require(a >= 0); require(b > a); require(b < integral.list.size)
  require(ListBoundUtils.allGreaterThan(integral.list, BigInt(0)))
  integral.apply(b) > integral.apply(a)
}.holds
```

This property is verified in the [IntegralProperties::assertIntegralStrictlyIncreasing](#).

4.6 Gaps Positivity

If the integral increases between consecutive positions, the corresponding list element is positive. The gap (difference between adjacent integral values) has the same sign as the underlying list element.

$$0 \leq p < n - 1, \quad I_{p+1} > I_p \implies L_{p+1} > 0$$

Proof. The consecutive difference law identifies the positive difference with the corresponding list value:

$$\begin{aligned}
I_{p+1} > I_p &\implies I_{p+1} - I_p > 0 \\
I_{p+1} - I_p &= L_{p+1} \quad [\S 4.3] \\
&\therefore L_{p+1} > 0. \quad \blacksquare \text{ [Q.E.D.]}
\end{aligned}$$

Stainless verification.

```
def assertGapsPositive(integral: Integral, pos: BigInt): Boolean = {
  require(pos >= 0); require(pos + 1 < integral.list.size)
  require(integral.apply(pos + 1) > integral.apply(pos))
  integral.list(pos + 1) > BigInt(0)
}.holds
```

This property is verified in the [IntegralProperties::assertGapsPositive](#).

5 Implementation Consistency Lemmas

These lemmas verify that the recursive implementation and its accumulated representation agree internally. They do not introduce new mathematical properties but are essential for formal software consistency.

- Element consistency: $I_k = acc_k$ — Section 5.2
- Accumulated delta consistency: $acc_{p+1} - acc_p = L_{p+1}$ — Section 5.3

- Last element agreement: $\text{last}(I) = \text{acc}_{n-1} = I_{n-1}$ — Section 5.4
- Size agreement: $|\text{acc}| = |L|$ — Section 5.5

5.1 Accumulated List Definition

The accumulated list represents the discrete integral as a full list of partial sums rather than element-by-element access.

Let:

$$\begin{aligned} \text{acc}(L, \text{init}) &\in \mathbb{Z}^{|L|} \\ L &= [x_0, x_1, \dots, x_{n-1}] \end{aligned}$$

Then, the accumulated list is defined recursively as:

$$\text{acc}(L, \text{init}) := \begin{cases} L_e & \text{if } L = L_e \\ (\text{head}(L) + \text{init}) :: \text{acc}(\text{tail}(L), \text{head}(L) + \text{init}) & \text{otherwise} \end{cases}$$

The full Integral implementation including the `acc` method is at [Integral.scala](#):

```
case class Integral(list: List[BigInt], init: BigInt = 0) {
  def apply(position: BigInt): BigInt = {
    require(list.nonEmpty)
    require(position >= 0 && position < list.size)
    if (position == 0) this.head else Integral(list.tail,
    this.head).apply(position - 1)
  }
  def acc: List[BigInt] = {
    decreases(list.size)
    if (list.isEmpty) list else List(this.head) ++ Integral(list.tail,
    this.head).acc
  }
  def head: BigInt = {
    require(list.nonEmpty)
    list.head + init
  }
  def tail: List[BigInt] = {
    require(list.nonEmpty)
    Integral(list.tail, this.head).acc
  }
  def last: BigInt = {
    require(list.nonEmpty)
    acc.last
  }
}
```

5.2 Element Consistency

The k -th element of the Integral equals the k -th element of the accumulated list.

$$\forall k \in [0, n - 1] : I_k = \text{acc}_k$$

$$\begin{array}{ll}
L = x_0 :: \text{tail}(L) & [\text{List decomposition}] \\
I = (x_0 + i) :: \text{tail}(I) & [\text{Integral decomposition}] \\
\text{acc}(L, i) = (x_0 + i) :: \text{acc}(\text{tail}(L), (x_0 + i)) & [\text{Definition of acc}] \\
I_0 = x_0 + i = \text{acc}_0 & [\text{Base case}] \\
I_{(p+1)} = \text{tail}(I)_p & [\text{Tail Access Shift Left}] \\
\text{acc}_{(p+1)} = \text{acc}(\text{tail}(L), (x_0 + i))_p & [\text{Recursive accumulation}] \\
\text{tail}(L)_p = \text{acc}(\text{tail}(L), (x_0 + i))_p & [\text{Inductive hypothesis}] \\
\implies I_{p+1} = \text{acc}_{p+1} & [\text{By substitution}] \\
& \vdots \\
\forall p \in [0..n-1], \quad I_p = \text{acc}_p & \blacksquare \quad [\text{Q.E.D.}]
\end{array}$$

This property is verified in the `IntegralProperties::assertAccMatchesApply`. The full Scala verification code is in Appendix A.5.

5.3 Accumulated Delta Consistency

The difference between two consecutive accumulated values in `Acc` equals the corresponding value from the original list.

$$\begin{array}{ll}
\forall p \in [0, n-2] : \text{acc}_{p+1} - \text{acc}_p = L_{p+1} & \\
L = [x_0, x_1, \dots, x_{n-1}] & [\text{List definition}] \\
L = x_0 :: \text{tail}(L) & [\text{List decomposition}] \\
\text{acc}(L, i) = (x_0 + i) :: \text{acc}(\text{tail}(L), x_0 + i) & [\text{Definition of acc}] \\
\text{acc}_0 = x_0 + i & [\text{Base case}] \\
\text{acc}_1 = x_1 + \text{acc}_0 & [\text{Recursive accumulation}] \\
\implies \text{acc}_1 - \text{acc}_0 = x_1 = L_1 & [\text{Cancellation}] \\
\text{acc}_{p+1} = x_{p+1} + \text{acc}_p & [\text{Recursive accumulation}] \\
\implies \text{acc}_{p+1} - \text{acc}_p = x_{p+1} = L_{p+1} & [\text{By subtraction}] \\
& \vdots
\end{array}$$

$$\forall p \in [0..n-2], \quad \text{acc}_{p+1} - \text{acc}_p = L_{p+1} \quad \blacksquare \quad [\text{Q.E.D.}]$$

This property is verified in the `IntegralProperties::assertAccDiffMatchesList`. The full Scala verification code is in Appendix A.6.

5.4 Last Element Agreement

The last element of the accumulated list equals the last element of the integral, which is the element at position $n-1$.

$$\begin{aligned}
\text{acc}_{(n-1)} &= \text{last}(I) \\
\text{acc}_{(n-1)} &= I_{(n-1)}
\end{aligned}$$

$$\begin{aligned}
L &= [x_0, x_1, \dots, x_{n-1}] && \text{[List definition]} \\
\text{last}(L) &= \begin{cases} x_0 & \text{if } |L| = 1 \\ \text{last}(\text{tail}(L)) & \text{if } |L| > 1 \end{cases} && \text{[Definition of last]} \\
\text{acc}(L, i) &= (x_0 + i) :: \text{acc}(\text{tail}(L), x_0 + i) && \text{[Definition of accumulation]} \\
I &= \text{acc}(L, i) && \text{[Integral as accumulated list]}
\end{aligned}$$

Base case: $|L| = 1$

$$\begin{aligned}
L &= [x_0] && \text{[Singleton list]} \\
\text{acc}(L, i) &= [x_0 + i] && \text{[By definition]} \\
I &= [x_0 + i] && \text{[Integral is acc]} \\
\text{last}(I) &= x_0 + i = \text{acc}_0 = I_0 && \text{[last on singleton]}
\end{aligned}$$

Inductive step: $|L| > 1$

$$\begin{aligned}
L &= x_0 :: \text{tail}(L) && \text{[List decomposition]} \\
I &= (x_0 + i) :: \text{acc}(\text{tail}(L), x_0 + i) && \text{[Recursive definition]} \\
\text{tail}(I) &= \text{acc}(\text{tail}(L), x_0 + i) && \text{[Tail of integral]} \\
\text{last}(I) &= \text{last}(\text{tail}(I)) && \text{[Recursive last]} \\
\text{last}(\text{tail}(I)) &= \text{acc}(\text{tail}(L), x_0 + i)_{(n-2)} && \text{[Inductive hypothesis]} \\
&= \text{acc}_{(n-1)} && \text{[Shifted indexing]} \\
\implies \text{last}(I) &= \text{acc}_{(n-1)} = I_{(n-1)} && \text{[By substitution]} \\
&\quad \quad \quad \therefore
\end{aligned}$$

$$\text{last}(I) = \text{acc}_{(n-1)} = I_{(n-1)} \quad \blacksquare \quad \text{[Q.E.D.]}$$

This property is verified in the `IntegralProperties::assertLast`. The full Scala verification code is in Appendix A.7.

5.5 Size Agreement

The size of the accumulated list equals the size of the original list.

$$|\text{acc}| = |L|$$

$$\begin{aligned}
L &= [x_0, x_1, \dots, x_{n-1}] && \text{[List definition]} \\
\text{acc}(L, i) &= (x_0 + i) :: \text{acc}(\text{tail}(L), x_0 + i) && \text{[Recursive accumulation]}
\end{aligned}$$

Empty List: $|L| = 0$

$$\begin{aligned}
L &= [] && \text{[Empty list]} \\
\text{acc}(L, i) &= [] && \text{[By definition]} \\
|\text{acc}(L, i)| &= 0 = |L| && \text{[Equal size]}
\end{aligned}$$

Singleton List: $|L| = 1$

$$\begin{aligned} L &= [x_0] && \text{[Singleton list]} \\ \text{acc}(L, i) &= [x_0 + i] && \text{[By definition]} \\ |\text{acc}(L, i)| &= 1 = |L| && \text{[Equal size]} \end{aligned}$$

Inductive step: $|L| > 1$

$$\begin{aligned} L &= x_0 :: \text{tail}(L) && \text{[Decomposition]} \\ \text{acc}(L, i) &= (x_0 + i) :: \text{acc}(\text{tail}(L), x_0 + i) && \text{[Recursive call]} \\ |\text{acc}(\text{tail}(L), x_0 + i)| &= |\text{tail}(L)| && \text{[Inductive hypothesis]} \\ |\text{acc}(L, i)| &= 1 + |\text{tail}(L)| = |L| && \text{[Cons adds 1]} \\ &&& \vdots \\ |\text{acc}(L, i)| &= |L| && \blacksquare \quad \text{[Q.E.D.]} \end{aligned}$$

This property is verified in the `IntegralProperties::assertSizeAccEqualsSizeList`. The full Scala verification code is in Appendix A.8.

6 Limitations

This article builds upon the foundational assumptions and constraints established in the earlier work [Using Formal Verification to Prove Properties of Lists Recursively Defined \[1\]](#).

Specifically:

- The focus remains on lists of unbounded integers (`BigInt`), without support for generalized numeric types via abstraction or type classes.
- Recursive functions such as `sum`, `head`, `tail`, and `concatenation` are reused from the prior work [1] and are not redefined here.
- Due to the recursive nature of these definitions, stack overflows may occur with extensive lists, but correctness and verifiability take priority over performance.

7 Conclusion

This article established and formally verified a property characterization of the recursive discrete integral over finite integer lists.

From the recursive definition of $I = \text{Integral}(L, \text{init})$, we proved and verified:

$$\begin{aligned} I_0 &= x_0 + \text{init} && \text{[Head Value Matches Definition]} \\ I_k &= \text{init} + \sum_{i=0}^k x_i && \text{[Integral Equals Sum Until Position]} \\ I_{n-1} &= \text{init} + \sum_{i=0}^{n-1} x_i && \text{[Final Element Equals Full Sum]} \\ I_{p+1} - I_p &= x_{p+1} && \text{[Incremental Change Matches List]} \\ (\forall x \in L, x > 0) \wedge 0 \leq a < b < n &\implies I_b > I_a && \text{[Strictly Increasing]} \\ 0 \leq p < n - 1, \quad I_{p+1} > I_p &\implies L_{p+1} > 0 && \text{[Gaps Positivity]} \end{aligned}$$

$I_k = acc_k$	[Element Consistency]
$last(I) = acc_{n-1} = I_{n-1}$	[Last Element Agreement]
$acc_{p+1} - acc_p = x_{p+1}$	[Accumulated Delta Consistency]
$ acc = L $	[Size Agreement]

These results establish that the recursive discrete integral exactly corresponds to the cumulative sum of the list elements plus the given initial value. Recursive lookup and the accumulated-list representation agree at every valid index, at the final value, and in length; their consecutive differences recover the corresponding original list entries. Positive input values make the integral strictly increasing, while a positive consecutive integral gap implies that the corresponding input value is positive.

All properties were formally verified in Scala using the Stainless verification system. The full verification code is in Appendix A.

8 Future Work

Extending the finite integral to repeating sequences of values would capture the relationship between modular arithmetic and gap-period decomposition — the foundation for reasoning about cumulative sums over cyclic structures.

References

- [1] T. H. Mata. Using Formal Verification to Prove Properties of Lists Recursively Defined. <https://github.com/thiagomata/prime-numbers/blob/master/articles/chapter3/list.md>, 2026.
- [2] The Rocq Development Team. The Rocq Standard Library: Lists. <https://rocq-prover.org/doc/V8.20.0/stdlib/Coq.Lists.List.html>.

A Scala Verification Code

A.1 Head Value Matches Definition — `assertHeadValueMatchDefinition`

Source: [IntegralProperties.scala](#)

```
def assertHeadValueMatchDefinition(integral: Integral): Boolean = {
  require(integral.list.nonEmpty)
  assert(integral.head == integral.list.head + integral.init)
  assert(integral.apply(0) == integral.head)
  assert(integral.acc(0) == integral.head)
  assert(integral.acc(0) == integral.apply(0))
  integral.head == integral.list.head + integral.init
}.holds
```

A.2 Integral Equals Sum Until Position — `assertIntegralEqualsSum`

Source: [IntegralProperties.scala](#)

```

def assertIntegralEqualsSum(integral: Integral, position: BigInt):
  Boolean = {
    require(integral.list.nonEmpty)
    require(position >= 0 && position < integral.list.size)
    require(integral.list.size > 1)
    decreases(position)

    assert(assertSizeAccEqualsSizeList(integral.list, integral.init))

    if (position == 0) {
      // base case
      assert(assertHeadValueMatchDefinition(integral))
      assert(ListUtils.slice(integral.list, 0, position) ==
List(integral.list.head))
      assert(integral.apply(0) == integral.init +
ListUtils.sum(List(integral.list.head)))
      assert(integral.apply(0) == integral.init +
ListUtils.sum(ListUtils.slice(integral.list, 0, position)))
    } else {
      // Inductive step
      assert(assertIntegralEqualsSum(integral, position - 1))
      assert(position > 0)
      assert(position < integral.list.size)
      assert(position - 1 < integral.list.size - 1)
      assert(integral.list.size == integral.acc.size)
      assert(integral.list.size > 1)
      assert(assertAccDiffMatchesList(integral, position - 1))

      val prevList = ListUtils.slice(integral.list, 0, position - 1)
      val prevSum = ListUtils.sum(prevList)
      assert(integral.apply(position - 1) == integral.init + prevSum)
      assert(integral.apply(position) == integral.apply(position - 1) +
integral.list(position))
      assert(integral.apply(position) == integral.init + prevSum +
integral.list(position))
      assert(ListUtils.listSumAddValue(integral.list,
integral.list(position)))
      assert(ListUtilsProperties.assertAppendToSlice(integral.list, 0,
position))
      assert(ListUtils.slice(integral.list, 0, position) ==
ListUtils.slice(integral.list, 0, position - 1) ++
List(integral.list(position)))
      assert(integral.apply(position) == integral.init +
ListUtils.sum(ListUtils.slice(integral.list, 0, position)))
    }
    integral.apply(position) == integral.init +
ListUtils.sum(ListUtils.slice(integral.list, 0, position))
  }.holds

```

A.3 Incremental Change — assertAccDiffMatchesList

Source: [IntegralProperties.scala](#)

```

def assertAccDiffMatchesList(integral: Integral, position: BigInt):
  Boolean = {
    require(integral.list.size > 1)
    require(position >= 0 && position < integral.list.size - 1)
    decreases(position)

    if (position == 0) {
      // base case
      assert(IntegralProperties.assertAccDifferenceEqualsTailHead(integral))
      assert(integral.apply(0) == integral.acc(0))
      assert(integral.apply(1) == integral.acc(1))
      assert(
        integral.acc(position + 1) - integral.acc(position) ==
        integral.list(position + 1) &&
        integral.acc(position) == integral.apply(position)
      )
    } else {
      assert(position > 0)
      assert(position < integral.list.size - 1)
      assert(position - 1 < integral.list.size)

      // Inductive step
      val next = Integral(integral.list.tail, integral.head)
      assert(next.size == integral.size - 1)
      assert(integral.tail == next.acc)
      assert(assertAccDiffMatchesList(next, position - 1))

      // link this values and next values
      assert(integral.apply(position) == next.apply(position - 1))
      assert(integral.apply(position + 1) == next.apply(position))

      assert(integral.apply(position) == integral.acc(position))
      assert(integral.apply(position + 1) == integral.acc(position + 1))
    }
    integral.acc(position + 1) - integral.acc(position) ==
    integral.list(position + 1) &&
    integral.acc(position + 1) == integral.apply(position + 1) &&
    integral.acc(position) == integral.apply(position)
  }.holds

```

A.4 Final Element Equals Full Sum — `assertLastEqualsSum`

Source: [IntegralProperties.scala](#)

```

def assertLastEqualsSum(integral: Integral): Boolean = {
  require(integral.list.nonEmpty)
  decreases(integral.list.size)

  if (integral.list.size == 1) {
    // base case
    assert(integral.last == integral.list.head + integral.init)
    assert(integral.last == integral.init + ListUtils.sum(integral.list))
  } else {

```

```

// inductive step
val next = Integral(integral.list.tail, integral.list.head +
integral.init)
assert(assertLastEqualsSum(next))
assert(integral.tail == next.acc)
assert(integral.tail.last == next.acc.last)
assert(next.last == next.acc.last)
assert(next.last == integral.last)
assert(next.last == next.init + ListUtils.sum(next.list))
assert(next.last == integral.init + integral.list.head +
ListUtils.sum(next.list))
assert(integral.last == integral.init + integral.list.head +
ListUtils.sum(next.list))
assert(ListUtils.listSumAddValue(next.list, integral.list.head))
assert(integral.list.head + ListUtils.sum(next.list) ==
ListUtils.sum(List(integral.list.head) ++ integral.list.tail))
assert(integral.list.head + ListUtils.sum(next.list) ==
ListUtils.sum(integral.list))
assert(integral.last == integral.init + ListUtils.sum(integral.list))
}
integral.last == integral.init + ListUtils.sum(integral.list)
}.holds

```

A.5 Element Consistency — assertAccMatchesApply

Source: [IntegralProperties.scala](#)

```

def assertAccMatchesApply(integral: Integral, position: BigInt): Boolean
= {
  require(integral.list.nonEmpty)
  require(position >= 0 && position < integral.list.size)
  decreases(position)

  assert(assertSizeAccEqualsSizeList(integral.list, integral.init))
  assert(integral.list.size == integral.acc.size)

  if (position == 0) {
    // base case
    assert(integral.apply(0) == integral.head)
    assert(integral.acc(0) == integral.head)
    integral.acc(position) == integral.apply(position)
  } else {
    // Inductive step
    assert(position > 0)
    assert(position < integral.list.size)
    assert(position - 1 < integral.list.size - 1)

    val next = Integral(integral.list.tail, integral.head)
    assert(integral.tail == next.acc)

    assert(integral.apply(position) == next.apply(position - 1))
    assert(integral.acc == List(integral.head) ++ next.acc)
    assert(integral.acc.tail == next.acc)
  }
}

```

```

    assert(integral.acc.nonEmpty)
    assert(integral.list.size == integral.acc.size)
    assert(position < integral.acc.size)
    assert(ListBoundUtils.assertTailShiftLeft(integral.acc, position))
    assert(integral.acc.tail(position - 1) == integral.acc(position))
    assert(integral.acc(position) == integral.acc.tail(position - 1))
    assert(integral.acc.tail(position - 1) == next.acc(position - 1))

    assert(integral.acc(position) == next.acc(position - 1))
    assert(integral.apply(position) == next.apply(position - 1))

    assert(assertAccMatchesApply(next, position - 1))
    assert(next.acc(position - 1) == next.apply(position - 1))
    assert(integral.acc(position) == integral.apply(position))
  }
  integral.acc(position) == integral.apply(position)
}.holds

```

A.6 Accumulated Delta Consistency — `assertAccDiffMatchesList`

Source: [IntegralProperties.scala](#)

This is the same function as Appendix A.3. The property is used for both the `apply`-based delta (Section 4.3) and the `acc`-based delta (Section 5.3).

A.7 Last Element Agreement — `assertLast`

Source: [IntegralProperties.scala](#)

```

def assertLast(integral: Integral): Boolean = {
  require(integral.list.nonEmpty)
  assert(
    integral.last ==
      integral.acc.last
  )
  assert(ListUtilsProperties.assertLastEqualsLastPosition(integral.acc))
  assert(assertSizeAccEqualsSizeList(integral.list, integral.init))
  assert(
    integral.acc.last ==
      integral.acc(integral.acc.size - 1)
  )
  assertAccMatchesApply(integral, integral.size - 1)
  assert(
    integral.acc(integral.size - 1) ==
      integral.apply(integral.size - 1)
  )
  integral.apply(integral.size - 1) == integral.last
}.holds

```

A.8 Size Agreement — `assertSizeAccEqualsSizeList`

Source: [IntegralProperties.scala](#)

```

def assertSizeAccEqualsSizeList(list: List[BigInt], init: BigInt = 0):
  Boolean = {
    decreases(list)

    val current = Integral(list, init)

    if (list.isEmpty) {
      // base case for empty list
      assert(current.list.size == 0)
      assert(current.acc.size == 0)
    }
    else if (list.size == 1) {
      // base case for single element list
      assert(current.list.size == 1)
      assert(current.acc.size == 1)
      assert(current.acc.size == current.list.size)
    } else {
      // inductive step for lists with more than one element
      val next = Integral(list.tail, current.head)

      assertSizeAccEqualsSizeList(next.list, next.init)
      assert(next.acc.size == next.list.size)
      assert(current.acc == List(current.head) ++ next.acc)
      assert(current.acc.size == 1 + next.acc.size)
      assert(1 + list.tail.size == list.size)
    }
    current.acc.size == current.list.size
  }.holds

```

B Stainless Verification Log Output

The latest `just verify` run verifies all the described properties without errors. The full log output is available at: [logs/verify.log](#)