Kripke - Scattering Kernel


for(int nm = 0; nm < num moments; ++nm)</pre>

```
datalayout=enum("DZG","DGZ","GDZ","GZD","ZDG","ZGD");
CodeReg Scattering {
  if (datalayout == "DGZ") {
     omploop="0.0.0.0";
  } elif (datalayout == "GDZ") {
     looporder=[1,2,0,3,4];
    omploop="0.0.0.0";
  } elif (datalayout == "GZD") {
    looporder=[1,2,3,4,0];
     omploop="0.0.0";
  } elif (datalayout == "ZGD") {
    looporder=[3,4,1,2,0];
     omploop="0";
  } elif (datalayout == "ZDG") {
    looporder=[3,4,0,1,2];
    omploop="0";
  } elif (datalayout == "DZG") {
    looporder=[0,3,4,1,2];
    omploop="0.0";
  sourcepath="scatter "+datalayout+".txt";
  BuiltIn.Altdesc(stmt="0.0.0.0.0.3", source=sourcepath);
 RoseLocus.Interchange(order=looporder);
  RoseLocus.LICM();
  RoseLocus.ScalarRepl();
  Pragma.OMPFor(loop=omploop);
```



Optimization of Arbitrary Loop Nests

- Generic Locus program to optimize source codes unknown beforehand
- Goal: reproduce Gong Zhangxiaowen et al.¹ work using Locus
- Selected 856 loops from 16 benchmarks
- Transformed loops with all subsets of two sequences:



Benchmark	# of loop	Variants
	nests	assessed
ALPBench [23]	13	39
ASC Sequoia [24]	1	3
Cortexsuite [25]	47	1,297
FreeBench [26]	30	431
Parallel Research Kernels [27]	37	1,055
Livermore Loops [28]	11	121
MediaBench [29]	39	159
Netlib [30]	18	260
NAS Parallel Benchmarks [31]	208	23,384
Polybench [32]	93	7,582
Scimark2 [33]	4	83
SPEC2000 [34]	71	2,228
SPEC2006 [35]	50	216
Extended TSVC [36]	156	6,943
Libraries [37]–[40]	61	1,966
Neural Network Kernels [41]	17	132
Total	856	45,899

