```sql
CREATE DATABASE cinemadb;

USE cinemadb;


-- Create table Cinemarooms

CREATE TABLE CINEMAROOMS

(

  RoomID INT NOT NULL AUTO_INCREMENT,

  RoomName VARCHAR(100) NOT NULL,

  Capacity INT NOT NULL,

  PRIMARY KEY (RoomID)

);

-- Test case

SELECT * FROM cinemarooms;
```

RoomID	RoomName	Capacity
1	Room 1	120
2	Room 2	120
3	Room 3	100
4	Room 4	100
5	Room 5	80
6	Room 6	80
7	Room 7	60
8	Room 8	60
NULL	NULL	NULL

```sql
-- Create table Movies

CREATE TABLE MOVIES

(

  MovieID INT NOT NULL AUTO_INCREMENT,

  MovieTitle VARCHAR(200) NOT NULL,

  Genre VARCHAR(100) NOT NULL,

  DurationMinutes INT NOT NULL,

  PRIMARY KEY (MovieID)

);
```

-- Test case

SELECT * FROM movies;

MovieID	MovieTitle	Genre	DurationMinutes
1	Avengers: Endgame	Action	181
2	Oppenheimer	Drama	180
3	Barbie	Comedy	114
4	John Wick 4	Action	169
5	Dune: Part Two	Sci-Fi	166
6	Spider-Man: Across the Spider-Verse	Animation	140
7	Godzilla Minus One	Action	125
8	Your Name	Animation	106
9	Suzume	Animation	122
10	Demon Slayer: Mugen Train	Animation	117
NULL	NULL	NULL	NULL

-- Create table Customers

```
CREATE TABLE CUSTOMERS
(
  CustomerID INT NOT NULL AUTO_INCREMENT,
  CustomerName VARCHAR(150) NOT NULL,
  PhoneNumber VARCHAR(20) NOT NULL,
  PRIMARY KEY (CustomerID)
);
```

-- Test case

SELECT * FROM customers; (510 customers)

CustomerID	CustomerName	PhoneNumber
1	Ava Thomas	6281467260
2	James Wilson	9949671363
3	Sophia Williams	6162250187
4	Isabella Martinez	1333881070
5	Ethan Taylor	3407783849
6	Michael Anderson	1011168695
7	Michael Thomas	4485173411
8	Noah Davis	5311900255
9	Leo Thomas	3708903588
10	Alice Jones	5274113900
11	Lucas Martinez	6701436481

-- Create table Screenings

CREATE TABLE SCREENINGS

(

ScreeningID INT NOT NULL AUTO_INCREMENT,

ScreeningTime VARCHAR(5) NOT NULL,

ScreeningDate DATE NOT NULL,

MovieID INT NOT NULL,

RoomID INT NOT NULL,

PRIMARY KEY (ScreeningID),

FOREIGN KEY (MovieID) REFERENCES MOVIES(MovieID),

FOREIGN KEY (RoomID) REFERENCES CINEMAROOMS(RoomID)

);

-- Test case

SELECT * FROM screenings; (50 screenings)

ScreeningID	ScreeningTime	ScreeningDate	MovieID	RoomID
1	17:30	2026-04-20	10	6
2	10:45	2026-04-25	2	3
3	14:00	2026-04-18	1	1
4	20:15	2026-04-28	10	8
5	21:30	2026-04-07	9	7
6	15:15	2026-04-16	5	8
7	14:45	2026-04-28	5	6
8	17:00	2026-04-15	8	3
9	21:30	2026-04-23	7	1
10	14:45	2026-04-08	5	4

-- Create table Tickets

CREATE TABLE TICKETS

(

TicketID INT NOT NULL AUTO_INCREMENT,

SeatNumber VARCHAR(10) NOT NULL,

ScreeningID INT NOT NULL,

CustomerID INT NOT NULL,

```
  PRIMARY KEY (TicketID),
  FOREIGN KEY (ScreeningID) REFERENCES SCREENINGS(ScreeningID),
  FOREIGN KEY (CustomerID) REFERENCES CUSTOMERS(CustomerID)
);
-- Test case
SELECT * FROM tickets; (510 tickets)
```

TicketID	SeatNumber	ScreeningID	CustomerID
1	B6	8	406
2	E3	3	374
3	E6	3	195
4	B2	2	136
5	E5	43	209
6	I10	22	60
7	B4	41	424
8	C2	33	46
9	E6	20	467
10	[illegible]	[illegible]	[illegible]