

```
Route::get('detail/{id}', function($id, $name) {
    return Home::class, "index");
});
```

```
class Home {
    public function index($value) {
        return $value;
    }
}
```

b

p

* H/số' tùy chọn (H/số' có 9 tr: mặc định)

' detail/{id}/{name?}'. detail/
↑ ↑
bắt buộc tùy chọn detail/1/aaa.

```
Route::get('detail/{id}/{name?}',  
function ($id, $name = Null){  
    ↓                    ↓  
    1                  null.  
    ───────────  
    1                  aaa.  
});
```

f) Routing name (đặt tên cho đq đầu)

trang chủ "/" \Rightarrow "/home"

A { < a href = "/" >
b |
c |
" / home " .

300 trang - mất 1 giây
cần

Route (" / ") \rightarrow name ("home page"); | n ref = 1 / 1 route

Route::get("/") → name("home page")

Route::get("/home")

name ⊆ phân biệt theo route method.

ts middle ware . (filter)

Request (đúng) → server → ctrl.

đk

Aln / data.

Route ("url", []) → middle ware (tên middleware)

4, Url : ~~x~~reb.php.

api.php. | prefix "api"

Code : Route Service Provider.

prefix \rightarrow tiền tố

Route::get("demo") \rightarrow prefix("test");

local host : 8000 / test / demo
prefix

file fixu to' admin.

Xu' ly' tong file admin.php.

Route :: prefix ("admin")

→ group (".routes/admin.php")

→ Query data :: all()
.. find
where
order.

→ save(). (insert & update)

→ relationship → raw query.	transaction.
--------------------------------	--------------

