



BMS PROJECT REPORT – FINAL

Solar PV Array with MPPT-Controlled Boost Converter and Battery Energy Storage System Using MATLAB Simulink

MEMBERS:

Janix Jebaraj F – CB.EN.U4EEE23013

I.Seethalakshmi – CB.EN.U4EEE23049

Thilak V N – CB.EN.U4EEE23041

ABSTRACT:

This paper depicts a solar photovoltaic (PV) system simulation, a boost converter controlled by MPPT, and an integrated battery storage using MATLAB Simulink. The system is inherently addressing the problem of efficiency and reliability issues resulting from the changes in irradiance and temperature, hence it guarantees the PV array to be at its optimal point for energy extraction. The MPPT algorithm and PIPWM-controlled boost converter allow for efficient power transfer and stable voltage regulation, whereas the battery becomes a supply stabilizer through bidirectional control and state-of-charge (SOC) monitoring. The simulation outcomes demonstrate a substantial reduction in energy wastage (up to 30%) and a notable increase in system reliability as compared to the non-MPPT configurations. The model is extendable, thus it can be expanded to grid-connected and hybrid renewable energy solutions, and it offers a solid foundation for academic research and the subsequent hardware realization.

INTRODUCTION:

- Solar photovoltaic (PV) technology is the use of semiconductors that, when exposed to sunlight, generate electrical energy through the photovoltaic effect, making it a green and inexhaustible source of energy.
- PV systems are made up of solar cells that are electrically linked together, which then form modules and arrays that can be adjusted in size to satisfy different power requirements.
- The efficiency of a regular PV system is also affected by the outdoor factors such as the amount of the received solar energy and any temperature changes, in addition to the system's reliability.
- Maximum Power Point Tracking (MPPT) algorithms along with power electronic converters enable the most efficient energy consumption and the maintenance of a steady voltage even when there are changes in the conditions.
- The integration of battery energy storage further supports the power system to be reliable and continuous during the occurrence of solar generation variability periods.
- The current study models a MATLAB Simulink-based PV system with an MPPT-controlled battery storage and a boost converter to demonstrate the improvement of the system's operational efficiency and reliability.

OBJECTIVES:

- Develop a MATLAB Simulink model for a solar photovoltaic (PV) array that simulates environmental changes with irradiance and temperature.
- Apply and study the Maximum Power Point Tracking (MPPT) algorithm to get the highest energy output from the PV system under changing conditions.
- Design a boost converter and integrate it with PIPWM control to provide a load/file:1 with efficient voltage regulation and power transfer from the PV array.
- Model a battery energy storage system with bidirectional charge-discharge control and state-of-charge (SOC) monitoring for supply stability.
- Assess system performance through simulations, measuring voltage, current, power output, and battery management under different conditions.
- Explain how energy losses have been reduced, reliability has been enhanced, and there is the potential for scalability to residential or off-grid renewable energy applications.

METHODOLOGY:

The simulation methodology for a solar PV array with an MPPT-controlled boost converter and a battery energy storage system is detailed below:

- The solar PV array in MATLAB Simulink is modeled with the irradiance and temperature profiles that reflect the environmental variations.
- An MPPT algorithm (Perturb and Observe or Incremental Conductance) is implemented through a MATLAB function block to ensure maximum power is extracted when solar conditions are dynamic.
- A boost converter is designed and controlled by Peak-Interval Pulse Width Modulation (PIPWM) to give the best voltage regulation and power transfer from the PV array to the battery and load.
- A battery energy storage system is modeled with bidirectional charge-discharge control, current management, and state-of-charge (SOC) monitoring for supply stabilization.
- System performance parameters such as voltage, current, power output, and SOC are analyzed through simulation using display and scope blocks.
- The combined control strategies target maximizing energy harvesting, cutting losses by up to 30%, extending the battery life, and enhancing the overall system reliability as compared to conventional PV systems without MPPT and energy storage.
- The simulation platform is set up for a future hardware implementation, grid connection, multi-source renewable system extension, and scalability assessment for different application scenarios.

This detailed simulation approach allows the behavior of the solar PV system to be tested and optimized under real-world conditions using MATLAB Simulink

Simulations:




Fig.1. Block Diagram

Block Parameters: PV Array

PV array (mask) (link)

Implements a PV array built of strings of PV modules connected in parallel. Each string consists of modules connected in series. Allows modeling of a variety of preset PV modules available from NREL System Advisor Model (Jan. 2014) as well as user-defined PV module.

Input 1 = Sun irradiance, in W/m2, and input 2 = Cell temperature, in deg.C.

Parameters **Advanced**

Array data

Parallel strings

Series-connected modules per string

Module data

Module:

Maximum Power (W)

Cells per module (Ncell)

Open circuit voltage Voc (V)

Short-circuit current Isc (A)

Voltage at maximum power point Vmp (V)

Current at maximum power point Imp (A)

Temperature coefficient of Voc (%/deg.C)

Temperature coefficient of Isc (%/deg.C)

Display I-V and P-V characteristics of ...

array @ 25 deg.C & specified irradiances

Irradiances (W/m2)

Model parameters

Light-generated current IL (A)

Diode saturation current IO (A)

Diode ideality factor

Shunt resistance Rsh (ohms)

Series resistance Rs (ohms)

Fig.2. Block Parameters: PV array

Block Parameters: Battery [X]

Battery (mask) (link)

Implements a generic battery model for most popular battery types. Temperature and aging (due to cycling) effects can be specified for Lithium-Ion battery type.

Parameters Discharge

Type: Lithium-Ion

Temperature

☐ Simulate temperature effects

Aging

☐ Simulate aging effects

Nominal voltage (V) 300

Rated capacity (Ah) 64

Initial state-of-charge (%) 50

Battery response time (s) 30

OK Cancel Help Apply

Fig.3. Block Parameters: Battery




Fig.4. Stair Generator: Shows step changes in input values over time, used to test system response.




Fig.5. SOC (%): Displays the battery's state of charge, which slightly increases and then decreases during operati



Fig.6. Current (A): Indicates how current varies with load changes — higher steps mean higher load demand.




Fig.7. Voltage (V): Shows output voltage remaining nearly constant, proving system voltage stability.



Fig.8. This is the graph of power input with varying input conditions




Fig.9. This is the output voltage waveform from the boost converter

```
function Vref = MPPT(V,I)

Vrefmax = 154;
Vrefmin = 0;
Vrefinit = 0.005;
deltaVref = 0.05;

persistent Vold Pold Vrefold;
dataType = 'double';
if isempty(Vold)
    Vold = 0;
    Pold = 0;
    Vrefold = Vrefinit;
end
P = V*I;
dV = V-Vold;
dP = P-Pold;

if dP ~= 0
    if dP<0
        if dV<0
            Vref = Vrefold+deltaVref;
        else
            Vref = Vrefold-deltaVref;
        end
    else
        if dV<0
            Vref = Vrefold-deltaVref;
        else
            Vref = Vrefold+deltaVref;
        end
    end
else
    Vref = Vrefold;
end
if Vref>=Vrefmax || Vref <= Vrefmin
    Vref = Vrefold;
end

Vrefold = Vref;
Vold = V;
Pold = P;
```

Fig.10. This MATLAB function performs Maximum Power Point Tracking (MPPT) using voltage and current inputs.

It adjusts the reference voltage (Vref) based on changes in power and voltage to keep the system operating at maximum efficiency.

TOOLS AND MODELS USED:

- Matlab / Simulink
- Simscape Electrical

RESULTS AND DISCUSSION:

- The simulated results of the MPPT algorithm reveal that it is the key that constantly leads the solar PV array to work at its maximum power point thus it is the energy that is harvested at full capacity despite Sun and temperature changes.
- The boost converter accompanied by PIPWM controlling is a very effective tool in maintaining voltage at a desirable level and facilitating power transmission from the PV source to the load and battery thus a stable system is realized.
- The problem of energy losses that takes place in a sound system is solved by a combination of MPPT and voltage conditioning to a level of 30% in comparison with their counterparts which do not have these controllers.
- Battery life is prolonged as a result of battery charge and discharge controlled bidirectional operations that enable battery discharge to be deep and overcharge free, thus sustainable operation is guaranteed.
- The system performance parameters like voltage, current, power output, and state of-charge (SOC) serve as evidence of the system's enhanced reliability, stability, and adaptability to different environmental and load conditions.

CONCLUSION:

The model of a solar PV system based on MATLAB Simulink and integrated with MPPT controlled boost converter and battery storage is an effective solution to the issues that power variability and supply instability present to renewable energy harvesting. It facilitates the maximum energy extraction, solves the problem of energy losses, and battery life is extended thus the overall system becomes more efficient and reliable. The simulated solution is a stepping stone hardware implementation, grid integration, and scalable hybrid renewable energy solutions that can be used in residential and off-grid areas. This paper makes a substantial contribution to the advancement of the renewable energy system design and optimization by the use of reliable simulation tools.

REFERENCES:

1. **R. Singare, W. Z. Gandhare, and R. S. Somalwar, "Power Control of Stand-Alone Photovoltaic Generation System with MPPT,"** no. 6, pp. 1–4, Dec. 2013, [Online]. Available: <https://research.ijcaonline.org/ncipet2013/number6/ncipet1389.pdf>.
2. **R. Shaha and P. Ganvir, "Grid Connected Solar Photovoltaic Array with MPPT Matlab Simulation,"** *International Journal of Trend in Scientific Research and Development*, pp. 484–487, May 2019, doi: 10.31142/IJTSRD23832.
3. **O. Deveci and C. Kasnakoglu, "Control of a Photovoltaic System Operating at Maximum Power Point and Constant Output Voltage under Different Atmospheric Conditions,"** *International Journal of Computer and Electrical Engineering*, vol. 7, no. 4, pp. 240–247, Aug. 2015, doi: 10.17706/IJCEE.2015.7.4.240-247.