

CS144: Web Applications

Professor Cho

Thilan Tran

Spring 2021

Contents

CS144: Web Applications	3
Web Standards	4
HTTP	4
HTTP/2	5
Content Encodings	5
HTML	7
CSS	9
Cookies and Sessions	10
Dynamic User Interaction	12
Dynamic Web Server	12
AJAX	14
JavaScript	15
Various Notes	15
Document Object Model	16
Advanced JavaScript	19
Browser Event Handling	22
Async Programming and Promises	23
Promises	24
Async and Await	25
TypeScript	26
MEAN Stack	29
MongoDB	29
Node.js	30

Express	31
Single Page Applications	35
Client Side Frameworks	38
Angular	38
Reactive Programming	41
CSS	43
Scaling	46

CS144: Web Applications

- covered topics:
 - core web standards eg. HTTP, Unicode, HTML, JSON, CSS
 - JavaScript programming
 - web programming paradigms eg. functional and asynchronous programming, MVC
 - website architecture, scalability, and security

Web Standards

- core Internet standards:
 - **domain name service (DNS)** maps domain names to IPs and details how to reach particular IPs in a hierarchical design
 - * ICANN manages **top-level domains (TLDs)**
 - **transmission control protocol and Internet protocol (TCP/IP)** is the main Internet routing and transportation protocol
 - **hypertext transportation protocol (HTTP)** is the communication protocol between web servers and clients
 - encoding standards such as ASCII or Unicode text
 - * multimedia types such as JPEG, MP3, H.264, etc.
 - **hypertext markup language (HTML)** is the markup standard
 - **cascading style sheets (CSS)** is the styling and formatting standard
 - **JavaScript** is the defacto web programming language
- the early Web was mainly designed to retrieve static content eg. HTML pages and images from servers:
 - can be set up with an HTTP server eg. Apache and filesystem
 - need a URL path to file mapping
 - the **uniform resource locator (URL)** is a unique ID for any object on the web:
 - * eg. `<protocol>://<hostname>/<path>?<query>#<fragment_id>`
 - the **fragment identifier** is the string behind the hash in the URL
 - * points to the HTML element with the given ID
 - the **query** is a set of name-value pairs
- four general layers of a site:
 - storage / data layer stores and retrieves data
 - application layer store and retrieves data
 - HTTP layer interprets request and serves response
 - encryption layer encrypts transport

HTTP

- HTTPS/2 is the most recent version from 2015:
 - but HTTP/1.1 is still extremely popular from 1996
 - major browsers support HTTP/2 only over HTTPS
- two key properties of HTTP:
 1. request and response paradigm
 - all interactions start with a client's request, to which a server can reply

- 2. HTTP is a stateless protocol:
 - every request is handled independently of others
 - server is not required to remember history of past requests
- any HTTP message is either a request or a response with the following structure:
 - request / status line eg. `GET / HTTP/1.0` or `HTTP/1.1 200 OK` :
 - * primary HTTP methods are `GET`, `POST`, `PUT`, `DELETE`
 - other methods include `HEAD`, `OPTIONS`, `TRACE`
 - * by convention, GET methods should leave no significant side effects at the server
 - * status codes fall into the categories
 - `2xx` success, `3xx` redirection, `4xx` client error, `5xx` server error
 - header lines
 - empty line
 - body

HTTP/2

- motivations:
 - many high-latency mobile devices with limited bandwidth
 - many objects are needed to display a single page:
 - * eg. HTML, images, CSS, JavaScript, etc.
 - * ie. 100s of HTTP requests may be needed to render a page
- HTTP/2 relaxes key assumptions for speed and efficiency:
 - server can now push messages
 - add stateful elements
 - binary encoding
- new features in HTTP/2:
 - multiplexed streams:
 - * multiple outstanding requests through a single connection
 - * split messages into small streams
 - * priority specification
 - HPACK
 - * stateful HTTP header compression
 - server push
 - * predictively cache responses pushed by the server

Content Encodings

-
- only bits are transmitted over the Internet, so it is essential to include the `Content-Type` header in the HTTP response

- eg. `Content-Type: text/html`
- the **multi-purpose Internet extension (MIME)** type is a standard way to indicate the type of transmission:
 - * formatted as `type/subtype` , case insensitive
 - * eg. `text/html`, `text/plain`, `image/jpeg`, `video/mp4`, `application/pdf`
- the character encoding is specified as the `charset` parameter
 - * eg. `Content-Type: text/html; charset=utf-8`
- for text, how does a browser map a sequence of bits to characters?
- ASCII standard from 1963:
 - 7-bit, represented 128 characters
 - extended to many 8-bit standards eg. ISO-8859-1
 - basis of current standards for roman characters
- EBCDIC standard from 1963:
 - created by IBM for IBM mainframes
 - 8-bit, designed to be easy to represent in punch cards
 - still used by some IBM mainframes
- local character codes developed by each country:
 - the **double byte code character set (DBCS)** used two bytes for a character
 - frequently used in Asia eg. Chinese GB2312, Korean EUC-KR
- how does a computer know what encoding standard is used for a certain file?
 - early solution was a system-wide specification in a global **code page** ie. unique number for a particular character encoding
- **Unicode** was a single standard for all existing characters in the world:
 - motivated by need to standardize all the various character encodings
 - v1.0 was published in October 1991
 - * almost yearly release of a new Unicode version
 - every character maps to a unique **code point**
 - * eg. `A` corresponds to `U+0041`
 - originally a fixed-length 16-bit standard AKA UCS-2, now currently 21-bit standard
 - Unicode initially had an issue with little vs. big endian storage
 - * use the Unicode byte order mark `U+FEFF` at the beginning of a Unicode string in order to give hints on the endian mode
 - an initial issue was many incompatibilities with legacy code
- need to make Unicode backward compatible with ASCII:

- Unicode-aware programs would work with ASCII data, and legacy code would work with basic Unicode data
- this is UTF-8
- both UTF-8 and ASCII encoding should map all ASCII characters to the *same* 1-byte number:
 - * eg. `A` with code point `U+0041` should be encoded as `41`
 - * to accomplish this, UTF-8 needs to be a *variable* length encoding
- all characters between `U+0000` and `U+007F` is encoded in a single byte
- all characters between `U+0080` and `U+07FF` is encoded in 2 bytes
 - * the initial prefixes of each byte are fixed as `110, 10` respectively
- all characters between `U+0800` and `U+FFFF` is encoded in 3 bytes
 - * the initial prefixes of each byte are fixed as `1110, 10, 10` respectively
- all characters between `U+10000` and `U+10FFFF` is encoded in 4 bytes
 - * the initial prefixes of each byte are fixed as `11110, 10, 10, 10` respectively
- this allows all existing ASCII-encoded data to be UTF-8 encoded
- UTF-16 is an extension of UCS-2 to cover 21 bit code points

HTML

- how does the browser extract the rich structure of a page from a pure text file?
- **hypertext markup language (HTML)** is the document standard of the web:
 - specifies both the content and the structure of a Web page
 - made up of text ie. content together with **tags** enclosed in `<...>` that represent the structure
 - * eg. `Fat cats go down alleys.`
 - history:
 - * initial HTML1 version introduced in 1991
 - * all the way up to HTML5 in 2014
 - standardized by WHATWG group, was competing with XML
- HTML document always starts with `<!DOCTYPE html>` :
 - earlier versions use different `DOCTYPE`
 - remnants from **standard generalized markup language (SGML)**
 - followed by `html, head, title, body` elements

Minimum HTML5 document:

```
<!DOCTYPE html>
<html>
<head>
  <title>...</title>
</head>
<body>...</body>
</html>
```

- an HTML **element** is a single HTML entity enclosed in an opening and closing tag:
 - eg. `<p>paragraph</p>`
 - an open tag is always followed by a closing tag except **void elements**
 - * eg. `br`, `hr`, `img`, `input`
 - tags in HTML5 should represent structure, not formatting
 - * HTML5 also added additional semantic elements such as `header`, `nav`, `article`, `section`
 - instead, CSS should be used to specify formatting
- special characters:
 - multiple white spaces and line breaks are always displayed as a single white space
 - * ` ` can be used for non-breaking space
 - `<`, `>`, `&` for `<` `>` `&`
 - `<!-- ... -->` for comments
- HTML tags can have **attributes**:
 - eg. ``
 - the **ID attribute** should be unique in a document
 - * acts as an unique identifier of an element, like a key
- embedding objects:
 - an `a` element with an `href` attribute can be used to embed links:
 - * can use relative or absolute URL
 - * eg. `...`
 - * we can embed another HTML page inside a page with an `iframe` element
 - images, videos, audio, and others can be embedded with the `img`, `video`, `audio`, `embed` elements, respectively
 - the **favorite icon (Favicon)** is displayed next to the title
 - * default path is `/favicon.ico`
- more in HTML5:
 - clearly defined logic to handle errors for improperly defined documents
 - programmable JavaScript API
 - * eg. canvas, web storage, offline web applications, drag-and-drop, document editing, etc.

- XHTML is mostly the same as HTML, but with must stricter formatting rules:
 - tags and attributes *must* be lowercase
 - no more empty elements, all tags have matching end tags
 - always use quotes around attribute values
 - ie. makes HTML XML-compliant
 - failed to become popular because it was too strict without much benefit

CSS

- **cascading style sheets (CSS)** is used to specify document formatting and presentation:
 - each CSS **rule** is a selector together with a declaration block
 - each declaration is a name-value pair
- can use a `style` tag within the HTML document, or link to a separate CSS file
 - `div`, `span` are structure-less tags used to format particular parts of the document
- CSS selectors:
 - `[src]` selects for attribute `src`
 - `[target="_blank"]` selects for attribute `target` with value `_blank`
 - `div, p` applies to multiple tags
 - `div p` applies to `p` that is a descendant of `div`
 - `div > p` applies to `p` that is a direct child of `div`
 - `p.class1.class2` applies to `p` belonging to both specified classes
 - `div + p` applies to immediate adjacent sibling `p` of `div`
 - `div ~ p` applies to any sibling `p` of `div`
 - `:hover` is a **pseudo class** selector
 - * class created by the browser
 - `::first-letter` is a **pseudo element** selector
 - * elements created by the browser

Example CSS:

```
h1 {
  font-family: "Arial";
  font-size: 40pt;
}

.code {
  font-family: monospace;
  white-space: pre;
  border: 1px solid black;
```

```
}  
  
#warning1 {  
  color: rgb(255, 0, 0);  
}
```

Cookies and Sessions

- HTTP is a stateless protocol where every request can be handled independently of others:
 - how does a website remember a user and customize its behavior?
 - how does a website detect two requests are from the same user?
 - idea behind cookies is to embed a unique identifier in every request from a user
- **cookies** allow a server to ask a client to remember `key=value` pairs and send them back in all future requests:
 - the `Set-Cookie` HTTP response header tells the client to remember a cookie
 - eg. `Set-Cookie: username=john; expires=...;`
 - `expire` is the expiration time:
 - * by default cookie becomes *transient* and is sent back only during the current browsing session
 - * setting `expire` makes the cookie *persistent* until expiration
 - `path` and `domain` specify which requests to send the cookie in
 - the **same origin policy** is where the client sends the cookie only to the domain from which it was obtained
 - but it is still possibly to track a user's requests across multiple domains through **third-party cookies**:
 - * a website will partner with partner sites in order to track the same user
 - * embed a tiny, invisible image that is requested when a user visits a partner site
 - * this request contains a `Referrer` header with cookies from the partner site
- cookie security:
 - cookies are generally unsafe since they can be stolen or tampered with
 - * need to be careful about what we store in the cookie
 - the `secure;` attribute only sends the cookie back over HTTPS
 - * protects against cookie theft
 - we can use signed cookies to prevent tampering

- * add a secret-key encrypted signature to the main cookie data
 - attaching an expiration date ensure the cookie expires eventually
 - * even if cookie is stolen, it will eventually become invalid
- **JSON web tokens (JWTs)** are a web standard to encode and exchange client-managed state with tampering protection:
 - format is `header.payload.signature`
 - header holds information on the token
 - payload holds the main body of the token
 - signature is an encrypted has value for tampering detection
 - the JWT header holds JSON data encoded into a `Base64` string:
 - * typically has two fields, the `alg` hashing algorithm and `typ` token type (JWT)
 - * eg. `{"alg": "HS259", "typ": "JWT"}`
 - the payload is also encoded JSON data:
 - * may include **registered claims** ie. standardized fields such as `iss` issuer, `jti` JWT ID, `iat` issued at, `exp` expires at
 - * can put anything else in the JSON, ie. as an **unregistered field**
 - the signature is a secret-key encrypted has of encoded `header.payload` :
 - * if the JWT is ever tampered, a correct signature cannot be generated without knowing the correct password
 - JWT is sent to the browser
 - * for future requests, the JWT will be sent back
- how does a server authenticate the identity of a user?
 - ask for a password
 - how can we let a user authenticate with their password once, without asking for authentication for every request?
 - use a cookie to keep track of username, or track **sessions** through a session ID
 - * using a session allows for more flexibility, but forces the server to maintain state on the server side

Dynamic User Interaction

- many sites generate content dynamically based on user input
 - eg. keyword search, social media status update, etc.
 - how can the server obtain user input?
 - * one way is to use the query string of the URL
 - * another approach is to use HTML forms

Example HTML form:

```
<form action="http://www.google.com/search" method="GET">
  <input type="text" name="q">
  <input type="submit">
</form>
```

- need to specify in the form *where* to send the input, and what method to use:
 - default action is current directory
 - the `input` element has different possible types and a name specifying the query name
 - * user provided input is sent as query name-value pairs of request
 - in a GET request, the query is added to the request path
 - * in a POST request, the query is added to the request body
 - the `submit` button indicates that the user has completed input
 - different input types include text, password, checkbox, radio, select, submit, button, textarea, hidden, file
 - * hidden field can be used to store state, ie. bypass HTTP stateless restrictions

Form for uploading a file:

```
<form action="..." method="POST" enctype="multipart/form-data">
  <input type="text" name="name">
  <input type="file" name="myfile">
  <input type="submit">
</form>
```

- `multipart/form-data` is a way to include multiple objects in a single message
 - the `boundary` attribute of the content type header specifies the object boundaries

Dynamic Web Server

- how can we write code to generate dynamic content at the server?
 - two general approaches, programmatic vs. template
 - * ie. write a program vs. write a Web page

Example programmatic approach with Java Servlet:

```
protected void doGet(HttpServletRequest request,
                    HttpServletResponse response)
    throws ServletException, IOException
{
    PrintWriter out = response.getWriter();
    out.println("<html><head><title>Hello</title></head>");
    out.println("<body>Hello, " + request.getParameter("fname"));
    out.println("</body>");
    out.println("</html>");
    out.close();
}
```

Example template approach with Java ServerPages:

```
<html>
<head><title>Hello</title></head>
<body>Hello, <%= request.getParameter("first_name") %>
</body>
</html>
```

- even though the template approach seems cleaner, the page will quickly get messy as complex application logic is added:
 - can we separate the code from the page?
 - ie. enforce code *ownership* where page design is done by designers, while app coding is done by developers
 - * we want to make each of these aspects as independent as possible
- in a **model-view-controller (MVC)**, we split the overall program into several parts:
 - data, application logic, and final result presentation
 - for the **data** layer:
 - * data may be stored in a file or database engine, locally or remotely
 - * where and how data is stored and managed may change over time
 - * should be encapsulated in a layer independent from other layers
 - for the **presentation** layer:
 - * same data may be presented in many different ways
 - * presentation changes should not affect other layers
 - thus, split the code into three modular components:
 1. the **models** deal with data storage and access
 2. the **views** deal with result presentation

3. the **controllers** deal with application logic
 - * each component may be owned by different people

MVC example in Java Servlet:

```
// Controller
protected void doGet(HttpServletRequest request,
                      HttpServletResponse response)
    throws ServletException, IOException
{
    user = getUser(...); // retrieve data
    ... // application logic here
    request.setAttribute("user_name", user.name); // dispatch data model to view
    request.getRequestDispatcher("/index.jsp").forward(request, response);
}

// Model
User getUser(String userid) {...}

// View
<html>
<head><title>Hello</title></head>
<body>Hello, <%= request.getAttribute("user_name") %></body>
</html>
```

AJAX

- in traditional website interactions:
 - all input is form-based
 - must press submit button and wait until the entire page *reloads*
 - leads to constant interruptions and significant delay
- **asynchronous JavaScript and XML (AJAX)** allows for:
 - immediate, in-place update of page content
 - allows for a user experience that is more similar to a desktop application
- new browser responsibilities:
 - AJAX is *event-driven*, where control flow is driven by **events**
 - * need to allow **callback functions** that map events to actions
- AJAX building blocks:
 1. JavaScript is *the* programming language for the Web
 - allows running complex code inside a browser
 2. **document object model (DOM)**:
 - tree-based model of HTML document

- JavaScript manipulates DOM to dynamically change page
 - JavaScript monitors events on the DOM and takes actions
3. asynchronous communication mechanism with the server
- eg. `fetch`, `XMLHttpRequest`

JavaScript

- originally created as a simple script to manipulate Web pages:
 - NodeJS (JavaScript interpreter) runs almost everywhere
 - supported by most modern browsers
 - allows running arbitrary code inside the browser
 - current standard is much more complex than originally intended
- basic syntax is very similar to C-style languages

Various Notes

- `=`, `≠` check if operands have the same value after type conversion:
 - while `==`, `===` check if operands have the same value and type
 - for equality on object, both check if operands reference the same object
- dynamically rather than statically typed
- `typeof` usually returns the current type of the variable, but not always
 - types are either primitive or object type
 - primitive types include `number`, `string`, `boolean`
 - * as well as `bigint`, `symbol`, `null`, `undefined`
- note that all numbers are represented as a 64-bit floating point number:
 - no integer numbers in JS
 - bitwise operators convert a number to a 32-bit integer
 - * truncate subdecimal digits if needed
 - `NaN`, `Infinity` are valid numbers
- `bigint` is a 64-bit integer that was added to ES2020 as a primitive type:
 - add `n` behind number type
 - note that this is *not* a number type
- booleans:
 - falsy values include `0`, `NaN`, `""`, `null`, `undefined`
 - everything else is truthy, including all arrays and objects
- strings are immutable
 - string manipulation creates a new string
- undefined and null types:
 - undefined indicates an uninitialized ie. default value *before* initialization

- null indicates absence of an object
 - * an object is expected but nothing can be returned
- however, `typeof null` returns object
- objects:
 - object assignment is by reference
 - object comparison is by reference
 - arrays are objects
- `RegExp` is a special regular expression object in JS:
 - enclosed inside slashes, eg. `/a?b*c/`
 - can be used with string methods `search`, `match`, `replace`, `split`
 - * as well as regex methods `exec`, `test`
- exception handling in JS:
 - use `try`, `catch`, `finally` blocks
 - we can `throw` any value or object
 - * but typically only `Error` objects are thrown because it provides a stack trace `Error.stack`
- **JavaScript object notation (JSON)** is the standard syntax to represent literal objects in JS:
 - object property names and strings *require* double quotes
 - useful methods `JSON.stringify`, `JSON.parse`
 - JSON values cannot be functions or undefined
 - * circular references cannot be stringified either

Document Object Model

- the **document object model (DOM)** is a standard to construct JavaScript objects from an HTML document:
 - allows JavaScript to interact with the webpage and manipulate elements
 - the HTML document is converted to a tree-like model
 - the `script` HTML tag is used to embed JavaScript code or link to a separate file
- three key node types:
 1. an **element node** represents an HTML element
 - every HTML tag creates an element node
 2. a **text node** is all text enclosed in an element
 - text node becomes a child of the element node
 3. an **attribute node** is the attribute of an element
 - is *associated* with its element node, but is *not* a child

Example HTML with DOM Conversion in Figure 1:


```

<!DOCTYPE html>
<html>
<head><title>Page Title</title></head>
<body>
  <h1>Heading</h1>
  <a href="good/">Link</a>
</body>
</html>

```




Figure 1: DOM Conversion Example

- note that white spaces are preserved from the header through the body:
 - allows the DOM representation to always be converted back into the exact HTML code
 - need to create additional text nodes for white spaces
- every DOM node becomes a JavaScript object:
 - with properties, methods, and associated events
 - * by changing these property values, calling the methods, etc. we can update the HTML element dynamically
 - the `document` object is the root object that has the parsed DOM tree as its child
 - DOM object properties for the tree structure:
 - * `childNodes` are the node's children
 - * `parentNode` is the node's parent
 - * `attributes` are the node's attributes
 - * `nodeType` is one of "Element", "Attribute", "Text"
 - * `nodeName` is the tag name eg. `HEAD` , attribute name eg. `href` , or `#text` for text nodes
 - * `nodeValue` is the enclosed text for text nodes, the attribute value for attribute nodes, and `null` otherwise
- accessing DOM nodes:

1. can traverse the tree directly using the `childNodes` property starting from the `document`
2. get nodes directly with `getElementById`, `getElementsByClassName`, `querySelectorAll`

DOM manipulation examples:

```
document.body.style.background = "yellow"; // body is a shortcut property
document.getElementById('warning1').style.color = "red";
document.body.innerHTML = "<p>new text </p>"; // innerHTML is parsed into a DOM tree
// and replaces the original children

let newP = document.createElement("p");
let newText = document.createTextNode("new text");
newP.appendChild(newText);
document.body.replaceChild(newP);
```

- manipulating the DOM:
 - methods include `createElement`, `createTextNode`
 - * as well as `appendChild`, `removeChild`, `replaceChild`
 - specific objects may have certain methods to take certain actions
 - * eg. `reset`, `submit` on a form element
- event-driven programming:
 - to dynamically update a web page based on user action, JavaScript must handle certain invoked events
 - 1. wait for relevant events
 - 2. take appropriate actions given an event
 - common DOM **events** include `load`, `click`, `input`, `mouseover` :
 - * an object has an associated **event handler** for each event
 - * this function is invoked when the event is triggered
 - can customize its action by setting the event handler
 - * when an event is fired AKA triggered on an object AKA event target, the associated callback function AKA event handler is called AKA invoked

Event handler example:

```
let colors = ["yellow", "blue", "red"];
let i = 0;

function changeColor(event) {
  document.body.style.color = colors[i++%3];
}

document.body.addEventListener("click", changeColor);
// alternatively, <body onclick="changeColor();"> (not recommended)
```

Advanced JavaScript

- variables scope:
 - variables declared outside any block has global scope
 - a variable declared with `let` has block-scope local variable
 - a variable used without an explicit `let` declaration has global scope
 - * strongly discouraged
 - before `let`, `var` was used:
 - * `var` has function scope as opposed to block scope
 - * `var` declarations are *hoisted* (but *not* the assignment)
 - * should always use `let` declarations

Scope example:

```
let a = "a"; // global
b = "a";    // global
function f() {
  c = "c";   // global
  let d = "d"; // local
}

var e = 10; // global
function g() {
  f = 15; // local!
  var f;
}
```

- in JS, functions are objects:
 - functions can be assigned to a variable, passed as a parameter, and can have properties
 - however, `typeof` operator returns `function`, not `object`
 - functions can also be nested:
 - * local variables in nested functions follow *lexical* scope rather than dynamic scope
 - * uses **closures** to hold references to variables declared lexically outside of the function
 - ie. a function bundled together with references to its enclosing state
 - * closures were used extensively before ES6

Using objects as functions:

```
function square(x) { return x*x; }
function foo(x, fn) { return fn(x); }
```

```
foo(10, square); // returns 100
foo(10, function(x) { return x*2; }) // anonymous function, returns 20
foo.a = 20;
```

Nested functions:

```
function f() {
  let a = 1;
  let b = 2;
  function g() {
    console.log(b); // prints 2
    b = 3; // updates the previous b to 3
  }
  if (a > 0) {
    let b = 4;
    g();
    console.log(b); // prints 4
  }
  console.log(b); // prints 3
}
f();
```

Closure example:

```
let age = 21;

function getFunc() {
  let age = 10;
  function printAge() { console.log(age++); }
  return printAge;
}

let myFunc = getFunc();
myFunc(); // prints 10
myFunc(); // prints 11
```

- the JS **arrow function** is a quick way to create an anonymous function in ES6:
 - in JS, we often have to pass a function as a parameter, so polluting the namespace can be simplified using anonymous functions
 - arrow function makes this even more concise
 - `() => expr` returns the value of the expression
 - in `() => { statements; }`, need to explicitly return a value
 - arrow functions retain the `this` binding of the enclosing lexical context
 - * ie. *inherits* its `this` binding

- **object-oriented programming (OOP)** in JavaScript:
 - using objects that wrap together data and methods
 - in JS, we can add a method to an object:
 - * inside an object's method, `this` points to the object itself
 - * note that arrow functions should not be used for object / class method definitions due to its lexical binding properties
 - original syntax for creating objects is `new Object()` :
 - * in ES2015, can use the typical `class` syntax with constructors, etc. as seen in other languages
 - * ES2015 also added class inheritance support using `extends`, `super`
 - * internally, class inheritance is implemented via a `prototype` object
- meaning of `this` in JavaScript:
 - becomes bound to different things depending on the context
 - 1. in a function called via an object or class method, `this` is bound to the called object or class
 - 2. in a function called via event triggering, `this` is bound to the DOM element in which the event handler was set
 - 3. everywhere else (in top-level block or other function calls), `this` is bound to the global object:
 - `window` in the browser or `global` in Node.js (now referable by the `globalThis` keyword in ES2020)
 - any variable assigned without declaration becomes a property of the global object

Arrow function lexical binding:

```
x = 10;
function_printx = function() { console.log(this.x); };
arrow_printx = () => { console.log(this.x); };

o = { x: 20 };
o.printx_f = function_printx;
o.printx_a = arrow_printx;

console.log(this.x); // prints 10
function_printx();  // prints 10
arrow_printx();     // prints 10
o.printx_f();       // prints 20
o.printx_a();       // prints 10
```

- array manipulation:
 - **mutators** modify the input array directly
 - * `reverse`, `sort`, `push`, `pop`, `shift`, `unshift`, `splice`
 - **accessors** leave the input array intact:

- * `concat`, `slice`, `filter`, `map`
- * creates and returns a new output array

Browser Event Handling

- the `event` object is passed as the only argument to the event handler function:
 - `event.target` is the target to which the event was originally triggered (similar to `this`)
 - we can set our own event handler to catch any DOM event:
 - * the *original* event handler is also invoked after our custom event handler
 - * to prevent the original handler, we need to call `event.preventDefault()`
 - eg. `onclick="alert('Clicked!'); event.preventDefault()"` inside an `a` link
 - * note that if an event handler is set using statements inside an HTML tag, they are wrapped into a function with the single input parameter `event`
 - `event.type` is the event type
- most DOM events *bubble up* through the DOM tree:
 - target's ancestors get the event all the way through the `document` and sometimes `window` object
 - * exceptions include `focus`, `scroll`
 - to stop event propagation, call `event.stopPropagation()` inside event handler
- inside the browser, JS code is executed in a *single* thread:
 - thus no two event handlers will ever run at the same time
 - document contents are never update simultaneously
 - * no concerns about locks or deadlock
 - but the web browser stops responding to user input while the handlers are running
 - * need to break into parts or use web workers
- JavaScript execution timeline in the browser:
 1. `document` object is created and `document.readyState` is set to `loading`
 2. browser downloads and parses the page:
 - scripts are downloaded and executed synchronously in the order they appear in the page
 - unless the script is `async`, in which they are downloaded asynchronously in the background and is executed as they are available
 3. once the page is completely parsed, `document.readyState` is set to `interactive`

4. then the browser fires the `DOMContentLoaded` event and calls the `document.onload` callback
5. `document.readyState` is set to `complete`
6. browser waits for events and calls appropriate event handlers
 - use `onload`, `onunload` handlers for initialization and cleanup code
- the `window` object is the global object within a browser:
 - `document` is really `window.document`
 - `window.location` is the URL of the current page
 - `window.history` gives the browsing history
 - `window.alert`, `confirm`, `prompt`

Async Programming and Promises

- in synchronous APIs, operations block on every step:
 - program becomes stuck at every step
 - how can the program handle many requests concurrently despite long, blocking waits?
 - traditionally, multithreading is used for multiple request processing:
 - * invoke multiple handlers in parallel
 - * *no change* in coding style
 - structure of each synchronous request handler remains the same
 - * used by most traditional servers, eg. Apache, Tomcat
 - * however, multithreading incurs a significant resource overhead:
 - high memory use
 - thread invocation overhead
 - concurrency handling logic eg. semaphores and locks
- existing JS engines are still *single threaded*:
 - cannot use multi-threading
 - instead, an asynchronous API is used for multiprocessing under the single threaded environment:
 - * do not wait, and return immediately
 - * invoke a callback function when ready
 - eg. `db.find({userid: id}, callback)` :
 - * `db.find` returns immediately
 - * the `callback` is invoked when the database object is ready
 - * retrieved object is passed as a parameter to `callback`
 - * only the `callback` can perform actions with the object
 - ie. the next line in the code does not have the required object
 - actions may be spread across multiple callback functions, leading to “callback hell”

Tradition synchronous programming example:

```
function sendPicture(id) {
  user = db.find({userid: id});
  picture = fs.readFile(user.picFile);
  socket.write(picture);
  console.log('done');
}
```

Illustrating callback hell:

```
function sendPicture(id) {
  db.find({userid: id}, (err, user) => {
    fs.readFile(user.picFile, (err, picture) => {
      socket.write(picture, () => console.log('done'));
    });
  });
}
```

Promises

- **promises** were introduced in ECMAScript 2015:
 - an asynchronous function *immediately* returns a “promise”
 - once a promise is obtained, a callback can be attached using `then`
 - * a resolve callback runs on a success called with the return value of the operation
 - * a reject callback runs on failure called with the error value
 - `then` returns a new promise:
 - * can set a callback to the returned promise, creating a **promise chain** of asynchronous callbacks
 - * makes the code look and work more like a synchronous program
 - * each asynchronous function is non-blocking and return immediately
- details of promises:
 - a promise is **settled** by being **resolved** or **rejected**
 - promise operation depends on what value is returned by a callback:
 - * if a regular value is returned by a callback, the chained promise is resolved
 - if a promise is returned by a callback, the chained promise returns either a value or error of that settled promise depending if it is resolved or rejected
 - * if an error is thrown at some point in the callback, the chained promise is rejected
- what if a call fails, but the rejection callback is not set?

- setting one rejection callback at the end is enough
 - * no need to set a rejection callback in every `then`
- `catch(rejectCB)` is shorthand for `then(null, rejectCB)`
- promise guarantees:
 - callbacks added with `then` even *after* the success or failure of the asynchronous operation *will* be called:
 - * ie. setting the `then` occurs after the asynchronous function completes
 - * this was a possible problem we had to consider with callbacks
 - callbacks will never be called before the completion of the current run of the JS event loop
 - these guarantees motivated the name “promise”
- creating a promise:
 - `Promise.resolve(val)` creates a promise that always resolves to `val`
 - `Promise.reject(err)` creates a promise that always rejects to `err`
 - `new Promise((res, rej))` creates a dynamic promise

Creating a dynamic promise:

```
let p = new Promise((resolve, reject) => {  
  ...  
  if (cond) resolve(val);  
  else reject(err);  
});
```

Async and Await

- `async/await` keywords are syntactic sugar to make asynchronous look almost like synchronous code:
 - `await` can be used on any function that returns a promise inside an `async` function
 - adding `async` to a function changes the function to one that returns a promise immediately, without blocking:
 - * ie. “promisifies” the function
 - * if the original function returns a regular value, the returned promise resolves to the value
 - * if the original function throws an error, the returned promise is rejected to the error
 - * if the original function returns a promise, the previous chaining logic applies
 - the `await` keyword can be used in front of a function that returns a promise:
 - * “blocks” the code in that location until it settles

- * the next action is performed after the promise is settled
- * can only be used inside an `async` function
- if we want to use `await` in the outer most block, we can use an IIFE

Using `async/await` :

```
async function sendPicture(id) {  
  try {  
    user = await db.find({userid: id});  
    picture = await fs.readFile(user.picFile);  
    await socket.write(picture);  
    return picture.size;  
  } catch (e) {  
    throw new Error("Cannot send picture");  
  }  
}
```

Parallel `await` gotchas:

```
function doubleAfter2(x) {  
  return new Promise((res, rej) => setTimeout(res, 2000, x*2));  
}  
  
async function addAsync1(x) {  
  return await doubleAfter2(x)  
    + await doubleAfter2(x)  
    + await doubleAfter2(x);  
}  
  
async function addAsync2(x) {  
  const a = doubleAfter2(x);  
  const b = doubleAfter2(x);  
  const c = doubleAfter2(x);  
  return await a + await b + await c;  
}  
  
addAsync1(10).then(v => console.log(v)); // prints 60 after 6 seconds  
addAsync2(10).then(v => console.log(v)); // prints 60 after *2* seconds
```

TypeScript

-
- TypeScript is a superset of JavaScript:
 - additional features include types, interfaces, decorators, etc.

- all additional TS features are strictly optional and not required
- thus any JS code is also a TS code
- TS must be compiled to JS using a `tsc`, the TypeScript compiler
- type annotations can be added to functions and variables:
 - allows for static type checking
 - makes large-scale code easier to manage
 - compile-time error vs. run-time error
 - * rigidity vs. flexibility
- type annotations:
 - eg. `number`, `string`, `boolean`
 - * three basic type values cannot be assigned to a different type variable
 - arrays and tuples eg. `number[]`, `[number, string]`
 - unions eg. `number | string`
 - objects eg. `{x: number, y: string}`
 - * object of type `A` can be assigned to a variable of type `B` if their structure is compatible ie. the properties of `A` should be a superset of `B`'s
 - also `any`, `void`, `never`
 - `undefined` and `null` can be assigned to any types

TS “hello, world” example with types:

```
function hello(greeting: string): string {
  return 'Hello, ' + greeting + '!';
}

const world: string = 'world';
hello(world);
hello([0, 1, 2]); // generates an error during compilation
```

TS object type compatibility:

```
interface Point2D {
  x: number;
  y: number;
};

function plot(p: Point2D): void { ... }
let point3D = { x: 1, y: 2, z: 3 };
plot(point3D); // no error
```

- type conversion:
 - primitives eg. `Number('1')`, `String(2)`, `Boolean('true')`

- objects eg. `<HTMLInputElement>document.querySelector('input[type="text"]')`
 - * `as` and `<>` are equivalent
 - * `HTMLInputElement` is a subclass of `HTMLElement`
- functions:
 - in JS, missing parameters are OK and are bound to `undefined`
 - in TS, all function parameters must be passed
 - * an optional parameter is indicated by the suffix `?`
- classes:
 - explicit member property declaration
 - * in JS, had to use a constructor to declare fields
 - adds access modifiers `public`, `private`, `protected`
 - interfaces like the Java interface
 - generic classes and functions
 - * promises can be generic types as well

TS generics:

```
class Dot<t> {  
    public x: T;  
    constructor(x: T) { this.x = x; }  
};  
let s = new Dot<number>(1);  
  
function log<T>(arg: T): void {  
    console.log(arg);  
}  
log<number>(1);
```

- decorators:
 - syntax `@decorator_name`
 - can be added to certain class or method declarations
 - * can modify various aspect of declared entities
 - eg. `@sealed` seals objects so that property values may change but the structure is fixed

MEAN Stack

- traditional web development:
 - stack includes:
 - * Apache / Nginx for HTTP
 - * PHP or Servlet for the server runtime
 - * MySQL for data storage
 - almost all code runs on the server
 - browser is a passive HTML / CSS rendering engine
 - after AJAX, most code runs in the browser as JS:
 - * server transformed into a back-end service that provides data persistence and transaction support
 - * leads to better user experience and less load on the server
 - challenges with AJAX development:
 - * increasing complexity in the JS code
 - * impedance mismatch of JS on the client and PHP or Java on the server
 - JSON for data transport vs. relational data for data storage
- modern full stack web development:
 - Angular / React / Vue for the client runtime
 - Node.js and its packages for the server runtime
 - MongoDB data engine
 - MEAN AKA MongoDB, Express.js, Angular, and Node.js

MongoDB

- database for JSON objects:
 - a NoSQL database with no predefined schema
 - no normalization or joins
 - other libraries eg. `Mongoose` can be used for ensuring structure in the data
- data in MongoDB is stored as a collection of documents:
 - a **document** is a JSON object
 - a **collection** is a group of similar documents
- document vs. relational databases:
 - a relational model flattens the data:
 - * stores as a set of independent tables
 - * removes redundancy
 - * table is designed around the intrinsic nature of the data
 - * efficient join algorithms

- a document model preserves the view of a particular application:
 - * hierarchically nested objects
 - * potential redundancy
 - * no need to decompose data for storage and join back for retrievals
 - * retrieving data with a different view is difficult
- CRUD operations:
 - `insertOne`, `insertMany`
 - `findOne`, `find`
 - `updateOne`, `updateMany`
 - `deleteOne`, `deleteMany`

Example MongoDB operations:

```
db.books.insertOne({title: "MongoDB", likes: 100});

db.books.find({$and: [{likes: {$gte: 10}}, {likes: {$lt: 20}}]});

db.books.updateOne({title: "MongoDB"}, {$set: {title: "MongoDB II"}});

db.books.deleteMany({likes: {$lt: 100}});
```

- administrative commands:
 - `show dbs` shows list of databases
 - `use <dbname>` uses a specific database
 - `db.dropDatabase()` deletes the current database
 - `show collections` shows list of collections
 - `db.createCollection(<cname>)` creates a collection
 - `db.cname.drop()` drops a collection
 - `db.cname.createIndex({title:1, likes:-1})` creates an index on combined attributes
 - * ascending or descending order

Node.js

- **Node.js** is a JavaScript runtime environment based on the Chrome V8 JavaScript engine:
 - allows JS to run on any computer
 - intended to run directly on OS, instead of inside a browser:
 - * removes browser-specific JS API like the HTML DOM
 - * adds support for OS APIs such as file system and network
- notably, Node.js is *single* threaded:
 - no overhead from multi-threading

- requires *asynchronous* programming:
 - * to avoid blocking calls
 - * nonblocking API
 - * very different from traditional procedural programming
 - * uses many callback functions

Example web server with Node:

```
let http = require("http");
let httpServer = http.createServer((req, res) => {
  // event-driven, defining callback whenever server receives a request
  res.writeHead(200, {'Content-Type': 'text/plain'});
  res.write('Hello world!\n');
  res.end('PATH: ' + req.url); // print URL
});
httpServer.listen(3000); // listen on port 3000, nonblocking call!
console.log("HTTP server started");
```

- Node modules is based on CommonJS instead of the ECMAScript 2015 standard:
 - syntax eg. `require(module_name)` and `module.exports`
- the **Node package manager (NPM)** helps install and manage third-party Node modules:
 - install eg. `npm install express`
 - the `package.json` file helps manage package dependencies:
 - * when installing packages, the package and its dependencies is added to `package.json`
 - * with `package.json` in the current directory, `npm install` installs all dependencies into `node_modules/`
 - * also contains `scripts` and `dependencies`
 - `package-lock.json` contains all the packages, including dependencies, in detail
 - * exact versions, etc.
 - version numbers follow the format `major.minor.patch` :
 - * the prefix `~` indicates any patch version
 - * the prefix `^` indicates an equal or higher version with the same major version

Express

- **Express.js** is a Node package for developing a web server with three key functionalities:

1. URL-routing mechanism
2. **middleware** integration
 - ie. a set of controllers / handlers
3. view template engine integration

Simple Express demo:

```
let express = require('express');
let app = express();

app.get('/', (req, res, next) => {
  res.send('Hello world');
});
app.get('/john', (req, res, next) => {
  res.send('Hello, John');
});
app.listen(3000);
```

- ExpresssURL routing:
 - `app.method(path, handler)` invokes `handler` for a request sent to an exact match on `path` via `method`
 - `app.all(path, handler)` handles *all* methods
 - parameters can be used embedded in the URL path itself:
 - * eg. `app.get('/dogs/:breed', ...)`
 - * `:breed` makes the matching substring available as a parameter at `req.params.breed`
 - a regular expression may also be used in the path
- request handlers take three parameters, `request`, `response`, `next` :
 1. the `request` object contains information on the HTTP request
 - eg. `app`, `body`, `query`
 2. the `response` object controls the response to be sent to the client
 - eg. `res.send(...)`
 3. `next` passes onto the request handling chain
- multiple handlers may be attached at the same path in a **request handling chain**:
 - when multiple handlers process a request, they are processed top down in the sequence they are attached
 - calling `next()` exits from the current handler and moves on to the next in the chain
- generating a response:
 - set status code eg. `res.status(200)`
 - set header field eg. `res.append(field, value)`
 - redirect eg. `res.redirect([status,] URL)`

- generating the body:
 1. raw string eg. `res.send(body)`
 2. static file eg. `res.sendFile(absPath)`
 3. JSON eg. `res.json(obj)`
 4. from a template eg. `res.render(templateFile, templateData)` :
 - * generates an HTML page from `templateFile` using `templateData`
 - * multiple template engines exist, eg. Pug, EJS, Mustache
- EJS is a popular template engine used with Express:
 - similar to JSP, uses scriptlet tags
 - `<% ... %>` is used for control-flow with no output
 - `<%= ... %>` prints out the result of the expression after HTML escaping
 - `<%- ... %>` prints out the raw result of the expression without HTML escaping

EJS example:

```
<!DOCTYPE html>
<html>
<head><title><%= title %></title></head>
<body>
  <ul>
    <% for (let post of posts) { %>
      <li><%= post.title %></li>
    <% } %>
  </ul>
</body>
```

- advanced URL routing:
 - `app.use([path,] middleware)` for prefix routing:
 - * `path` is interpreted as a prefix instead of an exact match
 - * `path` prefix is then removed in `req.path` passed to middleware
 - `express.Router()` creates a “mini Express app”:
 - * create one `Router` per prefix, and mount them on the corresponding prefix with `use`
 - * inside each router, use `router.method` to handle subpaths
 - * allows for modular, hierarchical development
- standard middleware:
 - `express.static(absPathRootDir)` serves static files from a root directory
 - `body-parser` package is a collection of HTTP body parsers
 - * eg. `bodyParser.json()`
- what if an error occurs during request handling?
 - call `next(err)` to get into an error-handling mode:

- * stops request handling chain and invokes an error handler
 - * `next()` with no parameter moves onto the next request handler, while `next(err)` moves onto the error handler
- similar to throwing and catching exceptions
- the **error handler** is a callback function `cb(err, req, res, next)` :
 - * additional `err` parameter
 - * the default error handler in Express simply prints out the error
 - * to use an error handler, simply mount it with `app.use` at the end of the middleware chain
 - * multiple error handlers can be attached and called in sequence with `next(err)`
- the Express application generator can be used to generate skeleton code
 - `express -e` , use EJS template engine
- MVC in Express:
 - templates corresponds to views
 - handlers, routers, middleware correspond to controller
 - nothing yet corresponds to the model

Single Page Applications

- a **single-page application (SPA)** is a web application where everything happens on a single page:
 - no page reload and waiting
 - even when the browser needs to obtain data from the server
 - creates a desktop-app like experience
 - mechanisms required:
 - * need to detect certain user events
 - * allow user interaction to continue while awaiting data from the server
 - * need an asynchronous HTTP request and response API
- `fetch(url)` is commonly used:
 - asynchronous API to issue an HTTP request
 - is a new “promisified” version of the old `XMLHttpRequest`
 - sends a request and returns a promise that will be resolved to the response from the server
 - to obtain the response body, we can use `response.text()` or `response.json()`
 - * returns another promise that resolves to the body in the request format
 - the request can be customized by adding options to `fetch`
 - * eg. methods, headers, body
 - note that the returned promise is rejected *only* in the case of a network error:
 - * `4xx`, `5xx` status codes resolve normally
 - * `response.ok` is set to `false` for non- `2xx` status code
 - * alternatively, access status code directly through `response.status`
- due to the **same-origin policy**, `fetch` can send a request only to the *same* host of the page:
 - ie. cannot send a request to a third-party site
 - a browser policy
 - possible workarounds:
 - * run a proxy on the same host that forwards the request
 - * **cross-origin resource sharing (CORS)**
 - browser gets an explicit approval from the third-party server to receive any requests by checking for the `Access-Control-Allow-Origin` header
 - * JSONP
 - modern browsers take care of CORS automatically:
 - * server should be configured to respond with the access control

header

- * by default, third-party cookies are not sent to the cross-origin server for added security
 - the option `{credential: include}` for `fetch` sends cookies, server needs to respond with the `Access-Control-Allow-Credentials` header
- **extensible markup language (XML)** is a data representation standard with a semantic tag:
 - any tag name can be used to represent the data
 - unlike HTML tags that are used entirely for document structure, not semantics
 - XML is still popularity, but JSON is growing
 - to parse an XML string into XML DOM, we can use the `DOMParser`
 - * the DOM tree can be accessed through JS DOM functions eg. `getElementsByTagName`
 - to serialize an XML DOM into an XML string, we can use the `XMLSerializer`

Example XML to HTML snippet:

```
function xml2html(res_text) {
  let parser = new DOMParser();
  let xml = parser.parseFromString(res_text, "text/xml");
  let s = xml.getElementsByTagName('suggestion');

  let htmlCode = "<ul>";
  for (let i = 0; i < s.length; i++) {
    let text = s[i].getAttribute("data");
    htmlCode += "<li><b>" + text + "</b></li>";
  }
  htmlCode += "</ul>";
  return htmlCode;
}
```

- the back button may cause a usability issue:
 - user may expect the previous app state *within* the SPA
 - browser may instead unload the app and go to the previous page
 - within a SPA, how can we solve this **deeplink** issue ie. go back to a particular state of the app if all states are the same page?
 - * one approach is to use a **URL fragment identifier**
 - changes in URL fragment identifiers do not reload a page:
 - * allow for navigation within the same page eg. `http://test/path#fragment`
 - * we can associate each state of the app with a unique URL fragment
 - * browser will change the URL, but the page will not change

- the client must monitor the fragment identifier change event to instead perform a state change event through `window.onhashchange`
 - * `window.location.hash` holds the URL fragment identifier
- the **session history API** added in HTML5 is another approach for sessions:
 - `history.pushState(obj, title, url)` and `history.replaceState(obj, title, url)`
 - allows saving an object
 - when users navigate history through the back button, the pop state event is triggered
 - * `window.onpopstate` is the event to update the app using the popped object
- the **web storage API** allows for persistent data storage on the client-side:
 - would allow SPA to work using saved data even with no network
 - downsides of a cookie?
 - * can expire, and must be sent to the server
 - `localStorage` is an associative array for persistent client-side data storage
 - * lasts over multiple browser sessions
 - `sessionStorage` persists only within the current browser tab:
 - * data disappears once the browser tab is closed
 - * if two tabs from the same server is opened, they get separate storage
 - standard allows storing any object for local and session storage, but most browsers only support string
 - `IndexedDB` is a more advanced local storage API with support for:
 - * JSON object storage
 - * transactions
 - * non-blocking asynchronous API

Client Side Frameworks

- as the app becomes more complex, the code becomes less simple to modularize and much more difficult to maintain:
 - what would the code for Gmail look like?
- 1. code complexity
 - thousands of lines of JS, HTML, CSS
- 2. lack of modularity:
 - many global variables and name conflicts
 - code maintenance difficulty
- 3. code reusability
- framework idea:
 - any complex UI apps consists of simpler **components**:
 - * each component should be mostly generic and independent of others
 - * structure and develop the app to exploit this independence and reusability
 - can we split a complex program into independent *modules*?
 - can we develop and provide a *library* of commonly-used independent modules?
 - can we program at a *higher-level* than DOM elements?
- component-based development:
 1. split the app into a hierarchy of simpler components
 2. develop each component independently with unit testing
 3. combine simple components into more complex ones
 - advocated first by React, now adopted by all popular frameworks:
 - * reduces development and maintenance complexity
 - * local changes are limited to a particular component
- case conventions:
 - camel case is typically used in JavaScript
 - kebab case is typically used in HTML and filenames

Angular

- **Angular** is a web frontend development framework developed by Google:
 - supports development of complex SPAs
 - provides easy-to-use end-to-end development tool-chain
 - encourages modular development through components and services
 - one of three most popular frameworks together with React.js and Vue.js
- Angular CLI:

- `ng new <app-name>` generates initial skeleton code
 - * main code is in `src/app`
- `ng build --prod` builds the final production HTML, CSS, and JS files in `dist/`
- `ng serve --host 0.0.0.0` starts up a temporary server that detects changes to source files:
 - * helps avoid manual recompilation and deployment
 - * only for development
 - * note that Angular runs in the browser and *not* the server
- `ng generate component <component-name>` generates skeleton code for a component
- in Angular, the app is split into modular components:
 - each component is developed independently with unit tests
 - a **component** is a specific part of an app responsible for a certain UI interaction:
 - * eg. label list, search box, email list, etc.
 - * the `@Component` decorator takes `selector`, `template`, `styles` as options
 - alternatively `templateUrl`, `styleUrls`
 - the HTML **template** for a component determines what a component displays on the page
 - **component directives** are custom Angular HTML tag extensions
 - * eg. `<app-search-box></app-search-box>`
- **data binding** allows interaction between template and its class:
 - we want the component template to interact with its class dynamically
 - * several different data binding mechanisms
 - 1. in **interpolation**, we use the syntax `{{ expr }}` to replace with the result of `expr` :
 - eg. `{{ title }}` displays the `title` property of the component in its template with
 - the expression should have no side effect
 - 2. in **property binding**, we use the syntax `[property]="expr"` to set the value of a property of an HTML element:
 - the `@Input` decorator defines which properties bindings are exposed to parent components
 - eg. `[value]="defaultQuery"` sets the default value of an input to the result of `defaultQuery`
 - importantly, whenever the value of `expr` changes, the `property` value is *dynamically* updated
 - 3. in **event binding**, we use the syntax `(event)="statement;"` to call a class method on a certain event:
 - executes `statement` when `event` is triggered:

- * all standard DOM events eg. from `input` will bubble up to parents
 - * but a component can throw its own *custom* events as well
- the statement may have side effect
- to get access to the default DOM event, we can use `$event`
- note that if we attach a regular click handler through `onclick=...`, this click handler will not have access to the component methods
 - * ie. this click handler is not compiled into Angular-specific code
- custom Angular events:
 - eg. `<app-search-box (advice)="onAdvice($event);">`
 - to “throw” a custom event:
 - * we need an `EventEmitter` object and assign it to a property
 - * add the `@Output` decorator to make the object available for event binding
 - * then, calling `emit(obj)` on the property will throw an event with the property name
 - `obj` is passed as the `$event` object
 - eg. `@output() advice = new EventEmitter<string[]>();` in search box component
 - * `onAdvice` will have access to an emitted string array when the child calls `emit(advice)`
 - note that custom events *do not* bubble up and only its direct parent can catch custom events
 - * vs. standard DOM events
- we can use attribute directives in components to allow interaction between parent and child components:
 - creating extended components that look and behave like a standard HTML element:
 - * property and event binding act as an API for the component
 - name is the component directive, inputs are property bindings, outputs are event bindings
 - * can eg. create custom properties that parent components can control
 - * can throw custom events that parent components can intercept and additionally add handlers for
 - eg. `<app-search-box [query]="title" (input)="onInput($event);">`
- **structural directives** allow different HTML elements depending on a class property value:
 - include `*ngIf`, `*ngFor`, `*ngSwitch`
 - eg. `<img [src]="imgUrl" *ngIf="imgUrl"` creates an element and its descendants only if the `imgUrl` is truthy
 - eg. `<li *ngFor="let item of items">` creates one DOM element per

each element in `items`

- * `item` is a template input variable

`ngSwitch` example:

```
<ng-container [ngSwitch]="media.type">
  <img [src]="media.url" *ngSwitchCase="'image'"/>
  <video [src]="media.url" *ngSwitchCase="'video'"></video>
  <embed [src]="media.url" *ngSwitchDefault>
</ng-container>
```

- an Angular **service** provides services that can be used by many components

Reactive Programming

- **reactive programming** is a programming paradigm that revolves around observables and events:
 - a functional, declarative, asynchronous paradigm
 - * **RxJS** is a JS library for reactive programming
 - useful for operating on lists that are expensive to iterate through:
 - * there may be latency associated with accessing the next element
 - * eg. a list being sent over a network
 - in a reactive program, we write a set of operators performed on observables:
 - * consists of *reactions* to input events
 - * ie. reactive programs “react to” input events
 - an **observable** is a generalization of an iterable object that accounts for asynchronous list accesses:
 - * `onNext` will be called on every item `e`
 - * `onCompleted` will be called
 - * AKA a publisher or an object that produces a sequence of events
 - * note that everything is observable eg. arrays, iterables, events, variables
 - eg. sequence of events, a variable is simply a single element array
 - an **observer** is an object interested in the events from an observable
 - * AKA a subscriber
 - an **operator** transforms input observables into output observables:
 - * eg. `filter`, `map`, `reduce`
 - * complex operators can be created by piping together simple operators
 - observables are most assumed to operate through a “push” operation

- * instead of constantly monitoring for the next element to be available, it will be notified
- when are observables useful:
 - observables can be used for any type of programming
 - particularly useful when dealing with *streams* of events:
 - * UI apps
 - * asynchronous programs
 - * servers
 - reactive programs are *declarative*:
 - * different from procedural or imperative programming
 - * declarative programs provide enormous optimization opportunity
 - reactive programming uses **pure functions**:
 - * the same input always gives the same output ie. function can be understood on its own
 - * no side effects ie. function does not change outside states
- reactive operators:
 - `filter` filters those events that meet a condition
 - `map` maps every input event to an output event
 - `flatMap` creates multiple output events from one input event
 - * ie. flattening the output
 - `reduce` performs cumulative operations to produce one final output at the end
 - `scan` is similar to reduce, but produces one output per every input based on the cumulative progress
 - `buffer(time)` buffers input events for a specified period and produces buffered inputs as output
 - * `bufferTime(timeSpan, creationInterval), bufferCount(m, n)` perform similarly
 - `debounce(time)` produces an output after a specified period of inactivity
- multi-way operators take multiple input streams as input:
 - `merge` merges events from all input streams into a single output stream
 - `zip` takes one event from each input stream and generates an output from the pair
 - `A.buffer(B)` buffers events from `A` until `B` emits a new event
 - * also `A.bufferToggle(opening, closing)`
 - `join(time)` produces one output per every input event pair within a time window
- ex. Convert a single-click stream into double or triple clicks if there is less than a 250ms pause between clicks:
 - `clickstream.buffer(clickstream.debounce(250)).map(e ⇒ e.length)`

CSS

Example CSS selectors:

```
p {}           /* p element */
p.notes {}    /* p element of notes class */
p .notes {}   /* element of notes class that is a descendant of p */
#text42 {}    /* id text42 */
img[src$=".svg"] {} /* src attribute ending with .svg */
```

- CSS inheritance:
 - CSS can be specified in three places:
 1. browser default
 2. user preference
 3. web page
 - if not set in any of these places, an element will *inherit* its parent's CSS properties
- the CSS **cascading rule** dictates which CSS rule wins in case of a conflict:
 1. more specific rules win
 - id > class > tag
 2. source order:
 - if equal specificity, a later rule wins
 - web page > user preference > browser default
- CSS **variables** AKA custom properties allows using a logical name to specify a value:
 - wherever a CSS custom property is defined, only the descendants can see the property
 - * thus variables are typically defined in `body` or `root`
 - must start with `--`
 - can be referenced with `var(..)`
 - * can also give fallback values
 - eg. `--dark-bg-color: brown` , `var(--dar-bg-color, black)`
- CSS box model and positioning:
 - width, height, padding, border, margin
 - `position` can be:
 - * `relative` ie. relative to its normal position
 - * `absolute` ie. relative to its nearest positioned ancestor
 - * `fixed` ie. relative to the viewport
 - * `static` is the default, ie. element is unpositioned
- block vs. inline elements:
 - inline elements do not create a separate block, and instead flow with surrounding text

- width, height, and vertical margin properties are ignored for inline elements

Example CSS for a fixed header and side menu:

```
#header {
  width: 100%;
  height: 90px;
  position: fixed;
  left: 0;
  top: 0;
}

#menu {
  width: 100px;
  height: calc(100% - 90px);
  position: fixed;
  left: 0;
  top: 90px;
}
```

- CSS grid:
 - container properties:
 - * `display: grid`
 - * `grid-template-rows` specifies the size for each row
 - similarly for `grid-template-columns`
 - item properties
 - * `grid-column-start`, `grid-column-end`, etc. specify how many rows or columns to span
- in **responsive web design**, we design for a wide range of devices:
 - eg. phone, tablet desktop, etc.
 - page design should dynamically adapt to the screen size
 - in *fixed* layout, elements have fixed width
 - * resizing the window does not change their sizes
 - in *fluid* layout, elements instead use a percentage of page width
 - * elements dynamically resize to fit window width
 - general rules:
 - * do not force users to scroll horizontally
 - * do not use fixed-width elements
 - * use CSS media queries to apply different styling based on screen size:
 - eg. `@media condition { ...rules... }` like `@media (max-width: 800px) {}`
 - media types include `screen`, `print`, `speech`, `all`
 - media features include `orientation`, `min-width`, `resolution` etc.

- boolean operators for the condition include `&`, `||`, and `!`
- the `viewport` meta tag defines a user's visible area of the web page:
 - * `width` is the viewport width
 - * `initial-scale` is the initial zoom level
 - * generally want to override the default viewport setting for smaller devices
- CSS flexbox:
 - a new addition to CSS to enable flexible layout of elements with `display: flex` on the container
 - * all children of a flex container become flex items
 - changing size:
 - * `flex-basis` is the default size of an element
 - * `flex-grow` specifies how to divide extra remaining space
 - * `flex-shrink` specifies how to take away space when there is space shortage
 - rearranging inputs:
 - * `flex-wrap` wraps the flexbox
 - * `flex-direction` determines the wrapping direction
- animations:
 - can use JavaScript, eg. with `setInterval/setTimeout` and `style` property of elements
 - CSS animation:
 - * `transition` property creates a transition effect eg. `transition: height 1s;`
 - * `@keyframes` rule specifies the keyframes of an animation
 - * `transform` can specify more complex shape transformations

Keyframes example:

```
@keyframes background-change {
  0%: { background: red; }
  50%: { background: yellow; }
  100%: { background: green; }
}

#someId {
  animation: background-change 3s;
}
```

Scaling

- how do we plan for capacity when deploying a website on servers?
 - number of machines and number of requests a machine can handle depends on different applications
 - 1. set your minimum acceptable service requirement
 - 2. characterize the workload
 - eg. measure requests per second, resource utilization per second
 - 3. premature optimization is “the root of all evil”
 - measure the workload first
- how many *static* web pages can a standard machine handle per second?
 - typical machine speeds:
 - * disk and DB IO transfers between 100-3000 MB/sec, and seeks on average 5-10 ms
 - * memory transfers 10-50 GB/sec
 - * network transfers 1-10 Gbps
 - just have to serve data from disk or memory over the network
 - * main bottleneck is mostly disk (reduced with caching) and network IO
 - DNS lookup is often very slow, so reverse DNS lookup should be disabled
 - tens of thousands per second per core, billion requests per day
- how many *dynamic* web page can a machine serve per second?
 - depends on the complexity of the application
 - * any of IOs, context switches, CPU may bottleneck
 - rule of thumb is 10 requests per second per core
- basic UNIX monitoring tools:
 - `top`, `ps`, `ps tree` for CPU and processes
 - `iostat` for disk IO
 - `netstat` for network IO
 - `free -m`, `ps aux`, `vmstat`, `memstat` for memory
- can we use **caching** to improve performance and scalability?
 - what layer to cache at?
 - * database, application, HTTP, encryption layer?
 - *below* the database layer, ie. at the filesystem level, cache disk blocks
 - * add RAM, or increase database bufferpool size
 - *above* the database layer, cache database objects like tuples in RAM:
 - * minimize number of requests hitting the DB
 - * common tools include Memcached and Redis
 - generally support distributed caching
- caching above the application layer:

- store and cache generated HTML page as a static file:
 - * avoids generating HTML for a short lifetime, eg. if page was already requested in the last 10 seconds, simply serve the last cached copy
 - * microcaching AKA caching for a very short period
- especially useful for slow-updating dynamic sites or if short delay is tolerable
 - * eg. blogs, web forums, etc.
- what if a *small* part of a page has to change every time?
 - * eg. Reddit
 - * use a **edge-side include (ESI)** to separate out uncachable parts from the cachable part
 - eg. `<esi:include src="part1.html"/>`
 - * the ESI server fetches all parts and synthesizes the final pages
 - regenerate and cache each part at a different granularity ie. expiration date
- caching above the HTTP layer:
 - use a **content distribution network (CDN)**
 - * cache pages, images, videos, etc. close to users at the *edge* of the network
 - users access cached objects located close to them:
 - * lower delay
 - * lower load on network
 - CDNs are a must for sites like YouTube
- caching above the encryption layer:
 - browser cache
 - let browser cache decrypted pages locally
- how can we scale a web site as it grows?
 - scale up and buy a larger, more expensive server
 - scale out and add more machines
- scaling DB layer?
 1. global read-only access:
 - requests do not change the underlying database
 - replication thus has no synchronization issue for read-only accesses
 2. local read and write:
 - touching a very specific part of the data eg. web mail, banking
 - if we are doing replication, we can only scale the reads, but not the writes
 - instead, partition / split up the database ie. **sharding**
 - * need to route requests to the correct machines
 3. global read and write:
 - writes are globally visible eg. online auction, social network

- replication and partition still work, but to less degree
 - * eventually write requests saturate the DB
 - CPU is rarely a bottleneck for scaling out:
 - * instead, DB and storage becomes the main bottleneck
 - * identify early on how we will cache / replicate / partition the DBMS as number of users grow
- cluster computing:
 - eg. Kubernetes: - automatic deployment and management of containerized applications - progressive rollout of application changes - automatic scaling and load balancing of apps based on CPU usage - automatic restart of failed, unresponsive nodes