Lecture Module - Frequency Response

ME3050 - Dynamics Modeling and Controls

Mechanical Engineering

Tennessee Technological University

Frequency Response

Lecture Module - Frequency Response

- Topic 1 - Frequency Response of First Order Systems

- Topic 2 - The Bode Diagram

- Topic 3 - Frequency Response of 2^{nd} Order Systems

- Topic 4 - Resonance

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Topic 1 - Frequency Response of First Order Systems

- Frequency Input Concept

- Complex Numbers Review

- Frequency Response of First Order Systems

- Graph of Frequency Response

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Frequency Input Concept

The term **frequency response** is used to describe a system's response to a periodic input. Frequency response analysis focuses on a system's response to *harmonic* input such as sines and cosines. The input (forcing) function is written below.

$$f(t) = A sin(\omega t)$$

Amplitude of the Input, $\quad A \quad (N)$

Frequency of Input, $\quad \omega \quad (\frac{rad}{s})$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Frequency Input Concept

Why do we care about the way a system responds to harmonic excitation? Why is **frequency analysis** important?

-
-
-

What causes **harmonic** (or sinusoidal) excitation in the real world?

-
-
-

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Frequency Input Concept

A linear, time-invariant (LTI) system has a **transfer function** $T(s)$ that describes the **input-output** relationship of the system. Under sinusoidal excitation (input) with frequency ω if the system is stable the transient affects in the response (output) will eventually disappear leaving the **steady state sinusoidal response** of the same frequency as the input but with a phase shift w.r.t. the input.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Complex Numbers Review

In an underdamped system the roots of the characteristic polynomial are complex. Before we proceed we need to review some rules of arithmetic and complex numbers.

The Complex Plane: $\mathbb{C}$

$$\mathbf{P} = x + jy$$
$$|\mathbf{P}| = \sqrt{x^2 + y^2}$$

Cartesian Representation:

$\mathsf{P} = x + jy$

Polar Representation:

$\mathsf{P} = |\mathsf{P}|\angle\theta$

Exponential Representation:

$\mathsf{P} = |\mathsf{P}|e^{j\theta} = |\mathsf{P}|\left(cos\theta + jsin\theta\right)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Complex Number Algebra

Consider two points P_1 and P_2 on the complex plane.

$P_1 = x_1 + jy_1$ and $P_2 = x_2 + jy_2$

Addition: $\qquad P_1 + P_2 = (x_1 + x_2) + j(y_1 + y_2)$

Multiplication: $\qquad P_1 P_2 = |P_1 P_2| \angle (\theta_1 + \theta_2)$

Division: $\qquad \dfrac{P_1}{P_2} = (x_1 + x_2) + j(y_1 + y_2)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

First Order Mass Damper

Consider our 1$\underline{st}$ order mass damper system.

$m\dot{v} + cv = f(t)$ with a **time constant** $\tau = \frac{m}{c}$

The system is commonly re-written as shown below.

$m\dot{v} + cv = f(t) \rightarrow \tau\dot{y} + y = f(t)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

First Order Transfer Function

$\tau \dot{y} + y = f(t)$

Take the Laplace transform of the ODE.

$\mathcal{L}\{\tau \dot{y} + y\} = \mathcal{L}\{f(t)\}$

$\tau(sY(s) + y_0)) + Y(s) = F(s)$ The initial conditions are zero.

$T(s) = \dfrac{Y(s)}{F(s)} = \dfrac{1}{\tau s + 1}$ First Order Transfer Function

This considers a *generalized* input function $f(t)$ and zero ICs.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Sinusoidal Input Function

Our model is now excited by a sinusoidal input function.

$$\tau \dot{y} + y = f(t) = A \sin(\omega t)$$

Take the Laplace transform. Then, solve for $Y(s)$ and expand.

$$\tau s Y(s) + Y(s) = \frac{A\omega}{s^2 + \omega^2}$$

$$Y(s) = \frac{A\omega}{(s^2 + \omega^2)(\tau s + 1)} = \frac{C_1}{\tau s + 1} + \frac{C_2 s}{(s^2 + \omega^2)} + \frac{C_3 \omega}{(s^2 + \omega^2)}$$

Now solve for the coefficients.

$$C_1 = \frac{A\omega\tau^2}{1 + \omega^2\tau^2} \quad , \quad C_2 = \frac{-A\omega\tau}{1 + \omega^2\tau^2} \quad , \quad C_3 = \frac{A}{1 + \omega^2\tau^2}$$

Substituting and take the inverse Laplace transform.

$$y(t) = \frac{A\omega\tau}{1 + \omega^2\tau^2} \left(e^{\frac{-t}{\tau}} - \cos\omega t + \frac{1}{\omega\tau}\sin\omega t \right)$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Steady State Time Response

$$y(t) = \frac{A\omega\tau}{1+\omega^2\tau^2}\left(e^{\frac{-t}{\tau}} - cos\omega t + \frac{1}{\omega\tau}sin\omega t\right)$$

After some amount of time passes, the transient term will disappear leaving just the sinusoidal terms.

$$y(t) = \frac{A}{1+\omega^2\tau^2}\left(sin\omega t - \omega\tau cos\omega t\right)$$

This is re-written as a single sine term with a phase shift.

Steady State Frequency Response of First Order System

$$y(t) = \frac{A}{\sqrt{1+\omega^2\tau^2}}sin\left(\omega t + \phi\right) \qquad , \quad \phi = -tan^{-1}\omega\tau$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Amplitude Ratio

$$y(t) = \frac{A}{\sqrt{1+\omega^2\tau^2}} \sin(\omega t + \phi) \quad , \quad \phi = -\tan^{-1}\omega\tau$$

Notice that the system responds at the same frequency as the input but with a different amplitude and a phase shift. The ratio of the response amplitude to the input amplitude is called the **amplitude ratio, M**.

$$M = \frac{\frac{A}{\sqrt{1+\omega^2\tau^2}}}{A} = \frac{1}{\sqrt{1+\omega^2\tau^2}}$$

Fortunately we can find the **amplitude ratio** and **phase shift** directly from the transfer function. Recall the transfer function we derived.

$$T(s) = \frac{1}{\tau s+1} \quad \text{let } s = j\omega \quad \implies \quad T(j\omega) = \frac{1}{\tau j\omega+1}$$

$$|T(j\omega)| = \frac{|1|}{|\tau j\omega+1|} = \frac{1}{\sqrt{(\tau\omega)^2+1^2}} = \frac{1}{\sqrt{1+\tau^2\omega^2}} \qquad \text{Look familiar?}$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Frequency Input Concept
Complex Numbers Review
Frequency Response of First Order Systems
Graph of Frequency Response

Phase Angle

$|T(j\omega)| = \frac{1}{\sqrt{1+\tau^2\omega^2}} = M(\omega)$

$\angle T(j\omega) = \angle 1 - \angle(1 + j\omega\tau) = tan^{-1}\left(\frac{0}{1}\right) - tan^{-1}\left(\frac{\omega\tau}{1}\right) =$

$-tan^{-1}(\omega\tau) = \phi(\omega)$

Substitute $s = j\omega$ into the transfer function and solve for the magnitude and phase angle of this complex number which represent the magnitude ratio and phase shift.

Therefore the steady state response is written as follows.

$y_{ss}(t) = A|T(j\omega)|sin(\omega t + \angle T(j\omega)) = MAsin(\omega t + \phi)$

Wasn't that fun? Can you believe we used to do that on the board?!?!

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Topic 2 - The Bode Diagram

- Review Frequency Response

- Amplitude ratio in Decibels

- The Bode Diagram

- Frequency Response in MATLAB

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Harmonic Input Function

The term **frequency response** is used to describe a system's response to a periodic input. Frequency response analysis focuses on a system's response to *harmonic* input such as sines and cosines. The input (forcing) function is written below.

$$f(t) = A\sin(\omega t)$$

Amplitude of the Input, A (N)

Frequency of Input, ω $(\frac{rad}{s})$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

First Order Frequency Response

The steady state response we derived is shown. Remember, after some amount of time passes, the transient term will disappear leaving just the sinusoidal terms.

$$y_{ss}(t) = A|T(j\omega)|sin(\omega t + \angle T(j\omega)) = MA sin(\omega t + \phi)$$

The amplitude ratio and phase shift can be found from $T(j\omega)$.

$$M(\omega) = |T(j\omega)| = \frac{1}{\sqrt{1+\tau^2\omega^2}}$$

$$\phi(\omega) = \angle T(j\omega) = -tan^{-1}(\omega\tau)$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Graph of Frequency Response

The amplitude of the response is determined by the input frequency.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

First Order Frequency Response

The steady state response we derived is shown. Remember, after some amount of time passes, the transient term will disappear leaving just the sinusoidal terms.

$$y_{ss}(t) = A|T(j\omega)|sin(\omega t + \angle T(j\omega)) = MA sin(\omega t + \phi)$$

The amplitude ratio and phase shift can be found from $T(j\omega)$.

$$M(\omega) = |T(j\omega)| = \frac{1}{\sqrt{1+\tau^2\omega^2}}$$

$$\phi(\omega) = \angle T(j\omega) = -tan^{-1}(\omega\tau)$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Amplitude ratio in Decibels

The amplitude of the response is determined by the input frequency.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Dependence on Input Frequency

You can see that the amplitude ratio decreases as the input frequency increases. The individual curves represent systems with different time constants.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Review Properties of Logarithms

Basic Properties of Logarithms:

Multiplication $log(pq) = log(p) + log(q)$

Division $log(\frac{x}{y}) = log(x) - log(y)$

Power $log(x^n) = nlog(x)$

Units of Decibels for Magnitude:

$m(dB) = 10log(M^2) = 20log(M)$ convert back: $M = 10^{\frac{m(dB)}{20}}$

Decibel (dB), unit for expressing the ratio between two physical quantities, usually amounts of acoustic or electric power, or for measuring the relative loudness of sounds. One decibel (0.1 bel) equals 10 times the common logarithm of the power ratio. - Britannica.com

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Amplitude ratio on a Logarithmic Scale

These relationships are more useful shown on a logarithmic scale.
We can make use of the properties of logarithms in our analysis.

$$m\left(dB\right) = 20log\left(\frac{1}{\sqrt{1+\omega^2\tau^2}}\right) = 20\left(log\left(1\right) - log\sqrt{1+\omega^2\tau^2}\right)$$

$$m\left(dB\right) = 20log\left(1\right) - 10log\left(1+\omega^2\tau^2\right) = -10log\left(1+\omega^2\tau^2\right)$$

$$m\left(dB\right) = -10log\left(1+\omega^2\tau^2\right)$$

amplitude ratio in decibels

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Amplitude ratio on a Logarithmic Scale

This is a Bode plot. It seems abstract but there is some very useful information shown.

Hendrik Bode (1905-1982)

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

The Bode Diagram

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

Bode Plot in MATLAB

MATLAB has a built it tool for making Bode plots.


```
figure(1)
sys=tf(1,[tau(3)
    1])
bode(sys);grid on
```

So what? What can you do with a Bode diagram?

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Frequency Response
Amplitude ratio in Decibels
The Bode Diagram
Frequency Response in MATLAB

References

- System Dynamics, Palm III, Third Edition - Chapter 9 - System Response in the Frequency Domain

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

Topic 3 - Frequency Response of 2nd Order Systems

- Review Transfer Functions

- Frequency Response of Overdamped Systems

- Frequency Response of Underdamped Systems

- MATLAB Bode Plots

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

Equivalent System Representations

The **Transfer Function** is the input-output relationship in the frequency domain and can be found from the equation of motion of the system.

$$T(s) = \frac{X(s)}{F(s)}$$

The Transfer Function is an equivalent representation of the system.

E.O.M	$\leftrightarrow$	T(s)	$\leftrightarrow$	Block Diagram

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

Transfer Function of 2nd Order System

$$m\ddot{x} + c\dot{x} + kx = f(t) \qquad \text{with} \qquad f(t) = A sin(\omega t)$$

The transfer function can easily be found by taking the Laplace transform of the equation of motion.

$$T(s) = \frac{X(s)}{F(s)} = \frac{1}{ms^2 + cs + k} \qquad \text{Second Order Transfer Function}$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

The Overdamped System

In an <u>overdamped</u> system, both roots are real and distinct.

The transfer function is shown below in terms of the system parameters

$T(s) = \frac{X(s)}{F(s)} = \frac{1/k}{\left(\frac{m}{k}\right)s^2 + \left(\frac{c}{k}\right)s + 1} = \frac{1/k}{(\tau_1 s + 1)(\tau_2 s + 1)}$ τ_1, τ_2 - time constants

Substitute $s = j\omega$ into the transfer function and find the amplitude ratio and phase angle.

$T(s) \rightarrow T(j\omega) = \frac{1/k}{(\tau_1 j\omega + 1)(\tau_1 j\omega + 1)}$

$M(\omega) = |T(j\omega)| = \frac{|1/k|}{|\tau_1 j\omega + 1||\tau_2 j\omega + 1|}$

$m(\omega) = 20 log M(\omega) = 20 log |1/k| - 20 log |\tau_1 \omega j + 1| - 20 log |\tau_2 \omega j + 1|$

$\phi(\omega) = \angle \frac{1}{k} - \angle (\tau_1 \omega j + 1) - \angle (\tau_2 \omega j + 1)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

The Bode Diagram

These three terms can be seen on the Bode diagram.

$$m\left(\omega\right) = 20logM\left(\omega\right) = 20log|1/k| - 20log|\tau_1\omega j + 1| - 20log|\tau_2\omega j + 1|$$

This shows that the magnitude ratio of the system across different regions of the input frequency.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

The Underdamped System

In an underdamped system, the roots are complex conjugates.

The transfer function is shown below in terms of the system parameters

$T(s) = \frac{X(s)}{F(s)} = \frac{1/k}{\left(\frac{m}{k}\right)s^2 + \left(\frac{c}{k}\right)s + 1} = \frac{1/k}{\left(\frac{s}{\omega_n}\right)^2 + 2\zeta\left(\frac{s}{\omega_n}\right) + 1}$

$T(s) = \frac{kX(s)}{F(s)} = \frac{\omega_n^2}{s^2 + 2\zeta\omega_n s + \omega_n^2}$

Notice we factored out k to form the ratio of output displacement $X(s)$ to input displacement $\frac{F(s)}{k}$. You can see this with Hooke's Law $F = kx \implies x = \frac{F}{k}$.

This also allows us to define the transfer function in terms of ζ and ω_n. Substitue $s = j\omega$ and mulitply the equation $\frac{1/\omega_n^2}{1/\omega_n^2}$.

$T(s) \rightarrow T(j\omega) = \frac{1}{\left(\frac{j\omega}{\omega_n}\right)^2 + \left(\frac{2\zeta}{\omega_n}\right)j\omega + 1} = \frac{1}{1 - \left(\frac{\omega}{\omega_n}\right)^2 + \left(\frac{2\zeta\omega}{\omega_n}\right)j}$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

The Frequency Ratio

To simplify this expression we define another new quantity the frequency ratio, r as the ratio of input frequency to natural frequency of the system. The transfer function is re-written in terms of the frequency ratio.

$r = \frac{\omega}{\omega_n} \quad \rightarrow \quad T(j\omega) \quad \rightarrow \quad T(r) = \frac{1}{1-r^2+2\zeta rj}$

Now the amplitude ratio and phase are written in tems of r.

$M = |T(r)| = \frac{1}{\sqrt{(1-r^2)^2+(2\zeta r)^2}}$

$\implies m = 20logM = -10log\left[\left(1-r^2\right)^2 + \left(2\zeta r\right)^2\right]$

$\phi = \angle 1 - \angle\left(1 - r^2 + 2\zeta rj\right) \implies \phi = -tan\left(\frac{2\zeta r}{1-r^2}\right)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

The Bode Diagram

In the underdamped second order system only two regions are present in the Bode diagram.

As the damping ratio decreases something significant happens. This Bode diagram shows something that the others before have not.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

MATLAB Bode Plots

Vary the system parameter in the scripts to make the plots shown.

```
clear variables;clc;close all

% define the system parameters
m=2;c=1;k=20;
zeta=c/(2*sqrt(m*k));

% create a system object from the transfer
    function
sys=tf(1/k,[(m/k) (c/k) 1]);

% use built-in MATLAB Bode Plot
figure(1)

bode(sys);grid on
```

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review Transfer Functions
Frequency Response of Overdamped Systems
Frequency Response of Underdamped Systems
MATLAB Bode Plots

References

- System Dynamics, Palm III, Third Edition - Chapter 9 - System Response in the Frequency Domain

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review 2^{nd} Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Topic 3 - Resonance

- Review 2^{nd} Order Frequency Response

- The Resonance Phenomenon

- The Resonance Frequency

- —

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Transfer Function of 2nd Order System

$$m\ddot{x} + c\dot{x} + kx = f(t) \qquad \text{with} \qquad f(t) = A\sin(\omega t)$$

The transfer function can easily be found by taking the Laplace transform of the equation of motion.

$$T(s) = \frac{X(s)}{F(s)} = \frac{1}{ms^2 + cs + k} \qquad \text{Second Order Transfer Function}$$

The amplitude ratio and phase angle can be found from the transfer function. Think about what M means.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Overdamped vs. Underdamped Systems

In an <u>overdamped</u> system, both roots are real and distinct.

$$M(\omega) = |T(j\omega)| = \frac{|1/k|}{|\tau_1 j\omega + 1||\tau_2 j\omega + 1|}$$

$$m(\omega) = 20logM(\omega) = 20log|1/k| - 20log|\tau_1 \omega j + 1| - 20log|\tau_2 \omega j + 1|$$

$$\phi(\omega) = \angle\frac{1}{k} - \angle(\tau_1 \omega j + 1) - \angle(\tau_2 \omega j + 1)$$

In an <u>underdamped</u> system, the roots are complex conjugates.

$$M(r) = |T(r)| = \frac{1}{\sqrt{(1-r^2)^2 + (2\zeta r)^2}} \quad \text{with} \quad r = \frac{\omega}{\omega_n}$$

$$\implies m = 20logM = -10log\left[(1-r^2)^2 + (2\zeta r)^2\right]$$

$$\phi = \angle 1 - \angle(1 - r^2 + 2\zeta rj) \implies \phi = -tan\left(\frac{2\zeta r}{1-r^2}\right)$$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

The Resonance Spike

In the underdamped second order system only two regions are present separated by the point near $r = 1$.

As the damping ratio decreases something significant happens at this points. Remember, these are graphs of $m = 20 log M$.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

The Effects of Resonance

Consider the extreme case in the figure shown. What is the physical significance of the values of m near $r = 1$?

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
**The Resonance Phenomenon**
The Resonance Frequency
—

The Effects of Resonance

Consider the extreme case in the figure shown. What is the physical significance of the values of m near $r = 1$?

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Resonance can be Destructive

The resonance peak represents a amplitude ratio greater than one meaning the output amplitude is larger that in the input amplitude. This large amplitude output displacement caused by resonance correspond to a large force in the spring members and the large forces are transmitted to the body. Large forces cause mechanical failure.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2^{nd} Order Systems
Resonance

Review 2^{nd} Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

The Resonance Frequency

Where on the frequency response graphs does resonance occur? It looks like it is *near $r = 1$*.

$$M(r) = \frac{1}{\sqrt{(1-r^2)^2 + (2\zeta r)^2}} \quad \text{with} \quad r = \frac{\omega}{\omega_n}$$

The value of M is maximized when the denominator is minimized. Therefore the resonance frequency is found by taking the derivative of the denominator and setting it equal to zero.

$$M_{max} \quad \text{occurs at } r = \sqrt{1 - 2\zeta^2} \implies \omega = \omega_n\sqrt{1 - 2\zeta^2}$$

An input frequency equal to the resonance frequency causes maximum output displacement.

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

The Resonance Frequency

The resonance event only occurs in second order systems when the radical shown is positive. This corresponds to systems with damping ratio in the range $0 < \zeta < 0.707$.

$\omega_r = \omega_n \sqrt{1 - 2\zeta^2}$ $0 < \zeta < 0.707$

$M_r = \frac{1}{2\zeta\sqrt{1-\zeta^2}}$ or in decibels $m_r = -20 log \left(2\zeta\sqrt{1-\zeta^2} \right)$

The phase at resonance can also be found.

$\phi_r = tan^{-1} \left(\frac{\sqrt{1-2\zeta^2}}{\zeta} \right)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

The Resonance Frequency

It is important to note that we multiplied the transfer function by k during the derivations. Therefore if me divide the expressions for M and M_r by k to find the amplitude ratio between input force, $f(t)$ and output displacement, $x_{ss}(t)$

$M = \frac{1}{k\sqrt{(1-r^2)^2+(2\zeta r)^2}}$

$\implies \quad m = -20log(k) - 10log\left[\left(1-r^2\right)^2 + (2\zeta r)^2\right]$

$M_r = \frac{1}{k2\zeta\sqrt{1-\zeta^2}}$

$\implies \quad m_r = -20log\left(k\right) - 20log\left(2\zeta\sqrt{1-\zeta^2}\right)$

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

References

- System Dynamics, Palm III, Third Edition - Chapter 9 - System Response in the Frequency Domain

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—

Frequency Response of First Order Systems
The Bode Diagram
Frequency Response of 2nd Order Systems
Resonance

Review 2nd Order Frequency Response
The Resonance Phenomenon
The Resonance Frequency
—