

Lecture Module - Electrical Signals

ME3023 - Measurements in Mechanical Systems


Mechanical Engineering
Tennessee Technological University

Topic 2 - Signal Analysis

Topic 2 - Signal Analysis

- Signal Mean Value
- Power Dissipation
- Signal Root Mean Square (RMS) Value
- Discrete-Time or Digital Signals

Signal Mean Value



Mean Value

$$\bar{y} \equiv \frac{\int_{t_1}^{t_2} y(t) dt}{\int_{t_1}^{t_2} dt}$$

Power Dissipation

Dissipation - Time Rate of Energy Dissipation

$$P = I^2 R$$

Total Electrical Energy

$$E = \int_{t_1}^{t_2} P dt = \int_{t_1}^{t_2} [I(t)]^2 R dt$$

Signal Root Mean Square (RMS) Value

- For a cyclically alternating electric current, RMS is equal to the value of the direct current that would produce the same average power dissipation in a resistive load.
- In Estimation theory, the root mean square error of an estimator is a measure of the imperfection of the fit of the estimator to the data.
- The RMS value of a signal having a zero mean is a statistical measure of the magnitude of the fluctuations in the signal.

Signal Root Mean Square (RMS) Value

$$(I_e)^2 R(t_2 - t_1) = \int_{t_1}^{t_2} [I(t)]^2 R dt$$

$$I_e = \sqrt{\frac{1}{t_2 - t_1} \int_{t_1}^{t_2} [I(t)]^2 dt}$$

$$y_{rms} = \sqrt{\frac{1}{t_2 - t_1} \int_{t_1}^{t_2} [y]^2 dt}$$

Discrete-Time or Digital Signals

$$\bar{y} = \frac{1}{N} \sum_{i=0}^{N-1} y_i$$

$$y_{RMS} = \sqrt{\frac{1}{N} \sum_{i=0}^{N-1} y_i^2}$$

Discrete-Time or Digital Signals