

DHC 均质混合泵 DHC Compound & homogeneous pump



产品简介

DHC 均质混合泵由多管混合头与混合泵组成，混合泵由2~5层的转子和定子组成，每层转子与定子的齿轮盘由粗到细，使原始各组不同成份的物料按比例要求在瞬间混合均质。该产品广泛应用于生产工艺流程中需要多种物料进行混合均质以及化工流程工艺中的中和混合。

使用该混合设备后，使原有的传统生产工艺进一步简化，生产效率大幅度提高，混合后的产品质量明显提高。

Product profile

DHC Compound homogeneous pump is consist of multi-pipe compound chamber and compound pump. This pump comprises 2~5 layers of stators and rotators, the gear clearance of each layer stator and rotator is from wide to slender, let different raw material to compound and homogenize moment according to rate requirement. These products is used widely in neutralization admixture of multimaterial need to compound homogeneous and chemical industry process technics.

These serial products can greatly simplify the traditional production processes and upgrade the production efficiency and product quality.

DHC 均质混合泵 DHC Compound & homogeneous pump



技术参数表 Technical parameters

型号 Type	流量 (m³/h) Flow	系统压力 (MPa) Pressure	转速 (r/min) Rotation speed	功率 (kw) Power	粘度 (cp) Viscosity
DHC10-185	1~3	0.1~1.6	260~1400	2.2~4	1~200000
DHC20-185	3~6	0.1~1.6	260~1400	3~5.5	1~200000
DHC10-200	5~10	0.1~1.6	260~1400	3~7.5	1~200000
DHC20-200	10~15	0.1~1.6	260~1400	4~11	1~200000
DHC15-260	15~20	0.1~1.6	260~1400	5.5~15	1~200000
DHC25-260	20~30	0.1~1.6	260~1400	7.5~18.5	1~200000
DHC15-300	40~50	0.1~1.6	260~1400	11~30	1~200000
DHC30-300	50~80	0.1~1.6	260~1400	15~45	1~200000
DHC15-360	80~120	0.1~1.6	260~1400	22~55	1~200000
DHC30-360	120~160	0.1~1.6	260~1400	30~75	1~200000
DHC15-400	160~220	0.1~1.6	260~1400	55~90	1~200000
DHC30-400	220~250	0.1~1.6	260~1400	75~110	1~200000
DHC15-460	260~320	0.1~1.6	260~1400	90~132	1~200000
DHC30-460	320~350	0.1~1.6	260~1400	110~160	1~200000