EA-PDF Workflow Decision Tree

Inputs, profile choices, switches, config flags, and output behavior in one page.

Start Here
What are you converting?

Local Email Files

- Input: .eml, .msg, .pst, .mbox
- CLI: EmailToPDFA
- Best when the source is already local

Gmail

- Input: live Gmail mailbox or folder
- CLI: GmailDownloadToPdf
- OAuth download plus conversion

Local Email Profiles

- Default: one 1s PDF per message.
- Archive profiles via --archive-profile: 1m, 1mi, 1c, 1ci.
- --archive-output chooses the container filename.
- --omit-source suppresses source where the profile allows it.

Gmail Profiles

- Use --archive-profile for 1m, 1mi, 1c, or 1ci.
- --folder selects the mailbox or label.
- --limit and --unread-only trim the fetched set.
- --omit-source affects non-isolated outputs.

CLI Switches

- EmailToPDFA: --out, --font, --icc, --global-id/-g, --email/-e, --jobs/-j, --omit-source, --archive-profile, --archive-output, --debug, --debug-dir.
- GmailDownloadToPdf: --user, --credentials, --token-dir, --folder, --out-pdf, --limit, --unread-only, plus the archive and rendering switches above.

Config JSON Flags

- branding: enabled.
- findingAid: excelEnabled, embedExcel, embedPdfInCollections.
- accessibility: addPdfUaFeatures, markInfoMarked, language, readingDirection, pageLabels.*.
- premis: enabled, writeSidecar.

Output Behavior

- 1s / 1si: one PDF per message.
- 1m: one archive PDF with messages rendered inside.
- 1mi: isolated archive PDF with no source embedding.
- 1c / 1ci: collection or portfolio outputs.
- Per-file logs are written to out/logs.

Parallel Processing

- Local non-archive conversions use a worker pool via --jobs.
- Archive input reading now runs in parallel while preserving order.
- Archive message rendering and collection member generation are parallelized.
- Gmail remains mostly API-bound and therefore less parallel.

Quick Guide

Use 1m or 1c for source-rich preservation and 1si / 1mi / 1ci for isolated outputs.