table

employee_id	name	department_name
1	Alice	HR
2	Bob	IT
3	Charlie	NOT Assigned
4	Dana	Finance

Q3 Find orders with Null Customer_id using IS NULL

Syntax

```
SELECT order_id,
       Customer_id
FROM orders
WHERE ISNULL (Customer_id);
```

Table

order_id	Customer_id
103	Null

Q4. Replace Null delivery dates with 'Pending'

Syntax

```
SELECT order_id,
       Customer_id,
       IFNULL (delivery_date, 'Pending') AS delivery
       Status
FROM Orders;
```

table

Order_id	customer_id	delivery_status
101	201	2024-12-01
102	202	Pending
103	NULL	2024-12-03

Q5. Replace NULL grades with 0

Syntax

```
SELECT Student_id,
       name,
       IFNULL(grade,0) AS Final_grade
FROM Students;
```

Table

Student_id	name	Final_grade
1	Ethan	85
2	Maya	0
3	Olivia	90

Q6 Count Students without grades.

Syntax

```
SELECT Count(*) AS not_graded_Count
FROM Students
WHERE grade IS NULL;
```

table

not_graded_Count
1

Q7. Calculate final price after discount

Syntax

```
SELECT product_id, name, Price - IFNull
       (discount,0) AS Final_price
FROM products;
```

table

product_id	name	final_price
S01	Keyboard	25
S02	Mouse	10
S03	Monitor	100

Q8. Count customers with no email

Syntax

```
SELECT COUNT(*) AS missing_email_count
FROM Customers
WHERE email IS NULL;
```

table

Missing_email_count
2

Q9 Display email or 'No email'

Syntax

```
SELECT customer_id,
       name,
       IFNULL(email, 'No email') AS email_
       display
FROM Customers;
```

table

Customer_id	name	email_display
1	Linda	No email
2	Joseph	joseph@mail.com
3	Nia	No email

Q10 Replace Null payment method with 'Unknown'

Syntax

```
SELECT payment_id,
       IFNULL(method, 'Unknown') AS method_display,
       Status
FROM Payments;
```

table

payment_id	method_display	Status
301	Credit	NULL
302	Paypal	Success
303	Unknown	Failed

Q11 Replace NULL Quantities with 0

Syntax

```
SELECT item_id,
       item_name,
       IFNULL(quantity, 0) AS quantity_checked
FROM Inventory;
```

table

item_id	item_name	quantity_checked
1	Pen	0
2	Notebook	150
3	Eraser	0

Q12 Show first available reward

Syntax

```
SELECT emp_id,
       COALESCE(bonus, commission, 0) AS first_available_reward
FROM Employees_Extra;
```

table

emp_id	first_available_reward
1	300
2	100
3	0

Q13 Count Classes without rooms

Syntax:

```
SELECT COUNT(*) AS no_room_count
FROM Classes
WHERE room IS NULL;
```

table.

no_room_count
2

Q14 Replace Null attendance Status 'Not marked'

Syntax

```
SELECT Student_id,
       date,
       IFNULL(Status, 'Not marked') As attendance_
       Status
FROM Attendance;
```

table.

Student_id	date	attendance_status
1	2025-04-01	Not marked
2	2025-04-01	Present
3	2025-04-01	Absent

Q15 Display account type and balance default

Syntax

```
SELECT account_id,
    IFNULL(account_type, 'unknown') AS type_display,
    IFNULL(balance, 0) AS balance_checked
FROM Bank_accounts;
```

table

account_id	type_display	balance_checked
A1	Savings	0
A2	Current	5000
A3	unknown	2000

Q16 Replace Null start dates with TBD

Syntax

```
SELECT project_id,
    title,
    IFNULL(start_date, 'TBD') AS start_display
FROM Projects;
```

table

Project_id	title	start_display
1	website revamp	2025-01-10
2	Mobile App	TBD
3	Data Migration	TBD

Q17 Replace Null comment and rating

Syntax

```
SELECT review_id,
       Product_id,
       IFNull (comment, 'No comment') AS comment_
       display,
       IFNull (rating, 0) As rating_display
From Reviews;
```

table

review_id	Product_id	comment_display	rating_display
1	501	Great Product	4
2	502	No comment	0
3	503	Works fine	3

Q18 Display Supplier contact number

Syntax

```
SELECT  Supplier_id,
        name,
        COALESCE (Phone, alt_phone, 'No Contact')
        AS Contact_number
From Suppliers;
```

table

Supplier_id	name	Contact_number
1	Global Goods	123456789
2	Best Suppliers	9876543210
3	ValueSource	No Contact

Q19 Replace all user settings Null values

Syntax

```
SELECT user_id,
    IFNull(theme, 'Light') As theme_set,
    IFNull(language, 'English') As language_set,
    IFNull(timezone, 'UTC') As timeZone_Set
FROM user_Settings;
```

table

user_id	theme_set	language_set	timezone
1	Light	English	UTC
2	Dark	English	UTC+1
3	Light	English	UTC

Q20 Display maintenance log with defaults.

Syntax

```
SELECT record_id,
    Machine_id,
    IFNull(issue, 'Unknown issue') As issue_log,
    IF Null(technician, 'Not assigned') AS technician_
        name
FROM Maintenance;
```

table

record_id	machine_id	issue_log	technician name
1	M101	overheating	Not Assigned
2	M102	Unknown issue	Not Assigned
3	M103	Jammed	Alex