

NAAN MUDHALVAN PROJECT PORTFOLIO | PHASE 6 OF 8

Phase 6: Quality Assurance, Validation Testing & Access Security

Project: Auto Ticket Classification using Flow Designer | Stage: System Testing, UAT & ACL Governance

1. Testing Objectives & Validation Methodology

Phase 6 certifies that the automated categorization logic behaves deterministically under standard conditions, edge cases, and typo variations. Furthermore, data security controls are validated to verify that only authorized IT staff can alter classified fields while callers retain read and submission capabilities.

2. Test Execution Scenarios & Empirical Results

Scenario ID	Input Short Description	Expected Category	Expected Subcategory	Email Status	Result
TC-01	WiFi not working in library	Network	Wi-Fi	Generated & Sent	PASS
TC-02	Projector not turning on in Hall B	Hardware	Projector	Generated & Sent	PASS
TC-03	Student forgot password for portal	Access	Forgot Password	Generated & Sent	PASS
TC-04	Lab 3 computer is extremely slow and freezing	Performance	Slow Computer	Generated & Sent	PASS
TC-05	General student query regarding books	Unclassified (Null)	Unclassified (Null)	Held for IT Triage	PASS

3. Email System Log Verification (sys_email)

Audit Procedure

1. Navigate to: **System Logs** → **Emails**.
2. Filter by Subject contains 'Your IT Support Ticket' and Created > Today.
3. Locate the transaction corresponding to the test incident execution.
4. Under *Related Links*, select **Preview Email** to verify HTML body rendering, variable data pill substitution, and recipient address correctness.

4. Data Integrity & Security Access Controls (ACLs)

Security Architecture

- **Auto-Number Immutability:** Number generation validated to guarantee zero duplicate keys across simultaneous multi-user submissions.
- **Access Control Lists (ACLs):**
 - `u_incident_workflow.create`: Granted to authenticated `snc_internal` / End-users.
 - `u_incident_workflow.write`: Restricted to `itil` role members once classified.
 - `u_incident_workflow.read`: Granted to ticket caller (`current.u_caller == gs.getUserID()`) and assigned fulfillers.