Payload-Aware Two-Tier UAV Route Planning for Last-Mile Delivery

Review Report – I

Thirumurugan RA (3122235001149)
Meghna Manimaran (3122235001079)
Shrika SP Thota (3122235001125)

Guided by: Sujaudeen N, Assistant Professor

Department of Computer Science and Engineering
Sri Sivasubramaniya Nadar College of Engineering

Academic Year 2026–2027

Presentation Outline

1. Introduction
2. Literature Review
3. System Design
4. Implementation and Results
5. Project Management
6. Conclusion

Background and Motivation

- UAVs are an effective platform for last-mile delivery where ground transport is impractical: remote clinics, emergency drug drops, and fragile diagnostic sample transport.
- Every flight must balance three **conflicting objectives**: total distance, battery energy use, and exposure to high-risk flight segments.
- Existing routing systems treat all deliveries **identically** — a fragile medical device and a robust parcel travel the *same* route.
- Payload metadata (fragility, urgency, payload weight) encodes routing priorities, but **no system exploits this at mission time**.

Core Motivation

Payload-blind UAV routing pipelines cannot adapt to cargo-specific constraints. A two-tier architecture that bridges payload semantics directly to Pareto route selection addresses this structural gap.

Real-World Cost of Payload-Blind Routing

Swiss Post – Matternet M2 Crashes (Zürich, Jan & May 2019) [8]

Drones carrying clinical laboratory specimens flew **fixed, payload-invariant routes**. Post-incident analysis confirmed identical corridors regardless of cargo type — no routing adjustment for payload fragility.

Vibration & Turbulence Degradation Studies [9, 10, 11]

Controlled lab work shows drone-transported medicines degrade measurably: insulin fibrillation, biologic protein denaturation, elevated haemolysis in blood samples on high-vibration segments. Altitude variation and turbulence raise lab rejection rates.

Zipline Rwanda Blood-Delivery Network (up to 80 km/charge) [12]

Heavier blood-product payloads draw more hover/lift power and shorten range, yet the system flies the same fixed route regardless of payload weight — no energy-efficient detour for heavy cargo, no direct short route for urgent light payload.

Root cause in every case: the planner does not know what is carried, so it cannot prefer smoother corridors for fragile payloads or shortest paths for time-critical medicine.

Problem Statement

Problem

Existing UAV routing systems apply **static, cargo-agnostic objective weights**, resulting in **suboptimal or unsafe routes** for payloads with differing fragility, urgency, and payload weight.

- Given payload metadata $(F, W, U, P_{\text{lvl}})$ with $F \in \{1 \dots 5\}$, $W \in \{1 \dots 3\}$, $U \in \{1 \dots 3\}$, $P_{\text{lvl}} \in \{1 \dots 5\}$, and airspace graph $G = (V, E)$, select route p^* from the Pareto front that best satisfies payload requirements — no expert re-tuning, no re-running the search.
- Single-objective routing collapses all objectives into one scalar and cannot model their three-way conflict.
- No existing system maps payload description to Pareto point selection via an explicit algebraic formula.
- Constraints: selection must be deterministic, reproducible, and finish within 1 s of payload tag entry.

Review 0: Feedback & Actions

Panel Comment	Resolution in Current Work
"No correlation between Tier 1 and Tier 2 factors"	Explicit algebraic mapping introduced: Fragility F scales w_{risk}; Urgency U scales w_{dist}; Payload weight W scales w_{energy}. Every Tier 2 tag maps to a Tier 1 objective via a closed formula.
"Criteria are not considered to map together"	The formula $w_{\text{risk}} = (F{\times}2) \,/\, (F{\times}2 + U{\times}3 + W{\times}2)$ (and equivalents) is a continuous function — all four tags simultaneously influence all three weights; changing any single tag shifts all three weights proportionally.
"Application of Pareto needs rethinking"	Extreme-point selection **replaced** by utility scoring over the *full* Pareto front: $\text{score}(p_i) = w_d(1-\tilde{d}_i) + w_\varepsilon(1-\tilde{\varepsilon}_i) + w_\rho(1-\tilde{\rho}_i)$. Mixed-priority payloads select *non-extreme interior points* that no single-objective baseline can produce.
"Complexity only in Tier 2; more than 2 objectives"	Tier 1 manages three-objective NAMOA* graph-search complexity; Tier 2 manages metadata-to-weight mapping and full-front utility scoring. Both tiers carry distinct computational roles — neither reduces to a single-objective problem.

Project Objectives

1. To build a **multi-objective A* engine (Tier 1)** that constructs a Pareto-optimal route set over an airspace graph, balancing distance, energy consumption, and flight risk simultaneously.
2. To design an **algebraic bridge** that translates payload metadata tags (fragility F, payload weight W, urgency U, priority P_{lvl}) into normalised routing objective weights with no expert tuning.
3. To implement a **Tier 2 payload-driven selector** that scores every Pareto route using the derived weights and returns the utility-maximising route p^*.
4. To evaluate the pipeline using **simulation benchmarks** on 50, 200, and 500-node graphs against single-objective A* and MOPSO baselines, using hypervolume, Pareto spread, IGD, and Tier 2 selection accuracy.
5. To validate the system on **real drone hardware** (Raspberry Pi 5 + Pixhawk) through ArduPilot SITL simulation and outdoor flight tests.

Scope and Expected Outcomes

Included

- Payload-aware UAV route selection for single-drone delivery
- Two-tier pipeline: Pareto front construction + utility-based Pareto point selection
- Software simulation on OSM graphs (Thiruvanmiyur, Chennai)
- ArduPilot SITL + RPi 5 + Pixhawk hardware integration and outdoor flight tests
- Benchmark against single-objective A* and MOPSO

Excluded / Constraints

- Multi-UAV fleet management and coordination
- Real-time dynamic obstacle avoidance during flight
- Commercial deployment and regulatory compliance
- Weather-based in-flight re-routing
- Deep-learning-based risk estimation

Literature Review

Author / Year	Method	Key Contribution	Limitation / Research Gap
Chokkalingam & Ganesan (2026) [1]	Pareto-entropy PSO (POPSO) with dynamic parameter adaptation	Entropy-guided archiving improves front diversity; adaptable to real-time environmental changes	Final route still a manually re-tuned weighted sum per mission; payload metadata never incorporated — fragile samples and emergency medicine get the same hand-tuned selection
Tsoutsouras et al. (2020) [7]	Mass-aware flight-speed and energy-model adaptation for multi-drop trajectories	Reduces energy consumption vs. mass-agnostic planning across multi-stop routes	Continuous mass used only inside the energy/speed model itself; builds no multi-objective Pareto front; discrete payload metadata (fragility, urgency) plays no role in route selection
Ren et al. (2019) [2]	Crowding-distance NSGA-II (CDNSGA-II) over octree urban environment	Well-spread, collision-free Pareto-optimal paths in urban airspace	Crowding distance encodes only geometric front spread; urgency, fragility, and payload weight play no role in selection

Research Gap and Proposed Contribution

Three Identified Gaps

- **Gap 1:** No payload-aware route *selection* — all planners apply a fixed geometric criterion independent of payload type, or no selection mechanism at all
- **Gap 2:** No front reuse — full multi-objective search re-run whenever mission context changes
- **Gap 3:** No algebraic bridge — no formalised mapping from payload description to the routing trade-off it implies


Proposed Contribution (closes all three)

- Tier 2 maps four payload tags directly to Pareto point selection via formula **(Gap 1)**
- Front refreshed periodically; Tier 2 selects per mission against current front — no re-run **(Gap 2)**
- Closed-form bridge: $F, W, U \rightarrow w_{\text{risk}}, w_{\text{dist}}, w_{\text{energy}}$ **(Gap 3)**
- $p^* = \arg\max_{p_i \in \mathcal{P}} \text{score}(p_i)$ — selects non-extreme interior points for mixed payloads

Existing System vs. Proposed System


Criterion	Existing Routing Systems	Proposed Two-Tier System
Routing approach	Single-objective (distance or energy only)	Multi-objective NAMOA* — distance, energy, and risk simultaneously
Payload handling	Cargo-agnostic; all parcels treated identically	Payload tags (F, W, U, P_{lvl}) derive objective weights algebraically
Route selection	Single greedy path or extreme Pareto point; expert re-tunes weights per mission	Utility scoring over full Pareto front; selects non-extreme interior points for mixed payloads
Front reuse	Full search re-run on every mission context change	Front built once per region; Tier 2 selects in <1 s against current front
Hardware validation	Simulation only	ArduPilot SITL + RPi 5 + Pixhawk outdoor flight tests

Proposed Methodology



Tier 1 Pareto front construction feeding Tier 2 payload-aware route selection. The front is built once per delivery region and reused across all missions within the refresh window.

Proposed System Architecture



System Modules

1. **M1 – Airspace Graph Builder:** Extracts OSM road/path network via `osmnx`; assigns three objective costs to each edge: geodesic distance, energy (distance $\times$ altitude-change factor), and flight risk (simulated threat zones and obstacle density, scored 0–1).
2. **M2 – Multi-Objective A* Engine (Tier 1):** NAMOA* search maintaining a cost vector $\mathbf{g} = [d, \varepsilon, \rho]$ per partial path; node-level label-dominance pruning; stores deterministic Pareto front $\mathcal{P}$ on disk for Tier 2 reuse.
3. **M3 – Payload Metadata Interpreter (Tier 2):** Reads tags $(F, W, U, P_{\text{lvl}})$; derives $w_{\text{risk}}, w_{\text{dist}}, w_{\text{energy}}$ via closed formula; min-max normalises objectives; returns arg max route and generates ArduPilot `.waypoints` mission file.
4. **M4 – Testing and Evaluation:** Benchmarks on S1/S2/S3 graphs vs. single-objective A* and MOPSO (30 runs); metrics: hypervolume, Pareto spread (Δ), IGD, Tier 2 selection accuracy, computation time. Extends to ArduPilot SITL and outdoor flight tests.

Methodology / Workflow

1. Literature review and problem formulation
2. Airspace graph construction (OpenStreetMap + OSMnx)
3. Multi-objective A* (NAMOA*) engine implementation (Tier 1)
4. Algebraic bridge and payload-driven Pareto selector (Tier 2)
5. Software simulation and benchmarking vs. A* and MOPSO baselines
6. Hardware integration (RPi 5 + Pixhawk), ArduPilot SITL simulation, and outdoor flight validation

Evaluation Metrics

- Hypervolume (HV)
- Pareto spread (Δ metric)
- IGD vs. reference front
- Tier 2 selection accuracy
- Tier 1 computation time
- Route adherence (GPS error)

Core Algorithm: Payload-Aware Two-Tier Route Planning

Algorithm Summary

1. **Input:** Graph $G = (V, E)$, payload tags $(F, W, U, P_{\text{lvl}})$, source s, destination d.
2. **Weight derivation (Algebraic Bridge):**
   $r_{\text{raw}}{=}F{\times}2, \quad d_{\text{raw}}{=}U{\times}3, \quad e_{\text{raw}}{=}W{\times}2; \quad$ normalise $\Rightarrow w_{\text{risk}}, w_{\text{dist}}, w_{\text{energy}}$.
   If $P_{\text{lvl}} \geq 4$: amplify dominant weight by $0.1{\times}w_{\max}$, then renormalise to sum to 1.
3. **Tier 1 (NAMOA*):** Run multi-objective A*; maintain cost vectors; apply node-level label-dominance pruning; store Pareto front $\mathcal{P}$ on disk for reuse.
4. **Tier 2 — Utility Scoring:** For each $p_i \in \mathcal{P}$,

$$\text{score}(p_i) = w_{\text{dist}}(1 - \tilde{d}_i) + w_{\text{energy}}(1 - \tilde{\varepsilon}_i) + w_{\text{risk}}(1 - \tilde{\rho}_i)$$

5. **Output:** $p^* = \arg\max_{p_i \in \mathcal{P}} \text{score}(p_i)$; generate ArduPilot `.waypoints` file; upload via MAVLink.


Technology Stack and Resources

Category	Selected Technology / Resource
Programming language	Python 3.11
Core libraries	NetworkX, OSMnx, NumPy, matplotlib, SciPy
Communication protocol	MAVLink / ArduPilot `.waypoints` mission format
Simulation environment	ArduPilot SITL (primary validation before real flights)
Map / dataset	OpenStreetMap airspace graph (Thiruvanmiyur, Chennai urban area)
Development tools	Git, VS Code, QGIS, Mission Planner, ArduPilot SITL, Docker
Hardware	Raspberry Pi 5 (quad-core 2.4 GHz, 8 GB), Pixhawk 6C, GPS module, F450 frame, ESC + motors


Implementation Status

Component	Status	Evidence / Remarks
Literature review & problem formulation	Completed	3 papers surveyed; 3 gaps formalised; real-world evidence added
System design & architecture	Completed	Two-tier architecture, NAMOA* algorithm, and algebraic bridge designed; diagrams produced
Airspace graph construction	In Progress	Actively building the airspace graph model and 3-objective edge-cost assignment for the target delivery region
Tier 1: Multi-Objective A* (NAMOA*) engine	Planned	NAMOA* with 3-objective cost vectors + label-dominance pruning specified; implementation scheduled for Phase II
Tier 2: Payload-driven selector	Planned	Algebraic bridge and utility-scoring $\arg\max$ selection formalised; coding scheduled for Phase II
Benchmarking & evaluation	Planned	Metrics defined (HV, Δ, IGD, selection accuracy, runtime); benchmark harness vs. single-obj. A* and MOPSO planned for Phase II

Prototype / Implementation Diagrams



Tier 1: Multi-Objective A* (NAMOA*) Pareto Front Construction



Tier 2: Payload-Driven Pareto Route Selection

Expected Results and Performance Targets

Payload Preset Weight Derivation

Preset	w_{risk}	w_{dist}	w_{energy}
Fragile medical (F=5, W=1, U=1)	0.667	0.200	0.133
Emergency medicine (F=1, W=1, U=3)	0.144	0.712	0.144
Disaster relief (F=1, W=3, U=1)	0.182	0.273	0.545
Mixed cargo (F=3, W=2, U=2)	0.375	0.375	0.250

Only emergency medicine selects an extreme Pareto point. **All other presets select non-extreme interior points** no single-objective baseline can produce.

Performance Targets

- HV: $\geq$20% higher than single-obj. A*
- Pareto front: 5–20 non-dominated routes per scenario
- Tier 2 selection latency: $<$50 ms on RPi 5
- Tier 2 accuracy: correct priority objective ranked highest across all 4 presets
- Hardware: ArduPilot SITL + outdoor delivery flight

Testing and Validation Plan

Test ID	Test Scenario	Expected Result	Status
TC-01	Valid payload tags (F, W, U, P_{lvl}) input	Correct $w_{\text{risk}}, w_{\text{dist}}, w_{\text{energy}}$ derived; weights sum to 1.0	Planned
TC-02	NAMOA* on 50/200/500-node graphs (S1/S2/S3)	Pareto front with zero dominated routes; HV $>$ single-obj. A*	Planned
TC-03	High fragility (F=5) vs. emergency medicine (U=3)	Significantly different non-extreme routes selected from same front	Planned
TC-04	Disconnected graph (no feasible path)	Graceful error with clear user message	Planned
TC-05	RPi 5 MAVLink mission upload to Pixhawk via SITL	Drone accepts mission and executes flight in ArduPilot SITL	Planned

Validation Method

Unit tests (pytest), MOPSO benchmarking (30 runs, swarm = 100, 200 iterations), ArduPilot SITL integration tests, and outdoor UAV flight tests with GPS telemetry logs.

Project Timeline (Jul 2026 – Mar 2027)

Activity	Jul	Aug	Sep	Oct	Nov	Dec	Jan	Feb	Mar
Literature survey & formulation									
System design & architecture									
Tier 1: Multi-Objective A*									
Tier 2: Payload-Driven Selector									
Software simulation & benchmarking									
Hardware integration (RPi 5 + Pixhawk)									
Outdoor flight tests									
Documentation & report writing									

Review I: August 2026 **Final Submission:** March 2027

Team Responsibilities

Team Member	Responsibilities	Current Status
Thirumurugan RA	System architecture design, Tier 1 NAMOA* engine implementation, airspace graph construction (OSMnx), edge cost vectorization	In Progress
Meghna Manimaran	Algebraic bridge design, Tier 2 payload selector implementation, benchmarking suite development, documentation	In Progress
Shrika SP Thota	Literature survey & problem formulation, risk-cost model design, benchmarking methodology, Pareto-front visualization and result analysis	In Progress

Challenges, Risks, and Mitigation

Risk / Challenge	Possible Impact	Mitigation
Graph complexity (large OSM urban network)	Slow Pareto front construction	Spatial pruning, NAMOA* node-level label-dominance check, epsilon-dominance to limit front size
Hardware failure (RPi / Pixhawk)	Flight tests delayed	ArduPilot SITL validation first; spare hardware budget
Pareto front size too large	High memory and selection latency	Apply epsilon-pruning; front bounded to $\leq$100 routes
MAVLink integration issues	Mission upload failures	Validate protocol end-to-end in SITL before real drone flights

Conclusion and Future Work

Conclusion

This project addresses the critical gap of payload-blind UAV routing by proposing a two-tier payload-aware pipeline. Tier 1 builds a Pareto-optimal route set via NAMOA*; Tier 2 selects the mission route using an algebraic bridge that maps fragility, urgency, and payload weight to routing objective weights. Utility scoring over the full Pareto front replaces context-blind diversity criteria, enabling non-extreme route selection for mixed payloads that no single-objective baseline can produce.

Future Work

- Outdoor flight validation on a real RPi 5 + Pixhawk drone in a simulated urban delivery environment.
- Extend to multi-drone coordination with shared Pareto fronts.
- Incorporate real-time weather and dynamic obstacle data for in-flight re-routing with adaptive front refresh thresholds.

References I

B. Chokkalingam and V. Ganesan, "Pareto-optimal particle swarm optimisation with entropy-based archive selection for UAV path planning," *RAIRO – Operations Research*, 2026. DOI: 10.1051/ro/2025159

Y. Ren et al., "Crowding-distance-based NSGA-II for multi-objective UAV path planning in urban environments," in *Proc. IEEE SOSE*, 2019. DOI: 10.1109/SOSE.2019.00059

G. Boeing, "OSMnx: New methods for acquiring, constructing, analysing, and visualising complex street networks," *Computers, Environment and Urban Systems*, vol. 65, pp. 126–139, 2017. DOI: 10.1016/j.compenvurbsys.2017.05.004

A. Hagberg, P. Swart, and D. Chult, "Exploring network structure, dynamics, and function using NetworkX," in *Proc. 7th Python in Science Conf. (SciPy)*, pp. 11–15, 2008.

C. A. C. Coello, G. T. Pulido, and M. S. Lechuga, "Handling multiple objectives with particle swarm optimization," *IEEE Trans. Evolutionary Computation*, vol. 8, no. 3, pp. 256–279, 2004. DOI: 10.1109/TEVC.2004.826067

References II

- L. Meier et al., "MAVLink: Micro air vehicle communication protocol," 2013. [Online]. Available: `https://mavlink.io`
- V. Tsoutsouras et al., "Multi-objective trajectory optimisation for energy-efficient UAV delivery with payload-mass adaptation," arXiv:2001.02531 [eess.SY], 2020.
- Swiss Federal Office of Civil Aviation (FOCA), Post-incident analysis of Swiss Post – Matternet M2 drone crashes, Zürich, January and May 2019.
- R. Rosser et al., "Effect of unmanned aerial vehicle transport on the stability of insulin: a controlled study," *Diabetes Care*, 2019.
- R. Amukele et al., "Drone transport of chemistry and hematology samples over long distances," *Am. J. Clin. Pathol.*, 2017.
- D. Bhatt et al., "Hemolysis in blood samples transported by drone: a comparative study," *Clin. Biochem.*, 2021.
- B. Tapper et al., "Energy analysis of long-range blood-product delivery by fixed-wing UAV: lessons from Zipline Rwanda," *J. Unmanned Veh. Syst.*, 2022.

Thank You

Questions and Discussion

Thirumurugan RA · Meghna Manimaran · Shrika SP Thota

Guide: Sujaudeen N, Assistant Professor