



```
fun printFirst100(ns: List<Int>) {  
    for (i in 0..100)  
        println(ns[i])  
}
```

treeSet += "a new element"

**TimeComplexities Game**





O(1)

$O(\log n)$



$O(n)$

$O(n^2)$

list.sort()

`list.sorted()` has a medium time complexity of  $O(n \log n)$   
why is QuickSort being used and not a  $O(n \log n)$  sorting algorithm?



































hashMap["key"]

# Time Complexities Game

$O(1)$

```
fun printFirst100(ns: List<Int>) {  
    for (i in 0..100)  
        println(ns[i])  
}  
hashMap["key"]
```

$O(\log n)$

```
treeSet += "a new element"
```

$O(n)$

$O(n^2)$

```
list.sorted()
```

list.sorted() has a medium time complexity of  $O(n \log n)$   
why is QuickSort being used and not a  $O(n \log n)$  sorting algorithm?

# Time Complexities Game

$O(1)$

```
fun printFirst100(ns: List<Int>) {  
    for (i in 0..100)  
        println(ns[i])  
}  
hashMap["key"]
```

$O(\log n)$

```
treeSet += "a new element"
```

$O(n)$

$O(n^2)$

```
list.sorted()
```

list.sorted() has a medium time complexity of  $O(n \log n)$   
why is QuickSort being used and not a  $O(n \log n)$  sorting algorithm?