


# Web API Design with Spring Boot Week 1 Coding Assignment

**Points possible:** 70

Category	Criteria	% of Grade
Functionality	Does the code work?	25
Organization	Is the code clean and organized? Proper use of white space, syntax, and consistency are utilized. Names and comments are concise and clear.	25
Creativity	Student solved the problems presented in the assignment using creativity and out of the box thinking.	25
Completeness	All requirements of the assignment are complete.	25

**Instructions:** In Eclipse, or an IDE of your choice, write the code that accomplishes the objectives listed below. Ensure that the code compiles and runs as directed. Take screenshots of the code and of the running program (make sure to get screenshots of all required functionality) and paste them in this document where instructed below. Create a new repository on GitHub for this week's assignments and push this document, with your Java project code, to the repository. Add the URL for this week's repository to this document where instructed and submit this document to your instructor when complete.

**Here's a friendly tip:** as you watch the videos, code along with the videos. This will help you with the homework. When a screenshot is required, look for the icon:  You will keep adding to this project throughout this part of the course. When it comes time for the final project, use this project as a starter.

**Here's a hint:** make sure you are running a version of Java that is 11+. To get the version, open a Windows command window or a Mac Terminal window and type `java -version`. If you need to upgrade, go here: <https://docs.aws.amazon.com/corretto/latest/corretto-11-ug/downloads-list.html>. Pick the .msi installer version (Windows) or the .pkg version (Mac).

**Project Resources:** <https://github.com/promineotech/Spring-Boot-Course-Student-Resources>

## Coding Steps:

- 1) Create a Maven project named `JeepSales` as described in the video.
  - a) In Spring Tool Suite, click the "File" menu. Select "New/Project...". In the popup, expand "Maven" and select "Maven Project". Click "Next".
  - b) Check "Create a simple project (skip archetype selection)". Click "Next".
  - c) Enter the following:

<b>Group Id</b>	<code>com.promineotech</code>
<b>Artifact Id</b>	<code>jeep-sales</code>

Click "Finish".

- 2) Navigate to the Spring Initializr (<https://start.spring.io/>).
  - a) Confirm the following settings:

<b>Project</b>	<b>Maven Project</b>
<b>Language</b>	Java
<b>Spring Boot</b>	Select the latest stable version (not SNAPSHOT or RC)
<b>Group</b>	<code>com.promineotech</code>
<b>Artifact</b>	<code>jeep-sales</code>
<b>Name</b>	<code>jeep-sales</code>
<b>Description</b>	Jeep Sales
<b>Package name</b>	<code>com.promineotech</code>
<b>Packaging</b>	Jar
<b>Java</b>	11

- b) Add the dependencies from the Initializr:
    - i) Web
    - ii) Devtools
    - iii) Lombok
  - c) Click "Explore" at the bottom of the page.
  - d) Click "Copy" to copy the `pom.xml` generated by the Initializr to the clipboard.

- 3) In Spring Tool Suite, open pom.xml (in the project root directory). Select all the text in the editor and replace it with the XML copied to the clipboard in the prior step.
- 4) Navigate to <https://mvnrepository.com/>. Search for springdoc-openapi-ui. Select the latest version and add the entry to the POM file in the <dependencies> section.
- 5) Create a package in src/main/java named com.promineotech.jeeep. In this package:
  - a) Create a Java class with a main method named JeepSales.
  - b) Add a class-level annotation: @SpringBootApplication and the import statement.
  - c) In the main() method, add a call to SpringApplication.run();. Use JeepSales.class as the first parameter, and the args parameter that was passed into the main() method as the second. The entire class should look like this:

```
package com.promineotech.jeeep;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class JeepSales {

    public static void main(String[] args) {
        SpringApplication.run(JeepSales.class, args);
    }
}
```

- 6) Refer to README.docx in the supplied project resources. Copy all files in the Files folder in the resources to your project as described in the README. **Do not copy the files in the Entity or Source folders at this time.**
  - a) Load the files that were added: right-click on the project in Package Explorer and select "Refresh".
  - b) Update the project with the new POM dependencies: right-click on the project in Package Explorer, select "Maven/Update Project". When the "Update Maven Project" panel appears, click "OK".
- 7) Using the MySQL Workbench or MySQL command line client (CLI), create a database named "jeeep".

- 8) Using dBeaver, or the MySQL client of choice, load the supplied .sql files (v1.0\_\_Jeep\_Schema.sql, and v1.1\_\_Jeep\_Data.sql) into the MySQL database to create the tables and populate them with data. These files are found in the project folder src/test/resources/flyway/migrations.
- 9) Create a new package in src/test/java named com.promineotech.jeep.controller. Create a Spring Boot integration test named FetchJeepTest using the techniques shown in the video.
  - a) Add the @SpringBootTest, @ActiveProfiles, and @Sql annotations as described in the video.
  - b) The class must not be public. It should have package-level access (i.e., not public, private, or protected).
  - c) The video extended FetchJeepTestSupport, but you don't need to do that for the homework. Just put everything in FetchJeepTest. It should look like this:

```
@SpringBootTest(webEnvironment = WebEnvironment.RANDOM_PORT)
@ActiveProfiles("test")
@Sql(scripts = {
    "classpath:flyway/migrations/V1.0__Jeep_Schema.sql",
    "classpath:flyway/migrations/V1.1__Jeep_Data.sql"},
    config = @SqlConfig(encoding = "utf-8"))
class FetchJeepTest {
}
```

- d) Create a test method in FetchJeepTest. The method must have the following method signature:
- e) Inject a TestRestTemplate in the test class. Name the variable restTemplate. Inject the port used in the test using the @LocalServerPort annotation. Name the variable serverPort. The variables and annotations should look like this:

```
@Autowired
private TestRestTemplate restTemplate;

@LocalServerPort
private int serverPort;
```

- 10) Create a new package in `src/main/java` named `com.promineotech.jeep.entity`. In that package, create an enum named `JeepModel`. Add all the jeep models from the `model_id` column in the `models` table in the database. You can use this query in dBeaver: `SELECT DISTINCT model_id FROM models`.
- 11) Create a `Jeep` class in the `com.promineotech.jeep.entity` package. Add the columns from the `models` table into this class as instance variables. Annotate the class with the Lombok annotations `@Data`, `@Builder` (and optionally both `@NoArgsConstructor` and `@AllArgsConstructor`). Note that `modelId` should be of type `JeepModel` and `basePrice` should be of type `BigDecimal`. The class should look like this (remember to add the appropriate import statements):

```
@Data
@Builder
@NoArgsConstructor
@AllArgsConstructor
public class Jeep {
    private Long modelPK;
    private JeepModel modelId;
    private String trimLevel;
    private int numDoors;
    private int wheelSize;
    private BigDecimal basePrice;
}
```

- 12) In the supplied resources, copy all files in the `Entities` folder to the `src/main/java/com/promineotech/jeep/entity` folder. **Do not copy anything from the Source folder at this time.**
- 13) Back in the test method that you were writing, create local variables for `JeepModel`, `trim`, and `uri`. Set them appropriately like this:

Variable Type	Variable Name	Variable Value
<b>JeepModel</b>	<code>model</code>	<code>JeepModel.WRANGLER</code>
<b>String</b>	<code>trim</code>	<code>"Sport"</code>
<b>String</b>	<code>uri</code>	<code>String.format("http://localhost:%d/jeeps?model=%s&amp;trim=%s", serverPort, model, trim);</code>

- a) Send an HTTP request to the REST service that passes a JeepModel and trim level as URI parameters (as shown in the video). Use this method call:

```
ResponseEntity<List<Jeep>> response = restTemplate.exchange(uri,  
    HttpMethod.GET, null, new ParameterizedTypeReference<>() {});
```


Make sure to use the import `java.util.List` and `org.springframework.http.HttpMethod`.

- b) Using [AssertJ](#), test that the response that comes back from the server is 200 (success) – or as is shown in the video: `HttpStatus.OK`. The code should look like this:

```
assertThat(response.getStatusCode()).isEqualTo(HttpStatus.OK);
```

Use the import statements:

```
import static org.assertj.core.api.Assertions.assertThat;
```

- c) Produce a screenshot showing the completed test class. 

14) In `src/main/java`, create a new package `com.promineotech.jeep.controller`. In this package, create an interface named `JeepSalesController`.

- a) Add the class-level annotation `@RequestMapping("/jeeps")`.
- b) Add the `fetchJeeps` method in a controller interface with the following signature:

```
List<Jeep> fetchJeeps(JeepModel model, String trim);
```

Make sure you use the `List` from `java.util.List`.

- c) Add OpenAPI documentation to document the four possible outcomes: 200 (success), 400 (bad input), 404 (not found) and 500 (unplanned error) as shown in the video.
- d) Add the parameter annotations in the OpenAPI documentation to describe the `model` and `trim` parameters.
- e) Add the `@GetMapping` annotation and the `@ResponseStatus(code = HttpStatus.OK)` annotation as method-level annotations to the `fetchJeeps` method.
- f) Add the `@RequestParam` annotations to the parameters as described in the video. The interface should look like this (omitting the OpenAPI annotations):

```
@RequestMapping("/jeeps")  
  
public interface JeepSalesController {  
    @GetMapping  
    @ResponseStatus(code = HttpStatus.OK)  
    List<Jeep> fetchJeeps(JeepModel model, String trim);  
}
```


```

        List<Jeep> fetchJeeps(@RequestParam JeepModel model,
                               @RequestParam String trim);
    }

```

g) Produce a screenshot showing the interface and OpenAPI documentation. 

15) Add the controller implementation class named `DefaultJeepSalesController`. Don't forget the `@RestController` annotation.

16) Run the application within the IDE and show the resulting OpenAPI (Swagger) documentation produced in the browser. Produce a screenshot of the documentation showing all four possible outcomes. 

### Screenshots of Code:

```

1  package com.promineotech.jeep;
2
3  import org.springframework.boot.SpringApplication;
4  import org.springframework.boot.autoconfigure.SpringBootApplication;
5  import org.springframework.boot.autoconfigure.jdbc.DataSourceAutoConfig
6
7  // https://www.baeldung.com/spring-boot-failed-to-configure-data-source
8  @SpringBootApplication(exclude={DataSourceAutoConfiguration.class})
9
10 //@SpringBootApplication
11 public class JeepSales {
12
13     public static void main(String[] args) { SpringApplication.run(Jeep
14     args); }
15
16
17

```

```

1  package jeep.controller.support;
2
3  public class FetchJeepTestSupport extends BaseTest {
4
5

```

```

1 package com.promineotech.jeep.controller;
2
3 import com.promineotech.jeep.entity.Jeep;
4 import org.springframework.web.bind.annotation.RestController;
5
6 import java.util.List;
7
8 @RestController
9 public class DefaultJeepSalesController implements JeepSalesController {
10     @Override
11     public List<Jeep> fetchJeeps(String model, String trim) { return null; }
12 }

```

```

1 package jeep.controller.support;
2
3 import org.springframework.beans.factory.annotation.Autowired;
4 import org.springframework.boot.test.web.client.TestRestTemplate;
5 import org.springframework.boot.web.server.LocalServerPort;
6
7 public class BaseTest {
8     @LocalServerPort
9     private int serverPort;
10
11     @Autowired
12     private TestRestTemplate restTemplate;
13
14     protected String getBaseUrl() { return String.format("http://localhost:%d/jeeps",
15         serverPort); }
16 }

```



```

1 package jeep.controller;
2
3 import com.pronineotech.jeeo.entity.Jeeo;
4 import com.pronineotech.jeeo.entity.JeeoModel;
5 import com.pronineotech.jeeo.JeeoSales;
6 import jeep.controller.support.FetchJeeoTestSupport;
7 import org.junit.jupiter.api.Test;
8 import org.springframework.beans.factory.annotation.Autowired;
9 import org.springframework.boot.test.context.SpringBootTest;
10 import org.springframework.boot.test.web.client.TestRestTemplate;
11 import org.springframework.boot.test.web.server.LocalServerPort;
12 import org.springframework.core.ParameterizedTypeReference;
13 import org.springframework.http.HttpMethod;
14 import org.springframework.http.HttpStatus;
15 import org.springframework.http.ResponseEntity;
16
17 import java.util.List;
18
19 import static org.assertj.core.api.Assertions.assertThat;
20
21 @SpringBootTest(webEnvironment = SpringBootTest.WebEnvironment.RANDOM_PORT,
22     classes={JeeoSales.class})
23 public class FetchJeeoTest extends FetchJeeoTestSupport {
24
25     @Autowired
26     private TestRestTemplate restTemplate;
27
28     @LocalServerPort
29     private int serverPort;

```

```

29
30 //    given when then, Martin Fowler
31 @Test
32 void testThatJeepsAreReturnedWhenAValidModelAndTrimAreSupplied() {
33     //    Given: a valid model, trim, and URI
34     JeepModel model = JeepModel.WRANGLER;
35     String trim = "Sport";
36     String uri = String.format("http://localhost:%d/jeeps?model=%s&trim=%s",
serverPort, model, trim);
37     System.out.println(uri);
38     //    String uri = String.format("%s?model=%s&trim=%s", getBaseUri(), model, trim);
39     //    System.out.println(uri);
40
41     //    When: a connection is made to the URI
42     ResponseEntity<List<Jeep>> response = restTemplate.exchange(
43         uri, HttpMethod.GET, requestEntity: null, new ParameterizedTypeReference<>() {
44     });
45     //    ResponseEntity<Jeep> response = restTemplate.getForEntity(uri, Jeep.class);
46
47     //    Then: a success (200 ok) status code is returned
48     assertEquals(response.getStatusCode(), HttpStatus.OK);
49     System.out.println(getBaseUri());
50 }
51
52 }

```

```

1 package com.pronineotech.jeeb.controller;
2
3 import com.pronineotech.jeeb.entity.Jeeb;
4 import io.swagger.v3.oas.annotations.OpenAPIDefinition;
5 import io.swagger.v3.oas.annotations.Operation;
6 import io.swagger.v3.oas.annotations.Parameter;
7 import io.swagger.v3.oas.annotations.info.Info;
8 import io.swagger.v3.oas.annotations.media.Content;
9 import io.swagger.v3.oas.annotations.media.Schema;
10 import io.swagger.v3.oas.annotations.responses.ApiResponse;
11 import io.swagger.v3.oas.annotations.servers.Server;
12 import org.springframework.http.HttpStatus;
13 import org.springframework.web.bind.annotation.GetMapping;
14 import org.springframework.web.bind.annotation.RequestMapping;
15 import org.springframework.web.bind.annotation.RequestParam;
16 import org.springframework.web.bind.annotation.ResponseStatus;
17
18 import java.util.List;
19
20 @RequestMapping("/jeebs")
21 @OpenAPIDefinition(info = @Info(title = "Jeeb Sales Service"), servers = {
22     @Server(url = "http://localhost:8080", description = "local server.")
23 })
24

```

```

25 public interface JeebSalesController {
26     // @formatter:off
27     @Operation(
28         summary = "Returns a list of Jeebs",
29         description = "Returns a list of Jeebs given an optional model and/or trim",
30         responses = {
31             @ApiResponse(
32                 responseCode = "200",
33                 description = "A list of Jeebs is returned.",
34                 content = @Content(
35                     mediaType="application/json",
36                     schema = @Schema(implementation = Jeeb.class))),
37             @ApiResponse(
38                 responseCode = "400",
39                 description = "The request parameters are invalid.",
40                 content = @Content(
41                     mediaType="application/json")),
42             @ApiResponse(
43                 responseCode = "404",
44                 description = "No Jeebs were found with the input criteria.",
45                 content = @Content(
46                     mediaType="application/json")),
47             @ApiResponse(
48                 responseCode = "500",
49                 description = "An unplanned error occurred.",
50                 content = @Content(
51                     mediaType="application/json"))
52         },
53

```

```

52         },
53         parameters = {
54             @Parameter(
55                 name = "model",
56                 allowEmptyValue = false,
57                 required = false,
58                 description = "The model name (i.e., 'WRANGLER')"),
59             @Parameter(
60                 name = "trim",
61                 allowEmptyValue = false,
62                 required = false,
63                 description = "The trim level (i.e., 'Sport')")
64         }
65     )
66     @GetMapping
67     @ResponseStatus(code = HttpStatus.OK)
68     List<Jeep> fetchJeeps(
69         @RequestParam(required = false)
70         String model,
71         @RequestParam(required = false)
72         String trim);
73     // @formatter:on
74
75 }

```

# Jeep Sales Service

[/v3/api-docs](#)

## Servers

## default-jeep-sales-controller

**GET** [/jeeps](#) Returns a list of Jeeps

## Schemas

Jeep >

## default-jeep-sales-controller

**GET** [/jeeps](#) Returns a list of Jeeps

Returns a list of Jeeps given an optional model and/or trim

### Parameters

[Try it out](#)

Name	Description
model <small>string (query)</small>	The model name (i.e., 'WRANGLER')
trim <small>string (query)</small>	The trim level (i.e., 'Sport')

### Responses

Code	Description	Links
200	<p>A list of Jeeps is returned.</p> <p>Media type</p> <p><input type="text" value="application/json"/></p> <p>Controls Accept header.</p> <p>Example Value   Schema</p> <pre>[   {     "modelPK": 0,     "modelId": "WRANGLER",     "trimLevel": "string",     "sunDoors": 0,     "wheelSize": 0,     "basePrice": 0   } ]</pre>	No links
400	<p>The request parameters are invalid.</p> <p>Media type</p> <p><input type="text" value="application/json"/></p>	No links
404	<p>No Jeeps were found with the input criteria.</p> <p>Media type</p> <p><input type="text" value="application/json"/></p>	No links
500	<p>An unplanned error occurred.</p> <p>Media type</p> <p><input type="text" value="application/json"/></p>	No links

## Schemas

```

Jeep {
  modelPK      integer($int64)
  modelId      string
              Enum
              > Array [ 1 ]
  trimLevel    string
  sunDoors     integer($int32)
  wheelSize    integer($int32)
  basePrice    number
}
```

**URL to GitHub Repository:** <https://github.com/thisLinda/SpringBootWk13Assignment>