The Determination of G

April 3, 2013

Magdalen Berns

History and motivation.

Experimental procedure. Systematic Errors. Random Errors. Final results. Questions.

History and motivation.

Experimental procedure. Systematic Errors. Random Errors. Final results. Questions.

History and motivation. Experimental procedure.

Systematic Errors.

Random Errors.

Final results.

Questions

Lessons learned

History and motivation. Experimental procedure. Systematic Errors.

Random Errors

Final results.

Questions

Lessons learned.

History and motivation. Experimental procedure. Systematic Errors. Random Errors.

Final results. Questions.

Lessons learned.

History and motivation.

Experimental procedure.

Systematic Errors.

Random Errors.

Final results.

Questions

Lessons learned

History and motivation.

Experimental procedure.

Systematic Errors.

Random Errors.

Final results.

Questions.

Lessons learned

History and motivation.

Experimental procedure.

Systematic Errors.

Random Errors.

Final results.

Questions.

Lessons learned.

Background Henry Cavendish 1731-1810

Cambridge drop out.

Used the torsion pendulum to try determine the density of the Earth.

The literature value for G is $6.67 \times 10^{-11} m^3 kg^{-1}s^2$

Background Henry Cavendish 1731-1810

Cambridge drop out.

Used the torsion pendulum to try determine the density of the Earth.

The literature value for G is 6.67 imes $10^{-11} m^3 kg^{-1} s^2$

Background Henry Cavendish 1731-1810

Cambridge drop out.

Used the torsion pendulum to try determine the density of the Earth.

The literature value for G is $6.67 \times 10^{-11} m^3 kg^{-1}s^2$

End Deflection

Uses equation

Acceleration.

Uses Gradient

End Deflection Uses equation

Acceleration.
Uses Gradien

End Deflection Uses equation

 ${\sf Acceleration}.$

Uses Gradient

End Deflection Uses equation

Acceleration.
Uses Gradient

How it works.

$$G = \frac{\pi^2 \Delta S b^2 d}{T^2 m_2 L} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

That's pretty much as exciting as it gets.

$$6.56(16) \times 10^{-11} \,\,\mathrm{m^3 kg^{-1}s^{-2}}!!!$$

How it works.

$$G = \frac{\pi^2 \Delta S b^2 d}{T^2 m_2 L} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

That's pretty much as exciting as it gets.

$$6.56(16) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$
!!!

How it works.

$$G = \frac{\pi^2 \Delta S b^2 d}{T^2 m_2 L} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

That's pretty much as exciting as it gets.

$$6.56(16) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$
!!!

How it works.

$$G = \frac{\pi^2 \Delta S b^2 d}{T^2 m_2 L} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

That's pretty much as exciting as it gets.

$$6.56(16) \times 10^{-11} \mathrm{\ m^3 kg^{-1}s^{-2}}!!!$$

How it works.

$$G = \frac{a_0 b^2}{2m_2} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

Where

$$a_0 = \frac{L}{d} =$$
 gradient of linear fit $\frac{a_0 L}{d}$ is the slope of linear graph Here's my result:

$$6.67(13) \times 10^{-11} \mathrm{\ m^3 kg^{-1}s^{-2}}!!!$$

How it works.

$$G = \frac{a_0 b^2}{2m_2} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

Where:

 $a_0 = \frac{L}{d} = \text{gradient of linear fit}$ $\frac{a_0 L}{d}$ is the slope of linear graph
Here's my result: $6.67(13) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2} \text{Hz}$

$$G = \frac{a_0 b^2}{2m_2} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

Where:
 $a_0 = \frac{L}{d} = \text{gradient of linear fit}$
 $\frac{a_0 L}{d}$ is the slope of linear graph
Here's my result:
 $6.67(13) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2} \text{Hz}$

$$G = \frac{a_0 b^2}{2m_2} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

Where:
 $a_0 = \frac{L}{d} = \text{gradient of linear fit}$
 $\frac{a_0 L}{d}$ is the slope of linear graph
Here's my result:
 $6.67(13) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2} \text{Hz}$

$$G = \frac{a_0 b^2}{2m_2} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2}$$

Where:
 $a_0 = \frac{L}{d} = \text{gradient of linear fit}$
 $\frac{a_0 L}{d}$ is the slope of linear graph
Here's my result:
 $6.67(13) \times 10^{-11} \text{ m}^3 \text{kg}^{-1} \text{s}^{-2} \text{Hz}$

$$G = \frac{a_0b^2}{2m_2} \; \mathrm{m}^3\mathrm{kg}^{-1}\mathrm{s}^{-2}$$
 Where:
$$a_0 = \frac{L}{d} = \text{gradient of linear fit}$$

$$\frac{a_0L}{d} \; \text{is the slope of linear graph}$$
 Here's my result:
$$6.67(13) \times 10^{-11} \; \mathrm{m}^3\mathrm{kg}^{-1}\mathrm{s}^{-2}!!!$$

Acceleration Downsides Reproducibility is questionable

Not Enough data points. Hard to swing it the same way, every time. a_o is the slope of linear graph.


Acceleration Upsides Damping and Crashing


Does not matter too much about damping.

Don't need to wait too long to get results.

With different software you can record more time steps.

Main Result






Systematic Errors

Influence of the large lead balls


Want:

$$\tau_g = 2F_0d = \frac{2Gm_1m_2}{b^2}$$



Random Errors

High risk zones



Analysis

The Acceleration was analysed using my java program The graphs with pgfplots End deflection was analysed using CASSY Lab for ΔS Maple for the algebra

Random Errors

Additional Forces Due to.

Atmospheric pressure.

Radiation pressure.

Magnetic field of earth.

Banging the swing doors.

People moving around in the room.

Error on G

$$\sigma_G = \sqrt{\left(\frac{\partial^2 G}{\partial a^2} \Delta a\right)^2 + \left(\frac{\partial^2 G}{\partial b^2} \Delta b\right)^2}$$

For b, d, m_{1rf} , T ΔS and L

Conclusions

This experiment can also be improved...

If the measurements are more exact

If the room is isolated from external noises and temperature/humidity controlled.

More time steps are recorded.

Questions?