

SAP How-to Guide

Mobility

SAP Mobile Platform

How To... Enable User On-boarding using MAF Logon (Android)

Applicable Releases:

SAP Mobile Platform 3.0 SP04

SAP Mobile SDK 3.0 SP05

Version 1.0



The Best-Run Businesses Run SAP™

© Copyright 2014 SAP AG. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors.

Microsoft, Windows, Excel, Outlook, and PowerPoint are registered trademarks of Microsoft Corporation.

IBM, DB2, DB2 Universal Database, System i, System i5, System p, System p5, System x, System z, System z10, System z9, z10, z9, iSeries, pSeries, xSeries, zSeries, eServer, z/VM, z/OS, i5/OS, S/390, OS/390, OS/400, AS/400, S/390 Parallel Enterprise Server, PowerVM, Power Architecture, POWER6+, POWER6, POWER5+, POWER5, POWER, OpenPower, PowerPC, BatchPipes, BladeCenter, System Storage, GPFS, HACMP, RETAIN, DB2 Connect, RACF, Redbooks, OS/2, Parallel Sysplex, MVS/ESA, AIX, Intelligent Miner, WebSphere, Netfinity, Tivoli and Informix are trademarks or registered trademarks of IBM Corporation.

Linux is the registered trademark of Linus Torvalds in the U.S. and other countries.

Adobe, the Adobe logo, Acrobat, PostScript, and Reader are either trademarks or registered trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Oracle is a registered trademark of Oracle Corporation.

UNIX, X/Open, OSF/1, and Motif are registered trademarks of the Open Group.

Citrix, ICA, Program Neighborhood, MetaFrame, WinFrame, VideoFrame, and MultiWin are trademarks or registered trademarks of Citrix Systems, Inc.

HTML, XML, XHTML and W3C are trademarks or registered trademarks of W3C®, World Wide Web Consortium, Massachusetts Institute of Technology.

Java is a registered trademark of Sun Microsystems, Inc.

JavaScript is a registered trademark of Sun Microsystems, Inc., used under license for technology invented and implemented by Netscape.

SAP, R/3, SAP NetWeaver, Duet, PartnerEdge, ByDesign, SAP BusinessObjects Explorer, StreamWork, and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries.

Business Objects and the Business Objects logo, BusinessObjects, Crystal Reports, Crystal Decisions, Web Intelligence, Xcelsius, and other Business Objects products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Business Objects Software Ltd. Business Objects is an SAP company.

Sybase and Adaptive Server, iAnywhere, Sybase 365, SQL Anywhere, and other Sybase products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of Sybase, Inc. Sybase is an SAP company.

All other product and service names mentioned are the trademarks of their respective companies. Data contained in this document serves informational purposes only. National product specifications may vary.

The information in this document is proprietary to SAP. No part of this document may be reproduced, copied, or transmitted in any form or for any purpose without the express prior written permission of SAP AG.

This document is a preliminary version and not subject to your license agreement or any other agreement with SAP. This document contains only intended strategies, developments, and functionalities of the SAP® product and is not intended to be binding upon SAP to any particular course of business, product strategy, and/or development. Please note that this document is subject to change and may be changed by SAP at any time without notice.

SAP assumes no responsibility for errors or omissions in this document. SAP does not warrant the accuracy or completeness of the information, text, graphics, links, or other items contained within this material. This document is provided without a warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement.

SAP shall have no liability for damages of any kind including without limitation direct, special, indirect, or consequential damages that may result from the use of these materials. This limitation shall not apply in cases of intent or gross negligence.

The statutory liability for personal injury and defective products is not affected. SAP has no control over the information that you may access through the use of hot links contained in these materials and does not endorse your use of third-party Web pages nor provide any warranty whatsoever relating to third-party Web pages.

SAP "How-to" Guides are intended to simplify the product implementation. While specific product features and procedures typically are explained in a practical business context, it is not implied that those features and procedures are the only approach in solving a specific business problem using SAP NetWeaver. Should you wish to receive additional information, clarification or support, please refer to SAP Consulting.

Any software coding and/or code lines / strings ("Code") included in this documentation are only examples and are not intended to be used in a productive system environment. The Code is only intended better explain and visualize the syntax and phrasing rules of certain coding. SAP does not warrant the correctness and completeness of the Code given herein, and SAP shall not be liable for errors or damages caused by the usage of the Code, except if such damages were caused by SAP intentionally or grossly negligent.

Disclaimer

Some components of this product are based on Java™. Any code change in these components may cause unpredictable and severe malfunctions and is therefore expressly prohibited, as is any decompilation of these components.

Any Java™ Source Code delivered with this product is only to be used by SAP's Support Services and may not be modified or altered in any way.

Document History

Document Version	Description
1.00	First official release of this guide



Typographic Conventions

Type Style	Description
Example Text	Words or characters quoted from the screen. These include field names, screen titles, pushbuttons labels, menu names, menu paths, and menu options. Cross-references to other documentation
Example text	Emphasized words or phrases in body text, graphic titles, and table titles
Example text	File and directory names and their paths, messages, names of variables and parameters, source text, and names of installation, upgrade and database tools.
Example text	User entry texts. These are words or characters that you enter in the system exactly as they appear in the documentation.
<Example text>	Variable user entry. Angle brackets indicate that you replace these words and characters with appropriate entries to make entries in the system.
EXAMPLE TEXT	Keys on the keyboard, for example, F2 or ENTER.

Icons





Icon	Description
	Caution
	Note or Important
	Example
	Recommendation or Tip

Table of Contents

1. Business Scenario	1
2. Background Information	1
3. Prerequisites.....	1
4. Step-by-Step Procedure	2
4.1 Create Android Project	2
4.2 Add required MAF artifacts	5
4.3 Set up dependencies	7
4.4 Review AndroidManifest.xml.....	14
4.5 Implement MAFLogonActivity.....	15
4.6 Run the Application.....	17
4.7 Verifying the registration	21
5. Appendix.....	22



1. Business Scenario

Before any communication with the SAP backend systems can take place at all, the app needs to on-board users onto the SAP Mobile Platform. The Mobile Application Framework (MAF) contains the MAF logon component that provides easy integration for applications that use logon UI behavior.

2. Background Information

The goal of this exercise is not to show how to create a project from scratch and dissect every line of code. Instead, it shows the key pieces of code and information needed to integrate MAF Logon component to a new or an existing Android Project in eclipse.

The purpose is to explain how developers can leverage the MAF Logon component to on-board users from scratch.

3. Prerequisites

This exercise has the following prerequisites:

- Java Standard Edition 7
- Eclipse Kepler
- Android SDK with API level 8 and 19 downloaded
- Android ATD Eclipse plugin installed
- To get the most out of this exercise, some experience with Java is recommended.
- SAP Mobile Platform 3.0 SP04
 - ⚠ This example assumes you have configured an application in SMP 3.0 called `com.sap.flight` for more information on how to create an application configuration, please visit [Deploying Applications](#)
- SAP Mobile SDK 3.0 SP05


4. Step-by-Step Procedure

The following sections provide a detailed step-by-step procedure on how to code an Android app to on-board/register a user onto the SAP Mobile Platform using the MAF Logon component.


The following section is optional, you can reuse an existing android project for the purpose of this exercise

4.1 Create Android Project


1. Go to File -> New -> Android Application Project




2. Enter the following information to create the android project and click the Next button




- Keep the default values as shown in the image and click Next.




- Select any icon and click Next.




5. You can choose any template to create an activity, for simplicity purposes we will chose a Blank Activity



6. Enter the following information to create the activity and its corresponding layout resources and click Finish




7. Your project should look like the image below.




4.2 Add required MAF artifacts


1. Select the libs folder and right-click to open the context menu and select Import



2. Select General -> File System and click Next




3. In the Import window, click Browse



4. Locate your SMP 3.0 SDK installation folder. You will find the jar files in the following folders:
 - a. <Client SDK dir>\NativeSDK\ODataFramework\Android\libraries
 - b. <Client SDK dir>\NativeSDK\MAFReuse\Android\libraries

5. Select the following jar and click Finish

- | | | |
|--------------------|-------------------------|----------------------------|
| • AfariaSLL.jar | • HttpConvAuthFlows.jar | • MobilePlace.jar |
| • ClientHubSLL | • HttpConversation.jar | • perflib.jar |
| • ClientLog.jar | • maflogoncore.jar | • Request.jar |
| • Common.jar | • maflogger.jar | • sap-e2etrace.jar |
| • Connectivity.jar | • maflogonui.jar | • SupportabilityFacade.jar |
| • CoreServices.jar | • mafuicomponents.jar | |
| • DataVaultLib.jar | • mafsettingscreen.jar | |



6. Save your changes

4.3 Set up dependencies

To use the MAF Login Component you must import a number of Libraries and Resources. MAF Libraries were installed with SMP Client SDK installer into the folder specified by you when you executed the installer. These libraries and resources are already included in the project. Please follow the steps to confirm the project was set up correctly.


MAF is shipped with various resources. These projects have Android nature, but don't ship any source code. Their only purpose is to ship all Android resource files like: images, layouts, localization, XMLs

As a result of the SDK installer you will find the following .apklib files in the installation folder:


- a. <Client SDK
dir>\NativeSDK\ODataFramework\Android\resources\maflogonui.apklib
- b. <Client SDK
dir>\NativeSDK\MAFReuse\Android\resources\mafsettingscreen.apklib
- c. <Client SDK
dir>\NativeSDK\MAFReuse\Android\resources\mafuicomponents.apklib

1. Open folder <Client SDK dir>\NativeSDK\ODataFramework\Android\resources\

- The resource archives have .apklib extension (i.e maflogonui-res-xxx.apklib). You will need to change this extension to .zip




- Unzip the .zip file into a local folder




- Open folder <Client SDK dir>\NativeSDK\MAFReuse\Android\resources\

The resource archives have .apklib extension (i.e mafsettingscreen-res-xxx.apklib). You will need to change this extension to .zip


- Unzip the .zip file into a local folder




6. In the same folder <Client SDK dir>\NativeSDK\MAFReuse\Android\resources\ you will find mafuicomponents.apklib
The resource archives have .apklib extension (i.e mafuicomponents-res-xxx.akplib). You will need to change this extension to .zip
7. Unzip the .zip flie into a local folder




8. Open eclipse, import the projects by selecting File -> Import menu.
9. The Import window will open, select Existing Android Code into Workspace and click Next.




10. In the Root Directory field, click the Browse button to locate the .zip files in your local folder (i.e. <Client_SDK_dir>\NativeSDK\ODataFramework\Android\resources\maflogonui-res-xxx.akplib) and click Finish.




11. Repeats steps 12-13 to import the other MAF project resources: mafsettingscreen and mafuicomponents




12. After importing the three MAF resources, in the Package Explorer view, check your project, it should look like the image below.




13. Select maflogonui-res-xxx project. Right click and select the project properties from the context menu. These MAF resources projects need to be marked as Android library project.




14. In the project properties you need to select Android and then mark the project as Library.


 Remember to repeat this step for all three of the resource projects: maflogonui, mafsettingscreen and mafuicomponents.




15. Select HelloWorldMAF and open the properties to set up the reference to the MAF resources




16. Select Android. In the Library section you need to click the Add button.




17. The Project Selection modal view will be shown. Select each of the maf resources and click OK




18. Once you have added the 3 resources, click OK



If your project has dependencies to the Android Support Library package (i.e appcompat_v7), when you add the MAF resources, you may encounter some errors.

 The Android Support Library package is a set of code libraries that provide backward-compatible versions of Android framework APIs as well as features that are only available through the library APIs. Each Support Library is backward-compatible to a specific Android API level. This design means that your applications can use the libraries' features and still be compatible with devices running Android 1.6 (API level 4) and up

 Please check the [Appendix A – Fixing Problems with Android Project](#) section at the end of this guide to remove the dependency to the Android Support Library package

Some sample errors messages you may get

Problems 4 errors, 29 warnings, 0 others				
Description	Resource	Path	Location	Type
▼ Errors (4 items)				
R cannot be resolved to a variable	MainActivity.j...	/...	line 13	Java Problem
R cannot be resolved to a variable	MainActivity.j...	/...	line 19	Java Problem
R cannot be resolved to a variable	MainActivity.j...	/...	line 29	Java Problem
Unparsed aapt error(s)! Check the console f...	sdf		line 1	Android ADT...
▶ Warnings (29 items)				

```

[2014-10-06 09:02:31 - sdf] /Development/Android/workspace_sp04/appcompat_v7/res/values/attrs.xml:185: error: Attribute "subtitle" has already been defined
[2014-10-06 09:02:32 - sdf] /Development/Android/workspace_sp04/appcompat_v7/res/values/attrs.xml:185: error: Attribute "subtitle" has already been defined
[2014-10-06 09:11:48 - sdf] /Development/Android/workspace_sp04/appcompat_v7/res/values/attrs.xml:185: error: Attribute "subtitle" has already been defined

```

4.4 Review AndroidManifest.xml

1. Ensure that AndroidManifest.xml contains the INTERNET permission:

```

<!-- allow connections to Internet Services. -->
<uses-permission android:name="android.permission.INTERNET" />

```

2. Define as main activity the MAFLogonActivity. This is a new activity we are going to create during this exercise that will reuse the MAF Logon component.

```

<activity
    android:name=".MAFLogonActivity"
    android:label="@string/app_name" >
    <intent-filter>
        <action android:name="android.intent.action.MAIN" />
        <category android:name="android.intent.category.LAUNCHER" />
    </intent-filter>
</activity>

```

3. Define the MainActivity as a second screen that will be displayed after the registration finishes.

```

<activity
    android:name=".MainActivity"
    android:configChanges="orientation|screenSize"
    android:label="@string/app_name"
    android:screenOrientation="portrait" >
</activity>

```


4. Your manifest file should look like the image below.



4.5 Implement MAFLogonActivity


Now that we have successfully set up the Android project, we can use the MAF Logon resources in our project.

1. Go to src -> com.sap.smp.maf
2. Right-click on the com.sap.smp.maf package to open the context menu
3. Select New -> Class



4. Enter the following information to create an Activity and click Finish
 - a. Name = MAFLogonActivity

- b. Superclass = android.app.Activity
- c. Interface = com.sap.maf.tools.logon.logonui.api.LogonListener




5. Define the following class variables

```
private final String TAG = MAFLogonActivity.class.getSimpleName();
private LogonUIFacade mLogonUIFacade;
private Context mContext;
```

6. Implement the onCreate method to initialize the LogonUIFacade with the following code

```
@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    // get an instance of the LogonUIFacade
    mLogonUIFacade = LogonUIFacade.getInstance();
    // set context reference
    mContext = this;
    this.showLogonScreen();
}
```

7. Define to the showLogonScreen method with the following code.

 This example assumes you have configured an application in SMP 3.0 called com.sap.flight
for more information visit [Deploying Applications](#)

```
private void showLogonScreen() {
    //TODO 1-2 COMPLETE showLogonScreen in MAFLogonActivity *****
```

```
// initialize the LogonUIFacade with context and application id
// This example assumes "com.sap.flight" exists in
// SMP 3.0 Management Cockpit
mLogonUIFacade.init(this, mContext, "com.sap.flight");

// ask LogonUIFacade to present the logon screen
// set the resulting view as the content view for this activity
setContentView(mLogonUIFacade.logon());
}
```



setContentView method is used to present the logon screen from the MAFLogonActivity

8. Locate onLogonFinished and complete the method with the following code. This method redirects to the main screen when the registration finishes

This callback method handles BOTH success and error cases.

```
@Override
public void onLogonFinished(String message, boolean isSuccess, LogonContext
lgContext) {
    //TODO 1-3 COMPLETE onLogonFinished in MAFLogonActivity *****
    Log.d(TAG, "onLogonFinished: "+message);
    //Check if it finished successfully
    if (isSuccess) {
        try {
            //For debugging purposes will log the app connection id and
            // the end point url.
            // In a productive app, remember to remove these logs
            String appConnID = LogonCore.getInstance().getLogonContext()
                .getConnId();
            Log.d(TAG, "onLogonFinished: appcid:"+ appConnID);
            Log.d(TAG, "onLogonFinished: endpointurl:"+
                lgContext.getEndPointUrl());

        } catch (LogonManagerException e) {
            Log.e(TAG, e.getLocalizedMessage(), e);
        } catch (LogonCoreException e) {
            Log.e(TAG, e.getLocalizedMessage(), e);
        }


        // Navigate to the Main menu screen
        Intent goToNextActivity = new Intent(this, MainActivity.class);
        startActivity(goToNextActivity);
        finish();
    }
}
```

7. Save the changes
8. Please find the MAFLogonActivity in [Appendix B - MAFLogonActivity.java](#)


4.6 Run the Application

If you haven't created the Debug Configuration, please review [Appendix C – Creating Debug Configuration](#)


9. In Eclipse, go to the Run icon and select the corresponding HelloWorld configuration




8. Click on the Login button




9. Click on Cancel



10. Enter the IP address of the SMP 3.0 server and backend credentials




11. Scroll down to enter port (8080 is default)




12. Keep scrolling until the end of the screen to

13. Enter a passcode or uncheck the Use


check the Unsecured option and click on Next



application passcode and click on Done




14. The main screen will be displayed



4.7 Verifying the registration

To verify that the user was registered successful, you can open the SAP Management Cockpit and check the number if the number of registrations increases when you register your device




The screenshot shows the SAP Mobile Platform Administration and Monitoring web interface. The 'APPLICATIONS' tab is selected, displaying a table of registered applications. The table has columns for Application ID, Name, Type, Vendor, Status, Registrations, and Logs. The first row shows an application with ID 'com.sap.flight', Name 'Flight Demo', Type 'Native', Vendor 'sap.com', Status 'checked', and Registrations '58'. The 'Registrations' value '58' is highlighted with a red box.

Application ID	Name	Type	Vendor	Status	Registrations	Logs
com.sap.flight	Flight Demo	Native	sap.com	✓	58	

5. Appendix


Appendix A – Fixing Problems with Android Project

1. Right-click on the project to open the context menu.
2. Select Android Tools -> Add Support Library... to add the support library as a jar file in the project




Remove dependency to appcompat_v7 resources.

3. Right-click on the project to open the context menu
4. Select Properties



5. Select appcompat_v7 and click on Remove.



Manually remove all dependencies to appcompat_v7 resources.

6. Open res -> values -> styles.xml and replace


This line of code that reference the appcompat_v7 resources

```
<style name="AppBaseTheme" parent="Theme.AppCompat.Light">
```

For this one

```
<style name="AppBaseTheme" parent="android:Theme.Light">
```

7. Styles.xml should look lik the image below




8. Open res -> values-v11 -> styles.xml and replace
This line of code that reference the appcompat_v7 resources

```
<style name="AppBaseTheme" parent="Theme.AppCompat.Light">
```

For this one

```
<style name="AppBaseTheme" parent="android:Theme.Light">
```

9. res -> values-v11 -> styles.xml should look like the image below




10. Open res -> values-v14 -> styles.xml and replace
This line of code that reference the appcompat_v7 resources

```
<style name="AppBaseTheme" parent="Theme.AppCompat.Light.DarkActionBar">
```

For this one

```
<style name="AppBaseTheme" parent="android:Theme.Holo.Light.DarkActionBar">
```

11. res -> values-v14 -> styles.xml should look like the image below




12. Open Res -> menu -> main.xml

13. You will get an error: No resource identifier found for attribute 'showAsAction' in package 'com.sap.smp.maf'

14. Remove the showAsAction from the item properties.

```
<item
    android:id="@+id/action_settings"
    android:orderInCategory="100"
    android:title="@string/action_settings"
    app:showAsAction="never"/>
```

14. Res -> menu -> main.xml should look like the image below



15. Open src -> com.sap.smp.maf -> MainActivity.java

16. Replace


This line of code

```
public class MainActivity extends ActionBarActivity {
```


for this one

```
public class MainActivity extends Activity {
```

17. Organize imports



18. MainActivity.java should look like



19. Save the changes

Appendix B – MAFLogonActivity.java

```
package com.sap.smp.maf;

import android.app.Activity;
import android.content.Context;
import android.content.Intent;
import android.os.Bundle;
import android.text.TextUtils;
import android.util.Log;

import com.sap.maf.tools.logon.core.LogonCore;
import com.sap.maf.tools.logon.core.LogonCoreContext;
import com.sap.maf.tools.logon.core.LogonCoreException;
import com.sap.maf.tools.logon.logonui.api.LogonListener;
import com.sap.maf.tools.logon.logonui.api.LogonUIFacade;
import com.sap.maf.tools.logon.manager.LogonContext;
import com.sap.maf.tools.logon.manager.LogonManager.LogonManagerException;

public class MAFLogonActivity extends Activity implements LogonListener {
    private final String TAG = MAFLogonActivity.class.getSimpleName();
    private LogonUIFacade mLogonUIFacade;
    private Context mContext;

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        // get an instance of the LogonUIFacade
        mLogonUIFacade = LogonUIFacade.getInstance();
        // set context reference
        mContext = this;
        this.showLogonScreen();
    }

    private void showLogonScreen() {
        //TODO 1-2 COMPLETE showLogonScreen in MAFLogonActivity *****
        // initialize the LogonUIFacade with context and application id
        mLogonUIFacade.init(this, mContext, "com.sap.flight");

        // ask LogonUIFacade to present the logon screen
        // set the resulting view as the content view for this activity
        setContentView(mLogonUIFacade.logon());
    }

    @Override
    public void objectFromSecureStoreForKey() {
        // TODO Auto-generated method stub
    }

    @Override
    public void onApplicationSettingsUpdated() {
        // TODO Auto-generated method stub
    }

    @Override
    public void onBackendPasswordChanged(boolean arg0) {
        // TODO Auto-generated method stub
    }

    @Override
    public void onLogonFinished(String message, boolean isSuccess, LogonContext lgContext) {
        //TODO 1-3 COMPLETE onLogonFinished in MAFLogonActivity *****
        Log.d(TAG, "onLogonFinished: "+message);
        //Check if it finished successfully
        if (isSuccess) {
            try {
                //For debugging purposes will log the app connection id and
                // the end point url.
                // In a productive app, remember to remove these logs
                String appConnID = LogonCore.getInstance().getLogonContext()
                    .getConnId();
            }
        }
    }
}
```

```
        Log.d(TAG, "onLogonFinished: appcid:" + appConnID);
        Log.d(TAG, "onLogonFinished: endpointurl:" + lgContext.getEndPointUrl());

    } catch (LogonManagerException e) {
        Log.e(TAG, e.getLocalizedMessage(), e);
    } catch (LogonCoreException e) {
        Log.e(TAG, e.getLocalizedMessage(), e);
    }

    // Navigate to the Main menu screen
    Intent goToNextActivity = new Intent(this, MainActivity.class);
    startActivity(goToNextActivity);
    finish();
}

}

@Override
public void onRefreshCertificate(boolean arg0, String arg1) {
    // TODO Auto-generated method stub

}

@Override
public void onSecureStorePasswordChanged(boolean arg0, String arg1) {
    // TODO Auto-generated method stub

}

@Override
public void onUserDeleted() {
    // TODO Auto-generated method stub

}


@Override
public void registrationInfo() {
    // TODO Auto-generated method stub

}


}
```

Appendix C – Creating Debug Configuration


1. In Eclipse, go to the Run icon and select Run Configurations




2. Select Android Application and click on the Create icon



3. Select the Android tab and select the corresponding HelloWorldMAF project



4. Select the Target tab and make sure you have one Android Virtual Device (AVD) selected. Then click on Apply and then on Debug.





www.sap.com/contactsap

www.sdn.sap.com/irj/sdn/howtoguides

© 2013 SAP AG or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP AG. The information contained herein may be changed without prior notice.

Some software products marketed by SAP AG and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP AG and its affiliated companies ("SAP Group") for informational purposes only, without representation or warranty of any kind, and SAP Group shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP Group products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP AG in Germany and other countries.

Please see

<http://www.sap.com/corporate-en/legal/copyright/index.epx#trademark>

for additional trademark information and notices.



The Best-Run Businesses Run SAP™