# NEO-7 series
u-blox 7 GNSS modules

Highlights

- GNSS engine for GPS, QZSS, GLONASS
- Product variants to meet performance and cost requirements
- Combines low power consumption and high sensitivity
- Simple integration with u-blox wireless modules
- Backward compatible with NEO-6 and NEO-5 families

NEO-7 series:
12.2 x 16.0 x 2.4 mm

Product description

The NEO-7 series of standalone GNSS modules is built on the exceptional performance of the u-blox 7 GNSS (GPS, GLONASS, Galileo, QZSS and SBAS) engine. The NEO-7 series delivers high sensitivity and minimal acquisition times in the industry proven NEO form factor.

The NEO-7 series provides maximum sensitivity while maintaining low system power. The NEO-7M is optimized for cost sensitive applications, while NEO-7N provides best performance and easier RF integration. The industry proven NEO form factor allows easy migration from previous NEO generations. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GPS-hostile environments.

The NEO-7 combines a high level of robustness and integration capability with flexible connectivity options. Future-proof the NEO-7N's internal Flash allows simple firmware upgrades for supporting additional GNSS systems. This makes NEO-7 perfectly suited to industrial and automotive applications. The DDC (I²C compliant) interface provides connectivity and enables synergies with u-blox SARA, LEON and LISA wireless modules. For RF optimization the NEO-7N features an additional front-end LNA for easier antenna integration and a front-end SAW filter for increased jamming immunity.

u-blox 7 modules use GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

Product selector

Model	Type							Supply			Interfaces				Features										
	GPS / QZSS	GLONASS	Galileo	BeiDou	Timing	Dead Reckoning	Precise Point Positioning	1.65 V – 3.6 V	2.7 V – 3.6 V	Lowest power (DC/DC)	UART	USB	SPI	DDC (I²C compliant)	Programmable (Flash)	Data logging	Extra front-end LNA	Front-end SAW filter	RTC crystal	Internal oscillator	Antenna supply	Antenna short circuit detection / protection	Antenna open circuit detection pin	Timepulse output	External interrupt / Wakeup
NEO-7N	•	•							•	•	•	•	Sel	•	•	•	•	•	•	T	o	o	o	•	•
NEO-7M	•	•							•	•	•	•	Sel	•					•	C	o	o	o	•	•

Sel = Select for either SPI or UART/DDC by HW configuration pin (D_SEL)
o = Optional, not activated per default or requires external components

C = Crystal / T = TCXO

u-blox

Features

Receiver type	56-channel u-blox 7 engine GPS L1 C/A, GLONASS L1 FDMA , QZSS L1 C/A SBAS: WAAS, EGNOS, MSAS		
Navigation update rate	up to 10 Hz		
		GPS	GLONASS
Accuracy	Position	2.5 m CEP	4 m
	SBAS	2.0 m CEP	n.a.
Acquisition	Cold starts:	29 s	30 s
	Aided starts:	5 s	n.a.
	Reacquisition:	1 s	3 s
Sensitivity	Tracking:	−162 dBm	−158 dBm
	Cold starts:	−148 dBm	−139 dBm
	Warm starts:	−148 dBm	−145 dBm
Assistance	AssistNow Online AssistNow Offline AssistNow Autonomous OMA SUPL & 3GPP compliant		
Oscillator	TCXO (NEO-7N), crystal (NEO-7M)		
RTC crystal	Built-In		
Anti jamming	Active CW detection and removal		
Memory	ROM (NEO-7M) or Flash (NEO-7N)		
Supported antennas	Active and passive		

Electrical data

Supply voltage	1.65 V to 3.6 V (NEO-7M) 2.7 V to 3.6 V (NEO-7N)
Power Consumption	17 mA @ 3 V (Continuous)[1] 5 mA @ 3 V Power Save mode (1Hz)[1]
Backup Supply	1.4 to 3.6 V

[1] NEO-7M.

Interfaces

Serial interfaces	1 UART 1 USB V2.0 full speed 12 Mbit/s 1 SPI (optional) 1 DDC (I²C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 1 kHz
Protocols	NMEA, UBX binary, RTCM

Package

24 pin LCC (Leadless Chip Carrier): 12.2 x 16.0 x 2.4 mm, 1.6 g

Pinout

Pin	Name		Name	Pin
13	GND		GND	12
14	ANT_ON/Reserved		RF_IN	11
15	Reserved		GND	10
16	Reserved		VCC_RF	9
17	Reserved		RESET_N	8
18	SDA	NEO-7 Top View	VDD_USB	7
19	SCL		USB_DP	6
20	TxD		USB_DM	5
21	RxD		EXTINT	4
22	V_BCKP		TIMEPULSE	3
23	VCC		D_SEL	2
24	GND		Reserved	1

Environmental data, quality & reliability

Operating temp.	−40° C to 85° C
Storage temp.	−40° C to 85° C

RoHS compliant (lead-free)

Qualification according to ISO 16750

Manufactured in ISO/TS 16949 certified production sites

Uses u-blox 7 chips qualified according to AEC-Q100

Support products

u-blox 7 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox 7 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-7N:	u-blox 7 GNSS Evaluation Kit, with TCXO, supports NEO-7N
EVK-7C:	u-blox 7 GNSS Evaluation Kit, with Crystal, supports NEO-7M

Ordering information

NEO-7M-0	u-blox 7 GNSS LCC Module, 12.2x16mm, 250 pcs/reel
NEO-7N-0	u-blox 7 GNSS LCC Module, Flash, TCXO, Low Noise Figure, 12.2x16mm, 250 pcs/reel

Available as samples and tape on reel

Contact us

HQ Switzerland / EMEA +41 44 722 7444 info@u-blox.com	India +91 959 1302 450 info_in@u-blox.com
Americas +1 703 483 3180 info_us@u-blox.com	Japan +81 3 5775 3850 info_jp@u-blox.com
APAC – Singapore +65 6734 3811 info_ap@u-blox.com	Korea +82 2 542 0861 info_kr@u-blox.com
China +86 10 68 133 545 info_cn@u-blox.com	Taiwan +886 2 2657 1090 info_tw@u-blox.com