

## 1. Installation and Importing

Installing	<code>pip install pandas</code>
Importing Convention	<code>import pandas as pd</code>

## 2. Reading and Writing data

Reading data	<pre>df = pd.read_csv('filename.csv')  # can extend for json, excel types too using pd.read_json/pd.read_excel, etc.</pre>
Writing data	<pre>df.to_csv('filename.csv')  # can extend for json, excel and such too using df.to_json/df.to_excel, etc.</pre>

## 3. Series and Dataframes

### a. Creating a series

```
pd.Series(['a', 'b', 'c'])
```

### b. Creating a dataframe

Row Oriented	<pre>pd.DataFrame([[ 'a', 1], [ 'b', 2]], columns=[ 'name', 'id'])</pre>
Column Oriented	<pre>pd.DataFrame({ 'name': [ 'a', 'b'], 'id': [1, 2] })</pre>

## 4. Info extraction

<b>Shape</b> (Return a tuple representing the dimensionality of the DataFrame.)	<code>df.shape</code>
---	-----------------------

	# e.g.-(2,3) for 2 rows and 3 columns
<b>Head</b> (first n rows, default 5)	<code>df.head(n)</code>
<b>Tail</b> (last n rows, default 5)	<code>df.tail(n)</code>
<b>Info</b> (return info of all columns)	<code>df.info()</code>
<b>Describe</b> (gives statistical information of data)	<code>df.describe()</code>

## 5. Accessing and Indexing

### a. Direct accessing columns and rows, as well as both together

<b>Accessing a row</b>	<code>df.loc[ei]</code> # ei here is explicit index <code>df.iloc[ii]</code> # ii here is implicit index
<b>Accessing a column</b>	<code>df['column_name']</code> # for single column  <code>df[['col1', 'col2']]</code> # for multiple columns

### b. Slicing

<b>Row</b>	<code>df.loc[1:3]</code> # 1 and 3 are the explicit indices here  <code>df.iloc[2:4]</code> # 2 and 4 are the implicit indices here
<b>Column</b>	<code>df.loc[:, 'a':'b']</code>

<b>Both rows and columns</b>	<pre>df.loc[1:3, 'a':'b'] # 1 and 3 are explicit indices here</pre>
------------------------------	---

### c. Feature exploration (masking, filtering)

<b>Masking</b> Creates a mask based on our required condition	<pre>df['col']&gt;value # E.g. df['age'] &gt; 30</pre>
<b>Filtering</b> Filters data based on conditions	<pre>df.loc[(df['col1'] == val1) &amp; (df['col2'] ==val2)]  # E.g df.loc[(df['month'] == 'January') &amp; (df['year']== '2022')] # filters out data for january 2022</pre>

## 6. Dataframe Manipulation

### a. Adding a new row/column

<b>Row</b>	<pre>df.loc[(df['col1'] == val1) &amp; (df['col2'] ==val2)]  # E.g:.. df.loc[len(df.index)] = ['a', 1]  # this will add a row at the end of the dataframe</pre>
<b>Column</b>	<pre>df['new_col']=data</pre>

## b. Deleting a new row/column

Row	<pre>df.drop(labels=None, axis=0)  # E.g. df.drop(3, axis=0) # Here 3 is the explicit index, axis=0 is for row</pre>
Column	<pre>df.drop('col_name', axis=1)</pre>

## c. Renaming a column

Column	<pre>df.rename({'old_name': 'new_name', axis=1})</pre>
Row	<pre>df.index=new_indices</pre>

## d. Duplicates and dropping duplicates

### i. Find duplicate rows

```
df.duplicated(subset=None, keep='first')

# subset can be used to specify certain column(s) for
identifying the duplicates
# keep determines which duplicates to mark
first : Mark duplicates as True except for the first
occurrence.
last : Mark duplicates as True except for the last
occurrence.
False : Mark all duplicates as True.

# Returns a boolean series for each duplicate row marked
as True
```

### ii. Drop duplicate values

```
df.drop_duplicates(subset=None, keep='first')
```

# Parameters have the same meaning as in df.duplicated, except here it will drop the rows marked duplicate

## 7. Operations

### a. Sorting

`df.sort_values(['col1'], ascending=[True])`

### b. Built in ops

- Built in ops such as mean, min, max, etc.
- E.g., `df['col1'].min()`, `df['col1'].count()`, etc.

### c. Apply



Applies a function along one of the axis of the dataframe  
`df['col'].apply(function)`

E.g.

`data[['revenue', 'budget']].apply(np.sum, axis=1)`

#sums values of revenue and budget across each row

## 8. Joins



9.

### a. Concat

`pd.concat([df1, df2], axis = 0)` (for concatenating horizontally, change axis

= 1)

### b. Merge

`df1.merge(df2, on='foreign_key', how='type_of_join')`

- Optional -> `left_on` and `right_on`
- Eg. `df1.merge(df2, on='id', how='inner')`

## 10. Groupby

**Grouping based on a single aggregate**

`df.groupby('group_col_name')['col(s)'].aggregate_function()`

E.g.

	<pre>df.groupby('director_name')['title'].count() # Finds number of titles per director</pre>
<b>Grouping based on multiple aggregates</b>	<pre>df.groupby(['group_col_name'])['col'].agg(['func1', 'func2'])  E.g. df.groupby(['director_name'])['year'].agg(['min', 'max']) # Finds first and recent year of movies made by all directors</pre>
<b>Group based filtering</b>	<pre>df.groupby('group_col_name').filter(boolean array based on condition)  E.g. data.groupby('director_name').filter(lambda x: x["budget"].max() &gt;= 100)  # This filters all rows of those directors whose maximum budget is greater than 100 million)</pre>
<b>Group based apply</b>	<pre>df.groupby('group_col_name').apply(function)  E.g. def func(x):     x["risky"] = x["budget"] - x["revenue"].mean() &gt;= 0     return x data_risky = data.groupby("director_name").apply(func)  # Finds movies whose budget is higher than its director's average revenue</pre>

## 11. Cleaning our data

### a. None and nan

- “NaN” is for columns with numbers as their values
- “None” is for columns with non-number entries(e.g. String, object type, etc.)
- Can check for null values using “isna()”

- E.g. `df.isna()` # returns the dataframe with True/False for null values in the respective element's position
- `df.isna().sum()` # returns number of null values per column.  
Can modify with `df.isna().sum(axis=1)` for each row's null count
- `df.isna().sum().sum()` # returns total number of null values

**b. Filling null values**

`df.fillna(n)` # fills null values with value 'n'

**c. Dropping null values**

`df.dropna(axis = 0)`

# Default axis=0, use 1 for columns

# Drops rows/columns with even a single missing value

## 12. Data Restructuring

<b>Melt</b> Convert dataframe from wide to long format	<code>pd.melt(df, id_vars=['list of columns'])</code>  E.g. <code>pd.melt(data, id_vars=['Date', 'Parameter', 'Drug_Name'])</code> # This will melt all the columns except the ones mentioned inside id_vars list
<b>Pivot</b> Opposite of melt, converts dataframe from long to wide format Outputs a multi-index dataframe	<code>df.pivot(index=['list of columns'], columns='col_name', values='col_name')</code>  E.g. <code>data_melt.pivot(index=['Date', 'Drug_Name', 'Parameter'], columns = 'time', values='reading')</code>  # This will keep the index columns mentioned as constant, while making new columns from the "time" column, whose values will be the ones in the "reading" column.
<b>Cut</b> Bins continuous data into categorical groups	<code>df['new_cat_column']=pd.cut(df['continuous_col'],bins=bin_values, labels=label_values)</code>

	<p>E.g.  <code>data_tidy['temp_cat'] =  pd.cut(data_tidy['Temperature'],  bins=temp_points,  labels=temp_labels)</code></p> <p># This will bin the temperature column into the respective bins, and will label the bins as per temp_labels</p>
<p><b>Shift</b>  Shifts the values of rows/columns</p>	<p><code>df['col'].shift(periods=n, axis=0)</code></p> <p>E.g.  <code>df["Marks"].shift(periods = 1, axis = 0)</code>  # This shifts the values of the Marks col by one, so basically the value of first row will be NaN, second row will be the one of first row, and so on.</p>

### 13. Misc Topics

#### a. Datetime

- i. Convert to Datetime object: `pd.to_datetime(df['col'])`
- ii. Extracting Information

<code>df['col'][0].year</code>	<p>Extracts the year for the 0th index value  Here 0 is the implicit index  Use .month and .day for the respective data</p>
<code>df['col'].dt.year</code>	<p>Extracts the year for whole columns (all the datetime values)</p>
<code>df['col'][0].strftime('%M%Y')</code>	<p>Formats the select data (0th index datetime value here) into the required data time format (month and year in this case)</p>

#### b. String functions

We can use .str to apply string functions to any column  
`df['col'].str.function()`

E.g.



- i. `data_tidy['Date'].str.split('-')`
  - # This will split the “Date” column into elements separated by “-”
- ii. `data_tidy.loc[data_tidy['Drug_Name'].str.contains('hydrochloride')]`
  - # Will filter out rows containing the string “hydrochloride”