

Build my own CNN

Practice – CNN

- Run "7.2. MyCNN.ipynb"



Build my own CNN model

The width and height of the feature maps are calculated based on input image size = 64 x 64 x 3

```
class MyCNN(nn.Module):
    def __init__(self):
        super(MyCNN, self).__init__()
        self.features = nn.Sequential(
            #Assume input image H/W=64
            nn.Conv2d(3, 32, 3, 1, 1), #feature map H/W=(64+2*1-3)/1+1 = 64
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0), #H/W=(64+2*0-2)/2+1 = 32
            nn.Conv2d(32, 8, 3, 1, 1), #H/W=(32+2*1-3)/1+1 = 32
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0), #H/W=(32+2*0-2)/2+1 = 16
        )
        self.classifier = nn.Sequential(
            nn.Dropout(),
            nn.Linear(8 * 16 * 16, 500),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(500, 100),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(100, 2),
        )

    def forward(self, x):
        x = self.features(x)
        x = torch.flatten(x, 1)
        x = self.classifier(x)
        return x
```

The MLP used in “4.2. Classification with CE loss”

```
MyNet = nn.Sequential(
    nn.Linear(2, 50),
    nn.ReLU(),
    nn.Linear(50, 100),
    nn.ReLU(),
    nn.Linear(100, 50),
    nn.ReLU(),
    nn.Linear(50, 2),
)
MyNet.to(device)
```

Practice: Draw the structure of MyCNN

```
model = MyCNN().to(device)
print(model)
```

```
MyCNN(
  (features): Sequential(
    (0): Conv2d(3, 32, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (1): ReLU(inplace=True)
    (2): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    (3): Conv2d(32, 8, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (4): ReLU(inplace=True)
    (5): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
  )
  (classifier): Sequential(
    (0): Dropout(p=0.5, inplace=False)
    (1): Linear(in_features=2048, out_features=500, bias=True)
    (2): ReLU(inplace=True)
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=500, out_features=100, bias=True)
    (5): ReLU(inplace=True)
    (6): Dropout(p=0.5, inplace=False)
    (7): Linear(in_features=100, out_features=2, bias=True)
  )
)
```

My own CNN

```
from torchsummary import summary
summary(model, input_size=(3, 64, 64))
```

Layer (type)	Output Shape	Param #
Conv2d-1	[-1, 32, 64, 64]	896
ReLU-2	[-1, 32, 64, 64]	0
MaxPool2d-3	[-1, 32, 32, 32]	0
Conv2d-4	[-1, 8, 32, 32]	2,312
ReLU-5	[-1, 8, 32, 32]	0
MaxPool2d-6	[-1, 8, 16, 16]	0
Dropout-7	[-1, 2048]	0
Linear-8	[-1, 500]	1,024,500
ReLU-9	[-1, 500]	0
Dropout-10	[-1, 500]	0
Linear-11	[-1, 100]	50,100
ReLU-12	[-1, 100]	0
Dropout-13	[-1, 100]	0
Linear-14	[-1, 2]	202
Total params: 1,078,010		
Trainable params: 1,078,010		
Non-trainable params: 0		
Input size (MB): 0.05		
Forward/backward pass size (MB): 2.42		
Params size (MB): 4.11		
Estimated Total Size (MB): 6.58		

MLP in "4.2. Classification with CE loss"


```
BATCH_SIZE = 30
summary(MyNet, input_size=(BATCH_SIZE, 2))
```

Layer (type)	Output Shape	Param #
Linear-1	[-1, 30, 50]	150
ReLU-2	[-1, 30, 50]	0
Linear-3	[-1, 30, 100]	5,100
ReLU-4	[-1, 30, 100]	0
Linear-5	[-1, 30, 50]	5,050
ReLU-6	[-1, 30, 50]	0
Linear-7	[-1, 30, 2]	102
Total params: 10,402		
Trainable params: 10,402		
Non-trainable params: 0		
Input size (MB): 0.00		
Forward/backward pass size (MB): 0.09		
Params size (MB): 0.04		
Estimated Total Size (MB): 0.13		

Input image after pre-processing

```
In [13]: #visualize the image after pre-processing
# Tensor is channel first, to plot, we need to convert to channel last
import numpy as np
PILImgArray = np.zeros((PILImg.shape[1], PILImg.shape[2], 3))
PILImgArray[:, :, 0] = PILImg[0, :, :]
PILImgArray[:, :, 1] = PILImg[1, :, :]
PILImgArray[:, :, 2] = PILImg[2, :, :]
PILImgArray = PILImgArray*0.5+0.5 # change  $N(0, 1)$  to  $[0, 1]$ 
print(PILImgArray.shape, PILImgArray.min(), PILImgArray.max())
plt.imshow(PILImgArray)
plt.show()
```


(64, 64, 3) 0.027450978755950928 1.0



Input image size = 64 x 64x 3


Initial filter weights

```
MyCNN(  
  (features): Sequential(  
    (0): Conv2d(3, 32, kernel_size=(3, 3), stride=(1, 1), padding:  
    (1): ReLU(inplace=True)  
    (2): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1  
    (3): Conv2d(32, 8, kernel_size=(3, 3), stride=(1, 1), padding:  
    (4): ReLU(inplace=True)  
    (5): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1
```




Output feature map, shape = 64x64x32

The width and height of the feature maps are calculated based on input image size = 64 x 64 x 3



Feature map after max pooling, shape = 32x32x32

```
torch.Size([1, 32, 32, 32])
```



Flatten

```
class MyCNN(nn.Module):
    def __init__(self):
        super(MyCNN, self).__init__()
        self.features = nn.Sequential(
            #Assume input image H/W=64
            nn.Conv2d(3, 32, 3, 1, 1), #feature map H/W=(64+2*1-3)/1+1 = 64
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0), #H/W=(64+2*0-2)/2+1 = 32
            nn.Conv2d(32, 8, 3, 1, 1), #H/W=(32+2*1-3)/1+1 = 32
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0), #H/W=(32+2*0-2)/2+1 = 16
        )
        self.classifier = nn.Sequential(
            nn.Dropout(),
            nn.Linear(8 * 16 * 16, 500),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(500, 100),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(100, 2),
        )

    def forward(self, x):
        x = self.features(x)
        x = torch.flatten(x, 1)
        x = self.classifier(x)
        return x
```

```
model = MyCNN().to(device)
print(model)
```

```
MyCNN(
  (features): Sequential(
    (0): Conv2d(3, 32, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (1): ReLU(inplace=True)
    (2): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
    (3): Conv2d(32, 8, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (4): ReLU(inplace=True)
    (5): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
  )
  (classifier): Sequential(
    (0): Dropout(p=0.5, inplace=False)
    (1): Linear(in_features=2048, out_features=500, bias=True)
    (2): ReLU(inplace=True)
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=500, out_features=100, bias=True)
    (5): ReLU(inplace=True)
    (6): Dropout(p=0.5, inplace=False)
    (7): Linear(in_features=100, out_features=2, bias=True)
  )
)
```

```
In [22]: WholeConvLayers = model.features
out1 = WholeConvLayers(imageTensor.to(device))
print(out1.shape)
```

```
torch.Size([1, 8, 16, 16])
```

```
In [23]: out2 = torch.flatten(out1, 1)
print(out2.shape)
```

```
torch.Size([1, 2048])
```

```
In [24]: ClassifierMLP = model.classifier
out = ClassifierMLP(out2)
```

Class practice

- Let the input image size be 224x224x3. Modify your CNN.


```
class MyCNN(nn.Module):
    def __init__(self):
        super(MyCNN, self).__init__()
        self.features = nn.Sequential(
            #Assume input image H/W=64
            nn.Conv2d(3, 32, 3, 1, 1), #feature map H/W=(64+2*1-3)/1+1 = 64
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0),      #H/W=(64+2*0-2)/2+1 = 32
            nn.Conv2d(32, 8, 3, 1, 1), #H/W=(32+2*1-3)/1+1 = 32
            nn.ReLU(inplace=True),
            nn.MaxPool2d(2, 2, 0),      #H/W=(32+2*0-2)/2+1 = 16
        )
        self.classifier = nn.Sequential(
            nn.Dropout(),
            nn.Linear(8 * 16 * 16, 500),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(500, 100),
            nn.ReLU(inplace=True),
            nn.Dropout(),
            nn.Linear(100, 2),
        )

    def forward(self, x):
        x = self.features(x)
        x = torch.flatten(x, 1)
        x = self.classifier(x)
        return x
```

```
[10]: from torchvision import transforms
transformer = transforms.Compose([
    transforms.Resize(64),
    transforms.CenterCrop(64),
    transforms.ToTensor(),
    transforms.Normalize(mean=[0.5, 0.5
```


VGG16

CNN family



Practice – Load ImageNet pre-trained VGG

```
import torchvision  
model = torchvision.models.vgg16(pretrained=True)
```

Downloading: "<https://download.pytorch.org/models/vgg16-397923af.pth>"
100%  528M/528M [00:10<00:00, 54.9MB/s]

Practice: Draw the structure of VGG16

```
model.eval()  
model.to(device)
```

```
VGG(  
  (features): Sequential(  
    (0): Conv2d(3, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (1): ReLU(inplace=True)  
    (2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (3): ReLU(inplace=True)  
    (4): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)  
    (5): Conv2d(64, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (6): ReLU(inplace=True)  
    (7): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (8): ReLU(inplace=True)  
    (9): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)  
    (10): Conv2d(128, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (11): ReLU(inplace=True)  
    (12): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (13): ReLU(inplace=True)  
    (14): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (15): ReLU(inplace=True)  
    (16): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)  
    (17): Conv2d(256, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (18): ReLU(inplace=True)  
    (19): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))  
    (20): ReLU(inplace=True)
```


Practice: Draw the structure of VGG16

```
(21): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
(22): ReLU(inplace=True)
(23): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
(24): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
(25): ReLU(inplace=True)
(26): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
(27): ReLU(inplace=True)
(28): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
(29): ReLU(inplace=True)
(30): MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False)
)
(avgpool): AdaptiveAvgPool2d(output_size=(7, 7))
(classifier): Sequential(
  (0): Linear(in_features=25088, out_features=4096, bias=True)
  (1): ReLU(inplace=True)
  (2): Dropout(p=0.5, inplace=False)
  (3): Linear(in_features=4096, out_features=4096, bias=True)
  (4): ReLU(inplace=True)
  (5): Dropout(p=0.5, inplace=False)
  (6): Linear(in_features=4096, out_features=1000, bias=True)
)
)
```


Transfer learning

Download images from Kaggle

The image shows the Kaggle website interface. On the left, a sidebar contains navigation links: Home, Compete, Data (circled in red), Code, Communities, Courses, and More. The main content area has a search bar at the top. Below it, the 'Datasets' section is visible, with a search filter 'cartoon' entered. A tag 'Computer Vision' is also circled in red. Under the '4 Datasets' heading, two datasets are listed: 'Landscape Pictures' and 'Tom & Jerry Detection' (circled in red). The 'Tom & Jerry Detection' dataset is by Vijayakumar, updated a year ago, with a usability of 7.5, 464 files, and 47 MB.

kaggle

- Home
- Compete
- Data**
- Code
- Communities
- Courses
- More

Search

Datasets

Search: cartoon

Computer Vision X

4 Datasets

- Landscape Pictures**
Arnaud ROUGETET · Updated a year ago
Usability 8.8 · 4319 Files (other) · 620 MB
- Tom & Jerry Detection**
Vijayakumar · Updated a year ago
Usability 7.5 · 464 Files (other) · 47 MB

Tom & Jerry

Tom & Jerry Detection | Kaggle

kaggle.com/vijayjoyz/tom-jerry-detection

應用程式 Microsoft Azure N... 免費線上影片轉Gif... YouTube Google 學術搜尋 GitHub Colaboratory 李弘毅 ML 元智大學個人portal 其他書籤

kaggle

Home

Compete

Data

Code

Communities


Courses

More

Search


Sign In Register

Dataset



Tom & Jerry Detection

Image Dataset For detecting tom & jerry

 Vijayakumar • updated a year ago (Version 1)

Data

TasksCode (2)DiscussionActivityMetadata

Download (49 MB)

New Notebook

Usability 7.5

License Database: Open Database, Contents: Database Contents

Tags arts and entertainment, computer science, classification, computer vision, comics and animation

Description

FaceDetection


Face Recognition is a recognition technique used to detect the faces of individuals whose images saved in the data set. Despite the point that other methods of identification can be more accurate, face recognition has always remained a significant focus of research because of its non-meddling nature and because it is people's facile method of personal identification.

We use cookies on Kaggle to deliver our services, analyze web traffic, and improve your experience on the site. By using Kaggle, you agree to our use of cookies.


Got it Learn more

19

Save images in your Google drive



Save images in your Google drive



Practice

- Run "7.3. Transfer learning.ipynb"



Build our own image classifier

- Suppose input image size = (224, 224, 3)
- Output has 5 classes: Angry, Happy, Sad, Surprised, Unknown

```
In [3]: import torch.nn as nn
        # fix the weight of convolution layers
        model.features.eval()

        # modify classifier
        model.classifier = torch.nn.Sequential(
            nn.Linear(25088, 4096),
            nn.ReLU(inplace=True),
            nn.Dropout(p=0.5, inplace=False),
            nn.Linear(4096, 4096),
            nn.ReLU(inplace=True),
            nn.Dropout(p=0.5, inplace=False),
            torch.nn.Linear(4096, 5))
```

Summary of parameters

```
Total params: 139,590,725
Trainable params: 139,590,725
Non-trainable params: 0
```

```
-----
Input size (MB): 0.57
Forward/backward pass size (MB): 238.68
Params size (MB): 532.50
Estimated Total Size (MB): 771.75
-----
```

MLP in "4.2. Classification with CE loss"

```
BATCH_SIZE = 30
summary(MyNet, input_size=(BATCH_SIZE, 2))
```

```
-----
Layer (type)                   Output Shape         Param #
=====
Linear-1                       [-1, 30, 50]         150
ReLU-2                         [-1, 30, 50]          0
Linear-3                       [-1, 30, 100]        5,100
ReLU-4                         [-1, 30, 100]         0
Linear-5                       [-1, 30, 50]         5,050
ReLU-6                         [-1, 30, 50]          0
Linear-7                       [-1, 30, 2]          102
=====
```

```
Total params: 10,402
Trainable params: 10,402
Non-trainable params: 0
```


```
-----
Input size (MB): 0.00
Forward/backward pass size (MB): 0.09
Params size (MB): 0.04
Estimated Total Size (MB): 0.13
-----
```



Connect to Google drive

```
from google.colab import drive  
drive.mount("/content/gdrive")
```

Go to this URL in a browser: <https://accounts.google.com/o/>



Enter your authorization code:


 使用 Google 帳戶登入



選擇帳戶

以繼續使用「Google Drive for desktop」



 使用其他帳戶

如要繼續進行，Google 會將您的姓名、電子郵件地址、語言偏好設定和個人資料相片提供給「Google Drive for desktop」。使用這個應用程式前，請先詳閱「Google Drive for desktop」的《[隱私權政策](#)》及《[服務條款](#)》。


繁體中文 ▼

說明 隱私權 條款

Connect to Google drive



Connect to Google drive



Please copy this code, switch to your application and paste it there:

4/1AY0e-

g4roX6ceHqek0M4JnYfPrHwEJCdrz8DP6nsD5y1m7Uu7B



```
from google.colab import drive  
drive.mount("/content/gdrive")
```

Go to this URL in a browser: <https://accounts.google.com/o/oauth2>

Enter your authorization code:

4/1AY0e-g4roX6ceHqek0M

Past the link and
press Enter

```
[7] from google.colab import drive  
drive.mount("/content/gdrive")
```

Mounted at /content/gdrive

Batch training using Image Folder

```
In [8]: from torchvision import transforms
transformer = transforms.Compose([
    transforms.Resize((224, 224)),
    transforms.ToTensor(),
    transforms.Normalize(mean=[0.5, 0.5, 0.5], std=[0.5, 0.5, 0.5] )])
```

```
In [9]: from torchvision import datasets
train_dataset = datasets.ImageFolder(root = "/content/gdrive/MyDrive/Image folders/train", transform = transformer)
```

```
n [10]: classes = train_dataset.classes
classes_index = train_dataset.class_to_idx
print(classes)
print(classes_index)

['angry', 'happy', 'sad', 'surprised', 'unknown']
{'angry': 0, 'happy': 1, 'sad': 2, 'surprised': 3, 'unknown': 4}
```

```
n [11]: import torch.utils.data as Data
loader = Data.DataLoader(dataset=train_dataset, batch_size=4, shuffle=True)
```

Batch training using data in RAM

```
In [9]: tensorX = torch.FloatTensor(trainX).to(device)
        tensorY_hat = torch.LongTensor(trainY_hat).to(device)
        print(tensorX.shape, tensorY_hat.shape)

        torch.Size([128, 2]) torch.Size([128])
```

```
In [10]: torch_dataset = Data.TensorDataset(tensorX, tensorY_hat)
```

```
In [11]: loader = Data.DataLoader(
            dataset=torch_dataset,
            batch_size=5,
            shuffle=True,
            num_workers=0,      # subprocesses for loading data
        )
```

```
In [12]: for (batchX, batchY_hat) in loader:
            break
        print(batchX.shape, batchY_hat)

        torch.Size([5, 2]) tensor([0, 0, 0, 1, 1], device='cuda:0')
```

One batch has 4 images

```
[12]: for batchX, batchY_hat in loader:
      break;
      print(batchX.shape, batchY_hat.shape, batchY_hat)

      torch.Size([4, 3, 224, 224]) torch.Size([4]) tensor([3, 2, 3, 2])
```

```
[13]: import numpy as np
      import matplotlib.pyplot as plt
      imgTensor = torchvision.utils.make_grid(batchX)
      imgArray = imgTensor.numpy()
      imgArray1 = np.zeros((imgArray.shape[1], imgArray.shape[2], 3))
      imgArray1[:, :, 0] = imgArray[0, :, :]
      imgArray1[:, :, 1] = imgArray[1, :, :]
      imgArray1[:, :, 2] = imgArray[2, :, :]
      imgArray1 = imgArray1*0.5+0.5
      plt.figure(figsize=(12, 6))
      plt.imshow(imgArray1)
      plt.show()
      print([classes[i] for i in batchY_hat])
```



```
['surprised', 'sad', 'surprised', 'sad']
```

Batch training loop

```
[16]: lossLst = []
accuracyLst = []
for epoch in range(1, 4):
    print("\nepoch = ", epoch, end = ", ")
    print("batch: ", end="")
    for step, (batch_x, batchY_hat) in enumerate(loader):
        if(step%5==0):
            print(step, end = ", ")
            tensorY = model(batch_x.to(device))
            loss = loss_func(tensorY, batchY_hat.to(device))
            lossLst.append(float(loss))
            optimizer.zero_grad()
            loss.backward()
            optimizer.step()

            correct = 0
            tensorY = torch.softmax(tensorY, 1)
            MaxIdxOfEachRow = torch.max(tensorY, 1)[1]
            for i in range(batchY_hat.shape[0]):
                if (int(MaxIdxOfEachRow[i]) == int(batchY_hat[i])):
                    correct += 1
            accuracy = correct/batchY_hat.shape[0]
            accuracyLst.append(accuracy)
```



```
epoch = 1, batch: 0, 5, 10, 15, 20, 25, 30, 35, 40, 45,
epoch = 2, batch: 0, 5, 10, 15, 20, 25, 30, 35, 40, 45,
epoch = 3, batch: 0, 5, 10, 15, 20, 25, 30, 35, 40, 45,
```

MLP in "4.2. Classification with CE loss"

```
lossLst = []
accuracyLst = []
for epoch in range(1, 500):
    for (batchX, batchY_hat) in loader:
        tensorY = MyNet(batchX)
        loss = loss_func(tensorY, batchY_hat)
        lossLst.append(float(loss))
        optimizer.zero_grad()
        loss.backward()
        optimizer.step()

        correct = 0
        tensorY = torch.softmax(tensorY, 1)
        MaxIdxOfEachRow = torch.max(tensorY, 1)[1]
        for i in range(batchY_hat.shape[0]):
            if (int(MaxIdxOfEachRow[i]) == int(batchY_hat[i])):
                correct += 1
        accuracy = correct/batchY_hat.shape[0]
        accuracyLst.append(accuracy)
```


Why training is not good?



Biased prediction, why?

```
In [24]: tensorY = torch.softmax(tensorY, 1)  
print(tensorY)
```

```
tensor([[0.1225, 0.1490, 0.1598, 0.2189, 0.3498]], device='cuda:0',  
        grad_fn=<SoftmaxBackward>)
```

```
In [25]: print(classes)
```

```
['angry', 'happy', 'sad', 'surprised', 'unknown']
```

Transfer learning design 2

Use first 10 layers in convolution section

Let input image size = (224, 224, 3), Output has 5 classes: Angry, Happy, Sad, Surprised, Unknown

```
[3] import torch.nn as nn
class MyCNN(nn.Module):
    def __init__(self):
        super(MyCNN, self).__init__()
        self.features = vgg19.features[0:10] #layer 0-9
        self.classifier = nn.Sequential(
            nn.Dropout(),
            nn.Linear(56*56*128, 4096),
            nn.ReLU(inplace=True),
            nn.Dropout(p=0.5, inplace=False),
            nn.Linear(4096, 4096),
            nn.ReLU(inplace=True),
            nn.Dropout(p=0.5, inplace=False),
            nn.Linear(4096, 5),
        )
    def forward(self, x):
        x = self.features(x)
        x = torch.flatten(x, 1)
        x = self.classifier(x)
        return x
```

1,661M parameters !

```
[5] from torchsummary import summary
summary(model, input_size=(3, 224, 224))
```

Layer (type)	Output Shape	Param #
Conv2d-1	[-1, 64, 224, 224]	1,792
ReLU-2	[-1, 64, 224, 224]	0
Conv2d-3	[-1, 64, 224, 224]	36,928
ReLU-4	[-1, 64, 224, 224]	0
MaxPool2d-5	[-1, 64, 112, 112]	0
Conv2d-6	[-1, 128, 112, 112]	73,856
ReLU-7	[-1, 128, 112, 112]	0
Conv2d-8	[-1, 128, 112, 112]	147,584
ReLU-9	[-1, 128, 112, 112]	0
MaxPool2d-10	[-1, 128, 56, 56]	0
Dropout-11	[-1, 401408]	0
Linear-12	[-1, 4096]	1,644,171,264
ReLU-13	[-1, 4096]	0
Dropout-14	[-1, 4096]	0
Linear-15	[-1, 4096]	16,781,312
ReLU-16	[-1, 4096]	0
Dropout-17	[-1, 4096]	0
Linear-18	[-1, 5]	20,485

```
Total params: 1,661,233,221
Trainable params: 1,661,233,221
Non-trainable params: 0
```

Total params: 139,590,725
Trainable params: 139,590,725
Non-trainable params: 0

Input size (MB): 0.57
Forward/backward pass size (MB): 238.68
Params size (MB): 532.50
Estimated Total Size (MB): 771.75

CUDA out of memory!

```
epoch = 1, batch: 0,
```

```
-----  
RuntimeError                                Traceback (most recent call last)
```

```
<ipython-input-17-94eca5998520> in <module>()
```

```
    11     lossLst.append(float(loss))  
    12     optimizer.zero_grad()  
--> 13     loss.backward()  
    14     optimizer.step()  
    15
```

⌄ 1 frames

```
_____  
/usr/local/lib/python3.7/dist-packages/torch/autograd/_init_.py in backward(tensors,  
grad_tensors, retain_graph, create_graph, grad_variables, inputs)
```

```
    145     Variable._execution_engine.run_backward(  
    146         tensors, grad_tensors_, retain_graph, create_graph, inputs,  
--> 147         allow_unreachable=True, accumulate_grad=True) # allow_unreachable flag  
    148  
    149
```

```
RuntimeError: CUDA out of memory. Tried to allocate 6.12 GiB (GPU 0; 11.17 GiB total  
capacity; 6.46 GiB already allocated; 4.27 GiB free; 6.47 GiB reserved in total by PyTorch)
```

HW – Can CNN recognize your facial expression?

- Use transfer learning to train an image classifier to recognize happy and angry faces.



HW5 – Recognize Alzheimer disease from MRI

Results by searching "dementia" in Kaggle

3 Results

Sort by: Relevancy



Dataset

Dataset_Alzheimer

by Yasir Hussein Shakir

3 months ago • 34 MB • 7

Alzheimer's treatments cannot stop Alzheimer's from progressing, they




Dataset

Alzheimer_binaryclassification

by Smiti14

2 months ago • 33 MB • 0



Dataset

combo01

by SHIYONA DASH

2 months ago • 94 MB • 0

Alzheimer_s Dataset

名稱

test

train

> Alzheimer_s Dataset > train

名稱

MildDemented


ModerateDemented

NonDemented


VeryMildDemented

端硬碟

HW5 (2) – Recognize Alzheimer disease from MRI



If you want to understand more about MRI brain scan images



<https://www.med.harvard.edu/aANliB/cases/caseNA/pb9.htm>

• Normal Brain:

- [Normal Anatomy in 3-D with MRI/PET \(Javascript\)](#)
- [Atlas of normal structure and blood flow](#)
 - [Top 100 Brain Structures](#)
 - [Can you name these brain structures?](#)
- [Normal aging: structure and function](#)
- [Normal aging: structure and function](#)
- [Normal aging: coronal plane](#)
- [Vascular anatomy](#)

• Cerebrovascular Disease (stroke or "brain attack"):

- [NEW: Multiple embolic infarction, diffusion and FLAIR imaging](#)
- [Acute stroke: speech arrest](#)
- [Acute stroke: speaks nonsense words, "fluent aphasia" \(time-lapse movies\)](#)
- [Acute stroke: writes, but can't read, "alexia without agraphia"](#)
- [Subacute stroke: hesitating speech, "transcortical aphasia"](#)
- [Subacute stroke: loss of sensation](#)
- [Chronic subdural hematoma](#)
- [Cavernous angioma](#)
- [Arteriovenous malformation, with MRA](#)
- [Vascular dementia](#)
- [Acute stroke \(MR diffusion imaging\) with MRA: Carotid or Circle of Willis](#)
- [Hypertensive encephalopathy](#)
- [Multiple embolic infarctions](#)
- [Hypertensive encephalopathy](#)
- [Fatal stroke](#)

<https://www.med.harvard.edu/aANliB/home.html>

HW – Can we recognize dementia disease from facial expression ?

Facial expressions can detect Parkinson's disease: preliminary evidence from videos collected online

Mohammad Rafayet Ali, Taylor Myers, Ellen Wagner, Harshil Ratnu, E. Ray Dorsey, Ehsan Hoque



<https://arxiv.org/abs/2012.05373>

中文解讀: https://ai-scholar.tech/zh/articles/image-recognition/facial_expressions_perkinson

HW5 (2) – Can CNN detect Autism from a facial image?


Datasets

Q facial image

Datasets Tasks Computer Science Education Cla

1 Tasks

Detect Autism with 98% accuracy
Gerry · 0 Submissions

 Detect Autism from a facial image
Gerry · Usability 7.5

- consolidated
- test
- train
- valid
- autism-2
- autism-S-224-89.33.h5

