Oracle 19c srvctl command quick reference

Below is a compact table of common srvctl activities using -db $ORACLE_UNQNAME, followed by two-node RAC service examples for adding, starting, relocating, stopping, and removing services.

Area	Purpose	Command (example)
Database	Add database metadata to GI	"srvctl add database -db $ORACLE_UNQNAME -o /u01/app/oracle/product/19.0.0/dbhome_1 -p +DATA/ORCL/spfileORCL.ora -r PRIMARY -n ORCL_DG -a DATA,RECO -s OPEN -y AUTOMATIC -t IMMEDIATE"
Database	Modify database attributes	"srvctl modify database -db $ORACLE_UNQNAME -r PRIMARY -n ORCL_DG -a DATA,RECO -y AUTOMATIC -t IMMEDIATE"
Database	Remove database from GI	"srvctl remove database -db $ORACLE_UNQNAME -f"
Database	Start entire database	"srvctl start database -db $ORACLE_UNQNAME -o open"
Database	Stop entire database	"srvctl stop database -db $ORACLE_UNQNAME -o immediate"
Database	Show database status	"srvctl status database -db $ORACLE_UNQNAME"
Database	Show database config	"srvctl config database -db $ORACLE_UNQNAME"
Database	Enable auto-restart	"srvctl enable database -db $ORACLE_UNQNAME"
Database	Disable auto-restart	"srvctl disable database -db $ORACLE_UNQNAME"
Database env	Set env vars on DB	"srvctl setenv database -db $ORACLE_UNQNAME -T TZ=UTC,LANG=en_US.UTF-8"
Database env	Get env vars	"srvctl getenv database -db $ORACLE_UNQNAME"
Database env	Unset env vars	"srvctl unsetenv database -db $ORACLE_UNQNAME -T TZ,LANG"
Instance	Add a RAC instance	"srvctl add instance -db $ORACLE_UNQNAME -i ORCL1 -n node1"

Instance	Remove a RAC instance	“srvctl remove instance -db $ORACLE_UNQNAME -i ORCL1”
Instance	Start an instance	“srvctl start instance -db $ORACLE_UNQNAME -i ORCL1 -o open”
Instance	Stop an instance	“srvctl stop instance -db $ORACLE_UNQNAME -i ORCL1 -o immediate”
Instance	Show instance status	“srvctl status instance -db $ORACLE_UNQNAME -i ORCL1”
Instance	Change instance placement	“srvctl modify instance -db $ORACLE_UNQNAME -i ORCL1 -n node2”
Instance	Enable an instance	“srvctl enable instance -db $ORACLE_UNQNAME -i ORCL1”
Instance	Disable an instance	“srvctl disable instance -db $ORACLE_UNQNAME -i ORCL1”
Service	Add a DB service	“srvctl add service -db $ORACLE_UNQNAME -s SALES_RO -r ORCL1,ORCL2 -a ORCL1 -P BASIC -e SESSION -m BASIC -B SERVICE_TIME -j SHORT -l PRIMARY -u SELECT -y AUTOMATIC -w 3 -z 5”
Service	Start a service	“srvctl start service -db $ORACLE_UNQNAME -s SALES_RO”
Service	Stop a service	“srvctl stop service -db $ORACLE_UNQNAME -s SALES_RO”
Service	Relocate a service	“srvctl relocate service -db $ORACLE_UNQNAME -s SALES_RO -i ORCL1 -t ORCL2 -f”
Service	Modify a service	“srvctl modify service -db $ORACLE_UNQNAME -s SALES_RO -e SELECT -m BASIC -B SERVICE_TIME”
Service	Remove a service	“srvctl remove service -db $ORACLE_UNQNAME -s SALES_RO”
Service	Status of services	“srvctl status service -db $ORACLE_UNQNAME”
Service	Service config details	“srvctl config service -db $ORACLE_UNQNAME -s SALES_RO”
PDB service	Add a PDB service	“srvctl add service -db $ORACLE_UNQNAME -pdb PDB1 -service PDB1_APP -preferred ORCL1,ORCL2 -e SESSION -m BASIC -y AUTOMATIC”
PDB service	Start PDB service	“srvctl start service -db $ORACLE_UNQNAME -pdb PDB1 -service PDB1_APP”
PDB service	Stop PDB service	“srvctl stop service -db $ORACLE_UNQNAME -pdb PDB1 -service PDB1_APP”
PDB service	Modify PDB service	“srvctl modify service -db $ORACLE_UNQNAME -pdb PDB1 -service PDB1_APP -preferred ORCL1 -available ORCL2”

Listener	Add a listener	“srvctl add listener -l LISTENER -p TCP:1521 -o /u01/app/19.0.0/grid”
Listener	Start/Stop listener	“srvctl start listener -l LISTENER” and “srvctl stop listener -l LISTENER”
Listener	Status/Config listener	“srvctl status listener -l LISTENER” and “srvctl config listener -l LISTENER”
Listener	Enable/Disable listener	“srvctl enable listener -l LISTENER” and “srvctl disable listener -l LISTENER”
SCAN	Modify SCAN cardinality	“srvctl modify scan -n scan-cluster.example.com -k 3”
SCAN listener	Start/Stop SCAN listener	“srvctl start scan_listener” and “srvctl stop scan_listener”
SCAN listener	Status/Config	“srvctl status scan_listener” and “srvctl config scan_listener”
VIP	Add a VIP	“srvctl add vip -n node1 -A 10.0.0.101/255.255.255.0/eth0 -k vip_node1”
VIP	Start/Stop VIP	“srvctl start vip -n node1” and “srvctl stop vip -n node1”
VIP	Relocate VIP	“srvctl relocate vip -n node1 -i node2”
VIP	Status/Config VIP	“srvctl status vip -n node1” and “srvctl config vip -n node1”
Nodeapps	Start/Stop nodeapps	“srvctl start nodeapps -n node1” and “srvctl stop nodeapps -n node1”
ASM	Start/Stop ASM	“srvctl start asm” and “srvctl stop asm -o immediate”
ASM	ASM status	“srvctl status asm -verbose”
Diskgroup	Manage diskgroups	“srvctl start diskgroup -g DATA”, “srvctl stop diskgroup -g DATA”, “srvctl status diskgroup -g DATA”
Env for service	Set/Get/Unset env	“srvctl setenv service -db $ORACLE_UNQNAME -s SALES_RO -T NLS_DATE_FORMAT=YYYY-MM-DD”; “srvctl getenv service -db $ORACLE_UNQNAME -s SALES_RO”; “srvctl unsetenv service -db $ORACLE_UNQNAME -s SALES_RO -T NLS_DATE_FORMAT”

Two-node RAC service operations (node1/ORCL1, node2/ORCL2)

- Add a read-write OLTP service on both instances
  “srvctl add service -db $ORACLE_UNQNAME -service OLTP_RW -preferred CDBINST1, CDBINST 2 -pdb PDBNAME”

- Start the OLTP service everywhere
  “srvctl start service -db $ORACLE_UNQNAME -service OLTP_RW”

- Relocate OLTP service from ORCL1 to ORCL2 (for maintenance)
  “srvctl relocate service -db $ORACLE_UNQNAME -service OLTP_RW -i ORCL1 -t ORCL2 -f”

- Stop the OLTP service
  “srvctl stop service -db $ORACLE_UNQNAME -service OLTP_RW”

- Drop the OLTP service
  “srvctl remove service -db $ORACLE_UNQNAME -s OLTP_RW”

- Add a read-only reporting service, preferred on ORCL2, available on ORCL1
  “srvctl add service -db $ORACLE_UNQNAME -s REPORT_RO -r ORCL2 -a ORCL1 -P BASIC -e SELECT -m BASIC -B SERVICE_TIME -j LONG -l PRIMARY -y AUTOMATIC”

- Start REPORT_RO
  “srvctl start service -db $ORACLE_UNQNAME -s REPORT_RO”

- Relocate REPORT_RO to ORCL1 during node2 patching
  “srvctl relocate service -db $ORACLE_UNQNAME -s REPORT_RO -i ORCL2 -t ORCL1 -f”

- Stop and drop REPORT_RO
  “srvctl stop service -db $ORACLE_UNQNAME -s REPORT_RO”
  “srvctl remove service -db $ORACLE_UNQNAME -s REPORT_RO”

Notes

- Lists for -r and -a are comma-separated with no spaces.
- -y AUTOMATIC ensures the service autostarts with the database.
- For PDB-scoped services add -pdb PDB_NAME and -service SERVICE_NAME.