ORACLE APPS DBA

Reference Guide — Scripts & SQL Queries

Covers: EBS Administration • Database Monitoring • RMAN Backup & Recovery
Patching (AD/TXK) • Concurrent Manager • Performance Tuning • OCI/Cloud DBA

Prepared by: Megha (Oracle Apps DBA & Cloud Engineer)

Version 1.0 | 18 March 2026

Table of Contents

1. EBS Services — Start / Stop / Status
2. Concurrent Manager Administration
3. Application Tier Health Checks
4. Database Monitoring Queries
5. User & Responsibility Management
6. RMAN Backup & Recovery Scripts
7. Patching — AD/TXK (adop)
8. Performance Tuning & AWR
9. Space Management & Tablespace
10. Data Pump (expdp / impdp)
11. OCI / Cloud DBA Essentials
12. Common DBA Utilities & Shortcuts

1. EBS Services — Start / Stop / Status

1.1 Start All EBS Services

```
# As applmgr user:
su - applmgr
source /u01/oracle/apps/EBSapps.env run

# Start all services (App Tier)
$ADMIN_SCRIPTS_HOME/adstrtal.sh apps/<APPS_PWD>

# Start individual services
$ADMIN_SCRIPTS_HOME/adoacorectl.sh start   # OACore (JVM)
$ADMIN_SCRIPTS_HOME/adapcctl.sh start      # Apache
$ADMIN_SCRIPTS_HOME/adformsctl.sh start    # Forms
$ADMIN_SCRIPTS_HOME/adcmctl.sh start apps/<APPS_PWD>  # Concurrent Manager
```

1.2 Stop All EBS Services

```
$ADMIN_SCRIPTS_HOME/adstpall.sh apps/<APPS_PWD>

# Stop individual
$ADMIN_SCRIPTS_HOME/adoacorectl.sh stop
$ADMIN_SCRIPTS_HOME/adapcctl.sh stop
$ADMIN_SCRIPTS_HOME/adformsctl.sh stop
$ADMIN_SCRIPTS_HOME/adcmctl.sh stop apps/<APPS_PWD>
```

1.3 Service Status Check

```
$ADMIN_SCRIPTS_HOME/adoacorectl.sh status
$ADMIN_SCRIPTS_HOME/adapcctl.sh status
$ADMIN_SCRIPTS_HOME/adformsctl.sh status
$ADMIN_SCRIPTS_HOME/adcmctl.sh status

# Check all process listeners
ps -ef | grep -E 'apache|opmn|forms|java|FNDLIBR' | grep -v grep

# Check DB listener
lsnrctl status
lsnrctl start
```

1.4 Environment Source Files

```
# Run edition (application server env)
source /u01/oracle/apps/EBSapps.env run

# Patch edition
source /u01/oracle/apps/EBSapps.env patch

# Database tier env
source /u01/oracle/db/EBS_env.env
export ORACLE_HOME=/u01/oracle/db/19.0.0
export ORACLE_SID=EBSDB
export PATH=$ORACLE_HOME/bin:$PATH
```

2. Concurrent Manager Administration

2.1 CM Status from SQL

```
-- Check Concurrent Manager status
SELECT fcq.user_concurrent_queue_name   manager_name,
       fcp.process_status_code           status,
       fcp.process_type,
       fcp.concurrent_process_id
FROM   fnd_concurrent_queues_vl fcq,
       fnd_concurrent_processes fcp
WHERE  fcq.concurrent_queue_id = fcp.concurrent_queue_id
  AND  fcp.process_status_code IN ('A','C','T')
ORDER BY 1;
```

2.2 Running / Pending Concurrent Requests

```
-- Running requests
SELECT fcr.request_id,
       fcpt.user_concurrent_program_name  program,
       fcr.phase_code, fcr.status_code,
       fcr.requested_by,
       TO_CHAR(fcr.actual_start_date,'DD-MON-YYYY HH24:MI') start_time,
       ROUND((SYSDATE - fcr.actual_start_date)*1440,1)       running_mins
FROM   fnd_concurrent_requests fcr,
       fnd_concurrent_programs_tl fcpt
WHERE  fcr.concurrent_program_id = fcpt.concurrent_program_id
  AND  fcpt.language = 'US'
  AND  fcr.phase_code = 'R'   -- R=Running
ORDER BY running_mins DESC;

-- Pending requests (change phase_code='P')
```

2.3 Long-running / Stuck Requests

```
SELECT fcr.request_id,
       fcpt.user_concurrent_program_name program,
       fcr.phase_code, fcr.status_code,
       ROUND((SYSDATE-fcr.actual_start_date)*1440,0) run_mins
FROM   fnd_concurrent_requests  fcr,
       fnd_concurrent_programs_tl fcpt
WHERE  fcr.concurrent_program_id = fcpt.concurrent_program_id
  AND  fcpt.language = 'US'
  AND  fcr.phase_code = 'R'
  AND  ROUND((SYSDATE-fcr.actual_start_date)*1440,0) > 60
ORDER BY run_mins DESC;
```

2.4 Cancel / Purge Requests

```
-- Cancel a specific request (run as APPS)
EXEC FND_CONCURRENT.CANCEL_REQUEST(<request_id>);

-- Purge completed requests older than 30 days
BEGIN
  FND_CONCURRENT.PURGE_JOBS(
    itemtype    => 'FNDCPJID',
    num_of_days => 30
  );
```

```
END;
/
```

2.5 Bounce Concurrent Manager (Quick)

```
$ADMIN_SCRIPTS_HOME/adcmctl.sh stop   apps/<APPS_PWD>
sleep 30
$ADMIN_SCRIPTS_HOME/adcmctl.sh start  apps/<APPS_PWD>
$ADMIN_SCRIPTS_HOME/adcmctl.sh status
```

---

3. Application Tier Health Checks

3.1 Check Workflow Mailer Status

```
-- WF Mailer (Notification Mailer) status
SELECT agent_name, status, last_update_date
FROM   wf_agents
WHERE  agent_name LIKE '%MAILER%';

-- Service Component Container status
SELECT component_name, component_status
FROM   fnd_svc_components
WHERE  component_type LIKE '%MAILER%';
```

3.2 TNS / DB Connectivity Test

```
tnsping <TNS_ALIAS>

# Connect via SQLPlus
sqlplus apps/<APPS_PWD>@<TNS_ALIAS>
sqlplus '/ as sysdba'
```

3.3 Check EBS Log Files

```
# Apache error log
tail -200f $INST_TOP/logs/ora/10.1.3/Apache/error_log

# Forms server log
tail -200f $INST_TOP/logs/forms/

# Concurrent Manager log
tail -200f $INST_TOP/logs/appl/conc/log/<request_id>.req

# adop log
tail -200f $NE_BASE/EBSapps/log/adop/*/adop_<phase>.log
```

3.4 Profile Option Values

```
SELECT fpo.profile_option_name,
       fpt.user_profile_option_name,
       fpov.profile_option_value,
       DECODE(fpov.level_id,
```

```
              10001,'SITE',10002,'APP',10003,'RESP',10004,'USER') level_type
FROM   fnd_profile_options      fpo,
       fnd_profile_options_tl   fpt,
       fnd_profile_option_values fpov
WHERE  fpo.profile_option_id = fpt.profile_option_id
  AND  fpo.profile_option_id = fpov.profile_option_id
  AND  fpt.language = 'US'
  AND  fpo.profile_option_name = '&PROFILE_NAME';
```

4. Database Monitoring Queries

4.1 Active Sessions

```
SELECT s.sid, s.serial#, s.username, s.status,
       s.machine, s.program, s.module,
       s.sql_id, s.event, s.wait_class,
       s.last_call_et   seconds_in_wait
FROM   v$session s
WHERE  s.type   = 'USER'
  AND  s.status = 'ACTIVE'
ORDER BY s.last_call_et DESC;
```

4.2 Blocking Locks

```
SELECT l.blocking_session,
       l.sid, l.serial#, l.username,
       l.wait_class, l.seconds_in_wait,
       o.object_name, o.object_type
FROM   v$session l
JOIN   dba_objects o ON o.object_id = l.row_wait_obj#
WHERE  l.blocking_session IS NOT NULL
ORDER BY l.seconds_in_wait DESC;

-- Kill a blocking session
ALTER SYSTEM KILL SESSION '<SID>,<SERIAL#>' IMMEDIATE;
```

4.3 Tablespace Usage

```
SELECT df.tablespace_name,
       ROUND(df.total_mb,1)           total_mb,
       ROUND(df.total_mb-fs.free_mb,1) used_mb,
       ROUND(fs.free_mb,1)            free_mb,
       ROUND((df.total_mb-fs.free_mb)/df.total_mb*100,1) pct_used
FROM  (SELECT tablespace_name, SUM(bytes)/1048576 total_mb
       FROM dba_data_files GROUP BY tablespace_name) df
JOIN  (SELECT tablespace_name, SUM(bytes)/1048576 free_mb
       FROM dba_free_space GROUP BY tablespace_name) fs
ON    df.tablespace_name = fs.tablespace_name
ORDER BY pct_used DESC;
```

4.4 Top 10 SQL by Elapsed Time

```
SELECT * FROM (
  SELECT sql_id,
```

```
         ROUND(elapsed_time/1e6,2)       elapsed_secs,
         executions,
         ROUND(elapsed_time/NULLIF(executions,0)/1e6,4) avg_secs,
         SUBSTR(sql_text,1,80)           sql_text
  FROM   v$sqlstats
  ORDER  BY elapsed_time DESC
) WHERE ROWNUM <= 10;
```

4.5 Redo Log Status

```
SELECT l.group#, l.members, l.status,
       ROUND(l.bytes/1048576,0) size_mb,
       l.archived
FROM   v$log l
ORDER  BY l.group#;

-- Redo log switch frequency (last 24h)
SELECT TO_CHAR(first_time,'DD-MON-YYYY HH24') hour,
       COUNT(*) switches
FROM   v$log_history
WHERE  first_time >= SYSDATE - 1
GROUP  BY TO_CHAR(first_time,'DD-MON-YYYY HH24')
ORDER  BY 1;
```

4.6 Archive Log Space Usage

```
SELECT dest_name, status, target, archived_seq#
FROM   v$archive_dest_status
WHERE  status <> 'INACTIVE';

-- FRA usage
SELECT name,
       ROUND(space_limit/1073741824,2)     limit_gb,
       ROUND(space_used/1073741824,2)       used_gb,
       ROUND(space_reclaimable/1073741824,2) reclaimable_gb,
       number_of_files
FROM   v$recovery_file_dest;
```

5. User & Responsibility Management

5.1 List Users and Their Responsibilities

```
SELECT fu.user_name,
       fu.description,
       fr.responsibility_name,
       fa.application_name,
       furg.start_date, furg.end_date
FROM   fnd_user                fu,
       fnd_user_resp_groups_all furg,
       fnd_responsibility_tl    fr,
       fnd_application_tl       fa
WHERE  fu.user_id           = furg.user_id
  AND  furg.responsibility_id = fr.responsibility_id
  AND  fr.application_id      = fa.application_id
  AND  fr.language            = 'US'
  AND  fa.language            = 'US'
```

```
  AND  (furg.end_date IS NULL OR furg.end_date >= SYSDATE)
  AND  fu.user_name = UPPER('&USERNAME')
ORDER BY fr.responsibility_name;
```

5.2 Create / Reset User Password

```
-- Reset password via API
BEGIN
  FND_USER_PKG.UPDATEUSER(
    x_user_name             => 'JSMITH',
    x_owner                 => 'CUST',
    x_unencrypted_password  => 'Welcome1#'
  );
  COMMIT;
END;
/
```

5.3 Expire a User / End-Date Responsibility

```
-- End-date a user account
UPDATE fnd_user
SET    end_date = TRUNC(SYSDATE)
WHERE  user_name = 'JSMITH';
COMMIT;

-- End-date a specific responsibility assignment
UPDATE fnd_user_resp_groups_all
SET    end_date = TRUNC(SYSDATE)
WHERE  user_id = (SELECT user_id FROM fnd_user WHERE user_name='JSMITH')
  AND  responsibility_id = (SELECT responsibility_id
        FROM fnd_responsibility_tl
        WHERE responsibility_name = 'System Administrator' AND language='US');
COMMIT;
```

5.4 Unlock a User Account (DB Level)

```
-- Check locked accounts
SELECT username, account_status, lock_date
FROM   dba_users
WHERE  account_status LIKE '%LOCK%';

-- Unlock
ALTER USER apps ACCOUNT UNLOCK;
ALTER USER applsys ACCOUNT UNLOCK;
```

6. RMAN Backup & Recovery Scripts

6.1 Full Database Backup (with Archivelog)

```
rman target / nocatalog <<EOF
RUN {
  ALLOCATE CHANNEL c1 DEVICE TYPE DISK
    FORMAT '/backup/rman/%d_%T_%s_%p.bkp';
  BACKUP AS COMPRESSED BACKUPSET DATABASE
```

```
    PLUS ARCHIVELOG DELETE ALL INPUT;
  BACKUP CURRENT CONTROLFILE
    FORMAT '/backup/rman/%d_CTL_%T_%s.ctl';
  BACKUP SPFILE;
  DELETE NOPROMPT OBSOLETE;
}
EOF
```

6.2 Incremental Backup (Level 0 / 1)

```
-- Level 0 (Sunday)
BACKUP INCREMENTAL LEVEL 0 DATABASE
  FORMAT '/backup/rman/INC0_%d_%T_%s.bkp';

-- Level 1 (Mon-Sat)
BACKUP INCREMENTAL LEVEL 1 DATABASE
  FORMAT '/backup/rman/INC1_%d_%T_%s.bkp';
```

6.3 Restore & Recover Database

```
-- Start DB in mount mode
STARTUP MOUNT;

rman target /
RUN {
  RESTORE DATABASE;
  RECOVER DATABASE;
}
ALTER DATABASE OPEN RESETLOGS;
```

6.4 Encrypted Backup with Oracle Wallet

```
-- Create wallet directory
mkdir -p /u01/oracle/wallet

-- In sqlnet.ora
ENCRYPTION_WALLET_LOCATION =
  (SOURCE=(METHOD=FILE)(METHOD_DATA=
    (DIRECTORY=/u01/oracle/wallet)))

-- Create wallet and set encryption key
ALTER SYSTEM SET ENCRYPTION KEY IDENTIFIED BY "WalletPass1";

-- Open wallet
ALTER SYSTEM SET WALLET OPEN IDENTIFIED BY "WalletPass1";

-- RMAN encrypted backup
SET ENCRYPTION ON IDENTIFIED BY "WalletPass1";
BACKUP DATABASE FORMAT '/backup/rman/enc_%d_%T_%s.bkp';
```

NOTE: For Standby DB restore with encryption: wallet must be present on standby at the same path, and must be opened before running RMAN restore.

6.5 Validate Backup

```
RMAN> VALIDATE DATABASE;
RMAN> RESTORE DATABASE VALIDATE;
RMAN> LIST BACKUP SUMMARY;
RMAN> CROSSCHECK BACKUP;
```

7. Patching — AD/TXK (adop)

7.1 adop Phases Overview

Phase	Command / Purpose
prepare	adop phase=prepare — creates patch edition
apply	adop phase=apply patches=<patch#> — apply patch
finalize	adop phase=finalize — promote patch edition
cutover	adop phase=cutover — switch to new edition (brief downtime)
cleanup	adop phase=cleanup — remove old edition
abort	adop phase=abort — roll back prepare/apply

7.2 Apply Online Patch (Zero Downtime)

```
# Source env
source /u01/oracle/apps/EBSapps.env run

# Prepare (no downtime)
adop phase=prepare

# Apply patch
adop phase=apply patches=<PATCH_NUMBER>

# Finalize
adop phase=finalize

# Cutover (brief ~5 min outage)
adop phase=cutover

# Cleanup (removes old edition)
adop phase=cleanup
```

7.3 Check Patch Application Status

```
-- Check if patch is applied
SELECT patch_name, patch_type, maint_pack_level,
       TO_CHAR(creation_date,'DD-MON-YYYY HH24:MI') applied_on
FROM   ad_applied_patches
WHERE  patch_name = '&PATCH_NUMBER'
ORDER  BY creation_date DESC;

-- Recent patch history
SELECT patch_name, creation_date
FROM   ad_applied_patches
ORDER  BY creation_date DESC
FETCH  FIRST 20 ROWS ONLY;
```

7.4 adop Status / Sessions

```
-- Active adop sessions
SELECT session_id, prepare_status, apply_status,
       finalize_status, cutover_status, cleanup_status,
       node_name
FROM   ad_adop_sessions
ORDER  BY session_id DESC;
```

8. Performance Tuning & AWR

8.1 Generate AWR Report

```
-- Get snap IDs
SELECT snap_id, TO_CHAR(begin_interval_time,'DD-MON HH24:MI') snap_time
FROM   dba_hist_snapshot
WHERE  begin_interval_time >= SYSDATE - 1
ORDER  BY snap_id;

-- Generate HTML AWR report
@$ORACLE_HOME/rdbms/admin/awrrpt.sql

-- Or via DBMS_WORKLOAD_REPOSITORY
SELECT output FROM TABLE(
  DBMS_WORKLOAD_REPOSITORY.AWR_REPORT_HTML(
    l_dbid    => (SELECT dbid FROM v$database),
    l_inst_num => 1,
    l_bid     => <start_snap_id>,
    l_eid     => <end_snap_id>
  )
);
```

8.2 Top Wait Events

```
SELECT event, total_waits, total_timeouts,
       ROUND(time_waited_micro/1e6,2) wait_secs,
       wait_class
FROM   v$system_event
WHERE  wait_class <> 'Idle'
ORDER  BY time_waited_micro DESC
FETCH  FIRST 15 ROWS ONLY;
```

8.3 SQL Execution Plan

```
EXPLAIN PLAN FOR
<your SQL here>;

SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY(
  format => 'ALL +PEEKED_BINDS'));

-- From cursor cache
SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY_CURSOR(
  '<sql_id>', NULL, 'ALLSTATS LAST'));
```

8.4 Check SGA / PGA Sizes

```
SELECT name, ROUND(value/1073741824,2) gb
FROM   v$sgainfo
WHERE  name IN ('Total SGA Size','Maximum SGA Size')
UNION ALL
SELECT 'PGA Aggregate Target',
       ROUND(value/1073741824,2)
FROM   v$parameter WHERE name='pga_aggregate_target';

-- Adjust (if needed)
ALTER SYSTEM SET SGA_TARGET      = 8G SCOPE=BOTH;
ALTER SYSTEM SET PGA_AGGREGATE_TARGET = 2G SCOPE=BOTH;
```

---

9. Space Management & Tablespace

9.1 Add Datafile to Tablespace

```
-- Add new datafile
ALTER TABLESPACE APPS_TS_TX_DATA
  ADD DATAFILE '/u01/oracle/data/apps_ts_tx01.dbf'
  SIZE 2G AUTOEXTEND ON NEXT 512M MAXSIZE 32G;

-- List datafiles for a tablespace
SELECT file_name, ROUND(bytes/1073741824,2) size_gb,
       autoextensible, ROUND(maxbytes/1073741824,2) max_gb
FROM   dba_data_files
WHERE  tablespace_name = 'APPS_TS_TX_DATA';
```

9.2 Segment Space Usage (Top Objects)

```
SELECT owner, segment_name, segment_type,
       ROUND(bytes/1073741824,2) size_gb
FROM   dba_segments
WHERE  owner NOT IN ('SYS','SYSTEM')
ORDER  BY bytes DESC
FETCH  FIRST 20 ROWS ONLY;
```

9.3 Shrink a Segment

```
-- Enable row movement first
ALTER TABLE <OWNER>.<TABLE_NAME> ENABLE ROW MOVEMENT;

-- Shrink (reclaim free space without locks)
ALTER TABLE <OWNER>.<TABLE_NAME> SHRINK SPACE COMPACT;

-- Shrink + reset HWM
ALTER TABLE <OWNER>.<TABLE_NAME> SHRINK SPACE;

-- Coalesce tablespace free space
ALTER TABLESPACE APPS_TS_TX_DATA COALESCE;
```

9.4 Check TEMP Tablespace

```
SELECT tablespace_name,
       ROUND(allocated_space/1048576,0)  alloc_mb,
       ROUND(free_space/1048576,0)        free_mb,
       ROUND((allocated_space-free_space)/1048576,0) used_mb
FROM   dba_temp_free_space;
```

10. Data Pump (expdp / impdp)

10.1 Schema Export

```
# Full schema export
expdp apps/<APPS_PWD>@<TNS> \
  schemas=AR,GL,AP \
  directory=DATA_PUMP_DIR \
  dumpfile=SCHEMA_EXP_%U.dmp \
  logfile=schema_exp.log \
  parallel=4 \
  compression=ALL
```

10.2 Table-Level Export

```
expdp apps/<APPS_PWD>@<TNS> \
  tables=GL.GL_LEDGERS,GL.GL_PERIODS \
  directory=DATA_PUMP_DIR \
  dumpfile=tables_exp.dmp \
  logfile=tables_exp.log
```

10.3 Schema Import (with Remap)

```
impdp system/<SYS_PWD>@<TARGET_TNS> \
  schemas=AR \
  remap_schema=AR:AR_NEW \
  remap_tablespace=APPS_TS_TX_DATA:USERS \
  directory=DATA_PUMP_DIR \
  dumpfile=SCHEMA_EXP_%U.dmp \
  logfile=schema_imp.log \
  parallel=4
```

10.4 Monitor Data Pump Jobs

```
-- Active data pump jobs
SELECT job_name, operation, job_mode,
       state, degree, attached_sessions
FROM   dba_datapump_jobs
WHERE  state <> 'NOT RUNNING';

-- Attach to running job
expdp attach=<JOB_NAME>
Export> status
Export> kill_job   -- to abort
```

11. OCI / Cloud DBA Essentials

11.1 OCI CLI — Common Commands

```
# Configure OCI CLI
oci setup config

# List DB Systems
oci db system list --compartment-id <OCID>

# Start / Stop DB System
oci db system launch --db-system-id <OCID>
oci db system terminate --db-system-id <OCID> --force

# Create manual backup
oci db backup create --db-system-id <OCID> --display-name 'Manual_Backup'

# List backups
oci db backup list --compartment-id <OCID>
```

11.2 OCI Security List — Ingress Rules

```
# Add ingress rule for port 8069 (ERPNext/Frappe)
oci network security-list update \
  --security-list-id <OCID> \
  --ingress-security-rules '[{
    "source":"0.0.0.0/0",
    "protocol":"6",
    "tcpOptions":{"destinationPortRange":{"min":8069,"max":8069}}
  }]'
```

11.3 OCI Block Volume — Expand Storage

```
# Resize volume in OCI Console, then:

# Rescan disk (Linux)
sudo dd iflag=direct if=/dev/oracleoci/oraclevdb of=/dev/null count=1
echo '1' | sudo tee /sys/class/block/sdb/device/rescan

# Grow partition
sudo growpart /dev/sdb 1

# Extend filesystem (ext4)
sudo resize2fs /dev/sdb1

# Verify
df -hT
```

11.4 SSH Key Setup on OCI Instance

```
# Generate key pair (on local machine)
ssh-keygen -t rsa -b 4096 -f ~/.ssh/oci_key

# Copy public key to instance
cat ~/.ssh/oci_key.pub
# Paste into: OCI Console > Instance > Edit > Add SSH Key
```

```
# Connect
ssh -i ~/.ssh/oci_key opc@<INSTANCE_PUBLIC_IP>

# Authorized_keys path on instance
~/.ssh/authorized_keys
```

11.5 EBS on OCI — Key Checks

```
# Check DB listener on OCI DB System
lsnrctl status LISTENER

# Verify EBS DB connection from App tier
tnsping EBSDB

# Check NFS mount (shared storage for EBS shared APPL_TOP)
mount | grep nfs
df -hT | grep nfs
```

12. Common DBA Utilities & Shortcuts

12.1 Gather Schema Statistics

```
-- Gather stats for schema (APPS)
BEGIN
  DBMS_STATS.GATHER_SCHEMA_STATS(
    ownname          => 'AR',
    estimate_percent => DBMS_STATS.AUTO_SAMPLE_SIZE,
    cascade          => TRUE,
    degree           => 4
  );
END;
/

-- Gather table stats
BEGIN
  DBMS_STATS.GATHER_TABLE_STATS(
    ownname => 'AR',
    tabname => 'AR_CUSTOMERS',
    cascade => TRUE
  );
END;
/
```

12.2 Compile Invalid Objects

```
-- Count invalid objects
SELECT owner, object_type, COUNT(*) cnt
FROM   dba_objects
WHERE  status = 'INVALID'
GROUP  BY owner, object_type
ORDER  BY owner, object_type;

-- Recompile all invalid objects
@$ORACLE_HOME/rdbms/admin/utlrp.sql
```

```
-- Or using adadmin:
adadmin   -- Choose: Compile/Reload Database Entities
```

12.3 Check DB Parameter

```
-- Single parameter
SHOW PARAMETER open_cursors;

-- All non-default params
SELECT name, value, description
FROM   v$parameter
WHERE  isdefault = 'FALSE'
ORDER  BY name;

-- Change parameter
ALTER SYSTEM SET open_cursors = 1000 SCOPE=BOTH;
ALTER SYSTEM SET undo_retention = 900 SCOPE=BOTH;
```

12.4 Useful One-Liners

```
-- DB version
SELECT banner FROM v$version;

-- Current DB time / timezone
SELECT SYSDATE, SYSTIMESTAMP, DBTIMEZONE FROM DUAL;

-- DB name and open mode
SELECT name, db_unique_name, open_mode, log_mode FROM v$database;

-- Alert log location
SELECT value FROM v$diag_info WHERE name='Diag Trace';

-- Session count by status
SELECT status, COUNT(*) FROM v$session GROUP BY status;

-- APPS schema password hash (for sync check)
SELECT name, password FROM fnd_user WHERE user_name='GUEST';
```

12.5 Autoconfig (EBS)

```
# Run Autoconfig on App Tier
cd $INST_TOP/admin/scripts
./adautocfg.sh apps/<APPS_PWD>

# Run Autoconfig on DB Tier
$ORACLE_HOME/appsutil/scripts/<SID>/adautocfg.sh
```

> **NOTE:** Always take a backup before running Autoconfig in production. It regenerates all config files from the context file — any manual config changes will be overwritten.

— End of Document —