

# Meta-learning how to forecast time series

Thiyanga S. Talagala  
Rob J Hyndman  
George Athanasopoulos

Monash University, Australia

# Large collections of time series



- Forecasting demand for thousands of products across multiple warehouses.

# Time series features

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

- Examples for time series features

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

- Examples for time series features
  - strength of trend

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

- Examples for time series features

- strength of trend
- strength of seasonality

## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

- Examples for time series features
  - strength of trend
  - strength of seasonality
  - lag-1 autocorrelation



## Objective

Develop a framework that automates the selection of the most appropriate forecasting model for a given time series by using an array of **features** computed from the time series.

- **Basic idea:**

Transform a given time series  $y = \{y_1, y_2, \dots, y_n\}$  to a feature vector  $F = (f_1(y), f_2(y), \dots, f_p(y))'$ .

- Examples for time series features

- strength of trend
- strength of seasonality
- lag-1 autocorrelation
- spectral entropy


# Feature-space of time series

## STL-decomposition


$$Y_t = T_t + S_t + R_t$$

- strength of trend:  $1 - \frac{\text{Var}(R_t)}{\text{Var}(Y_t - S_t)}$
- strength of seasonality:  $1 - \frac{\text{Var}(R_t)}{\text{Var}(Y_t - T_t)}$


**N0001**




**N0633**




**N0625**




**N0645**



**N1912**



**N2012**










# Feature-space of time series

## STL-decomposition

$$Y_t = T_t + S_t + R_t$$

- strength of trend:  $1 - \frac{\text{Var}(R_t)}{\text{Var}(Y_t - S_t)}$
- strength of seasonality:  $1 - \frac{\text{Var}(R_t)}{\text{Var}(Y_t - T_t)}$



# Time series features

- length
- strength of seasonality
- strength of trend
- linearity
- curvature
- spikiness
- stability
- lumpiness
- first ACF value of remainder series
- parameter estimates of Holt's linear trend method
- spectral entropy
- Hurst exponent
- nonlinearity
- parameter estimates of Holt-Winters' additive method
- unit root test statistics
- first ACF value of residual series of linear trend model
- ACF and PACF based features - calculated on both the raw and differenced series

**FFORMS:** Feature-based **FOR**ecast **M**odel **S**election


**Offline:** Classification algorithm is trained

**Online:** Use the classification algorithm to select appropriate forecast-models for new time series




**population**

# FFORMS: observed sample




# FFORMS: simulated time series







# FFORMS: reference set




# FFORMS: Meta-data




# FFORMS: Meta-data




# FFORMS: Meta-data




# FFORMS: Meta-data




# FFORMS: Meta-data



# FFORMS: Meta-data




# FFORMS: Random-forest classifier







# FFORMS: “online” part of the algorithm



# FFORMS: “online” part of the algorithm



# FFORMS: “online” part of the algorithm



# Application to M competition data

- Proposed algorithm is applied to yearly, quarterly and monthly series separately
- We run two experiments for each case.










|                  | Source | Experiment 1 |        |        | Source | Experiment 2 |         |        |
|------------------|--------|--------------|--------|--------|--------|--------------|---------|--------|
|                  |        | Y            | Q      | M      |        | Y            | Q       | M      |
| Observed series  | M1     | 181          | 203    | 617    | M3     | 645          | 756     | 1428   |
| Simulated series |        | 362000       | 406000 | 123400 |        | 1290000      | 1512000 | 285600 |
| New series       | M3     | 645          | 756    | 1428   | M1     | 181          | 203     | 617    |

# Experiment 1: Distribution of time series in the PCA space

observed - M1

simulated

new - M3




# Experiment 2: Distribution of time series in the PCA space

observed - M3


simulated

subset


new - M1



# Results: Yearly




# Results: Quarterly





# Results: Monthly



- FFORMS: framework for forecast-model selection using meta-learning based on time series features.

# Discussion and Conclusions

- FFORMS: framework for forecast-model selection using meta-learning based on time series features.
- FFORMS algorithm uses the knowledge of the past performance of candidate forecast models on a collection of time series in order to identify the best forecasting method for a new series.

- FFORMS: framework for forecast-model selection using meta-learning based on time series features.
- FFORMS algorithm uses the knowledge of the past performance of candidate forecast models on a collection of time series in order to identify the best forecasting method for a new series.
- For real-time forecasting, our framework involves only the calculation of features, the selection of a forecast method based on the FFORMS random forest classifier, and the calculation of the forecasts from the chosen model.

- FFORMS: framework for forecast-model selection using meta-learning based on time series features.
- FFORMS algorithm uses the knowledge of the past performance of candidate forecast models on a collection of time series in order to identify the best forecasting method for a new series.
- For real-time forecasting, our framework involves only the calculation of features, the selection of a forecast method based on the FFORMS random forest classifier, and the calculation of the forecasts from the chosen model.
- We have also introduced a simple set of time series features that are useful in identifying the "best" forecast method for a given time series.



available at: <https://github.com/thiyanngt/seer>

### Installation

```
devtools::install_github("thiyanngt/seer")  
library(seer)
```



available at: <https://github.com/thiyanagt/seer>

### Installation

```
devtools::install_github("thiyanagt/seer")  
library(seer)
```

Email: [thiyanga.talagala@monash.edu](mailto:thiyanga.talagala@monash.edu)