



MONASH
University

MONASH
BUSINESS
SCHOOL

Feature-based Time Series Forecasting

Thiyanga S. Talagala

13 March 2019

Joint work with

Introduction

Big picture of the problem


Time series features

- Transform a given time series $y = \{y_1, y_2, \dots, y_n\}$ to a feature vector $F = (f_1(y), f_2(y), \dots, f_p(y))'$.


Time series features

- Transform a given time series $y = \{y_1, y_2, \dots, y_n\}$ to a feature vector $F = (f_1(y), f_2(y), \dots, f_p(y))'$.


N0001




N0633




N0625




N0645



N1912




N2012




Time series features

- Transform a given time series $y = \{y_1, y_2, \dots, y_n\}$ to a feature vector $F = (f_1(y), f_2(y), \dots, f_p(y))'$.


N0001



N0633




N0625





N0645



N1912




N2012




Features used to select a forecasting model

- length
- strength of seasonality
- strength of trend
- linearity
- curvature
- spikiness
- stability
- lumpiness
- parameter estimates of Holt's linear trend method
- spectral entropy
- Hurst exponent
- nonlinearity
- parameter estimates of Holt-Winters' additive method
- unit root test statistics
- crossing points, flat spots
- peaks, troughs
- ACF and PACF based features - calculated on raw, differenced, and remainder series.
- ARCH/GARCH statistics and ACF of squared series and residuals.


Meta-learning



Meta-learning



Feature-based forecasting algorithms



FFORMS: Feature-based FOfecast Model Selection

Peeking inside FFORMS

Feature-based FOfRecast Model Averaging

Feature-based FOfRecast Model Performance Prediction

R packages

References