SRM Institute of Science and Technology
College of Engineering and Technology
School of Computing

DEPARTMENT OF COMPUTING TECHNOLOGIES
SRM Nagar, Kattankulathur – 603203, Chengalpattu District, Tamil Nadu
Academic Year: 2024-2025 (ODD)

Test: QUIZ 2& 3 **Date: 04/1 0 /2024**
Course Code & Title:21CSE203P -Advanced Programming Practices **Duration:**20 Minutes
Year & Sem: II year & III Sem SET :C **Max. Marks:** 10

S.No	Question	Answer

1.	Consider the following program and predict the output:
	
	class MyThread implements Runnable {
	public void run() {
	System.out.println(Thread.currentThread().getName());
	}
	}
	public class ThreadTest {
	public static void main(String arg[]) {
	Thread thread = new Thread(new MyThread());
	thread.run();
	thread.run();
	thread.start();
	}
	}
		main
		main
		Thread-0

2.	What is the significance of the Thread.yield() method in Java? A) It pauses the current thread permanently. B) It gives the processor a hint that the current thread is willing to yield its execution. C) It puts the current thread to sleep for a specified time. D) It kills the current thread immediately.	.option B
3.	Which of the following is the correct syntax for establishing a connection to a MySQL database in JDBC? A) Connection conn = DriverManager.getConnection("jdbc:mysql://localhost:3306/db_name"); B) Connection conn = DriverManager.connect("mysql://localhost/db_name"); C) Connection conn = new Connection("mysql:localhost/db_name"); D) Connection conn = DriverManager.connect("localhost", "db_name");	Option A

4.	What will be the output of the following code?
	import javax.swing.*;
	
	public class SwingExceptionApp {
	public static void main(String[] args) {
		When the button is clicked, the application will throw a RuntimeException, and the program will terminate with the message "An error occurred!"

	JFrame frame = new JFrame("Exception Example");
	JButton button = new JButton("Press Me");
	
	button.addActionListener(e -> {
	throw new RuntimeException("An error occurred!");
	});
	
	frame.add(button);
	frame.setSize(200, 200);
	
	frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
	frame.setVisible(true);
	}}	

5.	In the MVC architecture, what does the 'View' represent? A) The data structure of the application B) The user interface and presentation logic C) The interaction with the database D) The application logic	**Option B**
6.	What is the output of the following code snippet? list(map(lambda x: x * 2, [1, 2, 3, 4]))	[2, 4, 6, 8]
7.	numbers = [1, 2, 3, 4, 5] result = [x for x in numbers if x % 2 == 0 print(x)] What's wrong in the above code?	print(x) is used incorrectly inside the list comprehension. Separate the print() statement from the list comprehension. **Corrected Code:** result = [x for x in numbers if x % 2 == 0] for x in result: print(x)
8.	In Prolog, what is the result of the following query? ?- likes(john, pizza). A) The query is invalid B) It checks whether the fact "john likes pizza" is true C) It declares a fact that John likes pizza D) It returns the list of food items John likes	Option B
9	def add(a, b): return a + b result = add(3, 5) print(result) Is the function add is a pure function? Explain why?	Yes, the add function is a **pure function** because: • It always produces the same output for the same inputs (e.g., add(3, 5) always returns 8). • It has no side effects (does not modify any external state or variables).
10	from functools import reduce def multiply(x, y):	24

	return x * y numbers = [1, 2, 3, 4] result = reduce(multiply, numbers) print(result) What is the output of this code?	The reduce function applies the multiply function cumulatively to the numbers list, resulting in 1 * 2 * 3 * 4 = 24.