


## ▾ Lec 08B: RNN Network for Part of Speech (POS) Tagging

In practical, we shall learn how to construct an RNN Network for Part-of-Speech (POS) Tagging.

```
1 import torch
2 import torch.nn as nn
3 import torch.nn.functional as F
4 import torch.optim as optim
```

## ▾ Part-of-Speech Tagging

In this section, we will use an RNN to get part-of-speech tags.



- The input sentence is given by  $x^{<1>}, \dots, x^{<T>}$ , where  $x^{<t>} \in V_{in}$  where  $V_{in}$  is our vocab.
- The output sequence is given by  $y^{<1>}, \dots, y^{<T>}$ , where  $y^{<i>} \in V_{tag}$  where  $V_{tag}$  be our tag set, and  $y^{<t>}$  is the predicted tag of word  $x^{<t>}$ .
- The tag vocabulary is given by  $V_{tag} = ["DET", "NN", "V", "ADJ", "ADV"]$  where DET represents determiner (e.g., "the"), NN represents noun or pronouns (e.g., "dog" or "he"), V represents verb (e.g., "jumps"), ADJ represents adjective (e.g., friendly) and ADV represents adverb (e.g., "very").

## ▾ 2. Preprocessing

### ▾ Create the training set

We shall use only 11 sentences as our training data. For training, we use batch gradient descent (BGD) where we train with all samples in each batch.

```
1 raw_inputs = (
2     "the dog happily ate the big apple",
3     "the boy quickly drink the water",
4     "everybody read that good book quietly in the hall",
```

```

5     "she buys her book successfully in the bookstore",
6     "the old head master sternly scolded the naughty children for being very loud",
7     "i love you loads",
8     "he reads the book",
9     "she reluctantly wash the dishes",
10    "he kicks the ball",
11    "she is kind",
12    "he is naughty"
13 )
14
15 raw_targets = (
16     "DET NN ADV V DET ADJ NN",
17     "DET NN ADV V DET NN",
18     "NN V DET ADJ NN ADV PRP DET NN",
19     "PRN V ADJ NN ADV PRP DET NN",
20     "DET ADJ ADJ NN ADV V DET ADJ  NN PRP V ADJ NN",
21     "PRN V PRN ADV",
22     "PRN V DET NN",
23     "PRN ADV V DET NN",
24     "PRN V DET NN",
25     "PRN V ADJ",
26     "PRN V ADJ"
27 )

```

Add the padding to ensure all samples are of the same length

```

1 def add_padding(inputs, targets = None):
2
3     # compute the max length of all sentence in x
4     max_seqlen = max([len(sentence.split(' ')) for sentence in inputs])
5
6     # add padding to the inputs
7     padded_inputs = []
8     for input in inputs:
9         padded_inputs.append(input + ''.join([' PAD']* (max_seqlen - len(input.split(' '))))))
10
11    # add padding to the targets
12    padded_targets = []
13    if targets is not None:
14        for target in targets:
15            padded_targets.append(target + ''.join([' -']* (max_seqlen - len(target.split(' '))))))
16        return padded_inputs, padded_targets
17
18    return padded_inputs
19

```

```

1 train_feats, train_labels = add_padding(raw_inputs, raw_targets)

```

```

1 train_feats

```

```

['the dog happily ate the big apple PAD PAD PAD PAD PAD PAD',
 'the boy quickly drink the water PAD PAD PAD PAD PAD PAD PAD',
 'everybody read that good book quietly in the hall PAD PAD PAD PAD',

```

```
'she buys her book successfully in the bookstore PAD PAD PAD PAD PAD',
'the old head master sternly scolded the naughty children for being very loud',
'i love you loads PAD PAD PAD PAD PAD PAD PAD PAD PAD',
'he reads the book PAD PAD PAD PAD PAD PAD PAD PAD PAD',
'she reluctantly wash the dishes PAD PAD PAD PAD PAD PAD PAD PAD PAD',
'he kicks the ball PAD PAD PAD PAD PAD PAD PAD PAD PAD',
'she is kind PAD PAD PAD PAD PAD PAD PAD PAD PAD',
'he is naughty PAD PAD PAD PAD PAD PAD PAD PAD PAD']
```

```
1 train_labels
```

```
['DET NN ADV V DET ADJ NN - - - - -',
 'DET NN ADV V DET NN - - - - -',
 'NN V DET ADJ NN ADV PRP DET NN - - - - -',
 'PRN V ADJ NN ADV PRP DET NN - - - - -',
 'DET ADJ ADJ NN ADV V DET ADJ NN PRP V ADJ NN',
 'PRN V PRN ADV - - - - -',
 'PRN V DET NN - - - - -',
 'PRN ADV V DET NN - - - - -',
 'PRN V DET NN - - - - -',
 'PRN V ADJ - - - - -',
 'PRN V ADJ - - - - -']
```

## ▼ Create the vocabularies

Create a dictionary to map words into indices, and vice versa. We shall create 4 structures to do this:

1. `word_to_ix`: dictionary to map a word in an input sentence to its unique index
2. `ix_to_word`: dictionary to map an input index to its corresponding word
3. `ix_to_tag`: dictionary to map a tag (output label) to its unique index
4. `tag_to_ix`: dictionary to map a n output index to its corresponding tag

The following code gets all the words in `training_data` and assign a unique index to represent the word and store the mapping in the dictionary `word_to_ix`.

```
1 def get_vocab(sentences):
2     word_to_ix = {}
3     tag_to_ix = {}
4
5     for sentence in sentences:
6         for word in sentence.split():
7             if word not in word_to_ix and word != 'PAD': # word has not been assigned an index yet
8                 word_to_ix[word] = len(word_to_ix) # Assign each word with a unique
9     word_to_ix['PAD'] = len(word_to_ix)
10
11     return word_to_ix
```

```
1 word_to_ix = get_vocab(train_feats)
```

```
1 word_to_ix['happily']
```

Add the following additional words which does not exist in the training set to expand our vocabulary set. We may encounter them in the test set.

Now, let's create the `ix_to_word` which allows us to get back our sentence given a list of indices.

```
1 ix_to_word = {ix : word for word, ix in word_to_ix.items() }

1 ix_to_word[2]

    'happily'
```

Next, let's create `tag_to_ix` to map the tags to indices and `ix_to_tag` to map the indices back to the tags

```
1 tag_to_ix = {"DET": 0, "NN": 1, "V": 2, "ADJ": 3, "ADV": 4, "PRP": 5, "PRN": 6, "-": 7}

1 ix_to_tag = {ix : tag for tag, ix in tag_to_ix.items() }
```

## ▼ Converting a sentence to a list of indices

The function `encode_one_sentence` (`sentence`, `to_ix`)

- Receives a sentence (*string*) and converts all the words in the sentence into its corresponding index (integer).
- The output is a 1-D integer tensor
- For example:

*everybody read that good book quietly in the hall --> [6, 7, 8, 9, 10, 11, 12, 0, 13]*

The function `encode` (`sentences`, `to_ix`)

- receives a *list* of sentences
- outputs a *list* of 1-D integer tensor to represent sentences

```
1 def encode_one_sentence(seq, to_ix):
2     idxs = [to_ix[w] for w in seq.split()]
3     return torch.tensor(idxs, dtype=torch.long)
4
5 def encode(sentences, to_ix):
6     encoded = []
7     for sentence in sentences:
8         converted = encode_one_sentence(sentence, to_ix)
9         encoded.append(converted)
10    encoded = torch.stack(encoded)
11    return encoded
```

Create the input matrix `x` by converting the set of sentences into their index form

```
1 X = encode(train_feats, word_to_ix)
```

```
1 print("Number of samples in X:", len(X), '\n')
2 for i, (ori, x) in enumerate(zip(raw_inputs, X)):
3     print(f'Sentence {i}: "{ori}"')
4     print(f'    -> {x.detach().numpy()}')
```

Number of samples in X: 11

```
Sentence 0: "the dog happily ate the big apple"
-> [ 0  1  2  3  0  4  5 47 47 47 47 47 47]
Sentence 1: "the boy quickly drink the water"
-> [ 0  6  7  8  0  9 47 47 47 47 47 47 47]
Sentence 2: "everybody read that good book quietly in the hall"
-> [10 11 12 13 14 15 16  0 17 47 47 47 47]
Sentence 3: "she buys her book successfully in the bookstore"
-> [18 19 20 14 21 16  0 22 47 47 47 47 47]
Sentence 4: "the old head master sternly scolded the naughty children for being very loud"
-> [ 0 23 24 25 26 27  0 28 29 30 31 32 33]
Sentence 5: "i love you loads"
-> [34 35 36 37 47 47 47 47 47 47 47 47 47]
Sentence 6: "he reads the book"
-> [38 39  0 14 47 47 47 47 47 47 47 47 47]
Sentence 7: "she reluctantly wash the dishes"
-> [18 40 41  0 42 47 47 47 47 47 47 47 47]
Sentence 8: "he kicks the ball"
-> [38 43  0 44 47 47 47 47 47 47 47 47 47]
Sentence 9: "she is kind"
-> [18 45 46 47 47 47 47 47 47 47 47 47 47]
Sentence 10: "he is naughty"
-> [38 45 28 47 47 47 47 47 47 47 47 47 47]
```

Convert the output tags into their index form as well.

```
1 Y = encode(train_labels, tag_to_ix)
2 Y
```

```
tensor([[0, 1, 4, 2, 0, 3, 1, 7, 7, 7, 7, 7, 7],
        [0, 1, 4, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7],
        [1, 2, 0, 3, 1, 4, 5, 0, 1, 7, 7, 7, 7],
        [6, 2, 3, 1, 4, 5, 0, 1, 7, 7, 7, 7, 7],
        [0, 3, 3, 1, 4, 2, 0, 3, 1, 5, 2, 3, 1],
        [6, 2, 6, 4, 7, 7, 7, 7, 7, 7, 7, 7, 7],
        [6, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7, 7, 7],
        [6, 4, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7, 7],
        [6, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7, 7, 7],
        [6, 2, 3, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7],
        [6, 2, 3, 7, 7, 7, 7, 7, 7, 7, 7, 7, 7]])
```

```
1 for i, x in enumerate(Y):
2     print(f'Y{i}:')
3     print(f'    {list(x.numpy())}')
4     print(f'    -> {[ix_to_tag[i] for i in x.numpy()]}')

Y0:
```

```
[0, 1, 4, 2, 0, 3, 1, 7, 7, 7, 7, 7, 7]
```

```

-> ['DET', 'NN', 'ADV', 'V', 'DET', 'ADJ', 'NN', '-', '-', '-', '-', '-', '-']
Y1:
[0, 1, 4, 2, 0, 1, 7, 7, 7, 7, 7, 7]
-> ['DET', 'NN', 'ADV', 'V', 'DET', 'NN', '-', '-', '-', '-', '-', '-']
Y2:
[1, 2, 0, 3, 1, 4, 5, 0, 1, 7, 7, 7]
-> ['NN', 'V', 'DET', 'ADJ', 'NN', 'ADV', 'PRP', 'DET', 'NN', '-', '-', '-', '-']
Y3:
[6, 2, 3, 1, 4, 5, 0, 1, 7, 7, 7, 7]
-> ['PRN', 'V', 'ADJ', 'NN', 'ADV', 'PRP', 'DET', 'NN', '-', '-', '-', '-']
Y4:
[0, 3, 3, 1, 4, 2, 0, 3, 1, 5, 2, 3]
-> ['DET', 'ADJ', 'ADJ', 'NN', 'ADV', 'V', 'DET', 'ADJ', 'NN', 'PRP', 'V', 'ADJ', 'NN']
Y5:
[6, 2, 6, 4, 7, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'V', 'PRN', 'ADV', '-', '-', '-', '-', '-', '-', '-']
Y6:
[6, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'V', 'DET', 'NN', '-', '-', '-', '-', '-', '-', '-']
Y7:
[6, 4, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'ADV', 'V', 'DET', 'NN', '-', '-', '-', '-', '-', '-', '-']
Y8:
[6, 2, 0, 1, 7, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'V', 'DET', 'NN', '-', '-', '-', '-', '-', '-', '-']
Y9:
[6, 2, 3, 7, 7, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'V', 'ADJ', '-', '-', '-', '-', '-', '-', '-', '-']
Y10:
[6, 2, 3, 7, 7, 7, 7, 7, 7, 7, 7, 7]
-> ['PRN', 'V', 'ADJ', '-', '-', '-', '-', '-', '-', '-', '-']

```

--

### 3. Create the RNN Network

In this section, we create the following RNN network.

No	Layer	Configuration	Output shape
-	(Input)	-	(batch_size, seq_len)
1	Embedding	num_embedding = in_vocab_size (=48) embedding_size = 64	(batch_size, seq_len, embedding_size)
2	RNN	input_size = embedding_size hidden_size = 32 layer_num=1 batch_first= True	(batch_size, seq_len, hidden_size)
3	FC	in_features = rnn_hidden_size (=32) out_features = out_vocab_size (=8) activation = log_softmax	(batch_size, seq_len, out_vocab_size)

- **Input:**
  - Input is a tensor of shape (batch\_size, seq\_len) where each sample is a sequence of words of length seq\_len . Each sample is a list of integers and all samples have the same length.
- **Embedding Layer:**
  - Converts each word (an *integer*) into an embedding vector of length embedding\_size .

- The output of the layer has a shape of `(batch_size, seq_len, embedding_size)`.

- **RNN Layer:**

- `hidden_size` is the number of computational units
- The layer receives the input of shape `(batch_num, seq_len, embedding_size)` from the embedding layer.
- At each time step, the RNN outputs an output vector of length `hidden_size`. Hence, the output of the RNN layer has a shape `(batch_size, seq_len, hidden_size)`.

- **FC (Linear) Layer:**

- Outputs the tags, one for each time step.
- `out_vocab_size` is the number of possible tags (output classes)
- The [Linear](#) layer is able to process both multiple dimensional data (in our case, both the *batch* and *sequence*) simultaneously where the input is tensor of shape `(batch_size, *, in_features)` whereas the output is a tensor of shape `(batch_size, *, out_features)`
- The layer has *no* activation.

```
1 embedding_size = 64
2 rnn_hidden_size = 32
3 in_vocab_size = len(word_to_ix)
4 out_vocab_size = len(tag_to_ix)
```

```
1 class POSTagger(nn.Module):
2
3     def __init__(self, embedding_size, rnn_hidden_size, in_vocab_size, out_vocab_size):
4
5         super().__init__()
6
7         # embedding layer
8         self.word_embeddings = nn.Embedding(in_vocab_size, embedding_size)
9
10        # rnn layer
11        self.rnn = nn.RNN(embedding_size, rnn_hidden_size, batch_first=True)
12
13        # fc layer
14        self.fc = nn.Linear(rnn_hidden_size, out_vocab_size)
15
16    def forward(self, x):
17
18        # embedding layer
19        x = self.word_embeddings(x)
20
21        # rnn layer
22        x, _ = self.rnn(x)
23
24        # fc layer
25        x = self.fc(x)
26
27        return x
```

Create a POSTagger object.

```
1 model = POSTagger(embedding_size, rnn_hidden_size, in_vocab_size, out_vocab_size)
```

Display the model

```
1 print(model)

POSTagger(
  (word_embeddings): Embedding(48, 64)
  (rnn): RNN(64, 32, batch_first=True)
  (fc): Linear(in_features=32, out_features=8, bias=True)
)
```

## ▼ Train the model

### Define the loss function

We shall use the Cross Entropy cost function since this is a multi-class classification task.

```
1 loss_function = nn.CrossEntropyLoss()
```

Typically, the `CrossEntropyLoss` expects  $\hat{Y}$  to be of shape  $(batch\_size, output\_size)$  and  $Y$  to be of shape  $(batch\_size,)$ . However, the output of the RNN model  $\hat{Y}$  has a shape of  $(batch\_size, seq\_len, output\_size)$  and  $Y$  has a shape of  $(batch\_size, seq\_len)$ . To solve the problem, we collapse the *batch* and *time* dimensions as follows:

- $\hat{Y}$  from shape  $(batch\_size, seq\_len, output\_size) \rightarrow (batch\_size \times seq\_len, output\_size)^*$
- $Y$  from shape  $(batch\_size, seq\_len) \rightarrow (batch\_size \times seq\_len,)^*$

```
1 Yhat = model(X)
```

```
1 Yhat_resized = Yhat.view(-1, Yhat.size(-1))
2 Y_resized     = Y.view(-1)
```

```
1 loss_function(Yhat_resized, Y_resized)

tensor(2.1042, grad_fn=<NllLossBackward0>)
```

### Set the optimizer

```
1 optimizer = optim.SGD(model.parameters(), lr=0.5)
```

### Perform training



Prepare Y for training

```
1 Y = Y.view(-1)
```

Start training

```
1 print("Training Started")
2 num_epochs = 2000
3 for epoch in range(num_epochs):
4
5     # clear the gradients
6     model.zero_grad()
7
8     # Run the forward propagation
9     Yhat = model(X)
10
11    # Reshape Yhat
12    Yhat = Yhat.view(-1, Yhat.size(-1))
13
14    # compute loss
15    loss = loss_function(Yhat, Y)
16
17    # backpropagation
18    loss.backward()
19
20    # update network parameters
21    optimizer.step()
22
23    if (epoch+1) % 200 == 0 or epoch == 0 or epoch == num_epochs-1:
24        print(f'epoch: {epoch+1}: loss: {loss:.4f}')
```

```
Training Started
epoch: 1: loss: 2.1042
epoch: 200: loss: 0.0055
epoch: 400: loss: 0.0024
epoch: 600: loss: 0.0015
epoch: 800: loss: 0.0011
epoch: 1000: loss: 0.0008
epoch: 1200: loss: 0.0007
epoch: 1400: loss: 0.0006
epoch: 1600: loss: 0.0005
epoch: 1800: loss: 0.0004
epoch: 2000: loss: 0.0004
```

## ▼ Performing prediction

Now, let's perform prediction on the following new sentences.

```
1 X_test_raw = ["the boy read that good book in the hall",
2               "she reads the book",
```

```

3         "the boy scolded the dog",
4         "she happily kicks the ball"]

```

#### Pad data1

```

1 X_test_padded = add_padding(X_test_raw)
2 X_test_padded

['the boy read that good book in the hall',
'she reads the book PAD PAD PAD PAD PAD',
'the boy scolded the dog PAD PAD PAD PAD',
'she happily kicks the ball PAD PAD PAD PAD']

```

#### Encode data1

```

1 X_test = encode(X_test_padded, word_to_ix)
2 X_test

tensor([[ 0,  6, 11, 12, 13, 14, 16,  0, 17],
        [18, 39,  0, 14, 47, 47, 47, 47, 47],
        [ 0,  6, 27,  0,  1, 47, 47, 47, 47],
        [18,  2, 43,  0, 44, 47, 47, 47, 47]])

```

The function predict predicts the tags for the batch sample simultaneously.

```

1 def predict(X_test, ix_to_word, ix_to_tag):
2
3     with torch.no_grad():
4
5         # computes class score
6         yhat = model(X_test)
7
8         # get predicted labels
9         _, predicted = torch.max(yhat, -1)
10
11        # for each sample, convert the index back to word
12        for sentence, pred in zip(X_test, predicted):
13
14            print('input      | ', ''.join([f'{ix_to_word[i]:8}' for i in sentence.numpy()]))
15            print('predicted | ', ''.join([f'{ix_to_tag[i]:8}' for i in pred.numpy()]), '\n')

```

```

1 predict(X_test, ix_to_word, ix_to_tag)

```

```

input      | the   boy   read   that   good   book   in     the   hall
predicted | DET   NN    V      DET    ADJ    NN     PRP    DET   NN

input      | she   reads  the    book   PAD    PAD    PAD    PAD    PAD
predicted | PRN   V      DET    NN     -      -      -      -      -

input      | the   boy   scolded the   dog   PAD    PAD    PAD    PAD
predicted | DET   NN    NN     DET   NN     -      -      -      -

```

input		she	happily	kicks	the	ball	PAD	PAD	PAD	PAD
predicted		PRN	ADV	V	DET	NN	-	-	-	-

-- End of Lab8B --