

Data structure and algorithms lab

LINKED LIST

Lecturers : **Cao Tuan Dung**

**Dept of Software Engineering
Hanoi University of Science and
Technology**

Today's topics

- Introduction to Linked List
- Self referential structure in C
- Data structure "single linked LIST"
 - Implementation of single linked LIST
 - Algorithm for inserting, deleting, traversing, ...
- Data structure "double linked LIST"
 - Implementation of double linked LIST
 - Algorithm for inserting, deleting, traversing, ...

Towards Dynamic Data Structures


- ❑ Array is a collection of **homogeneous** elements which are stored at **consecutive** locations
- ❑ Main limitations of arrays:
 - It is a static data structure
 - Its size must be known at compilation time, in most programming languages
 - Inefficient insertion and deletion of elements
- ❑ A dynamic data structure can overcome these problems

What is a Dynamic Data Structure?

- ❑ A data structure that can shrink or grow during program execution
- ❑ The size of a dynamic data structure is not necessarily known at compilation time, in most programming languages
- ❑ Efficient insertion and deletion of elements
- ❑ The data in a dynamic data structure can be stored in non-contiguous (arbitrary) locations
- ❑ **Linked list** is an example of a dynamic data structure

What is a Linked List?


- ❑ A linked list is a collection of **nodes**, each node holding some **information** and a **pointer** to another node in the list
- ❑ In the following example, there are four nodes, which are not stored at consecutive locations



Self-Referential Structures


- One or more of its components is a pointer to itself.

```
struct list {
    char data;
    struct list *link;
};
list item1, item2, item3;
item1.data='a';
item2.data='b';
item3.data='c';
item1.link=item2.link=item3.link=NULL;
```



Implemetation of List in C

- "LIST" means data structure that keeps the information of the location of next element generally.
- The elements of "Single linked LIST" have only next location.
- In C, the pointer is used for the location of the next element.
- Array: We can access any data immediately.
- Linked List: We can change the number of data in it.



Question 3-1

- We are now designing "address list" for mobile phones.
- You must declare a record structure that can keep a name, a phone number, and a e-mail address at least.
- And you must make the program which can deals with any number of the data



Data structure implementation steps

- Data types definition of the data structure
 - for an INFO field, for a data structure item
- Global variable declaration
 - important pointers
- Functions implementation for useful operations on data structure
- Usage of Datastructure and functions in the program

9



Hint

- you can organize elements and data structure using following record structure **node_addr**. Define by your self a structure for storing information about an address.

```
typedef struct address_t {  
    char name[20];  
    char tel[11];  
    char email[25];  
} address;
```

10

Declaration of address list

```
typedef struct address_t {
    char name[20];
    char tel[11];
    char email[25];
} address;


struct list_el {
    address addr;
    struct list_el *next;
};
typedef struct list_el node_addr;
```

- "next" is the pointer variable which can express the next element; an element of node_addr.
- "addr" is instance of an address.

11

Important 3 factors of a LIST

- Root: It keeps the head of the list.
- NULL: The value of pointer. It means the tail of the list.
- Cur: Pointer variable that keeps the element just now.



12

Initialisation

```
node_addr *root, *cur;

/* in case you used prev */
node_addr* prev;
```

13

Make new node

```
node_addr* makeNewNode() {
    node_addr* new = (node_addr*)
        malloc(sizeof(node_addr));
    strcpy((new->addr).name, « Tran Van Thanh »);
    ...
    new->next = NULL;
    return new;
}

..
root = makeNewNode();
cur = root;
```

***allocate memory and
initialize one node but
do not add it to the list***

14

Attention

- You can modify the makeNewNode function to receive the data field as parameter:

```
node_addr* makeNewNode(address addr) {
    node_addr* new = (node_addr*)
    malloc(sizeof(node_addr));
    new->addr=addr;
    new->next =NULL;
    return new;
}
```

*allocate memory and
initialize one node but
do not add it to the list*

15

Input Data for Node

```
address readNode() {
    address tmp;
    printf("Nhap ten:");
    gets(tmp.name);
    ....
    return tmp;
}
```

16

Display node's information

- Write the function displaying the data inside a give node pointed by p.

```
void displayNode(node_addr* p){
/* display name, tel, email in columns */

}
```

17

Solution

```
void displayNode(node_addr* p){
if (p==NULL){printf("Loi con tro NULL\n");
return; }
address tmp = p->addr;
printf("%-20s\t%-15s\t%-30s %p\n", tmp.name,
tmp.tel, tmp.email, p->next);
}
void main(){
/* root = makeNewNode(); */
address tmp = readNode();
root = makeNewNode(tmp);
displayNode(root);
}
```

18

Exercise

- Create a singly linked list to store a list of phone address.
- Write a function to insert to a list a new element just after the current element and use it to add node to the list
- Write a function for traversing the list to print out all information stored.
- Write a function for the removal of a node in the list.

19

Insert node at head of the list

```
void insertAtHead(address addr){
    node_addr* new = makeNewNode(addr);
    new->next = root;
    root = new;
    cur = root;
}
```


```
void main(){
    address tmp = readNode();
    insertAtHead(tmp);
    displayNode(root);
}
```

20

Link list: insertion after the current position

- Pseudo code

```
create new_item
new->next = cur->next;
cur->next = new;
cur= cur->next;
```



21


insertion just after the current position

```
/* input of a address struct variable  addr */
...
new = makeNewNode(addr);
if (cur == NULL) return;
if ( root == NULL ) {
/* if there is no element */
root = new;
cur = root;
} else {
    new->next=cur->next;
    cur->next = new;
    /* prev=cur; */
    cur = cur->next;
}
...
}
```

22

Insertion before current position

- Another case: before the current position



23

insertBeforeCurrent

```
void insertBeforeCurrent(address e) {
    node_addr * new = makeNewNode(e);
    if ( root == NULL ) {
        /* if there is no element */
        root = new;
        cur = root;
        prev = NULL;
    } else {
        // Fill In the code here
        ....
    }
}
```

24


If you do not frequently update pointer prev

```
/* determine prev if cur does
not point to first element */
tmp = root;
while (tmp!=NULL && tmp->
next!=cur && cur !=NULL)
    tmp=tmp->next;
prev = tmp;
```

25


Traversing a list

```
void traversingList() {
    node_addr * p;
    for ( p = root; p!= NULL; p = p->next )
        displayNode(p);
}
```



Traversing a list

- Changing the value of pointer variable cur in sequence.
- These variables are called "iterator."
- The traversing is finished if the value is NULL



27

new test scenario


- Using a loop to input data to Linked List then display the whole list.

```
void main() {
    n=5;
    while (n){
        address tmp = readNode();
        insertAtHead(tmp);
        n--;
    }
    traversingList();
}
```

28

Deletion

- When we remove the first element
`root = del->next; free(del);`
- When we remove the first element, change the value of "root" into the value of "next" which is pointed by "del."



29

Delete first element

```
void deleteFirstElement() {
    /* do it your self */
}
```

30

Delete first element of the list


```
void deleteFirstElement() {
    node_addr* del = root;
    if (del == NULL) return;
    root = del->next;
    free(del);
    cur = root; /* prev = NULL; */
}
```

31

Deletion from the middle

- We want to remove the node pointed by cur
- Determine prev which point to the node just before the node to delete

```
prev->next = cur->next;
free(cur);
cur = prev->next;
```



32

Deletion from the middle

- Design and implement of deleteCurrentElement function

```
/* Do it your self
```

```
*/
```

33


Other useful function for deleting node

- Delete the first node corresponding to an address.
- void deleteElement(address adr);

34

Freeing a list


```
to_free = root ;
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



35

Freeing all nodes of a list

```
to_free = root ;
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```




36

Freeing all nodes of a list

```

to_free = root ;
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}

```




37

Freeing all nodes of a list

```

while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}


```



38

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



39

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



40

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



41

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



42

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



43

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



44

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



45

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



46

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



47

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



48

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



49

Freeing all nodes of a list


```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



50


Freeing all nodes of a list

```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```




Freeing all nodes of a list

```
while (to_free != NULL)
{
    root = root->next;
    free(to_free);
    to_free = root;
}
```



Reverse a list

- Write a function that reverse a list.



53

Solution

```
node_addr* list_reverse (node_addr* root)
{
    node_addr *cur, *prev;
    cur = prev = NULL;
    while (root != NULL) {
        cur = root;
        root = root->next;
        cur->next = prev;
        prev = cur;
    }
    return prev;
}
```

54



Exercise

- **Write a program that reads data from file phone.dat (created in previous assignment) and load them to a single linked list.**
- **You must use functions in your linked list library**
- **Display the contacts stored in list.**
- **Ask user to input more contacts and insert them to list in two ways:**
 - Insert at Head
 - or after current position of cur pointer.
- **Display the list again to verify.**

55



Exercise II

- Add to program in exercise I two functionalities: insert and delete element at given position.
 - You must use two functions in your library
- Implement a searching function by
 - Phone number
 - Name
- Test inverseList function.

56

Exercise III

- a) Write and test splitList function
 - Divide list in to 2 sub-lists.
 - Syntax split n1 n2: n1: start position (indexed from 0) – n2 number of element of sublist 1. The rest is the sublist 2
- b) Write a function that print the content of a list to a text file. Parameters are root pointer and file path. Use this function to view the sublists.
- c) Test data: Phone.dat

57

Homework

- **Make a improved version of PhoneDB Phone management program using linked list. Here is the functionalities in the menu:**
 - 1. Import from Text: read data from text file and build the list (using InsertAtHead)
 - 2. Import from Dat: read data from .dat file and build the list (using InsertAfterCurrentPos)
 - 3. Display List: Display all elements, each element in a line.
 - 4. Search phone by Model
 - 5. Search phone of which the price is under the value inputted.
 - 6. Export to Dat: store information in linked list to PhoneDB.dat
 - 7. Manual Insertion (Add data for a phone model). Program should ask the insertion mode: before or after current position.
 - 8. Quit

58



Homework

- **Continuing with the phone book management exercise, add the following functions that:**
 1. **delete the entire list**
 2. **insert an element before the Cur(rent) element**
 3. **Find an element in the list by phone number.**
 4. **Save the entire list elements in a text file (phonebook.txt) or binary file (phonebook.dat) based on the filetype parameter.**

59