

EEE: 103

Computer Programming

# L11: Structures in C



Prepared by: Sk Tahmed Salim Rafid

# The Problem: Storing Related Data

Let's say I want to store details of 10 students:

ID

Name

CGPA



## Solution 1: Multiple Variables

```
int s1id; char s1name[50]; float s1cgpa;  
int s2id; char s2name[50]; float s2cgpa;  
int s3id; char s3name[50]; float s3cgpa;  
// ... and so on for 10 students!
```

### Problems:

- ✗ Too many variables to manage
- ✗ Difficult to pass to functions
- ✗ Not scalable for large datasets

# The Problem: Storing Related Data

Let's say I want to store details of 10 students:

ID

Name

CGPA



## Solution 2: Separate Arrays

```
int studentID[10];  
char studentName[10][50];  
float studentCGPA[10];  
// Map 1-to-1: index 0 has data for student 1
```

### Problems:

- ✗ Data is scattered across arrays
- ✗ Hard to keep indices synchronized
- ✗ Passing to functions requires multiple arrays

# The Solution: Custom Data Structures

A struct (structure) is a user-defined data type that allows you to group different data types under a single name.

## Syntax 1 - Declare struct:

```
struct struct_name {  
    data_type var1;  
    data_type var2;  
};
```

✦ **Note:** To use struct, you must make an object of that struct

### Making Object - Method 1:

```
struct struct_name var_name = {data1, data2};
```

*// struct has 2 attributes*

### Making Object - Method 2:

```
struct struct_name var_name = {.var1 = data1, .var2 = data2};
```

*// Designated initialization*

## Syntax 2 - Anonymous Struct [Not Recommended]



This approach has limitations and is not recommended (Not reusable)

```
struct {  
  data_type var1;  
  data_type var2;  
} struct_var1, struct_var2;
```

**Explanation:** struct\_var1 and struct\_var2 are already 2 objects

**Initialize values to them:**

```
struct_var1.var1 = value;
```

*// Each attribute assigned individually*

# Syntax 3 - Using typedef [Recommended] ✓

Best practice for defining structures

```
typedef struct {  
    data_type var1;  
    data_type var2;  
} own_type_name; // own_type_name can be used like int now
```

## Method 1:

```
own_type_name var = {data1, data2};
```

## Method 2:

```
own_type_name var = {.var1 = data1, .var2 = data2};
```

## Printing:

```
printf("%specifier", var.var1);
```

## Input:

```
scanf("%specifier", &var.var1);
```

# Advanced Struct Operations

## Creating a Pointer to Struct:

```
own_type_name* var_name = &var;
```

## Accessing Data via Pointer:

```
var_name->var1
```

✦ **Note:** Needs & for scanf: `scanf("%d", &var_name->var1)`

## Making Array of Structs:

```
own_type_name var[2] = {  
    {data1, data2},  
    {data3, data4}}
```

# Complete Example: Student Structure

```
1  #include <stdio.h>
2  #include <string.h>
3
4  typedef struct {
5      int id;
6      char name[50];
7      float cgpa;
8  } Student;
9
10 int main() {
11     // Create and initialize
12     Student s1 = {101, "Alice", 3.85};
13
14     // Print details
15     printf("ID: %d\n", s1.id);
16     printf("Name: %s\n", s1.name);
17     printf("CGPA: %.2f\n", s1.cgpa);
18
19     return 0;
20 }
```

Step 1

Step 2

Step 3

Step 4

Step 5

## Output:

ID: 101

Name: Alice

CGPA: 3.85



# Example: Using Pointer to Struct

```
1  #include <stdio.h>
2
3  typedef struct {
4      int id;
5      char name[50];
6      float cgpa;
7  } Student;
8
9  int main() {
10     Student s1 = {101, "Alice", 3.85};
11     Student *ptr = &s1; // Pointer to struct
12
13     // Access using pointer
14     printf("ID: %d\n", ptr->id);
15     printf("Name: %s\n", ptr->name);
16     printf("CGPA: %.2f\n", ptr->cgpa);
17
18     return 0;
19 }
```

Step 1

Step 2

Step 3

Step 4

Step 5

## Syntax:

var.member

vs

ptr->member

## Example: Array of Structs

```
1  #include <stdio.h>
2
3  typedef struct {
4      int id;
5      char name[50];
6      float cgpa;
7  } Student;
8
9  int main() {
10     Student students[3] = {
11         {101, "Alice", 3.85},
12         {102, "Bob", 3.60},
13         {103, "Charlie", 3.92}
14     };
15
16     // Print all students
17     for (int i = 0; i < 3; i++) {
18         printf("Student %d: %s (%.2f)\n",
19             students[i].id,
20             students[i].name,
21             students[i].cgpa);
22     }
23
24     return 0;
```

### Output:

```
Student 101: Alice (3.85)
Student 102: Bob (3.60)
Student 103: Charlie (3.92)
```

# Practice Problems

1

## Simple Student Structure

Create a struct named student. The struct should be able to store student id, name and CGPA. Create one object of student and print all their details.

Basic

2

## Pointer to Struct

Modify task-1 in such a way that created student object is stored in a pointer and pointer is used to print the details.

Basic

3

## CGPA Calculator with Functions

Create a struct named student. The struct should store student id, name, number of 4 courses in an array and cgpa. CGPA will not be a user input. Create one object of this struct, take input from user for student id, name and 4 courses. Then using your custom function determine the GPA of each courses and then determine CGPA and store in the struct object.

Advanced

- Assume all courses are 3 credits
- Grading: 80+ → 4.0, 60+ → 3.0, 50+ → 2.0, otherwise → 0.0
- CGPA = Average of all course GPAs

# Key Takeaways

---

- ✓ Structures group related data together
- ✓ Use typedef for cleaner syntax
- ✓ Access members using dot (.) operator
- ✓ Access via pointer using arrow (->) operator
- ✓ Can create arrays of structures
- ✓ Structures can be passed to functions
- ✓ Essential for organizing complex data

# Thank You

Structure Your Code, Structure Your Thinking! 🎯