

RailsOnLisp

Thomas de Grivel <thoxdg@gmail.com>

<http://kmx.io>

10 octobre 2019

Intro

Common Lisp

Common Lisp is the programmable programming language.

Common Lisp

Standardisé en 1994 par l'ANSI

<http://www.lispworks.com/documentation/HyperSpec/Front/>

Common Lisp

De nombreux compilateurs respectant le standard ANSI existent :

- SBCL (open-source, x86, amd64, Windows, Linux, OSX, *BSD)
- ABCL (open-source, jvm)
- Clozure CL (open-source, x86, amd64, Windows, Linux, OSX, FreeBSD)
- ECL (open-source, compiles to C)
- LispWorks (proprietary, x86, amd64, Windows, Linux, OSX, FreeBSD)
- Allegro CL (proprietary, x86, amd64, sparc, Windows, Linux, OSX, FreeBSD)

Common Lisp

Lisp essays by Paul Graham
<http://www.paulgraham.com/lisp.html>

Setup

Installer SBCL

Ubuntu :

```
sudo apt-get install sbcl
```

MacOS X :

```
brew install sbcl
```


Installer repo

```
mkdir -p ~/common-lisp/thodg  
cd ~/common-lisp/thodg  
git clone https://github.com/thodg/repo.git  
cd ~/common-lisp  
ln -s thodg/repo/repo.manifest
```

Configurer SBCL

Éditer ~/.sbclrc

```
;; ASDF
(require :asdf)

;; repo
(load "~/common-lisp/thodg/repo/repo")
(repo:boot)
```

Lancer SBCL

```
$ sbcl
```

This is SBCL 1.5.3, an implementation of ANSI Common Lisp.

More information about SBCL is available at <http://www.sbcl.org/>.

SBCL is free software, provided as is, with absolutely no warranty. It is mostly in the public domain; some portions are provided under BSD-style licenses. See the CREDITS and COPYING files in the distribution for more information.

```
* _
```

Installer Slime

```
* (repo:install :slime)
```

```
$ /usr/bin/git -C /home/dx/common-lisp/slime clone https://github.com/slime/slime  
Cloning into 'slime'...
```

Configurer emacs

Éditer ~/.emacs

```
;; Common Lisp
(add-to-list 'load-path "~/common-lisp/slime/slime/")
(require 'slime-autoloads)
(add-to-list 'slime-contribs 'slime-fancy)
(setq inferior-lisp-program
  "sbcl")
(setq slime-net-coding-system
  'utf-8-unix)
```

Lancer emacs et slime

```
$ emacs
```

```
M-x slime
```

```
CL-USER> _
```

Common Lisp

La REPL

REPL : read, eval, print loop

```
(loop
  ;; setup REPL vars
  ;; handle errors, interactive debugger
  (print
    (eval
      (read))))
(force-output)) ;; flush output buffers
```


Les symboles

Un symbole est plus rapide à comparer qu'une chaîne de caractères (comparaison de pointeurs). Pour récupérer un symbole à travers `eval` il faut le quoter en le préfixant d'une apostrophe.

```
;; SLIME
```

```
CL-USER> 'hello-world
```

```
HELLO WORLD
```

```
CL-USER> (quote hello-world) ; equivalent sans syntaxe
```

```
HELLO WORLD
```

Les symboles

Si on ne quote pas le symbole on tombe dans le debugger interactif.

```
;; SLIME  
CL-USER> hello-world
```

The variable HELLO-WORLD is unbound.
[Condition of type UNBOUND-VARIABLE]

Restarts:

- 0: [CONTINUE] Retry using HELLO-WORLD.
- 1: [USE-VALUE] Use specified value.
- 2: [STORE-VALUE] Set specified value and use it.
- 3: [RETRY] Retry SLIME REPL evaluation request.
- 4: [*ABORT] Return to SLIME's top level.
- 5: [ABORT] abort thread (#<THREAD "repl-thread" RUNNING {1003B91BC3}>)

Backtrace:

- 0: (SB-INT:SIMPLE-EVAL-IN-LEXENV HELLO-WORLD #<NULL-LEXENV>)
 - 1: (EVAL HELLO-WORLD)
- more--

4

```
; Evaluation aborted on #<UNBOUND-VARIABLE HELLO-WORLD {1004AF3523}>.  
CL-USER>
```

Les fonctions

Pour définir une fonction on utilise `defun`. Si le premier élément d'une liste (entre parenthèses) est une fonction ou un symbole nommant une fonction alors c'est un appel de fonction.

```
;; SLIME
CL-USER> (defun hello-world ()
           (format t "Hello world !"))
HELLO-WORLD
CL-USER> (hello-world)
Hello world !
NIL
CL-USER> _
```

Lambda

Une fonction anonyme est introduite par `lambda`. On peut affecter une fonction anonyme à un symbole, reproduisant l'effet de `defun`.

```
;; SLIME  
CL-USER> (setf (symbol-function 'hello-world)  
               (lambda ()  
                 (format t "Hello world !"))))
```

```
CL-USER> (hello-world)  
Hello world !  
NIL  
CL-USER> _
```

Les fonctions d'ordre supérieur

Une fonction est une valeur comme une autre et peut être passée en paramètre d'une autre fonction. On appelle ces fonctions les fonctions d'ordre supérieur.

```
;; SLIME
CL-USER> (mapcar (lambda (x) (* x x)) '(1 2 3 4 5))
(1 4 9 16 25)
CL-USER> (reduce #'(1 2 3 4 5))
15
CL-USER> (reduce (function +) '(1 2 3 4 5))
15
CL-USER> (reduce '+ '(1 2 3 4 5))
15
CL-USER> _
```

Les macros

Les paramètres d'une macro ne sont pas évalués. Cela permet de faire des DSL et de la meta-programmation. Une macro génère du code qui est à son tour évalué.

```
;; SLIME
CL-USER> (defmacro hello (arg)
           `(format nil "Hello ~A !"
                    (string-capitalize ',arg)))

HELLO
CL-USER> (hello world)
"Hello World !"
CL-USER> _
```

RailsOnLisp

Installer RailsOnLisp

```
$ mkdir ~/common-lisp/RailsOnLisp
$ cd ~/common-lisp/RailsOnLisp
$ git clone https://github.com/RailsOnLisp/rol.git
Cloning into 'rol' ...
```

```
$ sh rol/bin/rol-install
Cloning into 'rol-assets' ...
```

```
$ cd rol && ls -l
lrwxrwxrwx 1 dx dx   13 oct.   9 17:52 assets -> ../rol-assets
drwxr-xr-x 2 dx dx 4096 oct.  10 10:44 bin
lrwxrwxrwx 1 dx dx   12 oct.   9 17:52 files -> ../rol-files
lrwxrwxrwx 1 dx dx   10 oct.   9 17:52 log -> ../rol-log
lrwxrwxrwx 1 dx dx   13 oct.   9 17:52 server -> ../rol-server
lrwxrwxrwx 1 dx dx   15 oct.   9 17:52 template -> ../rol-template
lrwxrwxrwx 1 dx dx   10 oct.   9 17:52 uri -> ../rol-uri

$ _
```