

Lab 7 Machine Learning 1

Thoi Tran (A17035545)

Today we are going to learn how to apply different machine learning methods beginning with clustering:

The goal here is to find group/clusters in your input data.


First I will make up some data with clear groups. For this I will use the `rnorm()` function.

```
rnorm(10)
```


```
[1] 0.04029517 -1.13658746 0.91907931 0.26975839 -1.72068771 -1.58037588  
[7] 1.27724954 0.77822301 0.85095336 0.83982910
```

```
hist(rnorm(10000, mean = 3))
```

Histogram of `rnorm(10000, mean = 3)`



```
x1 <- c(rnorm(10000, mean = 3),
        rnorm(10000, mean = -3))
hist(x1)
```



```
x <- c(rnorm(30, mean = 3),
        rnorm(30, mean = -3))
x
```

```
[1]  2.3768350  2.9973342  2.1842681  1.6847966  3.1513466  2.4196309
[7]  2.7152919  4.3935185  1.7428376  3.0174235  1.5159110  3.2200436
[13]  2.8960347  2.3559274  3.9095316  4.5949817  3.6737325  2.7482953
[19]  2.0404963  1.2657200  3.0884499  3.4294076  3.1764566  2.1219954
[25]  5.3136093  2.6428071  0.8516846  1.4160197  2.7002378  4.0210024
[31] -3.2208292 -4.3039351 -2.5446458 -1.9835657 -4.3624589 -3.2270507
[37] -2.1402619 -2.7537926 -1.7354415 -3.3719119 -2.1478115 -2.3539349
[43] -3.0914865 -3.2919338 -2.9899810 -3.4128246 -1.8160872 -3.5548561
[49] -3.6686480 -3.6754627 -4.8060391 -3.6178336 -3.1185065 -3.0816384
[55] -2.4309373 -2.6788785 -2.4847508 -3.7484769 -3.8243966 -2.8259836
```

```
y <- rev(x)
y
```


```
[1] -2.8259836 -3.8243966 -3.7484769 -2.4847508 -2.6788785 -2.4309373
[7] -3.0816384 -3.1185065 -3.6178336 -4.8060391 -3.6754627 -3.6686480
```

```
[13] -3.5548561 -1.8160872 -3.4128246 -2.9899810 -3.2919338 -3.0914865
[19] -2.3539349 -2.1478115 -3.3719119 -1.7354415 -2.7537926 -2.1402619
[25] -3.2270507 -4.3624589 -1.9835657 -2.5446458 -4.3039351 -3.2208292
[31]  4.0210024  2.7002378  1.4160197  0.8516846  2.6428071  5.3136093
[37]  2.1219954  3.1764566  3.4294076  3.0884499  1.2657200  2.0404963
[43]  2.7482953  3.6737325  4.5949817  3.9095316  2.3559274  2.8960347
[49]  3.2200436  1.5159110  3.0174235  1.7428376  4.3935185  2.7152919
[55]  2.4196309  3.1513466  1.6847966  2.1842681  2.9973342  2.3768350
```

```
z <- cbind(x, y)
head(z)
```

```
      x      y
[1,] 2.376835 -2.825984
[2,] 2.997334 -3.824397
[3,] 2.184268 -3.748477
[4,] 1.684797 -2.484751
[5,] 3.151347 -2.678878
[6,] 2.419631 -2.430937
```

```
plot(z)
```



K_means Clustering

Use `kmeans()` function setting `k` to 2 and `nstart = 10`

Inspect/print the results

Q. How many points are in each cluster?

```
km <- kmeans(z, centers = 2)
km
```

K-means clustering with 2 clusters of sizes 30, 30

Cluster means:

	x	y
1	2.788854	-3.075479
2	-3.075479	2.788854

Clustering vector:

[illegible]

Within cluster sum of squares by cluster:

```
[1] 47.5451 47.5451
(between_SS / total_SS = 91.6 %)
```

Available components:

```
[1] "cluster"      "centers"      "totss"        "withinss"     "tot.withinss"
[6] "betweenss"    "size"         "iter"         "ifault"
```

Results in kmeans object km.

```
attributes(km)
```

```
$names
[1] "cluster"      "centers"      "totss"        "withinss"     "tot.withinss"
[6] "betweenss"    "size"         "iter"         "ifault"
```

```
$class
```

```
[1] "kmeans"
```

Q. What component of your result object details? - Cluster size? - Cluster assignment/membership? - Cluster center?

Cluster size?

```
km$size
```

[1] 30 30

Cluster assignment/membership?

```
km$cluster
```

[illegible]

Cluster center?


```
km$centers
```

	x	y
1	2.788854	-3.075479
2	-3.075479	2.788854


Q. Plot z colored by the kmeans cluster assignment and add cluster centers as blue points.

R will recycle shorter color vectore to be the same length as the longer (number of data points) in z.

```
plot(z, col = c("red", "blue"))
```




```
plot(z, col = km$cluster)
```



We can use the `points()` function to add new points to an existing plot, like the cluster centers.


```
plot(z, col = km$cluster)
points(km$centers, col = "blue", pch = 15, cex = 3)
```



Q. Can you run `kmeans` and ask for 4 clusters and plot the results?

```
km_1 <- kmeans(z, centers = 4)
```

```
plot(z, col = km_1$cluster)
points(km_1$centers, col = "purple", pch = 15)
```



Hierarchical Clustering

Let's take our same data `z` and see how `hclust` works.

First we need a distance matrix of our data to be clustered

```
d <- dist(z)
hc <- hclust(d)
hc
```


Call:

```
hclust(d = d)
```

```
Cluster method : complete
Distance       : euclidean
Number of objects: 60
```

```
plot(hc)
abline(h = 8, col = "red")
```

Cluster Dendrogram




I can get my cluster membership vector by “cutting the tree” with the `cutree()` function.

```
grps <- cutree(hc, h = 8)
grps
```

```
[1] 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 2 2 2 2 2 2 2 2
[39] 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
```

Q. Can you plot `z` colored by our `hclust` results?

```
plot(z, col = grps)
```




PCA of UK food Data

Read data from the UK on food consumption in different parts of the UK.


```
url <- "https://tinyurl.com/UK-foods"
x <- read.csv(url, row.names = 1)
head(x)
```

	England	Wales	Scotland	N.Ireland
Cheese	105	103	103	66
Carcass_meat	245	227	242	267
Other_meat	685	803	750	586
Fish	147	160	122	93
Fats_and_oils	193	235	184	209
Sugars	156	175	147	139

```
barplot(as.matrix(x), beside=T, col=rainbow(nrow(x)))
```




```
barplot(as.matrix(x), beside=F, col=rainbow(nrow(x)))
```



A so-called “Pairs” plot can be usefull for small datasets like this.

```
pairs(x, col=rainbow(10), pch=16)
```



It’s hard to see structure and trends in even this small dataset. How will we ever do this when we have big datasets with 1,000s or 10s of thousands of things we are measuring.

PCA to the rescue

Let’s see how PCA deals with this dataset. So the main funciton in base R to do PCA is called `prcomp()`.

```
pca <- prcomp(t(x))
summary(pca)
```

Importance of components:

	PC1	PC2	PC3	PC4
Standard deviation	324.1502	212.7478	73.87622	3.176e-14
Proportion of Variance	0.6744	0.2905	0.03503	0.000e+00
Cumulative Proportion	0.6744	0.9650	1.00000	1.000e+00

Let's see what is inside this `pca` object that we created from running `prcomp()`.

```
attributes(pca)
```


```
$names
[1] "sdev"      "rotation" "center"    "scale"     "x"

$class
[1] "prcomp"
```

```
pca$x
```

	PC1	PC2	PC3	PC4
England	-144.99315	-2.532999	105.768945	-4.894696e-14
Wales	-240.52915	-224.646925	-56.475555	5.700024e-13
Scotland	-91.86934	286.081786	-44.415495	-7.460785e-13
N.Ireland	477.39164	-58.901862	-4.877895	2.321303e-13

```
plot(pca$x[,1],pca$x[,2], col = c("black", "red", "blue", "darkgreen"),
     pch = 16, xlab = "PC1 (67.4%)", ylab = "PC2 (29.0%)",
     text(pca$x[,1], pca$x[,2], colnames(x), col = c("black", "red", "blue", "darkgreen")))
```



Digging deeper (variable loadings)

```
par(mar=c(10, 3, 0.35, 0))  
barplot( pca$rotation[,1], las=2 )
```

