

# Surface-EMG Processing & Classification for Muscle Interfaces

University of Southern Denmark

Supervisors:

Poramate Manoonpong (poma@mmmi.sdu.dk)

Xiaofeng Xiong (xizi@mmmi.sdu.dk)

Date:

# 1 Abstract

Hello, this is my abstract...

## 2 Acknowledgements

Hello, here is some text without a meaning...

## Glossary

**Congenital** A disease or physical abnormality present from birth. 6

**sEMG** surface-electromyography. 7

**traumatic** A disease or physical abnormality due to trauma. 6

# Contents

<b>1</b>	<b>Abstract</b>	<b>2</b>
<b>2</b>	<b>Acknowledgements</b>	<b>3</b>
<b>3</b>	<b>Introduction</b>	<b>6</b>
<b>4</b>	<b>Problem Specification</b>	<b>7</b>
4.1	Motivation . . . . .	7
<b>5</b>	<b>Literature Review</b>	<b>9</b>
<b>6</b>	<b>Methodology</b>	<b>10</b>
6.1	Design . . . . .	10
6.1.1	Anatomy . . . . .	10
6.1.2	Simulated Hand Articulation design . . . . .	10
6.1.3	Sensor Locations etc. . . . .	10
6.2	Dataset Creation . . . . .	10
6.2.1	Brief of used Software . . . . .	10
6.2.2	Trial/motion overview . . . . .	10
6.3	Implementation . . . . .	10
6.3.1	Data Pre-Processing . . . . .	10
6.3.2	Network Design . . . . .	10
6.3.3	Software Hand Design . . . . .	10
<b>7</b>	<b>Tests &amp; Results</b>	<b>11</b>
<b>8</b>	<b>Discussion</b>	<b>12</b>
<b>9</b>	<b>Conclusion</b>	<b>13</b>
9.1	Perspectivation . . . . .	13
<b>10</b>	<b>References</b>	<b>15</b>

### 3 Introduction

The human hand is one of the most important factors of the human identity. The hand allows a person to perform complex muscolatory combinations to interact with the surrounding world, express complex emotions during speech, and aid in defining a person's individuality and personalty [?]. The hands are controlled by a complex combination on precise muscles designed to perform gentle, precise control of the fingers. This allows a person to grasp objects in many different ways, perform complex tasks such as writing, playing musical instruments, or even constructing a house. The hand also acts like a sensory device allowing us to perform precise observations through feeling and touch. This allows a person to understand the environment without seeing it, the hand is able to sensor heat/cold, create complex understanding of geometries and texture through touch and manipulation.

Missing limbs, either Congential or traumatic amputation severely reduces a person's ability to interact with- / understand the world, express themselves and perform simple day-to-day tasks. In order to alleviate some of the drawbacks of missing a limb, amputees are often able to aquire a prosthetic replacement of their lost limb. The aquired prosthetic tries to imitate the movements of the lost limb, through muscle-activated interfaces, that is then used to control the movements of the prosthetic. In the case of hand prosthetics, the prosthetic allows the user to perform simple, day-to-day tasks, and is able to alleviate some of the stress caused to the non-amputated hand through overusage. This thesis aims to summarize, and elaborate on current state-of-the-art research and products in the field of prostetics devices, and products the control of prosthetics and the existing limitations of these state-of-the-art products.

This thesis aims to contribute to the world of prosthetics control, by researching effective methods of collecting sensory data from the lower-/upper-arm, and by doing so, creating an state-of-the-art Artificial Intelligence (AI) based controller, that is able to imitate the intent and movements or a real hand. And by doing so, by improving sEMG controller design to increase functionality and the controllable DoF of the prosthetic, to provide a more true-to-life experience to the prosthetics user, and thus reduce the amount of patients that disregard prosthetics.

This thesis also aims to explore efficient methods of designing a network to identify lower-/upper-arm muscolatory intent, with the purpose of controlling a simulated prosthetics device, and by doing so, increase the controllable Degree-of-Freedom for the prostetics user.

## 4 Problem Specification

There is a large need for new technology that improves the effectiveness and ergonomics of human hand prosthetics.

Current state-of-the-art products on the market exhibits a severe reduction of controllable Degree of Freedom (Dof) compared to their biological counterparts. These products often rely on simple, grasp control based on 2 or more surface-electromyography (sEMG) interfaces, to classify “open/close” signals for the control scheme. The prosthetics user is then manually required to change grip control-scheme, creating very crude control dynamics that is very different from biological hand-control. A in-depth explanation of “open/close” control can be seen in section ?? This is a great pitfall in the field of Research and Creation of prosthetics, as unsatisfactory function of prosthetics lead to amputees, that exhibit a great deal of stress during the rehabilitation process.

This can cause the patient to repel the rehabilitation process and the prosthetic all-together. The repelling of the prosthetic increase in the cases of the most severe cases of amputation, where the largest amount of control muscles are lost. These amputations are often located further up the limbs, where the loss of mobility and controllability are greatest. The amount of muscles leftover from amputation also dictates the type of prosthetic a patient is able to receive. Patients of lower-arm amputation has less control over their prosthetic than patients of hand amputation, due to the loss of the muscles in the lower-arm. The loss of control increases as the amputation severity increases, and this is a problem in prosthetics design because it is impossible to create a standardized controller that suits most patient’s needs.

State-of-the-art commercial prosthetics further decrease the controllable DoF in order to increase robustness of the control experience, this is further elaborated upon in ??.

### 4.1 Motivation

The main goal of this thesis is to provide a meaningful contribution to the world of prosthetics design and control. In order to confine the workload done in this thesis, a set of development goals has been made:

1. Create a software-based, biology-inspired, anatomically realistic simulation of a humanoid lower-arm/hand that is able to imitate the movements of the humanoid limb.
2. Make the prosthetics simulation controllable from a widely-used robotics-software.
3. Design a sEMG muscle pre-processing pipeline for a prosthetics controller.
4. Design a state-of-the-art prosthetics controller based on AI, to control a simulated prosthetics device.
5. Create a custom dataset to train AI based controllers for prosthetics.

6. Test and Validate the created prosthetics controller against state-of-the-art methods.



## 5 Literature Rewiew

Hello, here is some text without a meaning...

## **6 Methodology**

Hello, here is some text without a meaning...

### **6.1 Design**

#### **6.1.1 Anatomy**

#### **6.1.2 Simulated Hand Articulation design**

#### **6.1.3 Sensor Locations etc.**

### **6.2 Dataset Creation**

#### **6.2.1 Brief of used Software**

#### **6.2.2 Trial/motion overview**

### **6.3 Implementation**

#### **6.3.1 Data Pre-Processing**

#### **6.3.2 Network Design**

#### **6.3.3 Software Hand Design**

## 7 Tests & Results

Hello, here is some text without a meaning...

## 8 Discussion

Hello, here is some text without a meaning...

## 9 Conclusion

Hello, here is some text without a meaning...

### 9.1 Perspectivation

## List of Figures

## List of Tables

## 10 References