Cellogent Backend — API Reference

For frontend implementation. Base URL: {{BASE_URL}}/api

Excluded from this doc (already known / separate): authentication, profile, API keys, sender IDs, contacts & contact groups (client + admin).

Generated from routes/api.php · 2026-11-12

1. Conventions

Auth headers

```
Client:  Authorization: Bearer {client_access_token}
Admin:   Authorization: Bearer {admin_access_token}
Accept:  application/json
Content-Type: application/json   (or multipart/form-data when uploading files)
```

Standard response envelope

```
{
  "in_error": false,
  "status_code": "200",
  "message": "…",
  "reason": "success",
  "data": { … },
  "point_in_time": "YYYY-MM-DD HH:mm:ss"
}
```

Validation errors: in_error=true, status_code=422, data = { field: ["message"] }.

Pagination

List endpoints accept ?page=&per_page=. Successful lists use a paginated envelope:

```
{
  …envelope,
  "data": [ /* items */ ],
  "meta": {
    "current_page": 1,
    "per_page": 15,
    "total": 42,
    "last_page": 3
  }
}
```

2. Public (no login)

GET /client/plans

Auth	None
Notes	Public plan catalogue for signup / subscribe UI.

Response data (inside standard envelope)

```
{
  "plans": [
    {
      "id": 1,
      "name": "Starter",
      "status": "active",
      "is_featured": true,
      "details": [
        {
          "months": 1,
          "units": 1000,
          "price": 50
        },
        {
          "months": 0,
          "units": 5000,
          "price": 200
        }
      ]
    }
  ]
}
```

GET /public/surveys/{token}

Auth	None
Notes	Respondent view. token = survey.public_token.

Response data (inside standard envelope)

```
{
  "name": "Customer feedback",
  "intro": "Thanks for taking a minute…",
  "status": "active",
  "accepting_responses": true,
  "questions": [
    {
      "id": 1,
      "prompt": "How was service?",
      "type": "rating",
      "options": null,
      "required": true,
      "position": 0
    }
  ],
  "reward": {
    "name": "YELLO 1GB Data",
    "type": "data",
    "size": "1GB",
    "amount": 4.2,
    "network": "YELLO",
    "currency": "GHS"
  }
}
```

POST /public/surveys/{token}/click

Auth	None

Request body

```
{
  "phone_number": "0244123456"
}
```

Response data (inside standard envelope)

```
{
  "tracked": true
}
```

POST /public/surveys/{token}/submit

Auth	None

Request body

```
{
  "phone_number": "0244123456",
  "answers": {
    "1": "5",
    "2": "Great service"
  }
}
```

Response data (inside standard envelope)

```
{
  "submitted": true,
  "reward_status": "queued|skipped|ineligible",
  "message": "optional note if YELLO data reward needs verified beneficiary"
}
```

POST /public/campaigns/{campaign}/click

Auth	None

Request body

```
{
  "phone_number": "0244123456"
}
```

Response data (inside standard envelope)

```
{
```

```
  "tracked": true
}
```

3. Client APIs

All routes below: prefix /api/client · middleware auth:client + account.active

3.1 Activity logs

GET /client/activity-logs

Auth	Bearer client

Query / path params

```
?page=&per_page=
```

Response data (inside standard envelope)

```
[{ id, action, subject_type, event, meta, created_at }]
```

3.2 Wallet

GET /client/wallet

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 1,
  "client_id": 9,
  "status": "active",
  "balance": 500,
  "reserved": 80,
  "available": 420,
  "currency": "GHS",
  "client": {
    "id": 9,
    "first_name": "Ama",
    "last_name": "Mensah",
    "email": "ama@example.com"
  }
}
```

GET /client/wallet/top-ups

Auth	Bearer client

Query / path params

```
?page=&per_page=&status=
```

Response data (inside standard envelope)

```
[{ id, amount, method, status, payment_id, created_at }]
```

POST /client/wallet/top-ups

Auth	Bearer client

Request body

```
{
  "amount": 100,
  "method": "momo",
  "phone_number": "0244123456",
  "network": "MTN"
}
```

Response data (inside standard envelope)

```
{
  "top_up": {
    "id": 1,
    "amount": 100,
    "status": "pending"
  },
  "payment": {
    "id": 55,
```

```
    "reference_id": "…",
    "status": "pending",
    "payment_link": "https://…",
    "amount": 100,
    "charge": 0,
    "total_amount": 100
  }
}
```

GET /client/wallet/transactions

Auth	Bearer client

Query / path params

```
?page=&per_page=&type=
```

Response data (inside standard envelope)

```
[{ id, type, amount, balance_after, description, created_at }]
```

3.3 Subscription

GET /client/subscription

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 1,
  "plan_id": 2,
  "plan_name": "Starter",
  "months": 1,
  "units": 1000,
  "status": "active",
  "starts_at": "…",
  "ends_at": "…",
  "is_non_expiry": false
}
```

GET /client/subscription/archives

Auth	Bearer client

Response data (inside standard envelope)

```
Paginated past subscriptions
```

POST /client/subscription

Auth	Bearer client
Notes	method optional — omit so Paystack shows card+momo; use wallet to debit balance. months=0 = non-expiry package.

Request body

```
{
  "plan_id": 2,
  "months": 1,
  "method": "momo",
  "phone_number": "0244123456",
  "network": "MTN"
}
```

Response data (inside standard envelope)

```
{
  "subscription": {
    "id": 1,
    "status": "pending|active"
  },
  "payment": {
    "id": 10,
    "status": "pending",
    "payment_link": "https://…",
    "method": null
  }
}
```

3.4 Payments & generic checkout

GET /client/payments

Auth	Bearer client

Query / path params

```
?status=&purpose=&from=&to=&page=&per_page=
```

Response data (inside standard envelope)

```
[
  {
    "id": 10,
    "resource": "payment",
    "purpose": "wallet_top_up",
    "method": "momo",
    "amount": 100,
    "charge": 0,
    "total_amount": 100,
    "currency": "GHS",
    "status": "pending|paid|failed",
    "payment_link": "https://…",
    "reference_id": "…",
    "paid_at": null,
    "created_at": "…"
  }
]
```

GET /client/payments/quote

Auth	Bearer client
Notes	Price breakdown before paying. purpose ∈ wallet_top_up, sms_units, campaign_fund, survey_fund, data_bundle, airtime, ecg, gotv, dstv, starttimes, mashup, results, utility_bulk.

Query / path params

```
{
  "purpose": "sms_units",
  "method": "momo",
  "plan_id": 2,
  "months": 1
}
```

Response data (inside standard envelope)

```
{
  "purpose": "sms_units",
  "method": "momo",
  "amount": 50,
  "charge": 0,
  "total": 50,
  "currency": "GHS",
  "line_items": []
}
```

POST /client/payments/checkout

Auth	Bearer client
Notes	Generic checkout. Prefer dedicated wallet/subscription/utility purchase endpoints when available.

Request body

```
{
  "purpose": "wallet_top_up",
  "amount": 50,
  "method": "card",
  "phone_number": "0244123456",
  "network": "MTN",
  "campaign_id": null,
  "survey_id": null,
  "plan_id": null,
  "months": null,
  "utility": {
    "beneficiary": "0244123456",
    "package_id": "yellow_1gb",
    "network": "YELLO",
    "amount": 10,
    "bill_type": null,
    "checker_type": null,
    "quantity": null
```

```
  }
}
```

Response data (inside standard envelope)

```
{
  "order": {
    "id": 1
  },
  "payment": {
    "id": 10,
    "status": "pending",
    "payment_link": "https://…"
  }
}
```

GET /client/payments/{payment}

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 10,
  "status": "paid",
  "total_amount": 50,
  "payment_link": null
}
```

POST /client/payments/{payment}/verify

Auth	Bearer client
Notes	Client taps "I have paid" — verifies with gateway immediately.

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 10,
  "status": "paid|pending|failed",
  "failure_reason": null
}
```

3.5 Orders

GET /client/orders

Auth	Bearer client

Query / path params

```
?page=&per_page=&status=&purpose=
```

Response data (inside standard envelope)

```
[{ id, purpose, amount, status, payment_id, created_at }]
```

POST /client/orders

Auth	Bearer client
Notes	Same body as POST /client/payments/checkout (StoreOrderRequest).

Request body

```
{
  "purpose": "sms_units",
  "plan_id": 2,
  "months": 1,
  "method": "wallet"
}
```

Response data (inside standard envelope)

```
{
  "order": {},
  "payment": {}
}
```

GET /client/orders/{order}

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 1,
  "purpose": "sms_units",
  "status": "completed"
}
```

3.6 Reports & exports

GET /client/reports/{report}

Auth	Bearer client
Notes	report ∈ sms | delivery | payments | wallet | subscriptions

Query / path params

```
?period=daily|weekly|monthly|yearly|custom&from=&to=&type=&status=&purpose=
```

Response data (inside standard envelope)

```
{
  "report": "sms",
  "period": "daily",
  "from": "…",
  "to": "…",
  "series": [
    {
      "bucket": "2026-11-01",
      "total": 120
    }
  ],
  "totals": {}
}
```

GET /client/reports/{report}/export

Auth	Bearer client
Notes	Downloads CSV/XLSX of the aggregated report.

Query / path params

```
?period=&from=&to=&format=csv|xlsx
```

GET /client/exports/{dataset}

Auth	Bearer client
Notes	dataset ∈ payments | wallet | subscriptions | sms | sms-delivery

Query / path params

```
?period=&from=&to=&format=csv|xlsx&inbox_id=
```

3.7 Rewards (read-only for clients)

GET /client/rewards

Auth	Bearer client
Notes	In-stock rewards for campaigns/surveys.

Response data (inside standard envelope)

```
[
  {
    "id": 3,
    "name": "YELLO 1GB Data",
    "type": "data",
    "size": "1GB",
    "amount": 4.2,
    "network": "YELLO",
    "currency": "GHS",
    "bundle_id": "yellow_1gb",
    "status": "instock"
  }
]
```

GET /client/rewards/catalog

Auth	Bearer client
Notes	Live Swift data/mashup packages for building inline rewards (with sell price after margin).

Response data (inside standard envelope)

```
{
  "currency": "GHS",
  "networks": [
    {
      "network": "YELLO",
      "product_type": "data_bundle",
      "plans": []
    }
  ],
  "plans": [
    {
      "package_id": "yellow_1gb",
      "network": "YELLO",
      "product_type": "data_bundle",
      "size": "1GB",
      "price": 4.7,
      "available": true
    }
  ]
}
```

GET /client/reward-disbursements

Auth	Bearer client

Query / path params

```
?page=&status=&type=&campaign_id=&survey_id=
```

Response data (inside standard envelope)

```
[{ id, type, status, phone_number, amount, network, package_id, campaign_id, survey_id, created_at }]
```

GET /client/reward-disbursements/{disbursement}

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 1,
  "type": "data",
  "status": "completed",
  "phone_number": "0244…",
  "amount": 4.2
}
```

3.8 Campaigns

Types: occasion | promotion. Occasion fields: occasion_type ∈ birthday, anniversary, holiday, custom; trigger_offset ∈ on, before, after, same_day, one_day_before, three_days_before, one_week_before, custom.

YELLO / plain MTN data rewards require verified beneficiaries — eligible_recipients counts only verified numbers; SMS still goes to reachable contacts.

GET /client/campaigns

Auth	Bearer client

Query / path params

```
?status=&type=&search=&page=
```

Response data (inside standard envelope)

```
[Campaign objects — see show]
```

POST /client/campaigns

Auth	Bearer client
Notes	Creates a draft only. Fund + activate separately.

Request body

```
{
```

```
  "name": "Birthday blast",
  "type": "occasion",
  "occasion_type": "birthday",
  "trigger_offset": "on",
  "send_time": "09:00",
  "repeat_yearly": true,
  "contact_group_ids": [
    9,
    12
  ],
  "sender": "CELLOGENT",
  "body": "Happy birthday {{name}}! Claim your gift: {{link}}",
  "send_at": null,
  "cta": {
    "enabled": true,
    "type": "link",
    "url": "https://example.com",
    "label": "Open",
    "triggers_reward": true
  },
  "reward_enabled": true,
  "reward_id": 3,
  "reward": {
    "enabled": true,
    "type": "data",
    "package_id": "yellow_1gb",
    "network": "YELLO",
    "amount": 4.2
  }
}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "draft",
  "tracking_url": "/api/public/campaigns/1/click",
  "reward": {
    "enabled": true,
    "requires_beneficiary": true,
    "eligible_recipients": 500,
    "not_eligible": 1000,
    "estimated_cost": 2100,
    "estimated_cost_units": 1200,
    "beneficiary_message": "500 verified beneficiaries can receive this data reward…"
  },
  "funding": {
    "funded": false,
    "reserved_amount": 0
  }
}
```

GET /client/campaigns/{campaign}

Auth	Bearer client

Response data (inside standard envelope)

```
Full campaign object (same shape as create response)
```

PUT /client/campaigns/{campaign}

Auth	Bearer client
Notes	All fields optional; type cannot change.

Request body

```
{
  "name": "Updated name",
  "body": "New SMS copy"
}
```

DELETE /client/campaigns/{campaign}

Auth	Bearer client
Notes	Only draft / cancelled typically.

POST /client/campaigns/{campaign}/fund

Auth	Bearer client

Request body

```
{
  "method": "wallet",
  "phone_number": null,
  "network": null,
  "estimated_cost": 2100
}
```

Response data (inside standard envelope)

```
{
  "funding": {
    "funded": true,
    "method": "wallet",
    "reserved_amount": 2100
  },
  "payment": null
}
```

POST /client/campaigns/{campaign}/activate

Auth	Bearer client

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "active",
  "activated_at": "…"
}
```

POST /client/campaigns/{campaign}/pause

Auth	Bearer client

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "paused"
}
```

POST /client/campaigns/{campaign}/resume

Auth	Bearer client

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "active"
}
```

POST /client/campaigns/{campaign}/complete

Auth	Bearer client

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "completed"
}
```

POST /client/campaigns/{campaign}/cancel

Auth	Bearer client

Request body

```
{}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "cancelled"
}
```

GET /client/campaigns/{campaign}/analytics

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "sent": 1200,
  "delivered": 1100,
  "clicks": 80,
  "rewards_paid": 40,
  "reserved_remaining": 500
}
```

GET /client/campaigns/{campaign}/events

Auth	Bearer client

Query / path params

```
?page=&event=
```

Response data (inside standard envelope)

```
[{ id, event, phone_number, meta, created_at }]
```

POST /client/campaigns/{campaign}/events

Auth	Bearer client

Request body

```
{
  "event": "click|open|reward_claimed|…",
  "phone_number": "0244123456",
  "meta": {}
}
```

3.9 Surveys

Question types: text, long_text, single_choice, multiple_choice, rating, yes_no, number. Max questions from SurveyService::MAX_QUESTIONS.

GET /client/surveys

Auth	Bearer client

Query / path params

```
?status=&search=&page=
```

POST /client/surveys

Auth	Bearer client

Request body

```
{
  "name": "NPS Q4",
  "intro": "Help us improve",
  "body": "Please take our short survey: {{link}}",
  "contact_group_ids": [
    9
  ],
  "sender": "CELLOGENT",
  "send_at": null,
  "reward_enabled": true,
  "reward_id": 3,
  "questions": [
    {
      "prompt": "Rate us 1–5",
```

```
      "type": "rating",
      "required": true,
      "position": 0
    },
    {
      "prompt": "Favourite feature?",
      "type": "single_choice",
      "options": [
        "SMS",
        "Campaigns",
        "Data"
      ],
      "required": true
    }
  ]
}
```

Response data (inside standard envelope)

```
{
  "id": 1,
  "status": "draft",
  "public_token": "abc…",
  "survey_url": "https://…/survey/abc…",
  "questions": [],
  "reward": {
    "requires_beneficiary": true,
    "eligible_recipients": 500,
    "beneficiary_message": "…"
  },
  "funding": {
    "funded": false
  }
}
```

GET /client/surveys/{survey}

Auth	Bearer client

PUT /client/surveys/{survey}

Auth	Bearer client
Notes	Sending questions replaces the list; keep id to update existing.

DELETE /client/surveys/{survey}

Auth	Bearer client

GET /client/surveys/{survey}/questions

Auth	Bearer client

Response data (inside standard envelope)

```
[{ id, prompt, type, options, required, position }]
```

PUT /client/surveys/{survey}/questions

Auth	Bearer client

Request body

```
{
  "questions": [
    {
      "id": 1,
      "prompt": "Updated?",
      "type": "yes_no",
      "required": true
    }
  ]
}
```

POST /client/surveys/{survey}/fund

Auth	Bearer client

Request body

```
{
  "method": "wallet"
}
```

POST /client/surveys/{survey}/activate

Auth	Bearer client

Request body

```
{}
```

POST /client/surveys/{survey}/pause

Auth	Bearer client

Request body

```
{}
```

POST /client/surveys/{survey}/resume

Auth	Bearer client

Request body

```
{}
```

POST /client/surveys/{survey}/complete

Auth	Bearer client

Request body

```
{}
```

POST /client/surveys/{survey}/cancel

Auth	Bearer client

Request body

```
{}
```

GET /client/surveys/{survey}/analytics

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "sent": 0,
  "responses": 0,
  "clicks": 0,
  "rewards_paid": 0,
  "reserved_remaining": 0
}
```

GET /client/surveys/{survey}/responses

Auth	Bearer client

Query / path params

```
?page=
```

Response data (inside standard envelope)

```
[{ id, phone_number, answers, created_at }]
```

3.10 Utilities (Swift)

Beneficiary verification is required ONLY for Affordable MTN SME data (network YELLO / plain MTN + product_type data_bundle). Mash Up, AT, TELECEL, airtime, ECG, TV, results skip the check.

GET /client/utilities/catalog

Auth	Bearer client

Response data (inside standard envelope)


```
{
  "currency": "GHS",
  "provider_reachable": true,
  "services": [
    {
      "service": "data",
      "product_type": "data_bundle",
      "available": true
    }
  ],
  "categories": {
    "YELLO": [],
    "AT": [],
    "TELECEL": [],
    "MTN Mash Up": []
  },
  "plans": [
    {
      "package_id": "yellow_1gb",
      "network": "YELLO",
      "product_type": "data_bundle",
      "price": 4.2,
      "requires_beneficiary": true,
      "available": true
    }
  ],
  "airtime": {
    "networks": [
      {
        "code": "MTN",
        "min_amount": 1,
        "max_amount": 500
      }
    ]
  },
  "tv": {
    "bill_types": [
      {
        "code": "DSTV",
        "order_type": "dstv"
      }
    ]
  },
  "ecg": {
    "min_amount": 1,
    "max_amount": 5000
  },
  "results": {
    "checkers": [
      {
        "type": "WASSCE",
        "unit_price": 17
      }
    ],
    "max_quantity": 100
  }
}
```


POST /client/utilities/quote

Auth	Bearer client
Notes	Single item OR items[] (max 50) OR contact_group_ids + package_id for group data buy.

Request body


```
{
  "service": "data",
  "package_id": "yellow_5gb",
  "beneficiary": "0244123456",
  "contact_group_ids": [
    9
  ],
  "items": null
}
```


Response data (inside standard envelope)


```
{
  "currency": "GHS",
```

```
  "items": [
    {
      "service": "data",
      "package_id": "yellow_5gb",
      "cost": 23,
      "sell": 25.76,
      "beneficiary": "233244…"
    }
  ],
  "totals": {
    "cost": 23,
    "sell": 25.76,
    "count": 1
  },
  "audience": {
    "total": 1500,
    "verified": 500,
    "message": "500/1500 verified — only verified contacts receive YELLO data."
  }
}
```

POST /client/utilities/lookup

Auth	Bearer client

Request body

```
{
  "service": "ecg|tv",
  "beneficiary": "meter_or_smartcard",
  "bill_type": "DSTV"
}
```

Response data (inside standard envelope)

```
{
  "account_name": "JOHN DOE",
  "beneficiary": "…",
  "service": "ecg"
}
```

POST /client/utilities/purchase

Auth	Bearer client
Notes	method ∈ wallet, momo, card. Group purchase expands contact_group_ids; unverified YELLO numbers are dropped.

Request body

```
{
  "service": "data",
  "package_id": "yellow_5gb",
  "beneficiary": "0244123456",
  "contact_group_ids": null,
  "method": "wallet",
  "phone_number": "0244123456",
  "momo_network": "MTN",
  "items": [
    {
      "service": "airtime",
      "network": "TELECEL",
      "amount": 5,
      "beneficiary": "0201234567"
    }
  ]
}
```

Response data (inside standard envelope)

```
{
  "orders": [
    {
      "id": 1,
      "status": "queued|pending_payment",
      "reference": "…"
    }
  ],
  "payment": null,
  "audience": {
    "verified": 500,
    "total": 1500
  }
}
```

GET /client/utilities/orders

Auth	Bearer client

Query / path params

```
?status=&service=&product_type=&batch_id=&from=&to=&page=
```

Response data (inside standard envelope)

```
[
  {
    "id": 1,
    "resource": "utility_order",
    "reference": "…",
    "service": "data",
    "product_type": "data_bundle",
    "network": "YELLO",
    "beneficiary": "23324…",
    "package_id": "yellow_5gb",
    "amount": 25.76,
    "status": "completed|failed|queued",
    "funding_method": "wallet"
  }
]
```

GET /client/utilities/orders/{order}

Auth	Bearer client

3.11 SMS

GET /client/sms/balance

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "balance": 850,
  "reserved": 0,
  "available": 850
}
```

GET /client/sms/units/history

Auth	Bearer client

Query / path params

```
?type=&page=
```

Response data (inside standard envelope)

```
[{ id, type, units, balance_after, description, created_at }]
```

POST /client/sms/quick

Auth	Bearer client
Notes	to accepts one number, CSV, or array (normalized to array).

Request body

```
{
  "from": "CELLOGENT",
  "to": [
    "0244123456",
    "0201234567"
  ],
  "message": "Hello from Cellogent"
}
```

Response data (inside standard envelope)

```
{
  "inbox": {
    "id": 99,
    "status": "queued",
    "recipients": 2,
    "units_used": 2
```

```
  }
}
```

POST /client/sms/bulk

Auth	Bearer client

Request body

```
{
  "from": "CELLOGENT",
  "contact_group_ids": [
    9,
    12
  ],
  "message": "Promo blast…"
}
```

Response data (inside standard envelope)

```
{
  "inbox": {
    "id": 100,
    "status": "queued",
    "recipients": 1500,
    "units_used": 1500
  }
}
```

GET /client/sms

Auth	Bearer client

Query / path params

```
?type=&status=&request_type=&mode=&contact_group_id=&from_date=&to_date=&page=
```

GET /client/sms/{inbox}

Auth	Bearer client

Response data (inside standard envelope)

```
{
  "id": 99,
  "from": "CELLOGENT",
  "message": "…",
  "status": "sent",
  "type": "quick|bulk",
  "recipients_count": 2,
  "delivered": 2,
  "failed": 0
}
```

GET /client/sms/{inbox}/recipients

Auth	Bearer client

Query / path params

```
?status=&page=
```

Response data (inside standard envelope)

```
[{ phone_number, status, parts, error }]
```

POST /client/sms/{inbox}/reblast

Auth	Bearer client

Request body

```
{
  "message": "optional new copy"
}
```

POST /client/sms/{inbox}/resend

Auth	Bearer client
Notes	Resend failed recipients only; message required.

Request body

```
{
  "message": "Retry copy"
}
```

4. Admin APIs

Prefix /api/admin · middleware auth:admin + account.active. Many routes also need a permission slug.

4.1 Onboarding

POST /admin/onboard/client

Auth	Bearer admin
Permission	onboarding.client
Notes	Same rules as client signup. Business → multipart with profile_image (logo).

Request body

```
{
  "account_type": "individual|business",
  "email": "user@example.com",
  "phone_number": "0244123456",
  "first_name": "Ama",
  "last_name": "Mensah",
  "date_of_birth": "1990-01-01",
  "business_name": null,
  "region": null,
  "city": null,
  "address": null,
  "gender": "female",
  "profile_image": "(file, required for business)"
}
```

POST /admin/onboard/admin

Auth	Bearer admin
Permission	onboarding.admin

Request body

```
{
  "first_name": "Kojo",
  "last_name": "Asante",
  "email": "admin2@cellogent.com",
  "phone_number": "0244000000",
  "role_id": 2,
  "profile_image": "(optional file)"
}
```

4.2 Clients

GET /admin/clients

Auth	Bearer admin
Permission	client.manage

Query / path params

```
?search=&status=&account_type=&page=
```

GET /admin/clients/{client}

Auth	Bearer admin
Permission	client.manage

PUT /admin/clients/{client}

Auth	Bearer admin
Permission	client.manage
Notes	POST also accepted for multipart profile image.

Request body

```
{
  "account_type": "business",
  "email": "…",
  "phone_number": "…",
  "business_name": "…",
  "region": "…",
```

```
  "city": "…",
  "address": "…",
  "profile_image": "(file)"
}
```

PUT /admin/clients/{client}/status

Auth	Bearer admin
Permission	client.manage

Request body

```
{
  "status": "active|inactive|suspended|…"
}
```

4.3 Admins

GET /admin/admins

Auth	Bearer admin
Permission	admin.manage

GET /admin/admins/{admin}

Auth	Bearer admin
Permission	admin.manage

PUT /admin/admins/{admin}

Auth	Bearer admin
Permission	admin.manage
Notes	POST also for multipart image.

Request body

```
{
  "first_name": "…",
  "last_name": "…",
  "email": "…",
  "phone_number": "…",
  "role_id": 2,
  "profile_image": "(file)"
}
```

PUT /admin/admins/{admin}/status

Auth	Bearer admin
Permission	admin.manage

Request body

```
{
  "status": "active|inactive|…"
}
```

PUT /admin/admins/{admin}/role

Auth	Bearer admin
Permission	admin.manage

Request body

```
{
  "role_id": 2
}
```

DELETE /admin/admins/{admin}

Auth	Bearer admin
Permission	admin.manage

4.4 Roles & permissions

GET /admin/roles

Auth	Bearer admin
Permission	role.manage

POST /admin/roles

Auth	Bearer admin
Permission	role.manage

Request body

```
{
  "name": "Support",
  "description": "…",
  "permission_ids": [
    1,
    2,
    3
  ]
}
```

GET /admin/roles/{role}

Auth	Bearer admin
Permission	role.manage

PUT /admin/roles/{role}

Auth	Bearer admin
Permission	role.manage

Request body

```
{
  "name": "Support",
  "description": "…",
  "permission_ids": [
    1,
    2
  ]
}
```

POST /admin/roles/assign

Auth	Bearer admin
Permission	role.manage

Request body

```
{
  "admin_id": 5,
  "role_id": 2
}
```

GET /admin/permissions

Auth	Bearer admin
Permission	permission.manage

Response data (inside standard envelope)

```
[{ id, slug, name, group }]
```

4.5 Activity logs

GET /admin/activity-logs/filters

Auth	Bearer admin
Permission	activity_log.view

GET /admin/activity-logs

Auth	Bearer admin
Permission	activity_log.view

Query / path params

```
?actor_type=&event=&search=&from=&to=&page=
```

GET /admin/clients/{client}/activity-logs

Auth	Bearer admin
Permission	activity_log.view

4.6 Plans

GET /admin/plans

Auth	Bearer admin
Permission	plan.manage

POST /admin/plans

Auth	Bearer admin
Permission	plan.manage
Notes	Max 4 packages. months 0 or omit = non-expiry.

Request body

```
{
  "name": "Growth",
  "status": "active",
  "is_featured": false,
  "details": [
    {
      "months": 1,
      "units": 2000,
      "price": 90
    },
    {
      "months": 3,
      "units": 7000,
      "price": 240
    },
    {
      "months": 0,
      "units": 20000,
      "price": 600
    }
  ]
}
```

GET /admin/plans/{plan}

Auth	Bearer admin
Permission	plan.manage

PUT /admin/plans/{plan}

Auth	Bearer admin
Permission	plan.manage

Request body

```
Same fields as POST
```

4.7 Rewards catalog

GET /admin/rewards

Auth	Bearer admin
Permission	plan.manage

POST /admin/rewards

Auth	Bearer admin
Permission	plan.manage
Notes	type ∈ money | airtime | data. For data, package_id from utilities catalog fills name/size/network/amount.

Request body

```
{
  "name": "YELLO 2GB",
  "type": "data",
  "package_id": "yellow_2gb",
  "amount": 8.4,
  "network": "YELLO",
  "currency": "GHS",
  "status": "instock",
  "meta": {
    "requires_beneficiary": true
  }
}
```

Response data (inside standard envelope)

```
{
  "id": 5,
  "package_id": "yellow_2gb",
  "api_price": 8.4,
  "price": 9.41,
  "profit": 1.01,
  "type": "data",
  "status": "instock"
}
```

GET /admin/rewards/{reward}

Auth	Bearer admin
Permission	plan.manage

PUT /admin/rewards/{reward}

Auth	Bearer admin
Permission	plan.manage

PUT /admin/rewards/{reward}/status

Auth	Bearer admin
Permission	plan.manage

Request body

```
{
  "status": "instock|out_of_stock"
}
```

DELETE /admin/rewards/{reward}

Auth	Bearer admin
Permission	plan.manage

4.8 Utilities (admin)

GET /admin/utilities/catalog

Auth	Bearer admin
Permission	payment.view or payment.manage

POST /admin/utilities/quote

Auth	Bearer admin
Permission	payment.view or payment.manage

Request body

```
Same as client quote
```

GET /admin/utilities/balance

Auth	Bearer admin
Permission	payment.view or payment.manage

Response data (inside standard envelope)

```
{
  "balance": 12000,
  "currency": "GHS",
  "provider": "swift"
}
```

GET /admin/utilities/profit

Auth	Bearer admin
Permission	payment.view or payment.manage

Query / path params

```
?from=&to=&product_type=&client_id=&funding_method=
```

Response data (inside standard envelope)

```
{
  "totals": {
    "cost": 1000,
    "sell": 1120,
    "profit": 120,
    "orders": 40
  },
  "by_product_type": []
}
```

GET /admin/utilities/orders

Auth	Bearer admin
Permission	payment.view or payment.manage
Notes	Admin present adds cost_amount, sell_amount, profit_amount, provider_* fields.

Query / path params

```
?status=&service=&product_type=&client_id=&funding_method=&from=&to=&page=
```

GET /admin/utilities/orders/{order}

Auth	Bearer admin
Permission	payment.view or payment.manage

GET /admin/reward-disbursements

Auth	Bearer admin
Permission	payment.view or payment.manage

GET /admin/reward-disbursements/{disbursement}

Auth	Bearer admin
Permission	payment.view or payment.manage

4.9 Profit margins

Most specific rule wins: package_id > network > product_type. Seeded defaults cover data_bundle, mashup, results, wallet_top_up.

GET /admin/margins

Auth	Bearer admin
Permission	payment.manage

GET /admin/margins/options

Auth	Bearer admin
Permission	payment.manage

Response data (inside standard envelope)

```
{
  "product_types": [
    "data_bundle",
    "mashup",
    "airtime",
    "ecg",
    "tv",
    "results",
    "sms_units",
    "wallet_top_up"
  ],
  "markup_types": [
    "percent",
    "fixed"
  ]
}
```

POST /admin/margins

Auth	Bearer admin
Permission	payment.manage

Request body

```
{
  "product_type": "data_bundle",
  "network": "YELLO",
  "package_id": null,
  "markup_type": "percent",
  "markup_value": 12,
  "active": true
}
```

GET /admin/margins/{margin}

Auth	Bearer admin
Permission	payment.manage

PUT /admin/margins/{margin}

Auth	Bearer admin
Permission	payment.manage

DELETE /admin/margins/{margin}

Auth	Bearer admin
Permission	payment.manage

4.10 Subscriptions

GET /admin/subscriptions

Auth	Bearer admin
Permission	subscription.view

Query / path params

```
?status=&client_id=&page=
```

GET /admin/subscription-archives

Auth	Bearer admin
Permission	subscription.view

GET /admin/clients/{client}/subscription

Auth	Bearer admin
Permission	subscription.view

POST /admin/clients/{client}/subscription

Auth	Bearer admin
Permission	subscription.assign
Notes	Admin assigns without payment. months=0 → non-expiry.

Request body

```
{
  "plan_id": 2,
  "months": 1,
  "type": "custom|non_expiry|monthly"
}
```

4.11 Wallets

GET /admin/wallets

Auth	Bearer admin
Permission	wallet.view

GET /admin/wallet-top-ups

Auth	Bearer admin
Permission	wallet.view

GET /admin/wallet-transactions

Auth	Bearer admin
Permission	wallet.view

GET /admin/clients/{client}/wallet

Auth	Bearer admin
Permission	wallet.view

4.12 Payment gateways & charges

GET /admin/payment-gateways

Auth	Bearer admin
Permission	payment_gateway.manage

Response data (inside standard envelope)

```
{
  "gateways": [
    {
      "code": "paystack",
      "name": "Paystack",
      "is_enabled": true,
      "is_primary": true,
      "priority": 1
    }
  ]
}
```

PUT /admin/payment-gateways/{code}

Auth	Bearer admin
Permission	payment_gateway.manage

Request body

```
{
  "is_enabled": true,
  "priority": 1
}
```

POST /admin/payment-gateways/{code}/primary

Auth	Bearer admin
Permission	payment_gateway.manage

Request body

```
{}
```

GET /admin/settings/payments

Auth	Bearer admin
Permission	payment_settings.manage

Response data (inside standard envelope)

```
{
  "charges": {
    "wallet_top_up": 0,
    "sms_units": 0
  }
}
```

PUT /admin/settings/payments

Auth	Bearer admin
Permission	payment_settings.manage

Request body

```
{
  "charges": {
    "wallet_top_up": 0,
    "sms_units": 1.5
  }
}
```

4.13 Reports & exports (admin)

GET /admin/reports/{report}

Auth	Bearer admin
Permission	report.view
Notes	report ∈ sms | delivery | payments | wallet | subscriptions | revenue

Query / path params

```
?period=&from=&to=
```

GET /admin/reports/{report}/export

Auth	Bearer admin
Permission	report.export

GET /admin/exports/{dataset}

Auth	Bearer admin
Permission	report.export
Notes	dataset ∈ payments | wallet | subscriptions | sms | sms-delivery

4.14 Payments (admin)

GET /admin/payments

Auth	Bearer admin
Permission	payment.view or payment.manage

Query / path params

```
?status=&purpose=&client_id=&from=&to=&page=
```

GET /admin/payments/{payment}

Auth	Bearer admin
Permission	payment.view or payment.manage
Notes	Includes gateway, gateway_reference, gateway_response, verify_attempts.

POST /admin/payments/{payment}/verify

Auth	Bearer admin
Permission	payment.manage

Request body

```
{}
```

POST /admin/payments/{payment}/complete

Auth	Bearer admin
Permission	payment.manage
Notes	Manually mark paid and deliver.

Request body

```
{}
```

POST /admin/payments/{payment}/fail

Auth	Bearer admin
Permission	payment.manage

Request body

```
{}
```

4.15 Orders (admin)

GET /admin/orders

Auth	Bearer admin
Permission	order.view

GET /admin/orders/{order}

Auth	Bearer admin
Permission	order.view

4.16 SMS (admin)

GET /admin/sms/overview

Auth	Bearer admin
Permission	sms.view

Response data (inside standard envelope)

```
{
  "today_sent": 0,
  "failed": 0,
  "queued": 0
}
```

GET /admin/sms/system

Auth	Bearer admin
Permission	sms.view
Notes	System / OTP style messages.

GET /admin/sms

Auth	Bearer admin

Permission	sms.view

Query / path params

```
?client_id=&status=&type=&page=
```

GET /admin/sms/{inbox}

Auth	Bearer admin
Permission	sms.view

GET /admin/sms/{inbox}/recipients

Auth	Bearer admin
Permission	sms.view

POST /admin/sms/quick

Auth	Bearer admin
Permission	sms.send

Request body

```
{
  "from": "CELLOGENT",
  "to": [
    "0244123456"
  ],
  "message": "Admin notice"
}
```

GET /admin/sms/aggregator/balance

Auth	Bearer admin
Permission	sms.aggregator

GET /admin/sms/aggregator/requests

Auth	Bearer admin
Permission	sms.aggregator

GET /admin/sms/aggregator/delivery-receipts/{sequenceNo}

Auth	Bearer admin
Permission	sms.aggregator

5. Frontend notes

1. Always read in_error + status_code; never assume HTTP alone.

2. After momo/card checkout, open payment_link (or wait for USSD prompt), then poll GET payment or POST …/verify.

3. Campaign/survey flow: create draft → fund (if rewards) → activate. Do not skip funding when rewards are enabled.

4. For YELLO data (utilities or rewards): show verified/total from audience or beneficiary_message before purchase/activate.

5. Utility quote/purchase: use package_id from catalog; never trust client-sent prices — server recalculates sell with margins.

6. Webhooks (Paystack, Kairos, Swift) are server-to-server — not needed in the app UI.

7. /api/v1/* (API-key SMS) is for client integrations, not the dashboard — omitted here with API keys.